

```
#include<stdio.h>
#include<stdlib.h>
#include<math.h>
#include<graphics.h>
#include<dos.h>
```

```
typedef struct coordinate
{
int x,y;
char code[4];
}PT;
```

```
void drawwindow();
void drawline(PT p1,PT p2);
PT setcode(PT p);
int visibility(PT p1,PT p2);
PT resetendpt(PT p1,PT p2);
```

```
void main()
{
int gd=DETECT,v,gm;
PT p1,p2,p3,p4,ptemp;
printf("\nEnter x1 and y1\n");
scanf("%d %d",&p1.x,&p1.y);
printf("\nEnter x2 and y2\n");
scanf("%d %d",&p2.x,&p2.y);
initgraph(&gd,&gm,"c:\\turbo3\\bgi");
drawwindow();
delay(500);
drawline(p1,p2);
```

```
delay(500);
cleardevice();
delay(500);
p1=setcode(p1);
p2=setcode(p2);
v=visibility(p1,p2);
delay(500);
switch(v)
{
case 0: drawwindow();
delay(500);
drawline(p1,p2);
break;
case 1: drawwindow();
delay(500);
break;
case 2: p3=resetendpt(p1,p2);
p4=resetendpt(p2,p1);
drawwindow();
delay(500);
drawline(p3,p4);
break;
}
delay(5000);
closegraph();
}
```

```
void drawwindow()
{
line(150,100,450,100);
```

```
line(450,100,450,350);  
line(450,350,150,350);  
line(150,350,150,100);  
}
```

```
void drawline(PT p1,PT p2)  
{  
line(p1.x,p1.y,p2.x,p2.y);  
}
```

```
PT setcode(PT p) //for setting the 4 bit code  
{  
PT ptemp;  
if(p.y<100)  
ptemp.code[0]='1'; //Top  
else  
ptemp.code[0]='0';  
if(p.y>350)  
ptemp.code[1]='1'; //Bottom  
else  
ptemp.code[1]='0';  
if(p.x>450)  
ptemp.code[2]='1'; //Right  
else  
ptemp.code[2]='0';  
if(p.x<150)  
ptemp.code[3]='1'; //Left  
else  
ptemp.code[3]='0';  
ptemp.x=p.x;
```

```
p-temp.y=p.y;  
return(p-temp);  
}
```

```
int visibility(PT p1,PT p2)  
{  
    int i,flag=0;  
    for(i=0;i<4;i++)  
    {  
        if((p1.code[i]!='0') || (p2.code[i]!='0'))  
            flag=1;  
    }  
    if(flag==0)  
        return(0);  
    for(i=0;i<4;i++)  
    {  
        if((p1.code[i]==p2.code[i]) && (p1.code[i]=='1'))  
            flag='0';  
    }  
    if(flag==0)  
        return(1);  
    return(2);  
}
```

```
PT resetendpt(PT p1,PT p2)  
{  
    PT temp;  
    int x,y,i;  
    float m,k;  
    if(p1.code[3]=='1')
```

```

x=150;
if(p1.code[2]=='1')
x=450;
if((p1.code[3]=='1') || (p1.code[2]=='1'))
{
m=(float)(p2.y-p1.y)/(p2.x-p1.x);
k=(p1.y+(m*(x-p1.x)));
temp.y=k;
temp.x=x;
for(i=0;i<4;i++)
temp.code[i]=p1.code[i];
if(temp.y<=350 && temp.y>=100)
return (temp);
}
if(p1.code[0]=='1')
y=100;
if(p1.code[1]=='1')
y=350;
if((p1.code[0]=='1') || (p1.code[1]=='1'))
{
m=(float)(p2.y-p1.y)/(p2.x-p1.x);
k=(float)p1.x+(float)(y-p1.y)/m;
temp.x=k;
temp.y=y;
for(i=0;i<4;i++)
temp.code[i]=p1.code[i];
return(temp);
}
else
return(p1);

```

}