
## ⟨ (http://peeterjoot.com) gdb TUI mode debugging



(https://www.youtube.com/watch?v=PorfLSr3DDI), where he gave a nice example of how to use the gdb TUI (text user interface) mode. I'd recently encountered the gdb –tui option, but thought that you had to have the foresight to remember to invoke gdb with –tui (which I usually didn't, but also didn't always want to since it's redraw was flaky

in a putty terminal session).

It turns out that there are command line keystrokes to enable TUI dynamically when you want it (or turn it off when you don't). That makes this TUI a much nicer feature!

The main key commands of interest (https://sourceware.org/gdb/onlinedocs/gdb/TUI-Keys.html) are:

I recently watched Greg Law's "I'll change your opinion on GDB" talk from CPPCON 2015

- C-x a, turn on (or off) TUI mode.
- C-x 2. Use two windows, or cycle to the next layout.
- C-x o. Change active window.
- C-L. Redraw screen.
- C-x p. command history (since up and down move the cursor)

Here's an example how things look after turning on TUI (C-x a):

```
regex — pjoot@nuc2:~/physicsplay/programming/stroustroupbook/noexcept — ssh nuc2 — 94×31
        foo.cc-
     22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
               void bar( void )
                   throw 1;
                int main()
B+>
                   int v = foo();
                   printf( "%d\n", v );
                   return 0;
     38
     39
native process 31202 In: main
                                                                                                            PC: 0x4007a7
                                                                                                    L30
(gdb)
```


(http://peeterjoot.com/wp-content/uploads/2016/06/Screen-Shot-2016-06-09-at-7.42.59-PM.png)

After turning on two window mode (C-X 2):

```
regex — pjoot@nuc2:~/physicsplay/programming/stroustroupbook/noexcept — ssh nuc2 — 94×31
       foo.cc-
    28
             int main()
    29
    30
B+>
                int v = foo();
    31
    32
                printf( "%d\n", v );
    33
    34
                return 0;
    35
    0x40079a <bar()+33>
                              calla
                                      0x400650 <__cxa_throw@plt>
    0x40079f <main()>
                              push
                                      %rbp
    0x4007a0 <main()+1>
                                      %rsp,%rbp
                              mov
                                      $0x10,%rsp
    0x4007a3 <main()+4>
                              sub
B+>
    0x4007a7 <main()+8>
                                      0x400760 <foo()>
                              calla
    0x4007ac <main()+13>
                              mov
                                      %eax, -0x4(%rbp)
                                      -0x4(%rbp),%eax
    0x4007af <main()+16>
                              mov
    0x4007b2 <main()+19>
                              mov
                                      %eax,%esi
                                      $0x400860, %edi
    0x4007b4 <main()+21>
                              mov
                                                                                  L30
                                                                                        PC: 0x4007a7
native process 31202 In: main
                0x40079f 4196255
rax
rbx
                0x0
                          0
                0x40
                          64
rcx
                0x7fffffffe2c8
                                   140737488347848
rdx
                0x7fffffffe2b8
rsi
                                   140737488347832
rdi
                0x1
                0x7ffffffffe1d0
                                   0x7ffffffffe1d0
rbp
                0x7ffffffffe1c0
                                   0x7ffffffffe1c0
rsp
                0x7fffff75b6e80
                                   140737343352448
r8
---Type <return> to continue, or q <return> to quit---
```

(http://peeterjoot.com/wp-content/uploads/2016/06/Screen-Shot-2016-06-09-at-7.44.05-PM.png)

This has a source view, an assembly view, and the output of 'info registers'. You can actually get a register window by cycling through the window layouts once (C-x 2 again):



(http://peeterjoot.com/wp-content/uploads/2016/06/Screen-Shot-2016-06-09-at-7.44.40-PM.png)

Some of the previous times that I'd tried 'gdb –tui' explicitly, I'd found it hit redraw issues, but didn't really want to detach and reattach the debugger just to change the TUI mode. It sounds like such issues can be dealt with either by turning off TUI mode (C-x a), or using redraw (C-L).

## Share this:




One comment



## Peeter Joot's Blog » peeking into relocation of function static in shared library &

(http://peeterjoot.com/2017/02/27/peeking-into-relocation-of-function-static-in-shared-library/) 4 years ago



♠ Back to top

© Peeter Joot's Blog

Theme by nehalist.io (http://nehalist.io)