

<https://codesandbox.io/s/lecture-15-sgzncm>

React Hooks

- `useState`
- `useEffect`
- `useRef`
- `useMemo`
- `useCallback`
- `useContext`
- `useReducer`

useRef

```
<p class="mark"> <span>Ref.jsx</span>  
<span>RefDOM.jsx</span> </p>
```

- `useRef` returns a mutable ref object whose `.current` property is initialized to the passed argument (`initialValue`).
- The returned object will persist for the full lifetime of the component.

```
function useRef(initialValue) {  
  const [ref, _] = useState({ current: initialValue });  
  return ref;  
}
```

refs vs state

refs	state
<code>useRef</code> returns <code>{current: initialValue}</code>	<code>useState</code> returns <code>[value, setValue]</code>
does not trigger re-render	triggers re-render
mutable	"immutable"

useMemo

<p class="mark">Memo.jsx</p>

- `useMemo` returns a memoized value.
- second argument is an array of dependencies, like `useEffect`.
- only recompute the memoized value when one of the dependencies has changed.
- usage
 - skip expensive calculations on every render
 - pass a callback to a child component that uses `useMemo` / `useCallback` to only re-render when the callback has changed

useCallback

<p class="mark">Callback.jsx</p>

- `useCallback` returns a memoized callback.
- second argument is an array of dependencies, like `useEffect`.
- usage
 - with `memo`, skip re-rendering a component if its props haven't changed

Routing in React

- Why do we need routing?
- How?

Why routing?

- Single Page Application (SPA)
- Multiple pages
- Different URLs for different contents
- Navigation

How?

- `react-router-dom`
- <https://reactrouter.com/en/main>

Installation and Setup

```
npm install react-router-dom
```

```
import { BrowserRouter as Router, Switch, Route } from 'react-router-dom';
```

Main Concepts

- Subscribing and manipulating the `history` stack
- Matching the URL to your routes
- Rendering a nested UI from the route matches

history stack

- Browsers maintain their own history stack as the user navigates around.

Action	Stack
clicks a link to /home	/home
clicks a link to /about	/home , /about
clicks the back button	/home
clicks the forward button	/home , /about

`window.location`

- `window.location` is an object that contains information about the current URL.
- `window.location.href = <url>` redirects the page to the specified URL.

Router

<p class="mark">Router-v5.jsx Router-v6.jsx</p> <div class="columns">

```
<Router>
  <Switch>
    <Route path="/about">
      <About />
    </Route>
    <Route path="/dashboard">
      <Dashboard />
    </Route>
    <Route path="/">
      <Home />
    </Route>
  </Switch>
</Router>
```

BrowserRouter vs HashRouter

- `BrowserRouter` uses the HTML5 `history` API to keep the UI in sync with the URL.
- `HashRouter` uses the hash portion of the URL (i.e. `window.location.hash`) to keep the UI in sync with the URL.
- `BrowserRouter` is preferred over `HashRouter` because it produces cleaner URLs.
- `HashRouter` is preferred over `BrowserRouter` if you need to support older browsers.

Link

```
<p class="mark">Link.jsx</p>
```

- `Link` is a component that renders an anchor tag (`<a>`) with a `href` to a location in the application.
- `reloadDocument` prop
- `state` prop

```
<Link to="/about">About</Link>
```


Route Matching in v5

<p class="mark">RouteMatching.jsx</p>

- path prop
- exact prop

```
<Route exact path="/">  
  <Home />  
</Route>
```

Route Matching in v6

<p class="mark">RouteMatching.jsx</p>

- path prop
- element prop
- index prop

```
<Route path="/" element={<App />}>
  <Route index element={<Home />} />
  <Route path="users" element={<Users />}>
    <Route path=":userId" element={<User />} />
    <Route path=":userId/edit" element={<User mode="edit" />} />
    <Route path="signup" element={<SignUp />} />
  </Route>
</Route>
```

Programmatic Navigation

<p class="mark">Navigation.jsx</p>

- `history.push(<url>)`
- `history.pop()`
- `history.replace(<url>)`
- `useNavigate` - `navigate(<url>)`

Private and Protected Routes

<p class="mark">ProtectedRoutes.jsx</p>

- ProtectedRoute to check if user exists
- if not, redirect to /login

React Router Hooks

- `useParams()`
- `useLocation()`
- `useNavigate()`

Performance

<p class="mark">LazyLoading.jsx</p>

- `React.lazy()` and `Suspense`