

Schoolink API Specification

(Carmel Holy Word Secondary School)

Version	Date	Author	Description
1.0	24-Feb-2025	Joshua Tam	Initial draft

Index

[1. General Information](#)

[Base URL](#)

[API Header](#)

[2. Get User Types](#)

[Request](#)

[Response](#)

[3. Get Users](#)

[Request](#)

[Parameters](#)

[Response](#)

[4. Update Users](#)

[Request](#)

[Parameters](#)

[Response](#)

[5. Delete Users](#)

[Request](#)

[Parameters](#)

[Response](#)

[6. Get Groups](#)

[Request](#)

[Parameters](#)

[Response](#)

[7. Update Groups](#)

[Request](#)

[Parameters](#)

[Response](#)

[8. Delete Groups](#)

[Request](#)

[Parameters](#)

[Response](#)

[9. Get User ECA Records](#)

[Request](#)

[Parameters](#)

[Response](#)

[10. Search Attendance Records](#)

[Request](#)

[Parameters](#)

[Response](#)

[11. Send Notice Message](#)

[Request](#)

[Parameters](#)

[Response](#)

[12. Get Message Reports](#)

[Request](#)

[Parameters](#)

[Response](#)

[Conventions](#)

[Status Codes](#)

Methods

1. General Information

Base URL

URL
<code>https://chw.schoolink.hk</code>

API Header

Every request should contain the following header:

Header	Value
<code>SchoolLinkKey</code>	<code>66b889d146b95ceb756c8d222a115bae</code>

2. Get User Types

Request

Method	URL
POST	api/getUserTypes

Response

Status	Response
200	Response will be an object containing the list of user types (array) . <pre>{ "success": true, "status": true, "data": [{ "typeID": "320", "name": "Student", "nameChi": "學生", "nameSChi": "学生" }, { "typeID": "321", "name": "Parent", "nameChi": "家長", "nameSChi": "家长" }, { "typeID": "322", "name": "Teacher", "nameChi": "老師", "nameSChi": "老师" }], "serverTime": "2017-04-10 11:51:13" }</pre>
400	The API is not called in POST request

3. Get Users

Request

Method	URL
POST	api/getUsers

Parameters

Type	Params	Values
POST	userID userID[]	number array of numbers

userID [optional]

The userID of any specific users

Response

Status	Response
200	Response will be an object containing the list of users (array) . <pre>{ "success": true, "status": true, "data": [{ "userID": "27233", "userID": "320", "username": "S13001", "nameEng": "Peter", "nameChi": "Peter", "nameSChi": null, "email": "na@schoolteam.hk", "mobileNumber1": null, "mobileNumber2": null, "mobileNumber3": null, "preferredLanguage": "TC", }] }</pre>

	<pre>"remarks": null, "apiToken": "XXXXXXXXXXXXXXXXXXXXXXXXX", "relatedUsers": [] }, { "userID": "27240", "userID": "321", "username": "P002", "nameEng": "Parent 2", "nameChi": "家長2", "nameSChi": null, "email": "na@schoolteam.hk", "mobileNumber1": null, "mobileNumber2": null, "mobileNumber3": null, "preferredLanguage": "TC", "remarks": null, "apiToken": "XXXXXXXXXXXXXXXXXXXXXXXXX", "relatedUsers": [27236, 27235] }], "serverTime": "2017-04-10 10:47:23" }</pre>
400	The API is not called in POST request

4. Update Users

Create / Update Users

Request

Method	URL
POST	api/updateUsers

Parameters

Type	Params	Values
BODY	JSON	Array of User Object

JSON

Array of User Object, there is a special field `password` that should be provided for new users. When no `password` supplied on existing users, the `password` remains unchanged.

`userID` [Required for update]

`userID` [Required]

`username` [Required]

`nameEng` [Required]

`nameChi` [optional]

`nameSChi` [optional]

`email` [optional]

`mobileNumber1` [optional]

`mobileNumber2` [optional]

`mobileNumber3` [optional]

`preferredLanguage` [Required, possible values (EN, TC, SC)]

`password` [optional for update], [required for create]

`relatedUsers` [optional, array of related userIDs, e.g. the userID of children of a parent]

JSON (Updating)	JSON (Creating)
[{	[{

<pre> "userID": "27233", "userTypeID": "320", "username": "S13001", "nameEng": "Peter", "nameChi": "Peter", "nameSChi": null, "email": "na@schoolteam.hk", "mobileNumber1": null, "mobileNumber2": null, "mobileNumber3": null, "preferredLanguage": "TC" // "password": "password" }] </pre>	<pre> "userTypeID": "320", "username": "S13002", "nameEng": "John", "nameChi": "John", "nameSChi": null, "email": "na@schoolteam.hk", "mobileNumber1": null, "mobileNumber2": null, "mobileNumber3": null, "preferredLanguage": "TC", "password": "password" }] </pre>
--	---

Response

Status	Response
200	Example response:- <pre> { "success": true, "status": true, "data": { "message": "Update Users Success." }, "serverTime": "2017-04-10 11:04:05" } </pre>
400	The API is not called in POST request
500	<pre> { "success": false, "status": false, "data": { "message": "The following userIDs not found! Not Updating. \n2723233" }, "serverTime": "2017-04-10 11:05:17" } </pre>

	}
500	<pre>{ "success": false, "status": false, "data": { "message": "There are some errors in your input, not inserting / updating.\n", "errors": [{ "row": 0, "errors": { "username": ["Username cannot be blank."] } }] }, "serverTime": "2017-04-10 11:09:54" }</pre>

5. Delete Users

Delete Users

Request

Method	URL
GET	api/deleteUsers

Parameters

Type	Params	Values
POST	userID userID[]	number array of numbers

userID [Required]

The **userID** of any specific users

Response

Status	Response
200	Example response:- { "success": true, "status": true, "data": { "message": "1 user(s) are deleted / marked inactive." }, "serverTime": "2017-04-10 18:29:01" }
400	The API is not called in POST request

6. Get Groups

Request

Method	URL
POST	api/getGroups

Parameters

Type	Params	Values
POST	groupID groupID[]	number array of numbers

groupID [optional]

The groupID of any specific groups

Response

Status	Response
200	Response will be an object containing the list of groups (array) . <pre>{ "success": true, "status": true, "data": [{ "groupID": "846", "nameEng": "ABCDEF", "nameChi": "ABCDEF", "nameSChi": "ABCDEF", "descriptionEng": null, "descriptionChi": null, "descriptionSChi": null, "isPrimaryGroup": "1", "remarks": null, "users": [{ "userID": "27235",</pre>

	<pre> "referenceNumber": "2" }] }, "serverTime": "2017-04-10 18:32:45" }</pre>
400	The API is not called in POST request

7. Update Groups

Create / Update Groups

Request

Method	URL
POST	api/updateGroups

Parameters

Type	Params	Values
BODY	JSON	Array of Group Object

JSON

Array of Group Object, there is a special field `users` that should be provided if there are any changes to `users`. When `users` is supplied on existing group, all existing `users` will be removed from the group and new `users` will be added.

`groupID` [Required for update]
`nameEng` [Required]
`nameChi` [optional]
`nameSChi` [optional]
`descriptionEng` [optional]
`descriptionChi` [optional]
`descriptionSChi` [optional]
`isPrimaryGroup` [Required, possible values (0, 1)]
`remarks` [optional]
`users` [optional, array]
(Format: {userID: <number>, referenceNumber: <class number>})

JSON (Updating)	JSON (Creating)
<pre>[{ "groupID": "846", "nameEng": "ABCDEF",</pre>	<pre>[{ "nameEng": "ABCDEF", "nameChi": "ABCDEF",</pre>

<pre> "nameChi": "ABCDEF", "nameSChi": "ABCDEF", "descriptionEng": null, "descriptionChi": null, "descriptionSChi": null, "isPrimaryGroup": "1", "remarks": null, "users": [{ "userID": "27233", "referenceNumber": "1" }, { "userID": "27234", "referenceNumber": "2" }] }] </pre>	<pre> "nameSChi": "ABCDEF", "descriptionEng": null, "descriptionChi": null, "descriptionSChi": null, "isPrimaryGroup": "1", "remarks": null, "users": [{ "userID": "27233", "referenceNumber": "1" }, { "userID": "27234", "referenceNumber": "2" }] }] </pre>
--	---

Response

Status	Response
200	Example response:- <pre> { "success": true, "status": true, "data": { "message": "Update Groups Success." }, "serverTime": "2017-04-10 11:04:05" } </pre>
400	The API is not called in POST request
500	<pre> { "success": false, "status": false, "data": { "message": "The following groupIDs not found! Not </pre>

	<pre>Updating. \n8466" }, "serverTime": "2017-04-10 11:05:17" }</pre>
500	<pre>{ "success": false, "status": false, "data": { "message": "There are some errors in your input, not inserting / updating.\n", "errors": [{ "row": 0, "errors": { "nameEng": ["Group Name (Eng) cannot be blank."] } }] }, "serverTime": "2017-04-10 11:09:54" }</pre>

8. Delete Groups

Delete Groups

Request

Method	URL
GET	api/deleteGroups

Parameters

Type	Params	Values
POST	groupID groupID[]	number array of numbers

groupID [Required]

The **groupID** of any specific groups

Response

Status	Response
200	Example response:- { "success": true, "status": true, "data": { "message": "1 group(s) are deleted." }, "serverTime": "2017-04-10 18:29:01" }
400	The API is not called in POST request

9. Get User ECA Records

Request

Method	URL
POST	api/getUsersECARecords

Parameters

Type	Params	Values
BODY	JSON	Username Object

Fields	JSON Sample
username [Required, array of usernames]	<pre>{ "username": ["S20005",] }</pre>

Response

Status	Response
200	<pre>{ "success": true, "status": true, "data": [{ "username": "S20005", "name": "Test Student", "ecaCode": "ECA001", "roleCode": "001" }, { "username": "S20005",</pre>

	<pre> "name": "Test Student", "ecaCode": "ECA002", "roleCode": null },], "serverTime": "2023-06-21 14:32:19", "page": 0, "total": 1 } }</pre>
400	The API is not called in POST request

10. Search Attendance Records

Request

Method	URL
POST	api/searchAttendanceRecords

Parameters

Type	Params	Values
BODY	JSON	Start Date End Date Username (Optional)

Fields	JSON Sample
startDate [Required, YYYY-MM-DD] endDate [Required, YYYY-MM-DD] username [Optional, array of usernames]	<pre>{ "startDate": "2024-04-30", "endDate": "2024-04-30", "username": ["S13003",] }</pre>

Response

Status	Response
200	<pre>{ "success": true, "status": true, "data": [{ "username": "S13003", "calendarDate": "2024-04-30", }] }</pre>

	<pre> "recordTime": "07:55:00", "session": "AM", "tapCount": 1, "status": "Present", "reason": null }, { "username": "S13003", "calendarDate": "2024-04-30", "recordTime": "13:45:59", "session": "PM", "tapCount": 3, "status": "Present", "reason": null },], "serverTime": "2024-04-30 18:01:24", "page": 0, "total": 1 } }</pre>
400	The API is not called in POST request or missing startDate / endDate

11. Send Notice Message

Request

Method	URL
POST	api/sendNoticeMessage

Parameters

Type	Params	Values
BODY	JSON	Array of Message Object

Fields	JSON Sample
<code>messageTypeID [Required]</code> <code>title [Required]</code> <code>body [Required]</code> <code>sendDate [optional]</code> <code>sendTime [optional]</code> <code>groups [optional, array of groups' nameEng]</code> <code>usernames [optional, array of users' username]</code>	<pre>{ "messageTypeID": "640", "title": "Test From API", "body": "<h1>Test from API</h1>", "sendDate": "2024-01-01", "sendTime": "12:00:00", "groups": ["1A"], "usernames": ["t001", "t002"] }</pre>

Note: If sendDate and sendTime are left empty, the message will be sent out immediately.

Response

Status	Response
200	<pre>{ "success": true, "serverTime": "2023-06-12 17:57:16" }</pre>
400	The API is not called in POST requests, or any field values invalid.

12. Get Message Reports

Request

Method	URL
POST	api/getMessageReports

Parameters

Type	Params	Values
POST	messageID	number

Response

Status	Response
200	<pre>{ "success": true, "status": true, "data": [{ "className": "1A", "班別": "1A", "學號": "1", "使用者名稱": "S19001", "顯示名稱(英文)": "Peter", "顯示名稱(繁中)": "Peter", "傳送時間": "2025-05-15 15:57:34", "使用者已讀取?": "否", "讀取時間": null, "家長使用者": "家長1 (P001)", "家長讀取時間": "2025-05-15 15:57:40", "已回覆?": "否", "回覆時間": null, "Q1": "" }], "serverTime": "2024-04-30 18:01:24", }</pre>

	<pre>"page": 0, "total": 1 }</pre>
400	The API is not called in POST request or missing startDate / endDate

Glossary

Conventions

- **Client** - Client application.
- **Status** - HTTP status code of response.
- All the possible responses are listed under 'Responses' for each method. Only one of them is issued per request server.
- All response are in JSON format.
- All request parameters are mandatory unless explicitly marked as [optional]
- The type of values accepted for a *request* parameter are shown the the values column like this [**10**|<any number>] .The | symbol means *OR*. If the parameter is [optional], the default value is shown in blue bold text, as **10** is written in [**10**|<any number>].

Status Codes

All status codes are standard HTTP status codes. The below ones are used in this API.

2XX - Success of some kind

4XX - Error occurred in client's part

5XX - Error occurred in server's part

Status Code	Description
200	OK
201	Created
202	Accepted (Request accepted, and queued for execution)
400	Bad request
401	Authentication failure
403	Forbidden
404	Resource not found

405	Method Not Allowed
409	Conflict
412	Precondition Failed
413	Request Entity Too Large
500	Internal Server Error
501	Not Implemented
503	Service Unavailable