


### PRODUCT



### DESCRIPTION

AN IN-LINE, DIRECT ACTING RELIEF VALVE WITH MALE JIC CONNECTIONS THAT LIMITS MAXIMUM SYSTEM PRESSURE OR MAINTAINS A DESIRED PRESSURE WITHIN A CIRCUIT.

### OPERATION

- FLOW FROM (1) TO (2) IS BLOCKED UNTIL THE SPECIFIED RELIEF PRESSURE SETTING HAS BEEN EXCEEDED.
- FLOW FROM (2) TO (1) IS ALWAYS BLOCKED.


### FEATURES

- STEEL COMPONENTS.
- CHROME BALL / HARDENED SEAT.
- LOW INTERNAL LEAKAGE.

### SPECIFICATIONS

OPERATING PRESSURE	5000 PSI
TEMPERATURE RANGE	250°F TO -40°F
RELIEF TOLERANCE	+/- 10%

### ORDERING INFORMATION



MODEL	INLET / OUTLET	THREAD	FLOW CAPACITY	L	HEX
4033X-608	-08 JIC	3/4-16	5 GPM	3.16	0.88

This document, as well as all catalogs, price lists and information provided by Vonberg Valve, Inc., is intended to provide product information for further consideration by users having substantial technical expertise due to the variety of operating conditions and applications for these valves, the user, through its own analysis, testing and evaluation, is solely responsible for making the final selection of the products and ensuring that all safety, warning and performance requirements of the application or use are met. The valves described herein, including without limitation, all component features, specifications, designs, pricing and availability, are subject to change at any time at the sole discretion of Vonberg Valve, Inc. without prior notification.

Page last updated: October 01, 2015



**Vonberg Valve, inc.**  
Hydraulic Valve Specialists

3800 Industrial Avenue • Rolling Meadows, IL 60008-1085 USA © 2015  
phone: 847/259-3800 • fax 847/259-3997 • email: info@vonberg.com