




PRODUCT



SCHEMATIC



TYPICAL PERFORMANCE



DESCRIPTION

AN IN-LINE STYLE CHECK VALVE INTENDED FOR BLOCKING FLUID FLOW.

OPERATION

- FLOW FROM (1) TO (2) IS ALLOWED WITH A STANDARD CRACK PRESSURE OF 3-5 PSI.
- FLOW FROM (2) TO (1) IS BLOCKED WITH A SPRING BIAS TO ASSIST IN STATIC AND LOW LOAD CONDITIONS.


FEATURES

- STEEL BODY AND POPPET.
- LOW INTERNAL LEAKAGE, 5 DPM.
- SPECIAL CRACK PRESSURES AVAILABLE UPON REQUEST.

SPECIFICATIONS

OPERATING PRESSURE	3500 PSI
TEMPERATURE RANGE	250° F TO -40° F
STANDARD CRACK PRESSURE	3-5 PSI

ORDERING INFORMATION



MODEL	INLET 1	OUTLET 2	THREAD	CAPACITY	L	T	HEX
1904FF	-04 JIC PORT	-04 JIC	7/16-20	2 GPM	1.72	0.530	0.625
1906FF	-06 JIC PORT	-06 JIC	9/16-18	4 GPM	1.94	0.545	0.750
1908FF	-08 JIC PORT	-08 JIC	3/4-16	8 GPM	1.88	0.635	0.938
1910FF	-10 JIC PORT	-10 JIC	7/8-14	12 GPM	2.38	0.760	1.125
1912FF	-12 JIC PORT	-12 JIC	1 1/16-12	20 GPM	2.50	0.860	1.375
1916FF	-16 JIC PORT	-16 JIC	1 5/16-12	40 GPM	3.19	0.880	1.625
1920FF	-20 JIC PORT	-20 JIC	1 5/8-12	50 GPM	4.00	0.950	2.000

This document, as well as all catalogs, price lists and information provided by Vonberg Valve, Inc., is intended to provide product information for further consideration by users having substantial technical expertise due to the variety of operating conditions and applications for these valves, the user, through its own analysis, testing and evaluation, is solely responsible for making the final selection of the products and ensuring that all safety, warning and performance requirements of the application or use are met. The valves described herein, including without limitation, all component features, specifications, designs, pricing and availability, are subject to change at any time at the sole discretion of Vonberg Valve, Inc. without prior notification.

Page last updated: February 13, 2015



Vonberg Valve, inc.
 Hydraulic Valve Specialists

3800 Industrial Avenue • Rolling Meadows, IL 60008-1085 USA © 2015
 phone: 847/259-3800 • fax 847/259-3997 • email: info@vonberg.com