

Safety Valves




PRODUCT



SCHEMATIC



TYPICAL PERFORMANCE



DESCRIPTION

AN IN-LINE, 90° SWIVEL ELBOW VELOCITY FUSE WITH AN NPTF OUTLET PORT THAT PROVIDES FULL-LINE SHUT-OFF IN THE EVENT OF A LINE FAILURE.

OPERATION

- A FLOW BELOW THE SPECIFIED LIMIT IS ALLOWED FROM (1) TO (2).
- FLOW ABOVE THE SPECIFIED LIMIT IS ASSUMED TO BE A LINE FAILURE AND IS BLOCKED.
- FLOW FROM (2) TO (1) PASSES THROUGH THE CONTROLLING ORIFICE BUT IS UNCONTROLLED.


FEATURES

- · STEEL COMPONENTS.
- FAIL SAFE DESIGN.
- · RAPID RESPONSE.
- POSITIVE CLOSE
- SWIVEL DESIGN FOR EASY ALIGNMENT.
- 90° ELBOW FOR LOW PROFILE APPLICATIONS.

SPECIFICATIONS

OPERATING PRESSURE	3500 PSI				
TEMPERATURE RANGE	250° F TO -40° F				
REOPENING DIFFERENTIAL	50 PSI				
CLOSING FLOW TOLERANCE	+15% / -0%				

ORDERING INFORMATION



Model	PORT 1	PORT 2	FLOW RANGE	L	Т	N	P (MIN)	SQ
8302	-06 SAE - 9/16-18	1/4-18 NPTF	0.2 TO 8.0 GPM	2.125	1.160	0.390	1.000	0.875
8303	-08 SAE - 3/4-16	3/8-18 NPTF	0.5 TO 15.0 GPM	2.555	1.430	0.550	1.250	1.000
8304	-10 SAE - 7/8-14	1/2-14 NPTF	1.0 TO 25.0 GPM	3.230	1.870	0.850	1.688	1.125
8306	-12 SAE - 1 1/16-12	3/4-14 NPTF	2.0 TO 40.0 GPM	3.625	2.065	0.905	1.980	1.375

This document, as well as all catalogs, price lists and information provided by Vonberg Valve, Inc., is intended to provide product information for further consideration by users having substantial technical expertise due to the variety of operating conditions and applications for these valves, the user, through its own analysis, testing and evaluation, is solely responsible for making the final selection of the products and ensuring that all safety, warning and performance requirements of the application or use are met. The valves described herein, including without limitation, all component features, specifications, designs, pricing and availability, are subject to change at any time at the sole discretion of Vonberg Valve, Inc. without prior notification.

Page last updated: February 19, 2015

