




PRODUCT



SCHEMATIC



TYPICAL PERFORMANCE



DESCRIPTION

AN IN-LINE STYLE CHECK VALVE INTENDED FOR BLOCKING FLUID FLOW.

OPERATION

- FLOW FROM (1) TO (2) IS ALLOWED WITH A STANDARD CRACK PRESSURE OF 3-5 PSI.
- FLOW FROM (2) TO (1) IS BLOCKED WITH A SPRING BIAS TO ASSIST IN STATIC AND LOW LOAD CONDITIONS.


FEATURES

- STEEL BODY AND POPPET.
- FULLY ENCAPSULATED SPRING.
- NO SNAP-RING.
- LOW INTERNAL LEAKAGE, 5 DPM.
- HIGH FLOW CAPACITY.
- SPECIAL CRACK PRESSURES AVAILABLE UPON REQUEST.

SPECIFICATIONS

OPERATING PRESSURE	5000 PSI
TEMPERATURE RANGE	250° F TO -40° F
STANDARD CRACK PRESSURE	3-5 PSI

ORDERING INFORMATION



MODEL	INLET 1	OUTLET 2	L	J	S	HEX
1104J	-04 ORS - 9/16-18	-04 SAE - 7/16-20	1.07	0.38	0.43	0.625
1106J	-06 ORS - 11/16-16	-06 SAE - 9/16-18	1.16	0.44	0.47	0.750
1108J	-08 ORS - 13/16-16	-08 SAE - 3/4-16	1.40	0.50	0.55	0.875
1110J	-10 ORS - 1-14	-10 SAE - 7/8-14	1.65	0.61	0.63	1.125
1112J	-12 ORS - 1 3/16-12	-12 SAE - 1 1/16-12	1.90	0.67	0.73	1.250

This document, as well as all catalogs, price lists and information provided by Vonberg Valve, Inc., is intended to provide product information for further consideration by users having substantial technical expertise due to the variety of operating conditions and applications for these valves, the user, through its own analysis, testing and evaluation, is solely responsible for making the final selection of the products and ensuring that all safety, warning and performance requirements of the application or use are met. The valves described herein, including without limitation, all component features, specifications, designs, pricing and availability, are subject to change at any time at the sole discretion of Vonberg Valve, Inc. without prior notification.

Page last updated: February 09, 2015



Vonberg Valve, inc.
Hydraulic Valve Specialists

3800 Industrial Avenue • Rolling Meadows, IL 60008-1085 USA © 2015
phone: 847/259-3800 • fax 847/259-3997 • email: info@vonberg.com