




PRODUCT



SCHEMATIC



TYPICAL PERFORMANCE



DESCRIPTION

AN IN-LINE STYLE, POPPET TYPE CHECK VALVE INTENDED FOR BLOCKING FLUID FLOW.

OPERATION

- FLOW FROM (1) TO (2) IS ALLOWED WITH A STANDARD CRACK PRESSURE OF 3-5 PSI.
- FLOW FROM (2) TO (1) IS BLOCKED WITH A SPRING BIAS TO ASSIST IN STATIC AND LOW LOAD CONDITIONS.


FEATURES

- STEEL BODY AND HARDENED POPPET.
- METAL TO METAL SEAT
- . LOW PRESSURE DROP.
- EXTERNAL O-RING INCLUDED (EXCEPT MODEL 14101).
- SPECIAL CRACK PRESSURES AVAILABLE UPON REQUEST.
- *MODEL 14101 REQUIRES AND EXTERNAL SEAL #008 AT INLET CHAMFER.

SPECIFICATIONS

OPERATING PRESSURE	3500 PSI
TEMPERATURE RANGE	250° F TO -40° F
STANDARD CRACK PRESSURE	3-5 PSI

ORDERING INFORMATION



MODEL	FLOW RANGE	Α	С	L	REC. BORE DIA.	ASSEMBLED GAP
14101*	0.1 TO 1.0 GPM	0.306 / 0.311	0.172	0.620 / 0.630	0.3125 / 0.3145	0.015 / 0.025
14103	1.0 TO 5.0 GPM	0.494 / 0.499	0.420	0.835 / 0.845	0.5000 / 0.5020	0.015 / 0.025
14106	2.0 TO 10.0 GPM	0.650 / 0.655	0.500	1.215 / 1.225	0.6562 / 0.6582	0.015 / 0.025
14108	5.0 TO 20.0 GPM	0.806 / 0.811	0.640	1.490 / 1.500	0.8125 / 0.8145	0.015 / 0.025

This document, as well as all catalogs, price lists and information provided by Vonberg Valve, Inc., is intended to provide product information for further consideration by users having substantial technical expertise due to the variety of operating conditions and applications for these valves, the user, through its own analysis, testing and evaluation, is solely responsible for making the final selection of the products and ensuring that all safety, warning and performance requirements of the application or use are met. The valves described herein, including without limitation, all component features, specifications, designs, pricing and availability, are subject to change at any time at the sole discretion of Vonberg Valve, Inc. without prior notification.

Page last updated: February 09, 2015

