



PRODUCT



SCHEMATIC



TYPICAL PERFORMANCE



DESCRIPTION

AN IN-LINE STYLE CHECK VALVE INTENDED FOR BLOCKING FLUID FLOW.

OPERATION

- FLOW FROM (1) TO (2) IS ALLOWED WITH A STANDARD CRACK PRESSURE OF 3-5 PSI.
- FLOW FROM (2) TO (1) IS BLOCKED WITH A SPRING BIAS TO ASSIST IN STATIC AND LOW LOAD CONDITIONS.

FEATURES

- STEEL BODY AND POPPET.
- LOW INTERNAL LEAKAGE, 5 DPM.
- SPECIAL CRACK PRESSURES AVAILABLE UPON REQUEST.

SPECIFICATIONS

OPERATING PRESSURE	5000 PSI
TEMPERATURE RANGE	250° F TO -40° F
STANDARD CRACK PRESSURE	3-5 PSI

ORDERING INFORMATION

19	XX	J	XX
SERIES NUMBER _____ THREAD SIZE _____ CRACK PRESSURE (PSI) _____ (IF NON-STANDARD) ORIFICE DIAMETER (0.001") _____ (OPTIONAL)			

MODEL	INLET 1	OUTLET 2	CAPACITY	L	J	S	HEX
1904J	-04 ORS - 9/16-18	-04 SAE - 7/16-20	2 GPM	1.06	0.38	0.43	0.625
1906J	-06 ORS - 11/16-16	-06 SAE - 9/16-18	4 GPM	1.42	0.44	0.47	0.750
1908J	-08 ORS - 13/16-16	-08 SAE - 3/4-16	8 GPM	1.42	0.50	0.55	0.875
1910J	-10 ORS - 1-14	-10 SAE - 7/8-14	12 GPM	1.62	0.61	0.63	1.125
1912J	-12 ORS - 1 3/16-12	-12 SAE - 1 1/16-12	30 GPM	2.00	0.67	0.73	1.250
1916J	-16 ORS - 1 7/16-12	-16 SAE - 1 5/16-12	40 GPM	2.27	0.69	0.73	1.500
1920J	-20 ORS - 1 11/16-12	-20 SAE - 1 5/8-12	50 GPM	2.40	0.69	0.73	1.875

This document, as well as all catalogs, price lists and information provided by Vonberg Valve, Inc., is intended to provide product information for further consideration by users having substantial technical expertise due to the variety of operating conditions and applications for these valves, the user, through its own analysis, testing and evaluation, is solely responsible for making the final selection of the products and ensuring that all safety, warning and performance requirements of the application or use are met. The valves described herein, including without limitation, all component features, specifications, designs, pricing and availability, are subject to change at any time at the sole discretion of Vonberg Valve, Inc. without prior notification.

Page last updated: February 13, 2015

