

Flow Regulating Valves
CARTRIDGE
2400 SERIES
NON-ADJUSTABLE

## **PRODUCT**



# **DESCRIPTION**

A NON-ADJUSTABLE, CARTRIDGE STYLE, PRESSURE-COMPENSATED, FLOW REGULATOR INTENDED FOR FIXED DISPLACEMENT HYDRAULIC CIRCUIT APPLICATIONS.

# **OPERATION**

- THIS REGULATOR WILL MAINTAIN A CONSTANT FLOW RATE FROM (1) TO (2) THROUGHOUT A SPECIFIED PRESSURE RANGE.
- REVERSE FLOW PASSES THROUGH THE CONTROLLING ORIFICE AND IS UNCONTROLLED PRODUCING A PRESSURE DIFFERENTIAL OF 120 PSI MAX. AT 150% OF CONTROLLED FLOW.


#### **FEATURES**

- S.I.D. SURGES INTERNALLY DAMPENED FEATURE IS OPTIONAL FOR LOAD LOWERING APPLICATIONS.
- · STEEL BODY, STEEL INTERNALS.
- HYDRAULIC FLUIDS GENERAL.
- INDUSTRY COMMON CAVITY.

## **SPECIFICATIONS**

PRESSURE RANGE	50 PSI TO 3500 PSI
TEMPERATURE RANGE	250°F TO -40°F
FLOW TOLERANCE	+/- 10% (+/- 15% UNDER 1.5 GPM)

#### ORDERING INFORMATION



Model	THREAD	FLOW RANGE	CAVITY	L1	L2	HEX	Α	TORQUE
2404	7/16 - 20	0.4 TO 2.0 GPM	VC04-2	0.94	0.55	0.56	0.277 / 0.278	10 ft-lbs
2406	9/16 - 18	0.4 TO 4.0 GPM	FC06-2	0.84	0.53	0.69	0.467 / 0.468	15 ft-lbs
2408	3/4 - 16	0.4 TO 8.0 GPM	VC08-2	1.10	0.85	0.88	0.495 / 0.497	20 ft-lbs
2410	7/8 - 14	0.5 TO 10.0 GPM	VC10-2	1.25	0.80	1.00	0.621 / 0.623	25 ft-lbs
2412	1 1/16 - 12	2.0 TO 20.0 GPM	VC12-2	1.81	1.35	1.25	0.870 / 0.873	40 ft-lbs
2416	1 5/16 - 12	2.0 TO 30.0 GPM	VC16-2	1.75	1.35	1.50	1.121 / 1.123	60 ft-lbs

This document, as well as all catalogs, price lists and information provided by Vonberg Valve, Inc., is intended to provide product information for further consideration by users having substantial technical expertise due to the variety of operating conditions and applications for these valves, the user, through its own analysis, testing and evaluation, is solely responsible for making the final selection of the products and ensuring that all safety, warning and performance requirements of the application or use are met. The valves described herein, including without limitation, all component features, specifications, designs, pricing and availability, are subject to change at any time at the sole discretion of Vonberg Valve, Inc. without prior notification.

Page last updated: June 07, 2017

