




#### **PRODUCT**



#### **SCHEMATIC**



# **TYPICAL PERFORMANCE**



# **DESCRIPTION**

AN IN-LINE STYLE CHECK VALVE INTENDED FOR BLOCKING FLUID FLOW.

### **OPERATION**

- FLOW FROM (1) TO (2) IS ALLOWED WITH A STANDARD CRACK PRESSURE OF 3-5 PSI.
- FLOW FROM (2) TO (1) IS BLOCKED WITH A SPRING BIAS TO ASSIST IN STATIC AND LOW LOAD CONDITIONS.


## **FEATURES**

- STEEL BODY AND POPPET.
- LOW INTERNAL LEAKAGE, 5 DPM.
- SPECIAL CRACK PRESSURES AVAILABLE UPON REQUEST.

#### **SPECIFICATIONS**

| OPERATING PRESSURE      | 3500 PSI         |  |  |  |  |
|-------------------------|------------------|--|--|--|--|
| TEMPERATURE RANGE       | 250° F TO -40° F |  |  |  |  |
| STANDARD CRACK PRESSURE | 3-5 PSI          |  |  |  |  |

#### ORDERING INFORMATION



| MODEL | INLET 1 | OUTLET 2 | THREAD    | CAPACITY | L    | Т     | S     | HEX   |
|-------|---------|----------|-----------|----------|------|-------|-------|-------|
| 1904F | -04 JIC | -04 SAE  | 7/16-20   | 2 GPM    | 1.23 | 0.540 | 0.360 | 0.562 |
| 1906F | -06 JIC | -06 SAE  | 9/16-18   | 4 GPM    | 1.45 | 0.540 | 0.390 | 0.750 |
| 1908F | -o8 JIC | -08 SAE  | 3/4-16    | 8 GPM    | 1.47 | 0.655 | 0.440 | 0.875 |
| 1910F | -10 JIC | -10 SAE  | 7/8-14    | 12 GPM   | 1.62 | 0.760 | 0.500 | 1.000 |
| 1912F | -12 JIC | -12 SAE  | 1 1/16-12 | 30 GPM   | 2.00 | 0.860 | 0.594 | 1.250 |
| 1916F | -16 JIC | -16 SAE  | 1 5/16-12 | 40 GPM   | 2.27 | 0.910 | 0.594 | 1.500 |
| 1920F | -20 JIC | -20 SAE  | 1 5/8-12  | 50 GPM   | 2.75 | 0.960 | 0.594 | 1.875 |
| 1924F | -24 JIC | -24 SAE  | 1 7/8-12  | 80 GPM   | 3.50 | 1.080 | 0.594 | 2.125 |

This document, as well as all catalogs, price lists and information provided by Vonberg Valve, Inc., is intended to provide product information for further consideration by users having substantial technical expertise due to the variety of operating conditions and applications for these valves, the user, through its own analysis, testing and evaluation, is solely responsible for making the final selection of the products and ensuring that all safety, warning and performance requirements of the application or use are met. The valves described herein, including without limitation, all component features, specifications, designs, pricing and availability, are subject to change at any time at the sole discretion of Vonberg Valve, Inc. without prior notification.

Page last updated: February 13, 2015

