




PRODUCT



SCHEMATIC



TYPICAL PERFORMANCE



DESCRIPTION

AN IN-LINE VELOCITY FUSE WITH A FEMALE NPTF INLET AND A MALE NPTF OUTLET THAT PROVIDES FULL-LINE SHUT-OFF IN THE EVENT OF A LINE FAILURE.

OPERATION

- A FLOW BELOW THE SPECIFIED LIMIT IS ALLOWED FROM (1) TO (2).
- FLOW ABOVE THE SPECIFIED LIMIT IS ASSUMED TO BE A LINE FAILURE AND IS BLOCKED.
- FLOW FROM (2) TO (1) PASSES THROUGH THE CONTROLLING ORIFICE BUT IS UNCONTROLLED.

FEATURES

- STEEL COMPONENTS.
- FAIL SAFE DESIGN.
- RAPID RESPONSE.

SPECIFICATIONS

OPERATING PRESSURE	3500 PSI
TEMPERATURE RANGE	250° F TO -40° F
REOPENING DIFFERENTIAL	50 PSI
CLOSING FLOW TOLERANCE	+15% / -0%

ORDERING INFORMATION

28901-1XX-XX			
SERIES NUMBER	28901	1	XX
PORT SIZE		XX	XX
CLOSING FLOW (GPM)			

Model	INLET 1	OUTLET 2	FLOW RANGE	L	HEX
28901-102	1/4-18 NPTF PORT	1/4-18 NPTF	0.5 TO 10.0 GPM	2.85	0.750
28901-103	3/8-18 NPTF PORT	3/8-18 NPTF	1.0 TO 25.0 GPM	3.25	0.785
28901-104	1/2-14 NPTF PORT	1/2-14 NPTF	2.0 TO 40.0 GPM	3.30	1.125
28901-106	3/4-14 NPTF PORT	3/4-14 NPTF	2.0 TO 50.0 GPM	3.65	1.375

This document, as well as all catalogs, price lists and information provided by Vonberg Valve, Inc., is intended to provide product information for further consideration by users having substantial technical expertise due to the variety of operating conditions and applications for these valves, the user, through its own analysis, testing and evaluation, is solely responsible for making the final selection of the products and ensuring that all safety, warning and performance requirements of the application or use are met. The valves described herein, including without limitation, all component features, specifications, designs, pricing and availability, are subject to change at any time at the sole discretion of Vonberg Valve, Inc. without prior notification.

Page last updated: February 19, 2015



Vonberg Valve, inc.
 Hydraulic Valve Specialists

3800 Industrial Avenue • Rolling Meadows, IL 60008-1085 USA © 2015
 phone: 847/259-3800 • fax 847/259-3997 • email: info@vonberg.com