




PRODUCT



SCHEMATIC



TYPICAL PERFORMANCE



DESCRIPTION

AN IN-LINE, DIRECT ACTING RELIEF VALVE THAT LIMITS MAXIMUM SYSTEM PRESSURE OR MAINTAINS A DESIRED PRESSURE WITHIN A CIRCUIT.

OPERATION

- FLOW FROM (1) TO (2) IS BLOCKED UNTIL THE SPECIFIED RELIEF PRESSURE SETTING HAS BEEN EXCEEDED.
- FLOW FROM (2) TO (1) IS ALWAYS BLOCKED.

FEATURES

- STEEL COMPONENTS.
- CHROME STEEL BALL / HARDENED SEAT.
- LOW INTERNAL LEAKAGE.

SPECIFICATIONS

OPERATING PRESSURE	5000 PSI
TEMPERATURE RANGE	250°F TO -40°F
RELIEF TOLERANCE	+/- 10%

ORDERING INFORMATION

	4030	X	-	10	X	-	XX
SERIES NUMBER							
PRESSURE RANGE							
1.....	10 – 150 PSI						
2.....	180 – 1000 PSI						
3.....	800 – 3000 PSI						
4.....	3000 – 4000 PSI						
5.....	4000 – 5000 PSI						
FEMALE NPTF / FEMALE NPTF							
THREAD SIZE							
RELIEF PRESSURE (PSI)							

MODEL	INLET / OUTLET	L	HEX
4030X-102	1/4-18 NPTF	3.85	0.750
4030X-103	3/8-18 NPTF	3.65	0.875
4030X-104	1/2-14 NPTF	4.50	1.125

This document, as well as all catalogs, price lists and information provided by Vonberg Valve, Inc., is intended to provide product information for further consideration by users having substantial technical expertise due to the variety of operating conditions and applications for these valves, the user, through its own analysis, testing and evaluation, is solely responsible for making the final selection of the products and ensuring that all safety, warning and performance requirements of the application or use are met. The valves described herein, including without limitation, all component features, specifications, designs, pricing and availability, are subject to change at any time at the sole discretion of Vonberg Valve, Inc. without prior notification.

Page last updated: January 19, 2015



Vonberg Valve, Inc.
Hydraulic Valve Specialists

3800 Industrial Avenue • Rolling Meadows, IL 60008-1085 USA © 2015
phone: 847/259-3800 • fax 847/259-3997 • email: info@vonberg.com