


CONNECTION IMAGE



CONNECTION DETAILS / PERFORMANCE

SEE **SAE J514** – HYDRAULIC TUBE FITTINGS

SEE **SAE J1926** – CONNECTIONS FOR GENERAL USE AND FLUID POWER – PORTS AND STUD ENDS WITH ISO 725 THREADS AND O-RING SEALING.

CAUTIONS

- ⚠ **USE WRENCHES WITH FLAT ENGAGEMENT SURFACES (i.e. – OPEN END OR CRESCENT WRENCH), PIPE WRENCHES CAN DAMAGE VALVE BODY!**
- ⚠ **USING WRENCH HANDLE EXTENSIONS OR “CHEATER BARS” CAN LEAD TO OVER-TORQUE OF CONNECTION AND VALVE DAMAGE, MALFUNCTION, OR FAILURE!**
- ⚠ **WRENCH TO BE POSITIONED AS CLOSE TO THREADS AS POSSIBLE TO PREVENT SIDE LOAD ON THREADS!**

DESCRIPTION

1. INSPECT MALE AND FEMALE THREADS, PORT AND MATING SURFACES, AND O-RING (IF APPLICABLE) TO ENSURE THAT ALL ARE FREE OF BURRS, NICKS, SCRATCHES OR ANY FOREIGN MATERIAL.
2. LUBRICATE O-RING WITH LIGHT COATING OF SYSTEM FLUID OR COMPATIBLE OIL.
3. SCREW THE VALVE INTO THE MATING PORT OR FITTING UNTIL THE O-RING(S) IS FULLY ENGAGED. LIGHT WRENCHING MAY BE NECESSARY.

NOTE: IF THREADING BECOMES DIFFICULT BEFORE O-RING(S) IS ENGAGED, UN-SCREW VALVE AND ENSURE COMPONENTS ARE NOT CROSS-THREADED OR DAMAGED.

4. TIGHTEN TO RECOMMENDED TORQUE FOR THE CORRESPONDING THREAD SIZE FROM THE TABLE BELOW.

NOTE: TORQUE RECOMMENDATIONS BELOW ARE FOR VALVE CONNECTED TO A COMPATIBLE FITTING, ADAPTER, OR BLOCK. IF VALVE IS CONNECTED TO FEMALE SWIVEL CONNECTION, REFER TO SWIVEL MANUFACTURER'S TORQUE RECOMMENDATION FOR THAT JOINT.

PORT SIZE	THREAD SIZE	ASSEMBLY TORQUE (ft.-lbs.) +10% / -0	HEX (TYPICAL) (in.)	
			MALE → MALE	FEMALE → FEMALE / MALE
-04	7/16 – 20 UNF	10	0.562	0.625
-06	9/16 – 18 UNF	15	0.750	0.750
-08	3/4 – 16 UNF	20	0.875	0.938
-10	7/8 – 14 UNF	25	1.000	1.125
-12	1 1/16 – 12 UN	40	1.250	1.375
-16	1 5/16 – 12 UN	60	1.500	1.625
-20	1 5/8 – 12 UN	85	1.875	2.000
-24	1 7/8 – 12 UN	110	2.125	2.250

This document, as well as all catalogs, price lists and information provided by Vonberg Valve, Inc., is intended to provide product information for further consideration by users having substantial technical expertise due to the variety of operating conditions and applications for these valves, the user, through its own analysis, testing and evaluation, is solely responsible for making the final selection of the products and ensuring that all safety, warning and performance requirements of the application or use are met. The valves described herein, including without limitation, all component features, specifications, designs, pricing and availability, are subject to change at any time at the sole discretion of Vonberg Valve, Inc. without prior notification.