



ANALYZING POLICE ACTIVITY WITH PANDAS

Stanford Open Policing Project dataset

Kevin Markham

Founder, Data School



Introduction to the dataset

- Traffic stops by police officers



- Download data for any state: <https://openpolicing.stanford.edu/>



Preparing the data

- Examine the data
- Clean the data

```
import pandas as pd

ri = pd.read_csv('police.csv')

ri.head()
```

	state	stop_date	stop_time	county_name	driver_gender	driver_race
0	RI	2005-01-04	12:55	NaN	M	White
1	RI	2005-01-23	23:15	NaN	M	White
2	RI	2005-02-17	04:15	NaN	M	White
3	RI	2005-02-20	17:15	NaN	M	White
4	RI	2005-02-24	01:20	NaN	F	White
...						

- Each row represents one traffic stop
- NaN indicates a missing value



Locating missing values

```
ri.isnull()

   state stop_date stop_time county_name driver_gender driver_race
0  False      False      False         True          False        False
1  False      False      False         True          False        False
2  False      False      False         True          False        False
3  False      False      False         True          False        False
...

ri.isnull().sum()

state                0
stop_date            0
stop_time            0
county_name        91741
driver_gender       5205
driver_race        5202
...
```

- `sum()` calculates the sum of each column
- `True = 1, False = 0`



Dropping a column

```
ri.isnull().sum()
```

```
state                0
stop_date            0
stop_time            0
county_name        91741
driver_gender        5205
driver_race         5202
...
```

```
ri.shape
(91741, 15)
```

- county_name column only contains missing values
- Drop county_name using the drop() method

```
ri.drop('county_name', axis='columns', inplace=True)
```



Dropping rows

- `dropna()`: Drop rows based on the presence of missing values

```
ri.head()
```

	state	stop_date	stop_time	driver_gender	driver_race
0	RI	2005-01-04	12:55	M	White
1	RI	2005-01-23	23:15	M	White
2	RI	2005-02-17	04:15	M	White
3	RI	2005-02-20	17:15	M	White
4	RI	2005-02-24	01:20	F	White
...					

```
ri.dropna(subset=['stop_date', 'stop_time'], inplace=True)
```



ANALYZING POLICE ACTIVITY WITH PANDAS

Let's practice!



ANALYZING POLICE ACTIVITY WITH PANDAS

Using proper data types

Kevin Markham

Founder, Data School



Examining the data types

```
ri.dtypes

stop_date           object
stop_time           object
driver_gender       object
driver_race         object
violation_raw       object
violation           object
search_conducted    bool
search_type         object
stop_outcome        object
is_arrested         object
stop_duration       object
drugs_related_stop  bool
district           object
dtype: object
```

- object: Python strings (or other Python objects)
- bool: True and False values
- Other types: int, float, datetime, category



Why do data types matter?

- Affects which operations you can perform
- Avoid storing data as strings (when possible)
 - int, float: enables mathematical operations
 - datetime: enables date-based attributes and methods
 - category: uses less memory and runs faster
 - bool: enables logical and mathematical operations



Fixing a data type

```
apple
```

```
   date    time  price
0  2/13/18  16:00  164.34
1  2/14/18  16:00  167.37
2  2/15/18  16:00  172.99
```

```
apple.price.dtype
dtype('O')
```

```
apple['price'] = apple.price.astype('float')
```

```
apple.price.dtype
dtype('float64')
```

- Dot notation: `apple.price`
- Bracket notation: `apple['price']`
 - Must be used on the left side of an assignment statement



ANALYZING POLICE ACTIVITY WITH PANDAS

Let's practice!



ANALYZING POLICE ACTIVITY WITH PANDAS

Creating a DatetimeIndex

Kevin Markham

Founder, Data School



Using datetime format

```
ri.head()

   stop_date stop_time driver_gender driver_race
0  2005-01-04    12:55             M        White
1  2005-01-23    23:15             M        White
2  2005-02-17    04:15             M        White
3  2005-02-20    17:15             M        White
4  2005-02-24    01:20             F        White
...

ri.dtypes

stop_date      object
stop_time      object
driver_gender   object
driver_race     object
...
```

1. Combine stop_date and stop_time into one column
2. Convert it to datetime format



Combining object columns

```
apple
```

```
   date    time  price
0 2/13/18 16:00 164.34
1 2/14/18 16:00 167.37
2 2/15/18 16:00 172.99
```

```
apple.date.str.replace('/', '-')
```

```
0    2-13-18
1    2-14-18
2    2-15-18
Name: date, dtype: object
```

```
combined = apple.date.str.cat(apple.time, sep=' ')
```

```
combined
```

```
0    2/13/18 16:00
1    2/14/18 16:00
2    2/15/18 16:00
Name: date, dtype: object
```



Converting to datetime format

```
apple['date_and_time'] = pd.to_datetime(combined)
```

```
apple
```

	date	time	price	date_and_time
0	2/13/18	16:00	164.34	2018-02-13 16:00:00
1	2/14/18	16:00	167.37	2018-02-14 16:00:00
2	2/15/18	16:00	172.99	2018-02-15 16:00:00

```
apple.dtypes
```

date	object
time	object
price	float64
date_and_time	datetime64[ns]
dtype:	object



Setting the index

```
apple.set_index('date_and_time', inplace=True)
```

```
apple
```

	date	time	price
date_and_time			
2018-02-13 16:00:00	2/13/18	16:00	164.34
2018-02-14 16:00:00	2/14/18	16:00	167.37
2018-02-15 16:00:00	2/15/18	16:00	172.99

```
apple.index
```

```
DatetimeIndex(['2018-02-13 16:00:00', '2018-02-14 16:00:00',  
               '2018-02-15 16:00:00'],  
              dtype='datetime64[ns]', name='date_and_time', freq=None)
```

```
apple.columns
```

```
Index(['date', 'time', 'price'], dtype='object')
```



ANALYZING POLICE ACTIVITY WITH PANDAS

Let's practice!