

Codebook

July 30, 2023

Contents

1 Setup	1	8.4 FFT	12
1.1 Template	1	8.5 NTT	13
1.2 vimrc	2	8.6 GeneratingFunctions	14
2 Data-structure	2	8.7 Numbers	14
2.1 PBDS	2	8.8 Theorem	14
2.2 SparseTable	2		
2.3 SegmentTree	2	1 Setup	
2.4 LazyTagSegtree	3	1.1 Template	
2.5 LiChaoTree	3		
2.6 Treap	4		
2.7 DSU	5		
2.8 RollbackDSU	5		
3 Graph	5		
3.1 RoundSquareTree	5		
3.2 SCC	6		
3.3 2SAT	6		
3.4 Bridge	6		
3.5 BronKerboschAlgorithm	6		
3.6 Theorem	7		
4 Tree	7		
4.1 HLD	7		
5 Geometry	7		
5.1 Point	7		
5.2 Geometry	8		
5.3 ConvexHull	8		
5.4 Theorem	9		
6 String	9		
6.1 RollingHash	9		
6.2 SuffixArray	9		
6.3 KMP	10		
6.4 Trie	10		
6.5 Zvalue	10		
7 Flow	11		
7.1 Dinic	11		
7.2 MCMF	11		
8 Math	12		
8.1 FastPow	12		
8.2 EXGCD	12		
8.3 EXCRT	12		

```

1 #include <bits/stdc++.h>
2 #include <bits/extc++.h>
3 #define F first
4 #define S second
5 #define pb push_back
6 #define pob pop_back
7 #define pf push_front
8 #define pof pop_front
9 #define mp make_pair
10 #define mt make_tuple
11 #define all(x) (x).begin(),(x).end()
12 #define mem(x,i) memset((x),(i),sizeof((x)))
13 using namespace std;
14 //using namespace __gnu_pbds;
15 using pii = pair<long long,long long>;
16 using ld = long double;
17 using ll = long long;
18 mt19937 mtrd(chrono::steady_clock::now() \
19 .time_since_epoch().count());
20 const int mod = 1000000007;
21 const int mod2 = 998244353;
22 const ld PI = acos(-1);
23 #define Bint __int128
24 #define int long long
25 namespace DEBUG{
26 template <typename T, typename T2>
27 ostream& operator<<(ostream& os, const pair<T,
28   T2>& pr) {
29   os << "(" << pr.first << ", " << pr.second <<
30   ")";
31   return os;
32 }
33 template <typename T>
34 inline void _printv(T l, T r){
35   cerr << "DEBUG: [ ";
36   for(; l != r; l++){
37     cerr << *l << ", ";
38   }
39   cerr << "]" << endl;
40 }
41 template <typename T>
42 inline void _debug(const char* format, T t) {
43   cerr << format << '=' << t << endl;

```

```

41 }
42 template <class First, class... Rest>
43 inline void _debug(const char* format, First
↪ first, Rest... rest) {
44     while (*format != ',')
45         cerr << *format++;
46     cerr << '=' << first << ", ";
47     _debug(format + 1, rest...);
48 }
49 #define TEST
50 #ifdef TEST
51 #define printv(x, y) _printv(x, y)
52 #define debug(...) cerr << "DEBUG:
↪ ", _debug(__VA_ARGS__, __VA_ARGS__)
53 #else
54 #define debug(...) void(0)
55 #define printv(x, y) void(0)
56 #endif
57 } // namespace DEBUG
58 using namespace DEBUG;
59 /* ----- */
60 void solve(){
61 }
62 signed main(){
63     ios::sync_with_stdio(0);
64     cin.tie(0);
65     int t = 1;
66     // cin >> t;
67     while(t--)
68         solve();
69 }

```

1.2 vimrc

```

1 syntax on
2 set mouse=a
3 set nu
4 set ts=4
5 set sw=4
6 set smartindent
7 set cursorline
8 set hlsearch
9 set incsearch
10 set t_Co=256
11 noremap y ggyG
12 colorscheme afterglow
13 au BufNewFile *.cpp Or ~/default_code/default.cpp |
↪ let IndentStyle = "cpp"

```

2 Data-structure

2.1 PBDS

```

1 gp_hash_table<T, T> h;
2 tree<T, null_type, less<T>, rb_tree_tag,
↪ tree_order_statistics_node_update> tr;
3 tr.order_of_key(x); // find x's ranking
4 tr.find_by_order(k); // find k-th minimum, return
↪ iterator

```

2.2 SparseTable

```

1 template <class T, T (*op)(T, T)> struct
↪ SparseTable{
2     // idx: [0, n - 1]
3     int n;
4     T id;
5     vector<vector<T>>tbl;
6     T query(int l, int r){
7         int lg = __lg(r - l + 1);
8         return op(tbl[lg][l], tbl[lg][r - (1 << lg) +
↪ 1]);
9     }
10     SparseTable(): n(0) {}
11     SparseTable(int _n, vector<T>&arr, T _id) {
12         n = _n;
13         id = _id;
14         int lg = __lg(n) + 2;
15         tbl.resize(lg, vector<T>(n + 5, id));
16         for(int i = 0; i < n; i++)
17             tbl[0][i] = arr[i];
18         for(int i = 1; i <= lg; i++)
19             for(int j = 0; j + (1 << (i - 1)) < n; j++)
20                 tbl[i][j] = op(tbl[i - 1][j], tbl[i - 1][j
↪ + (1 << (i - 1))]);
21     }
22     SparseTable(int _n, T *arr, T _id) {
23         n = _n;
24         id = _id;
25         int lg = __lg(n) + 2;
26         tbl.resize(lg, vector<T>(n + 5, id));
27         for(int i = 0; i < n; i++)
28             tbl[0][i] = arr[i];
29         for(int i = 1; i <= lg; i++)
30             for(int j = 0; j + (1 << (i - 1)) < n; j++)
31                 tbl[i][j] = op(tbl[i - 1][j], tbl[i - 1][j
↪ + (1 << (i - 1))]);
32     }
33 };

```

2.3 SegmentTree

```

1 template <class T, T (*op)(T, T)> struct
↪ Segment_tree{
2     int L, R;
3     T id;
4     vector<T>seg;
5     void _modify(int p, T v, int l, int r, int idx =
↪ 1){
6         assert(p <= r && p >= 1);
7         if(l == r){
8             seg[idx] = v;
9             return;
10        }
11        int mid = (l + r) >> 1;
12        if(p <= mid)
13            _modify(p, v, l, mid, idx << 1);
14        else
15            _modify(p, v, mid + 1, r, idx << 1 | 1);
16        seg[idx] = op(seg[idx << 1], seg[idx << 1 |
↪ 1]);
17    }

```

```

18 T _query(int ql, int qr, int l, int r, int idx =
   ↳ 1){
19     if(ql == l && qr == r)
20         return seg[idx];
21     int mid = (l + r) >> 1;
22     if(qr <= mid)
23         return _query(ql, qr, l, mid, idx << 1);
24     else if(ql > mid)
25         return _query(ql, qr, mid + 1, r, idx << 1 |
   ↳ 1);
26     return op(_query(ql, mid, l, mid, idx << 1),
   ↳ _query(mid + 1, qr, mid + 1, r, idx << 1 | 1));
27 }
28 void modify(int p, T v){ _modify(p, v, L, R, 1);
   ↳ }
29 T query(int l, int r){ return _query(l, r, L, R,
   ↳ 1); }
30 Segment_tree(): Segment_tree(0, 0, 0) {}
31 Segment_tree(int l, int r, T _id): L(l), R(r) {
32     id = _id;
33     seg.resize(4 * (r - l + 10));
34     fill(seg.begin(), seg.end(), id);
35 }
36 };

```

2.4 LazyTagSegtree

```

1 struct segment_tree{
2     int seg[N << 2];
3     int tag1[N << 2], tag2[N << 2];
4     void down(int l, int r, int idx, int pidx){
5         int v = tag1[pidx], vv = tag2[pidx];
6         if(v)
7             tag1[idx] = v, seg[idx] = v * (r - l + 1),
   ↳ tag2[idx] = 0;
8         if(vv)
9             tag2[idx] += vv, seg[idx] += vv * (r - l +
   ↳ 1);
10    }
11    void Set(int l, int r, int ql, int qr, int v, int
   ↳ idx = 1){
12        if(ql == l && qr == r){
13            tag1[idx] = v;
14            tag2[idx] = 0;
15            seg[idx] = v * (r - l + 1);
16            return;
17        }
18        int mid = (l + r) >> 1;
19        down(l, mid, idx << 1, idx);
20        down(mid + 1, r, idx << 1 | 1, idx);
21        tag1[idx] = tag2[idx] = 0;
22        if(qr <= mid)
23            Set(l, mid, ql, qr, v, idx << 1);
24        else if(ql > mid)
25            Set(mid + 1, r, ql, qr, v, idx << 1 | 1);
26        else{
27            Set(l, mid, ql, mid, v, idx << 1);
28            Set(mid + 1, r, mid + 1, qr, v, idx << 1 |
   ↳ 1);
29        }
30        seg[idx] = seg[idx << 1] + seg[idx << 1 | 1];
31    }

```

```

32 void Increase(int l, int r, int ql, int qr, int
   ↳ v, int idx = 1){
33     if(ql == l && qr == r){
34         tag2[idx] += v;
35         seg[idx] += v * (r - l + 1);
36         return;
37     }
38     int mid = (l + r) >> 1;
39     down(l, mid, idx << 1, idx);
40     down(mid + 1, r, idx << 1 | 1, idx);
41     tag1[idx] = tag2[idx] = 0;
42     if(qr <= mid)
43         Increase(l, mid, ql, qr, v, idx << 1);
44     else if(ql > mid)
45         Increase(mid + 1, r, ql, qr, v, idx << 1 |
   ↳ 1);
46     else{
47         Increase(l, mid, ql, mid, v, idx << 1);
48         Increase(mid + 1, r, mid + 1, qr, v, idx << 1
   ↳ | 1);
49     }
50     seg[idx] = seg[idx << 1] + seg[idx << 1 | 1];
51 }
52 int query(int l, int r, int ql, int qr, int idx =
   ↳ 1){
53     if(ql == l && qr == r)
54         return seg[idx];
55     int mid = (l + r) >> 1;
56     down(l, mid, idx << 1, idx);
57     down(mid + 1, r, idx << 1 | 1, idx);
58     tag1[idx] = tag2[idx] = 0;
59     if(qr <= mid)
60         return query(l, mid, ql, qr, idx << 1);
61     else if(ql > mid)
62         return query(mid + 1, r, ql, qr, idx << 1 |
   ↳ 1);
63     return query(l, mid, ql, mid, idx << 1) +
   ↳ query(mid + 1, r, mid + 1, qr, idx << 1 | 1);
64 }
65 void modify(int l, int r, int ql, int qr, int v,
   ↳ int type){
66     // type 1: increasement, type 2: set
67     if(type == 2)
68         Set(l, r, ql, qr, v);
69     else
70         Increase(l, r, ql, qr, v);
71 }

```

2.5 LiChaoTree

```

1 struct line{
2     int m, c;
3     int val(int x){
4         return m * x + c;
5     }
6     line(){}
7     line(int _m, int _c){
8         m = _m, c = _c;
9     }
10 };
11 struct Li_Chao_Tree{
12     line seg[N << 2];
13     void ins(int l, int r, int idx, line x){

```

```

14     if(l == r){
15         if(x.val(l) > seg[idx].val(l))
16             seg[idx] = x;
17         return;
18     }
19     int mid = (l + r) >> 1;
20     if(x.m < seg[idx].m)
21         swap(x, seg[idx]);
22     // ensure x.m > seg[idx].m
23     if(seg[idx].val(mid) <= x.val(mid)){
24         swap(x, seg[idx]);
25         ins(l, mid, idx << 1, x);
26     }
27     else
28         ins(mid + 1, r, idx << 1 | 1, x);
29 }
30 int query(int l, int r, int p, int idx){
31     if(l == r)
32         return seg[idx].val(l);
33     int mid = (l + r) >> 1;
34     if(p <= mid)
35         return max(seg[idx].val(p), query(l, mid, p,
↪ idx << 1));
36     else
37         return max(seg[idx].val(p), query(mid + 1, r,
↪ p, idx << 1 | 1));
38 }

```

2.6 Treap

```

1 struct Treap{
2     Treap *l, *r;
3     int pri, key, sz;
4     Treap(){ }
5     Treap(int _v){
6         l = r = NULL;
7         pri = mtrd();
8         key = _v;
9         sz = 1;
10    }
11    ~Treap(){
12        if ( l )
13            delete l;
14        if ( r )
15            delete r;
16    }
17    void push(){
18        for(auto ch : {l, r}){
19            if(ch){
20                // do something
21            }
22        }
23    }
24 };
25 int getSize(Treap *t){
26     return t ? t->sz : 0;
27 }
28 void pull(Treap *t){
29     t->sz = getSize(t->l) + getSize(t->r) + 1;
30 }
31 Treap* merge(Treap* a, Treap* b){
32     if(!a || !b)
33         return a ? a : b;

```

```

34     if(a->pri > b->pri){
35         a->push();
36         a->r = merge(a->r, b);
37         pull(a);
38         return a;
39     }
40     else{
41         b->push();
42         b->l = merge(a, b->l);
43         pull(b);
44         return b;
45     }
46 }
47 void splitBySize(Treap *t, Treap *&a, Treap *&b,
↪ int k){
48     if(!t)
49         a = b = NULL;
50     else if(getSize(t->l) + 1 <= k){
51         a = t;
52         a->push();
53         splitBySize(t->r, a->r, b, k - getSize(t->l) -
↪ 1);
54         pull(a);
55     }
56     else{
57         b = t;
58         b->push();
59         splitBySize(t->l, a, b->l, k);
60         pull(b);
61     }
62 }
63 void splitByKey(Treap *t, Treap *&a, Treap *&b, int
↪ k){
64     if(!t)
65         a = b = NULL;
66     else if(t->key <= k){
67         a = t;
68         a->push();
69         splitByKey(t->r, a->r, b, k);
70         pull(a);
71     }
72     else{
73         b = t;
74         b->push();
75         splitByKey(t->l, a, b->l, k);
76         pull(b);
77     }
78 }
79 // O(n) build treap with sorted key nodes
80 void traverse(Treap *t){
81     if(t->l)
82         traverse(t->l);
83     if(t->r)
84         traverse(t->r);
85     pull(t);
86 }
87 Treap *build(int n){
88     vector<Treap*> st(n);
89     int tp = 0;
90     for(int i = 0, x; i < n; i++){
91         cin >> x;
92         Treap *nd = new Treap(x);
93         while(tp && st[tp - 1]->pri < nd->pri)
94             nd->l = st[tp - 1], tp--;
95         if(tp)

```

```

96     st[tp - 1]->r = nd;
97     st[tp++] = nd;
98 }
99 if(!tp){
100     st[0] = NULL;
101     return st[0];
102 }
103 traverse(st[0]);
104 return st[0];
105 }

```

2.7 DSU

```

1 struct Disjoint_set{
2     int n;
3     vector<int>sz, p;
4     int fp(int x){
5         return (p[x] == -1 ? x : p[x] = fp(p[x]));
6     }
7     bool U(int x, int y){
8         x = fp(x), y = fp(y);
9         if(x == y)
10             return false;
11         if(sz[x] > sz[y])
12             swap(x, y);
13         p[x] = y;
14         sz[y] += sz[x];
15         return true;
16     }
17     Disjoint_set() {}
18     Disjoint_set(int _n){
19         n = _n;
20         sz.resize(n, 1);
21         p.resize(n, -1);
22     }
23 };

```

2.8 RollbackDSU

```

1 struct Rollback_DSU{
2     vector<int>p, sz;
3     vector<pair<int, int>>history;
4     int fp(int x){
5         while(p[x] != -1)
6             x = p[x];
7         return x;
8     }
9     bool U(int x, int y){
10         x = fp(x), y = fp(y);
11         if(x == y){
12             history.push_back(make_pair(-1, -1));
13             return false;
14         }
15         if(sz[x] > sz[y])
16             swap(x, y);
17         p[x] = y;
18         sz[y] += sz[x];
19         history.push_back(make_pair(x, y));
20         return true;
21     }
22     void undo(){

```

```

23         if(history.empty() || history.back().first ==
↪ -1){
24             if(!history.empty())
25                 history.pop_back();
26             return;
27         }
28         auto [x, y] = history.back();
29         history.pop_back();
30         p[x] = -1;
31         sz[y] -= sz[x];
32     }
33     Rollback_DSU(): Rollback_DSU(0) {}
34     Rollback_DSU(int n): p(n), sz(n) {
35         fill(p.begin(), p.end(), -1);
36         fill(sz.begin(), sz.end(), 1);
37     }
38 };

```

3 Graph

3.1 RoundSquareTree

```

1 int cnt;
2 int dep[N], low[N]; // dep == -1 -> unvisited
3 vector<int>G[N], rstree[2 * N]; // 1 ~ n: round, n
↪ + 1 ~ 2n: square
4 vector<int>stk;
5 void init(){
6     cnt = n;
7     for(int i = 1; i <= n; i++){
8         G[i].clear();
9         rstree[i].clear();
10        rstree[i + n].clear();
11        dep[i] = low[i] = -1;
12    }
13    dep[1] = low[1] = 0;
14 }
15 void tarjan(int x, int px){
16     stk.push_back(x);
17     for(auto i : G[x]){
18         if(dep[i] == -1){
19             dep[i] = low[i] = dep[x] + 1;
20             tarjan(i, x);
21             low[x] = min(low[x], low[i]);
22             if(dep[x] <= low[i]){
23                 int z;
24                 cnt++;
25                 do{
26                     z = stk.back();
27                     rstree[cnt].push_back(z);
28                     rstree[z].push_back(cnt);
29                     stk.pop_back();
30                 }while(z != i);
31                 rstree[cnt].push_back(x);
32                 rstree[x].push_back(cnt);
33             }
34         }
35         else if(i != px)
36             low[x] = min(low[x], dep[i]);
37     }
38 }

```

3.2 SCC

```

1 struct SCC{
2     int n;
3     int cnt;
4     vector<vector<int>>>G, revG;
5     vector<int>stk, sccid;
6     vector<bool>vis;
7     SCC(): SCC(0) {}
8     SCC(int _n): n(_n), G(_n + 1), revG(_n + 1),
    ↪ sccid(_n + 1), vis(_n + 1), cnt(0) {}
9     void addEdge(int u, int v){
10         // u -> v
11         assert(u > 0 && u <= n);
12         assert(v > 0 && v <= n);
13         G[u].push_back(v);
14         revG[v].push_back(u);
15     }
16     void dfs1(int u){
17         vis[u] = 1;
18         for(int v : G[u]){
19             if(!vis[v])
20                 dfs1(v);
21         }
22         stk.push_back(u);
23     }
24     void dfs2(int u, int k){
25         vis[u] = 1;
26         sccid[u] = k;
27         for(int v : revG[u]){
28             if(!vis[v])
29                 dfs2(v, k);
30         }
31     }
32     void Kosaraju(){
33         for(int i = 1; i <= n; i++)
34             if(!vis[i])
35                 dfs1(i);
36         fill(vis.begin(), vis.end(), 0);
37         while(!stk.empty()){
38             if(!vis[stk.back()])
39                 dfs2(stk.back(), ++cnt);
40             stk.pop_back();
41         }
42     }
43 };

```

3.3 2SAT

```

1 struct two_sat{
2     int n;
3     SCC G; // u: u, u + n: ~u
4     vector<int>ans;
5     two_sat(): two_sat(0) {}
6     two_sat(int _n): n(_n), G(2 * _n), ans(_n + 1) {}
7     void disjunction(int a, int b){
8         G.addEdge((a > n ? a - n : a + n), b);
9         G.addEdge((b > n ? b - n : b + n), a);
10    }
11    bool solve(){
12        G.Kosaraju();
13        for(int i = 1; i <= n; i++){

```

```

14            if(G.sccid[i] == G.sccid[i + n])
15                return false;
16            ans[i] = (G.sccid[i] > G.sccid[i + n]);
17        }
18        return true;
19    }
20 };

```

3.4 Bridge

```

1 int dep[N], low[N];
2 vector<int>G[N];
3 vector<pair<int, int>>bridge;
4 void init(){
5     for(int i = 1; i <= n; i++){
6         G[i].clear();
7         dep[i] = low[i] = -1;
8     }
9     dep[1] = low[1] = 0;
10 }
11 void tarjan(int x, int px){
12     for(auto i : G[x]){
13         if(dep[i] == -1){
14             dep[i] = low[i] = dep[x] + 1;
15             tarjan(i, x);
16             low[x] = min(low[x], low[i]);
17             if(low[i] > dep[x])
18                 bridge.push_back(make_pair(i, x));
19         }
20         else if(i != px)
21             low[x] = min(low[x], dep[i]);
22     }
23 }

```

3.5 BronKerboschAlgorithm

```

1 vector<vector<int>>>maximal_clique;
2 int cnt, G[N][N], all[N][N], some[N][N],
    ↪ none[N][N];
3 void dfs(int d, int an, int sn, int nn)
4 {
5     if(sn == 0 && nn == 0){
6         vector<int>v;
7         for(int i = 0; i < an; i++)
8             v.push_back(all[d][i]);
9         maximal_clique.push_back(v);
10        cnt++;
11    }
12    int u = sn > 0 ? some[d][0] : none[d][0];
13    for(int i = 0; i < sn; i++){
14        {
15            int v = some[d][i];
16            if(G[u][v])
17                continue;
18            int tsn = 0, tnn = 0;
19            for(int j = 0; j < an; j++)
20                all[d + 1][j] = all[d][j];
21            all[d + 1][an] = v;
22            for(int j = 0; j < sn; j++)
23                if(g[v][some[d][j]])
24                    some[d + 1][tsn++] = some[d][j];

```

```

25     for(int j = 0; j < nn; j ++){
26         if(g[v][none[d][j]])
27             none[d + 1][tnn ++] = none[d][j];
28         dfs(d + 1, an + 1, tsu, tnn);
29         some[d][i] = 0, none[d][nn ++] = v;
30     }
31 }
32 void process(){
33     cnt = 0;
34     for(int i = 0; i < n; i ++){
35         some[0][i] = i + 1;
36         dfs(0, 0, n, 0);
37     }

```

3.6 Theorem

- Kosaraju's algorithm visit the strong connected components in topological order at second dfs.
- Euler's formula on planar graph: $V - E + F = C + 1$
- Kuratowski's theorem: A simple graph G is a planar graph iff G doesn't has a subgraph H such that H is homeomorphic to K_5 or $K_{3,3}$
- A complement set of every vertex cover correspond to a independent set. \Rightarrow Number of vertex of maximum independent set + Number of vertex of minimum vertex cover = V
- Maximum independent set of G = Maximum clique of the complement graph of G .
- A planar graph G colored with three colors iff there exist a maximal clique I such that $G - I$ is a bipartite.

4 Tree

4.1 HLD

```

1 struct Heavy_light_decomposition{
2     int n;
3     int cnt;
4     vector<int>dep, sz, mx_son, fa, top;
5     vector<int>id, inv_id;
6     vector<vector<pii>>G;
7     void addEdge(int u, int v, int c){
8         G[u].push_back(make_pair(v, c));
9         G[v].push_back(make_pair(u, c));
10    }
11    void dfs1(int x, int px){
12        dep[x] = dep[px] + 1;
13        sz[x] = 1;
14        fa[x] = px;
15        for(auto [i, c] : G[x])if(i != px){
16            dfs1(i, x);
17            sz[x] += sz[i];
18            mx_son[x] = (sz[i] > sz[mx_son[x]] ? i :
19            ↪ mx_son[x]);
20        }
21    void dfs2(int x, int root){
22        top[x] = root;
23        id[x] = ++cnt;

```

```

24        inv_id[cnt] = x;
25        if(mx_son[x])
26            dfs2(mx_son[x], root);
27        for(auto [i, c] : G[x]){
28            if(i != fa[x] && i != mx_son[x])
29                dfs2(i, i);
30        }
31    }
32    void decompose(){
33        dfs1(1, 0);
34        dfs2(1, 1);
35        // initialize data structure
36    }
37    int lca(int u, int v){
38        int mx = 0;
39        while(top[u] != top[v]){
40            if(dep[top[u]] < dep[top[v]])
41                swap(u, v);
42            u = fa[top[u]];
43        }
44        if(dep[u] > dep[v])
45            swap(u, v);
46        return u;
47    }
48    Heavy_light_decomposition():
49    ↪ Heavy_light_decomposition(0) {}
50    Heavy_light_decomposition(int _n): n(_n), cnt(0)
51    ↪ {
52        dep.resize(_n + 1, 0);
53        sz.resize(_n + 1, 0);
54        mx_son.resize(_n + 1, 0);
55        fa.resize(_n + 1);
56        top.resize(_n + 1);
57        id.resize(_n + 1);
58        inv_id.resize(_n + 1);
59        G.resize(_n + 1, vector<pii>(0));
60    }
61 };

```

5 Geometry

5.1 Point

```

1 template<class T> struct Point {
2     T x, y;
3     Point(): x(0), y(0) {};
4     Point(T a, T b): x(a), y(b) {};
5     Point(pair<T, T>p): x(p.first), y(p.second) {};
6     Point operator + (const Point& rhs){ return
7     ↪ Point(x + rhs.x, y + rhs.y); }
8     Point operator - (const Point& rhs){ return
9     ↪ Point(x - rhs.x, y - rhs.y); }
10    Point operator * (const int& rhs){ return Point(x
11    ↪ * rhs, y * rhs); }
12    Point operator / (const int& rhs){ return Point(x
13    ↪ / rhs, y / rhs); }
14    T cross(Point rhs){ return x * rhs.y - y * rhs.x;
15    ↪ }
16    T dot(Point rhs){ return x * rhs.x + y * rhs.y; }
17    T cross2(Point a, Point b){ // (a - this) cross
18    ↪ (b - this)
19    return (a - *this).cross(b - *this);

```



```

14 }
15 T dot2(Point a, Point b){ // (a - this) dot (b -
    ↪ this)
16     return (a - *this).dot(b - *this);
17 }
18 };

```

5.2 Geometry

```

1 template<class T> int ori(Point<T>a, Point<T>b,
    ↪ Point<T>c){
2     // sign of (b - a) cross(c - a)
3     auto res = a.cross2(b, c);
4     // if type is double
5     // if(abs(res) <= eps)
6     if(res == 0)
7         return 0;
8     return res > 0 ? 1 : -1;
9 }
10 template<class T> bool collinearity(Point<T>a,
    ↪ Point<T>b, Point<T>c){
11     // if type is double
12     // return abs(c.cross2(a,b)) <= eps;
13     return c.cross2(a, b) == 0;
14 }
15 template<class T> bool between(Point<T>a,
    ↪ Point<T>b, Point<T>c){
16     // check if c is between a, b
17     return collinearity(a, b, c) && c.dot2(a, b) <=
    ↪ 0;
18 }
19 template<class T> bool seg_intersect(Point<T>p1,
    ↪ Point<T>p2, Point<T>p3, Point<T>p4){
20     // seg (p1, p2), seg(p3, p4)
21     int a123 = ori(p1, p2, p3);
22     int a124 = ori(p1, p2, p4);
23     int a341 = ori(p3, p4, p1);
24     int a342 = ori(p3, p4, p2);
25     if(a123 == 0 && a124 == 0)
26         return between(p1, p2, p3) || between(p1, p2,
    ↪ p4) || between(p3, p4, p1) || between(p3, p4,
    ↪ p2);
27     return a123 * a124 <= 0 && a341 * a342 <= 0;
28 }
29 template<class T> Point<T> intersect_at(Point<T> a,
    ↪ Point<T> b, Point<T> c, Point<T> d) {
30     // line(a, b), line(c, d)
31     T a123 = a.cross(b, c);
32     T a124 = a.cross(b, d);
33     return (d * a123 - c * a124) / (a123 - a124);
34 }
35 template<class T> int
    ↪ point_in_convex_polygon(vector<Point<T>>& a,
    ↪ Point<T>p){
36     // 1: IN
37     // 0: OUT
38     // -1: ON
39     // the points of convex polygon must sort in
    ↪ counter-clockwise order
40     int n = a.size();
41     if(between(a[0], a[1], p) || between(a[0], a[n -
    ↪ 1], p))
42         return -1;

```

```

43     int l = 0, r = n - 1;
44     while(l <= r){
45         int mid = (l + r) >> 1;
46         auto a1 = a[0].cross2(a[mid], p);
47         auto a2 = a[0].cross2(a[(mid + 1) % n], p);
48         if(a1 >= 0 && a2 <= 0){
49             auto res = a[mid].cross2(a[(mid + 1) % n],
    ↪ p);
50             return res > 0 ? 1 : (res >= 0 ? -1 : 0);
51         }
52         else if(a1 < 0)
53             r = mid - 1;
54         else
55             l = mid + 1;
56     }
57     return 0;
58 }
59 template<class T> int
    ↪ point_in_simple_polygon(vector<Point<T>>&a,
    ↪ Point<T>p, Point<T>INF_point){
60     // 1: IN
61     // 0: ON
62     // -1: OUT
63     // a[i] must adjacent to a[(i + 1) % n] for all i
64     // collinearity(a[i], p, INF_point) must be false
    ↪ for all i
65     // we can let the slope of line(p, INF_point) be
    ↪ irrational (e.g. PI)
66     int ans = -1;
67     for(auto l = prev(a.end()), r = a.begin(); r !=
    ↪ a.end(); l = r++){
68         if(between(*l, *r, p))
69             return 0;
70         if(seg_intersect(*l, *r, p, INF_point)){
71             ans *= -1;
72             if(collinearity(*l, p, INF_point))
73                 assert(0);
74         }
75     }
76     return ans;
77 }
78 template<class T> T area(vector<Point<T>>&a){
79     // remember to divide 2 after calling this
    ↪ function
80     if(a.size() <= 1)
81         return 0;
82     T ans = 0;
83     for(auto l = prev(a.end()), r = a.begin(); r !=
    ↪ a.end(); l = r++){
84         ans += l->cross(*r);
85     }
86     return abs(ans);

```

5.3 ConvexHull

```

1 template<class T> vector<Point<T>>
    ↪ convex_hull(vector<Point<T>>&a){
2     int n = a.size();
3     sort(a.begin(), a.end(), [](Point<T>p1,
    ↪ Point<T>p2){
4         if(p1.x == p2.x)
5             return p1.y < p2.y;
6         return p1.x < p2.x;

```



```

7   });
8   int m = 0, t = 1;
9   vector<Point<T>>ans;
10  auto addPoint = [&](const Point<T>p) {
11      while(m > t && ans[m - 2].cross2(ans[m - 1], p)
↪      <= 0)
12      ans.pop_back(), m--;
13      ans.push_back(p);
14      m++;
15  };
16  for(int i = 0; i < n; i++)
17      addPoint(a[i]);
18  t = m;
19  for(int i = n - 2; ~i; i--)
20      addPoint(a[i]);
21  if(a.size() > 1)
22      ans.pop_back();
23  return ans;
24 }

```

5.4 Theorem

- Pick's theorem: Suppose that a polygon has integer coordinates for all of its vertices. Let i be the number of integer points interior to the polygon, b be the number of integer points on its boundary (including both vertices and points along the sides). Then the area A of this polygon is:

$$A = i + \frac{b}{2} - 1$$

6 String

6.1 RollingHash

```

1 struct Rolling_Hash{
2     int n;
3     const int P[5] = {146672737, 204924373,
↪     585761567, 484547929, 116508269};
4     const int M[5] = {922722049, 952311013,
↪     955873937, 901981687, 993179543};
5     vector<int>PW[5], pre[5], suf[5];
6     Rolling_Hash(): Rolling_Hash("") {}
7     Rolling_Hash(string s): n(s.size()){
8         for(int i = 0; i < 5; i++){
9             PW[i].resize(n), pre[i].resize(n),
↪             suf[i].resize(n);
10            PW[i][0] = 1, pre[i][0] = s[0] - 'a';
11            suf[i][n - 1] = s[n - 1] - 'a';
12        }
13        for(int i = 1; i < n; i++){
14            for(int j = 0; j < 5; j++){
15                PW[j][i] = PW[j][i - 1] * P[j] % M[j];
16                pre[j][i] = (pre[j][i - 1] * P[j] + s[i] -
↪                'a') % M[j];
17            }
18        }
19        for(int i = n - 2; i >= 0; i--){
20            for(int j = 0; j < 5; j++){
21                suf[j][i] = (suf[j][i + 1] * P[j] + s[i] -
↪                'a') % M[j];
22            }
23        }

```

```

24 int _substr(int k, int l, int r) {
25     int res = pre[k][r];
26     if(l > 0)
27         res -= 1LL * pre[k][l - 1] * PW[k][r - l + 1]
↪     % M[k];
28     if(res < 0)
29         res += M[k];
30     return res;
31 }
32 vector<int>substr(int l, int r){
33     vector<int>res(5);
34     for(int i = 0; i < 5; ++i)
35         res[i] = _substr(i, l, r);
36     return res;
37 }
38 };

```

6.2 SuffixArray

```

1 struct Suffix_Array{
2     int n, m; // m is the range of s
3     string s;
4     vector<int>sa, rk, lcp;
5     // sa[i]: the i-th smallest suffix
6     // rk[i]: the rank of suffix i (i.e. s[i, n - 1])
7     // lcp[i]: the longest common prefix of sa[i] and
↪     sa[i - 1]
8     Suffix_Array(): Suffix_Array(0, 0, "") {}
9     Suffix_Array(int _n, int _m, string _s): n(_n),
↪     m(_m), sa(_n), rk(_n), lcp(_n), s(_s) {}
10    void Sort(int k, vector<int>&bucket,
↪    vector<int>&idx, vector<int>&lst){
11        for(int i = 0; i < m; i++)
12            bucket[i] = 0;
13        for(int i = 0; i < n; i++)
14            bucket[lst[i]]++;
15        for(int i = 1; i < m; i++)
16            bucket[i] += bucket[i - 1];
17        int p = 0;
18        // update index
19        for(int i = n - k; i < n; i++)
20            idx[p++] = i;
21        for(int i = 0; i < n; i++)
22            if(sa[i] >= k)
23                idx[p++] = sa[i] - k;
24        for(int i = n - 1; i >= 0; i--)
25            sa[--bucket[lst[idx[i]]]] = idx[i];
26    }
27    void build(){
28        vector<int>idx(n), lst(n), bucket(max(n, m));
29        for(int i = 0; i < n; i++)
30            bucket[lst[i] = (s[i] - 'a')]++; // may
↪        change
31        for(int i = 1; i < m; i++)
32            bucket[i] += bucket[i - 1];
33        for(int i = n - 1; i >= 0; i--)
34            sa[--bucket[lst[i]]] = i;
35        for(int k = 1; k < n; k <= 1){
36            Sort(k, bucket, idx, lst);
37            // update rank
38            int p = 0;
39            idx[sa[0]] = 0;
40            for(int i = 1; i < n; i++){

```

```

41     int a = sa[i], b = sa[i - 1];
42     if(lst[a] == lst[b] && a + k < n && b + k <
↪ n && lst[a + k] == lst[b + k]);
43     else
44         p++;
45     idx[sa[i]] = p;
46 }
47 if(p == n - 1)
48     break;
49 for(int i = 0; i < n; i++)
50     lst[i] = idx[i];
51 m = p + 1;
52 }
53 for(int i = 0; i < n; i++)
54     rk[sa[i]] = i;
55 buildLCP();
56 }
57 void buildLCP(){
58     // lcp[rk[i]] >= lcp[rk[i - 1]] - 1
59     int v = 0;
60     for(int i = 0; i < n; i++){
61         if(!rk[i])
62             lcp[rk[i]] = 0;
63         else{
64             if(v)
65                 v--;
66             int p = sa[rk[i] - 1];
67             while(i + v < n && p + v < n && s[i + v] ==
↪ s[p + v])
68                 v++;
69             lcp[rk[i]] = v;
70         }
71     }
72 }
73 };

```

6.3 KMP

```

1 struct KMP {
2     int n;
3     string s;
4     vector<int> fail;
5     // s: pattern, t: text => find s in t
6     int match(string &t){
7         int ans = 0, m = t.size(), j = -1;
8         for(int i = 0; i < m; i++){
9             while(j != -1 && t[i] != s[j + 1])
10                 j = fail[j];
11             if(t[i] == s[j + 1])
12                 j++;
13             if(j == n - 1){
14                 ans++;
15                 j = fail[j];
16             }
17         }
18         return ans;
19     }
20     KMP(string &s){
21         s = _s;
22         n = s.size();
23         fail = vector<int>(n, -1);
24         int j = -1;
25         for(int i = 1; i < n; i++){

```

```

26         while(j != -1 && s[i] != s[j + 1])
27             j = fail[j];
28         if(s[i] == s[j + 1])
29             j++;
30         fail[i] = j;
31     }
32 }
33 };

```

6.4 Trie

```

1 struct Node {
2     int hit = 0;
3     Node *next[26];
4     // 26 is the size of the set of characters
5     // a - z
6     Node(){
7         for(int i = 0; i < 26; i++)
8             next[i] = NULL;
9     }
10 };
11 void insert(string &s, Node *node){
12     // node cannot be null
13     for(char v : s){
14         if(node->next[v - 'a'] == NULL)
15             node->next[v - 'a'] = new Node;
16         node = node->next[v - 'a'];
17     }
18     node->hit++;
19 }

```

6.5 Zvalue

```

1 struct Zvalue {
2     const string inf = "$"; // character that has
↪ never used
3     vector<int> z;
4     // s: pattern, t: text => find s in t
5     int match(string &s, string &t){
6         string fin = s + inf + t;
7         build(fin);
8         int n = s.size(), m = t.size();
9         int ans = 0;
10        for(int i = n + 1; i < n + m + 1; i++){
11            if(z[i] == n)
12                ans++;
13        }
14        return ans;
15    }
16    void build(string &s){
17        int n = s.size();
18        z = vector<int>(n, 0);
19        int l = 0, r = 0;
20        for(int i = 0; i < n; i++){
21            z[i] = max(min(z[i - 1], r - i), 0LL);
22            while(i + z[i] < n && s[z[i]] == s[i + z[i]])
23                l = i, r = i + z[i], z[i]++;
24        }
25    };

```

7 Flow

7.1 Dinic

```

1 struct Max_Flow{
2     struct Edge{
3         int cap, to, rev;
4         Edge(){}
5         Edge(int _to, int _cap, int _rev){
6             to = _to, cap = _cap, rev = _rev;
7         }
8     };
9     const int inf = 1e18+10;
10    int s, t; // start node and end node
11    vector<vector<Edge>>G;
12    vector<int>dep;
13    vector<int>iter;
14    void addE(int u, int v, int cap){
15        G[u].pb(Edge(v, cap, G[v].size()));
16        // direct graph
17        G[v].pb(Edge(u, 0, G[u].size() - 1));
18        // undirect graph
19        // G[v].pb(Edge(u, cap, G[u].size() - 1));
20    }
21    void bfs(){
22        queue<int>q;
23        q.push(s);
24        dep[s] = 0;
25        while(!q.empty()){
26            int cur = q.front();
27            q.pop();
28            for(auto i : G[cur]){
29                if(i.cap > 0 && dep[i.to] == -1){
30                    dep[i.to] = dep[cur] + 1;
31                    q.push(i.to);
32                }
33            }
34        }
35    }
36    int dfs(int x, int fl){
37        if(x == t)
38            return fl;
39        for(int _ = iter[x] ; _ < G[x].size() ; _++){
40            auto &i = G[x][_];
41            if(i.cap > 0 && dep[i.to] == dep[x] + 1){
42                int res = dfs(i.to, min(fl, i.cap));
43                if(res <= 0)
44                    continue;
45                i.cap -= res;
46                G[i.to][i.rev].cap += res;
47                return res;
48            }
49            iter[x]++;
50        }
51        return 0;
52    }
53    int Dinic(){
54        int res = 0;
55        while(true){
56            fill(all(dep), -1);
57            fill(all(iter), 0);
58            bfs();
59            if(dep[t] == -1)
60                break;

```

```

61        int cur;
62        while((cur = dfs(s, INF)) > 0)
63            res += cur;
64    }
65    return res;
66 }
67 void init(int _n, int _s, int _t){
68     s = _s, t = _t;
69     G.resize(_n + 5);
70     dep.resize(_n + 5);
71     iter.resize(_n + 5);
72 }
73 };

```

7.2 MCMF

```

1 struct MCMF{
2     struct Edge{
3         int from, to;
4         int cap, cost;
5         Edge(int f, int t, int ca, int co): from(f),
6         to(t), cap(ca), cost(co) {}
7     };
8     int n, s, t;
9     vector<Edge>edges;
10    vector<vector<int>>G;
11    vector<int>in_queue, prev_edge;
12    MCMF(){}
13    MCMF(int _n, int _s, int _t): n(_n), G(_n + 1),
14    ↪ d(_n + 1), in_queue(_n + 1), prev_edge(_n + 1),
15    ↪ s(_s), t(_t) {}
16    void addEdge(int u, int v, int cap, int cost){
17        G[u].push_back(edges.size());
18        edges.push_back(Edge(u, v, cap, cost));
19        G[v].push_back(edges.size());
20        edges.push_back(Edge(v, u, 0, -cost));
21    }
22    bool bfs(){
23        bool found = false;
24        fill(d.begin(), d.end(), (int)1e18+10);
25        fill(in_queue.begin(), in_queue.end(), false);
26        d[s] = 0;
27        in_queue[s] = true;
28        queue<int>q;
29        q.push(s);
30        while(!q.empty()){
31            int u = q.front();
32            q.pop();
33            if(u == t)
34                found = true;
35            in_queue[u] = false;
36            for(auto &id : G[u]){
37                Edge e = edges[id];
38                if(e.cap > 0 && d[u] + e.cost < d[e.to]){
39                    d[e.to] = d[u] + e.cost;
40                    prev_edge[e.to] = id;
41                    if(!in_queue[e.to]){
42                        in_queue[e.to] = true;
43                        q.push(e.to);
44                    }
45                }
46            }
47        }
48    }

```

```

45     }
46     return found;
47 }
48 pair<int, int>flow(){
49     // return (cap, cost)
50     int cap = 0, cost = 0;
51     while(bfs()){
52         int send = (int)1e18 + 10;
53         int u = t;
54         while(u != s){
55             Edge e = edges[prev_edge[u]];
56             send = min(send, e.cap);
57             u = e.from;
58         }
59         u = t;
60         while(u != s){
61             Edge &e = edges[prev_edge[u]];
62             e.cap -= send;
63             Edge &e2 = edges[prev_edge[u] ^ 1];
64             e2.cap += send;
65             u = e.from;
66         }
67         cap += send;
68         cost += send * d[t];
69     }
70     return make_pair(cap, cost);
71 }
72 };

```

8 Math

8.1 FastPow

```

1 long long qpow(long long x, long long powcnt, long
  ↳ long tomod){
2     long long res = 1;
3     for(; powcnt ; powcnt >= 1 , x = (x * x) %
  ↳ tomod)
4         if(1 & powcnt)
5             res = (res * x) % tomod;
6     return (res % tomod);

```

8.2 EXGCD

```

1 // ax + by = c
2 // return (gcd(a, b), x, y)
3 tuple<long long, long long, long long>exgcd(long
  ↳ long a, long long b){
4     if(b == 0)
5         return make_tuple(a, 1, 0);
6     auto[g, x, y] = exgcd(b, a % b);
7     return make_tuple(g, y, x - (a / b) * y);

```

8.3 EXCRT

```

1 long long inv(long long x){ return qpow(x, mod - 2,
    ↪ mod); }
2 long long mul(long long x, long long y, long long
    ↪ m){
3     x = ((x % m) + m) % m, y = ((y % m) + m) % m;
4     long long ans = 0;
5     while(y){
6         if(y & 1)
7             ans = (ans + x) % m;
8         x = x * 2 % m;
9         y >>= 1;
10    }
11    return ans;
12 }
13 pii ExCRT(long long r1, long long m1, long long r2,
    ↪ long long m2){
14     long long g, x, y;
15     tie(g, x, y) = exgcd(m1, m2);
16     if((r1 - r2) % g)
17         return {-1, -1};
18     long long lcm = (m1 / g) * m2;
19     long long res = (mul(mul(m1, x, lcm), ((r2 - r1)
    ↪ / g), lcm) + r1) % lcm;
20     res = (res + lcm) % lcm;
21     return {res, lcm};
22 }
23 void solve(){
24     long long n, r, m;
25     cin >> n;
26     cin >> m >> r; // x == r (mod m)
27     for(long long i = 1; i < n; i++){
28         long long r1, m1;
29         cin >> m1 >> r1;
30         if(r != -1 && m != -1)
31             tie(r, m) = ExCRT(r % m, r1, m1);
32     }
33     if(r == -1 && m == -1)
34         cout << "no solution\n";
35     else
36         cout << r << '\n';
37 }

```

8.4 FFT

```

1 struct Polynomial{
2     int deg;
3     vector<int>x;
4     void FFT(vector<complex<double>>&a, bool invert){
5         int a_sz = a.size();
6         for(int len = 1; len < a_sz; len <= 1){
7             for(int st = 0; st < a_sz; st += 2 * len){
8                 double angle = PI / len * (invert ? -1 :
9 ↪ 1);
10                complex<double>wnow(1), w(cos(angle),
11 ↪ sin(angle));
12                for(int i = 0; i < len; i++){
13                    auto a0 = a[st + i], a1 = a[st + len +
14 ↪ i];
15                    a[st + i] = a0 + wnow * a1;
16                    a[st + i + len] = a0 - wnow * a1;
17                }
18            }
19        }
20    }
21 };

```

```

14     wnow *= w;
15 }
16 }
17 }
18 if(invert)
19     for(auto &i : a)
20         i /= a_sz;
21 }
22 void change(vector<complex<double>>&a){
23     int a_sz = a.size();
24     vector<int>rev(a_sz);
25     for(int i = 1; i < a_sz; i++){
26         rev[i] = rev[i / 2] / 2;
27         if(i & 1)
28             rev[i] += a_sz / 2;
29     }
30     for(int i = 0; i < a_sz; i++)
31         if(i < rev[i])
32             swap(a[i], a[rev[i]]);
33 }
34 Polynomial multiply(Polynomial const&b){
35     vector<complex<double>>A(x.begin(), x.end()),
    ↪ B(b.x.begin(), b.x.end());
36     int mx_sz = 1;
37     while(mx_sz < A.size() + B.size())
38         mx_sz <<= 1;
39     A.resize(mx_sz);
40     B.resize(mx_sz);
41     change(A);
42     change(B);
43     FFT(A, 0);
44     FFT(B, 0);
45     for(int i = 0; i < mx_sz; i++)
46         A[i] *= B[i];
47     change(A);
48     FFT(A, 1);
49     Polynomial res(mx_sz);
50     for(int i = 0; i < mx_sz; i++)
51         res.x[i] = round(A[i].real());
52     while(!res.x.empty() && res.x.back() == 0)
53         res.x.pop_back();
54     res.deg = res.x.size();
55     return res;
56 }
57 Polynomial(): Polynomial(0) {}
58 Polynomial(int Size): x(Size), deg(Size) {}
59 };

```

8.5 NTT

```

1  /*
2   $p = r * 2^k + 1$ 
3   $p$        $r$        $k$        $root$ 
4  998244353      119 23 3
5  2013265921      15 27 31
6  2061584302081    15 37 7
7  */
8  template<int MOD, int RT>
9  struct NTT {
10     #define OP(op) static int op(int x, int y)
11     OP(add) { return (x += y) >= MOD ? x - MOD : x;
    ↪ }
12     OP(sub) { return (x -= y) < 0 ? x + MOD : x; }

```

```

13     OP(mul) { return ll(x) * y % MOD; } // multiply
    ↪ by bit if  $p * p > 9e18$ 
14     static int mpow(int a, int n) {
15         int r = 1;
16         while (n) {
17             if (n % 2) r = mul(r, a);
18             n /= 2, a = mul(a, a);
19         }
20         return r;
21     }
22     static const int MAXN = 1 << 21;
23     static int minv(int a) { return mpow(a, MOD -
    ↪ 2); }
24     int w[MAXN];
25     NTT() {
26         int s = MAXN / 2, dw = mpow(RT, (MOD - 1) /
    ↪ MAXN);
27         for (; s; s >>= 1, dw = mul(dw, dw)) {
28             w[s] = 1;
29             for (int j = 1; j < s; ++j)
30                 w[s + j] = mul(w[s + j - 1], dw);
31         }
32     }
33     void apply(vector<int>&a, int n, bool inv = 0)
    ↪ {
34         for(int i = 0, j = 1; j < n - 1; ++j) {
35             for (int k = n >> 1; (i ^= k) < k; k
    ↪ >>= 1);
36             if (j < i) swap(a[i], a[j]);
37         }
38         for (int s = 1; s < n; s <<= 1) {
39             for (int i = 0; i < n; i += s * 2) {
40                 for (int j = 0; j < s; ++j) {
41                     int tmp = mul(a[i + s + j], w[s
    ↪ + j]);
42                     a[i + s + j] = sub(a[i + j],
    ↪ tmp);
43                     a[i + j] = add(a[i + j], tmp);
44                 }
45             }
46         }
47         if(!inv)
48             return;
49         int iv = minv(n);
50         if(n > 1)
51             reverse(next(a.begin()), a.end());
52         for (int i = 0; i < n; ++i)
53             a[i] = mul(a[i], iv);
54     }
55     vector<int>convolution(vector<int>&a,
    ↪ vector<int>&b){
56         int sz = a.size() + b.size() - 1, n = 1;
57         while(n <= sz)
58             n <<= 1; // check  $n \leq MAXN$ 
59         vector<int>res(n);
60         a.resize(n), b.resize(n);
61         apply(a, n);
62         apply(b, n);
63         for(int i = 0; i < n; i++)
64             res[i] = mul(a[i], b[i]);
65         apply(res, n, 1);
66         return res;
67     }
68 };

```

8.6 Generating Functions

- Ordinary Generating Function $A(x) = \sum_{i \geq 0} a_i x^i$

$$\begin{aligned} - A(rx) &\Rightarrow r^n a_n \\ - A(x) + B(x) &\Rightarrow a_n + b_n \\ - A(x)B(x) &\Rightarrow \sum_{i=0}^n a_i b_{n-i} \\ - A(x)^k &\Rightarrow \sum_{i_1+i_2+\dots+i_k=n} a_{i_1} a_{i_2} \dots a_{i_k} \\ - xA(x)' &\Rightarrow n a_n \\ - \frac{A(x)}{1-x} &\Rightarrow \sum_{i=0}^n a_i \end{aligned}$$

- Exponential Generating Function $A(x) = \sum_{i \geq 0} \frac{a_i}{i!} x^i$

$$\begin{aligned} - A(x) + B(x) &\Rightarrow a_n + b_n \\ - A^{(k)}(x) &\Rightarrow a_{n+k} \\ - A(x)B(x) &\Rightarrow \sum_{i=0}^n n! a_i b_{n-i} \\ - A(x)^k &\Rightarrow \sum_{i_1+i_2+\dots+i_k=n} n! i_1, i_2, \dots, i_k a_{i_1} a_{i_2} \dots a_{i_k} \\ - xA(x) &\Rightarrow n a_n \end{aligned}$$

- Special Generating Function

$$\begin{aligned} - (1+x)^n &= \sum_{i \geq 0} n! x^i \\ - \frac{1}{(1-x)^n} &= \sum_{i \geq 0} \binom{n+i-1}{i} x^i \end{aligned}$$

8.7 Numbers

- Stirling numbers of the second kind Partitions of n distinct elements into exactly k groups. $S(n, k) = S(n-1, k-1) + kS(n-1, k)$, $S(n, 1) = S(n, n) = 1$ $S(n, k) = \frac{1}{k!} \sum_{i=0}^k (-1)^{k-i} \binom{k}{i} i^n$ $x^n = \sum_{i=0}^n S(n, i) (x)_i$
- Catalan numbers $C_n = \frac{1}{n+1} 2n! = 2n! - 2n! + 1$, $\forall n \geq 0$
 $C_{n+1} = \sum_{i=0}^n C_i C_{n-i} = \frac{2(2n+1)}{n+2} C_n$, $C_0 = 1$

8.8 Theorem

- Cayley's Formula

- Given a degree sequence d_1, d_2, \dots, d_n for each labeled vertices, there are $\frac{(n-2)!}{(d_1-1)!(d_2-1)!\dots(d_n-1)!}$ spanning trees.
- Let $T_{n,k}$ be the number of labeled forests on n vertices with k components, such that vertex $1, 2, \dots, k$ belong to different components. Then $T_{n,k} = kn^{n-k-1}$.

- Erdős–Gallai theorem A sequence of nonnegative integers $d_1 \geq \dots \geq d_n$ can be represented as the degree sequence of a finite simple graph on n vertices if and only if $d_1 + \dots + d_n$

is even and $\sum_{i=1}^k d_i \leq k(k-1) + \sum_{i=k+1}^n \min(d_i, k)$ holds for every $1 \leq k \leq n$.

- Gale–Ryser theorem A pair of sequences of nonnegative integers $a_1 \geq \dots \geq a_n$ and b_1, \dots, b_n is bigraphic if and only if $\sum_{i=1}^n a_i = \sum_{i=1}^n b_i$ and $\sum_{i=1}^k a_i \leq \sum_{i=1}^n \min(b_i, k)$ holds for every $1 \leq k \leq n$.

- Flooring and Ceiling function identity

$$\begin{aligned} - \lfloor \frac{\lfloor \frac{a}{b} \rfloor}{c} \rfloor &= \lfloor \frac{a}{bc} \rfloor \\ - \lceil \frac{\lceil \frac{a}{b} \rceil}{c} \rceil &= \lceil \frac{a}{bc} \rceil \\ - \lceil \frac{a}{b} \rceil &\leq \frac{a+b-1}{b} \\ - \lfloor \frac{a}{b} \rfloor &\leq \frac{a-b+1}{b} \end{aligned}$$

- Möbius inversion formula

$$\begin{aligned} - f(n) &= \sum_{d|n} g(d) \Leftrightarrow g(n) = \sum_{d|n} \mu(d) f(\frac{n}{d}) \\ - f(n) &= \sum_{n|d} g(d) \Leftrightarrow g(n) = \sum_{n|d} \mu(\frac{d}{n}) f(d) \end{aligned}$$

$$\begin{aligned} - \sum_{d|n}^{n=1} \mu(d) &= 1 \\ - \sum_{d|n}^{n \neq 1} \mu(d) &= 0 \end{aligned}$$

- Spherical cap

- A portion of a sphere cut off by a plane.
- r : sphere radius, a : radius of the base of the cap, h : height of the cap, θ : $\arcsin(a/r)$.
- Volume $= \pi h^2(3r-h)/3 = \pi h(3a^2+h^2)/6 = \pi r^3(2+\cos\theta)(1-\cos\theta)^2/3$.
- Area $= 2\pi r h = \pi(a^2+h^2) = 2\pi r^2(1-\cos\theta)$.