

TEAM USER GUIDE

JShotz

Capture browser flows as timestamped screenshots with API evidence, modal states, and a shareable PDF.

Current release: v2.8.6

Chrome, Microsoft Edge, and Firefox | Prepared 3 September 2026

1. Install

Chrome or Microsoft Edge

1. Download **JShotz-2.8.6-chrome-edge.zip** from the team repository.
2. Extract the ZIP to a permanent folder. Do not load the ZIP file itself.
3. Open `chrome://extensions` in Chrome or `edge://extensions` in Edge.
4. Enable **Developer mode**.
5. Select **Load unpacked**, then choose the extracted JShotz folder.
6. Approve the permissions request. Pin JShotz from the extensions menu for quick access.

Firefox

1. Download and extract **JShotz-2.8.6-firefox.zip**.
2. Open `about:debugging#/runtime/this-firefox`.
3. Choose **Load Temporary Add-on...**
4. Open the extracted folder and select `manifest.json`.

Firefox note: temporary add-ons are removed when Firefox restarts. A permanent Firefox installation requires Mozilla signing or a suitable developer/ESR setup.

2. Permissions and privacy

JShotz needs access to the pages you choose to record. Depending on the browser build, it requests access to tabs, downloads, page instrumentation, storage, and network request metadata.

Data warning: API mode can capture request payloads and response bodies. Do not record passwords, access tokens, payment data, personal data, or customer secrets. Use only on approved environments and share PDFs securely.

3. Start a recording

1. Open the target web application.
2. Reload the extension after installing or updating it.
3. Reload the target page after the extension is active. This ensures the API hook is installed early.
4. Open the JShotz popup and select a capture source.
5. Choose **Start recording**.

Capture source	Use it for
Tab viewport only	Page screenshots without API tables.
API + Screenshot	Page screenshots plus API Name, Origin and Referer, Payload, and Response text.
Screen / window	Desktop capture including DevTools, taskbar, browser UI, and native application dialogs. Choose the shared screen/window when prompted.

4. What JShotz captures

- Page loads, SPA route changes, and hash changes.
- Button, link, checkbox, radio, tab, dropdown, and selection actions.
- Text edits after the user pauses typing.
- Selected page text or selected text inside input fields.
- Webpage dialogs and modals after they appear, including modal OK-button actions.
- API requests made through `fetch` and `XMLHttpRequest`.
- Page title changes, with a generated title-bar strip added to every capture.

Duplicate page images are skipped for passive navigation events when the visible page has not changed. Explicit actions such as clicks, field edits, modal openings, title changes, API captures, and manual hotkeys are retained.

5. Manual shortcuts

Shortcut	Action
<code>Ctrl+Alt+Q</code>	Capture a manual screenshot during a recording while the webpage is focused.
<code>Alt+Shift+S</code>	Capture the current desktop/screen frame, useful when a DevTools Headers, Payload, or Response panel is visible.

To assign a browser-wide extension shortcut, open `chrome://extensions/shortcuts` or the equivalent Edge/Firefox shortcuts page. If a shortcut conflicts with the browser or another application, choose a different key combination.

6. API evidence

In **API + Screenshot** mode, API information is attached to the next screenshot. The table includes:

Column	Contents
API Name	HTTP method, request path, and status.
Origin and Referer	Request URL, actual outgoing Origin/Referer when available, and reliable page-origin/page-URL fallbacks.
Payload	Request body, or an indication that the request has no body.
Response	Response body and status outcome. Failed API Name and Response cells are highlighted yellow.

Long payloads and responses are wrapped and paginated instead of being drawn over neighbouring columns or silently discarded.

7. Stop and save

1. Choose **Stop recording**.
2. Choose **Yes, keep** to save the session.
3. Edit the default PDF filename if needed.
4. Select **Save PDF**. Select **Cancel** to return to the keep/delete prompt.
5. Choose **No, delete** only when you want to remove the captured session files.
6. Confirm deletion with **Yes, delete**, or choose **No, go back**.

Saved output is placed in the browser Downloads folder under `flow-captures/<session>/`. This includes individual PNGs when enabled, a flow manifest, and the PDF when enabled.

8. Create a PDF later

1. Open the JShotz popup while no recording is active.
2. Select **Create PDF from saved screenshots**.
3. Choose the folder containing the saved PNG or JPEG screenshots.
4. Enter the desired PDF filename.
5. Select **Generate PDF**, then choose the final save location in the browser dialog.

Screenshots are sorted by their filenames, so sequence-prefixed files such as `001_...`, `002_...` produce the expected order. API tables cannot be reconstructed from ordinary screenshots alone; this workflow creates a clean image-only PDF from the selected images.

9. Troubleshooting

Problem	Fix
Extension will not load	Extract the ZIP, load the extracted folder, and make sure you selected the correct browser package. Reload the extension after updates.
API hook warning or no API calls	Reload the extension, then reload the target web page, then start a new recording in API mode.
Native browser or OS dialog is missing	Use Screen / window mode and press <code>Ctrl+Alt+Q</code> while the dialog is visible. Page scripts cannot observe browser-owned dialogs.
DevTools panel is missing	Use Screen / window mode. Open the required DevTools panel and press <code>Alt+Shift+S</code> .
Too many screenshots	Passive duplicate page images are filtered, but explicit clicks and edits are intentionally retained.
Browser becomes slow during a long recording	Stop and save in shorter sessions, avoid recording sensitive/high-volume API traffic, and use the latest package. v2.8.6 releases image resources and runtime buffers during capture and exit.

10. Team distribution

Repository: `github.com/ciamjobin/Jobins-browser-screen-grab`

Current packages:

- Chrome and Edge: `dist/JShotz-2.8.6-chrome-edge.zip`
- Firefox: `dist/JShotz-2.8.6-firefox.zip`

Install the package appropriate to the browser. Do not mix the Firefox manifest with the Chrome/Edge package.