

The propositions package

Cian Dorr (with help from Claude)
ciandorr@gmail.com

v0.9: 2026/08/02

Abstract

The **propositions** package provides a key-value driven system for labelling propositions, theses, and premises in academic papers. Items may be given names like ‘(P)’ or ‘Physicalism’, or auto-numbered using different counters; all carry robust cross-references with configurable formatting. The package integrates with **amsmath**, **hyperref**, and **cleveref**.

Contents

1	Introduction	2
2	History	2
3	Basic usage	2
4	Advanced usage	3
5	Basic environments and commands	5
6	Keys	6
6.1	Item-level keys	6
6.2	Keys for prop environments	9
6.3	Keys for prop and inlineprop environments	11
6.4	Global key	12
7	Cross-referencing commands	13
7.1	How cross-referencing works	15
8	Defining and modifying styles	16
9	Built-in styles	17
10	Compatibility	25
11	Known issues	25
12	Release notes	25

1 Introduction

In some academic disciplines (such as philosophy), it is common to have displayed propositions (examples, theses, premises, . . .) with various kinds of labels. A thesis might be referred to as ‘(P)’ or ‘Physicalism’; the premises of an argument might be numbered as ‘P1’, ‘P2’, ‘P3’, . . . ; or examples might be numbered consecutively over the course of a whole article. Standard $\text{\LaTeX}$ environments like `enumerate` can handle some of these cases, but cross-referencing is awkward: `\ref` produces a bare number or letter, and the author must manually add parentheses or other formatting at every point of reference. The standard `description` environment does not allow cross-referencing at all.

The `propositions` package solves this by attaching formatting information to each label. A short item like `\item[P]` (inside `prop`^{P.5}) is displayed as “(P)” and `\ref` automatically produces “(P)” as well—complete with parentheses, hyperlinks, and `cleveref` support. The full key-value interface supports named items, numbered items, custom counters, glosses, shorthands, and per-item format overrides.

The `\ptag`^{P.5} command (which requires `amsmath`) extends this to displayed math environments: an equation can be tagged with a proposition label instead of (or using) its equation number.

2 History

I wrote the ancestor to this package in the 90s while finishing my Ph.D. thesis, but never documented it or shared it with the world. This new version is a thorough re-implementation in $\text{\LaTeX}3$, written in 2026 with extensive help from Claude Code. I hope others will find it as useful as I have.

3 Basic usage

Load the package with `\usepackage{propositions}` or `\usepackage[options]{propositions}` (see [subsection 6.4](#) below for valid package options).

The `prop` environment generates a list of propositions, each introduced by `\item`. `\item` with an optional argument gives a `description`-like label:

```
\begin{prop}
  \item[Physicalism] Everything is physical. \label{phys}
  \item[Idealism] Everything is mental. \label{ideal}
\end{prop}
```

Physicalism Everything is physical.
Idealism Everything is mental.

Unlike the standard `description` environment, one can refer back to these propositions using the standard `\ref` command (or with new cross-referencing commands described in [section 7](#)):

```
\ref{phys} is more plausible than \ref{ideal}.
```

Physicalism is more plausible than **Idealism**.

With no optional argument, `\item` will by default generate numbered items similar to `enumerate`, but with numbering that persists across the document:

```
\begin{prop}
  \item Every atom is physical. \label{atoms}
\end{prop}
\ref{phys} follows from the conjunction of \ref{atoms} and
\begin{prop}
  \item Everything is an atom. \label{atomism}
\end{prop}
```

(1) Every atom is physical.

Physicalism follows from the conjunction of (1) and

(2) Everything is an atom.

As with `enumerate`, the counter and formatting depend on the nesting level:

```
\begin{prop}
  \item \label{dual}
  \begin{prop}
    \item Some things are physical. \label{some}
    \item Some things are not physical. \label{notall}
  \end{prop}
\end{prop}
Without \ref{some}, \ref{dual} would be consistent
with \ref{ideal}.
```

(3) a. Some things are physical.

b. Some things are not physical.

Without (3a), (3) would be consistent with **Idealism**.

4 Advanced usage

The format of the proposition labels, and of subsequent references, are both configurable using a key=value syntax (see [section 6](#) for the possible keys):

```
\begin{prop}
  \item[No Overlap,
        align=flush,
        display format=\textsc{#1},
        ref format=\textit{#1}]
    Nothing mental is physical. \label{incomp}
\end{prop}
Is \ref{incomp} consistent with \ref{phys}?
```

NO OVERLAP Nothing mental is physical.

Is *No Overlap* consistent with **Physicalism**?

The prop environment can also take an optional argument with a list of keys:

```
\begin{prop}[leftmargin=5em, display format=[#1]]
  \item Every mental thing is physical.
\end{prop}
```

[4] Every mental thing is physical.

Preset styles can be declared and used in place of a set of key-value pairs:

```
\begin{prop}
  \item[Nihilism, style=thesis] There is nothing. \label{nihilism}
\end{prop}
Does \ref{nihilism} imply \ref{phys}, \ref{dual}, or both? Discuss.
```

NIHILISM There is nothing.

Does **Nihilism** imply **Physicalism**, (3), or both? Discuss.

Shortcut commands—e.g., `\titem[⟨keys⟩]` for `\item[style=thesis, ⟨keys⟩]`—can also be defined. The package loads with a range of predefined styles (listed in section 9).

When the package is loaded with `\usepackage[equations]{propositions}`, a first-level `\item` within `\prop`^{P.5} will use the counter as equations. (This looks better with the `leqno` option to `\documentclass`.)

```
\begin{equation}
  \exists x (\text{Mental}(x) \wedge \text{Physical}(x))
\end{equation}
\begin{prop}
  \item There is overlap between the mental and the physical.
\end{prop}
```

(5) $\exists x(\text{Mental}(x) \wedge \text{Physical}(x))$

(6) There is overlap between the mental and the physical.

The `\ptag→P.5` command (requires `amsmath`) is a replacement for the standard `\tag` command that behaves just like an `\item` in a `\prop→P.5` environment.

```
\begin{equation}
  \ptag[Monism] \label{mon}
  \exists x \forall y (y = x)
\end{equation}
Is \ref{mon} compatible with \ref{dual}?
```

Monism $\exists x \forall y (y = x)$

Is **Monism** compatible with (3)?

5 Basic environments and commands

```
\begin{prop}[<keys>]
  <environment content>
\end{prop}
```

Creates a displayed list of propositions. It is a standard L^AT_EX list, so by default its formatting will depend on the standard length parameters like `\itemsep` and `\topsep`, although these can be overridden by setting keys.

Within `prop`, `\item` creates the propositions (see below).

The optional `<keys>` argument can contain a list of keys, which will affect only the given environment (not any other `prop` environments that may be nested within it).

```
\begin{inlineprop}[<keys>]
  <environment content>
\end{inlineprop}
```

Like `prop`, but does not create a list. Allows `\item` to be used outside list environments, e.g. for generating numbers at the beginning of paragraphs. Steps the `prop` counter and increments the nesting level. Accepts the same optional `<keys>` as `prop`.

Within `prop` and `inlineprop`, `\item` is redefined to act as the proposition-item command. Its optional argument is a comma-separated list of `<key>=<value>` pairs (see section 6). A bare string without `=` is treated as a proposition name.

When used without an optional argument (or without setting `name`^{→ P. 7}, `counter`^{→ P. 7}, or `style`^{→ P. 6}), the style is determined by the `nameless style`^{→ P. 11} key (section 6). By default this is `numbered`, which dispatches by nesting depth to `levelone`, `leveltwo`, ... via `\proplevelchoice`^{→ P. 17}.

```
\ptag[<keys>]
```

(Available only when `amsmath` is loaded.) Works inside displayed math environments like `equation` and `align`. Accepts the same keys as `\item` within `prop`, except that `align`^{→ P. 6} has no effect (since positioning is controlled by the tag placement system).

Any display math environment (`equation`, `align`, etc.) used inside `prop` or `inlineprop` automatically increments the nesting level for its duration, so that `\ptag` inside such an environment behaves as if it were one level deeper.

```
\propoptions{<keys>}
```

Sets default keys (see section 6), which take effect for all subsequent uses of `prop`, `inlineprop`, `\item`, and `\ptag` (within the current scope).

Further commands are described below, especially in section 8 (defining styles) and section 7 (cross-referencing).

6 Keys

6.1 Item-level keys

The keys listed in this subsection can be used in the following places:

- In the optional argument of `\item` or `\ptag→P.5`: the key applies to that item only.
- In the optional argument of `prop→P.5` or `inlineprop→P.5`: the key applies to every top-level `\item` within that environment, unless overridden by the `\item`'s own optional argument. (If another `prop→P.5` or `inlineprop→P.5` environment is used inside this one, the key will not apply to its `\items`.)
- In the argument of `\propoptions→P.5`: the key will apply to every subsequent `\item` or `\ptag→P.5` (in the current group), unless overridden by that `\item`'s optional argument, or that of its parent environment.
- In the optional argument of `\usepackage{propositions}`: equivalent to `\propoptions→P.5`, except that keys that require the `#` character cannot be set here, (due to a limitation in how L^AT_EX processes options)
- With `\SetPropStyle→P.16` or `\DeclareNumberedStyle→P.16`, to add the key to a given style.

`style=⟨style⟩` (no default)

A style, equivalent to a preset collection of keys: see section 8 for details.

`align=left|right|center|flush|nextline|flush-nextline` (initially `left`)

How the label should be positioned. `left` is the standard left-aligned label, its offset controlled by `labelwidth→P.9` and `labelsep→P.9`; `right` is right-aligned within the label box, like `enumerate`; `center` is centred within it; `flush` aligns the label with the left margin of the item text; `nextline` puts the label on a line of its own, and `flush-nextline` does both. Has no effect inside `inlineprop→P.5` or `\ptag→P.5`.

```
\begin{prop}
  \item[A, align=left] Left aligned label.
  \item[A, align=center] Center aligned label.
  \item[A, align=right] Right aligned label.
  \item[Long label, align=center] As in standard \LaTeX\ lists,
    longer labels expand to fill the label box and then push
    the following text along to make room for themselves.
  \item[A, align=flush] Flush aligned label.
  \item[But sometimes a long label deserves its own line,
    align=nextline] Nextline aligned label.
  \item[Another rather long label,
    align=flush-nextline] Flush-nextline aligned label.
\end{prop}
```

A Left aligned label.
A Center aligned label.
A Right aligned label.
Long label As in standard L^AT_EX lists, longer labels expand to fill the label box and then push the following text along to make room for themselves.
A Flush aligned label.
But sometimes a long label deserves its own line
Nextline aligned label.
Another rather long label
Flush-nextline aligned label.

name=*<text>* (no default)

The proposition's name. A bare string (without =) is equivalent to **name**=*<text>*. (To be precise: if the optional argument contains no = at all, the whole of it is the name; otherwise, it is read as a key list, and any entry of it without an = is the name, so a bare name can be combined with other keys, as in `\item[No Overlap, align=flush]`. In that case a name containing a comma must be braced—`\item[{Alpha, Beta}, align=flush]`—and a name containing an = needs the explicit **name**=*<text>* form.)

counter=*<name>* (no default)

Counter to use. The counter is automatically stepped, and the item's **name** is set to `\the<name>` (though this can be overridden by **counter format** or **name**).

counter format=*<template>* (no default)

How to display the counter value. Use #1 for the counter name, e.g. **counter format**=`\roman{#1}`. When both this key and **counter** are set, this is used instead of `\the<counter>` for generating the item's **name**.

format=*<template>* (no default)

Formatting applied to the **name**: use #1 for the argument, e.g. **format**=`\textbf{(#1)}`. Shorthand for setting both **display format** and **ref format**.

display format=*<template>* (no default)

Format for displaying the name in the proposition's label. Does not affect cross-references.

ref format=*<template>* (no default)

Format for subsequent cross-references to this proposition. Does not affect the display.

shorthand=*<text>* (no default)

An abbreviation displayed after the name. If present, the shorthand becomes the reference text: `\ref` produces the shorthand (formatted with **ref format**) rather than the full name.

```

\begin{prop}
  \item[Global Physical Supervenience, shorthand=GPS] \label{global}
  Every fact is entailed by some fact about
  the physical world.
\end{prop}
There are several interesting arguments for \ref{global}.

```

Global Physical Supervenience [GPS] Every fact is entailed by some fact about the physical world.

There are several interesting arguments for **GPS**.

shorthand *format*=*<template>* (initially ~[#1])
 Format for displaying the shorthand in the label.

gloss=*<text>* (no default)
 A parenthetical gloss displayed after the name. Does not affect cross-references.

```

\begin{prop}
  \item[Humean Supervenience, gloss=after David Lewis]
  Every fact is entailed by some fact about the
  fundamental properties and spatiotemporal relations
  of points.
\end{prop}

```

Humean Supervenience (after David Lewis) Every fact is entailed by some fact about the fundamental properties and spatiotemporal relations of points.

gloss *format*=*<template>* (initially ~(#1))
 Format for displaying the gloss in the label.

label *format*=*<template>* (no default)
 Format applied to the *entire* assembled label, i.e. the name (after **display format**^{→ P.7}), shorthand, and gloss together. Use #1 for the whole assembled text. For example, **label format**=#1: appends a colon after the complete label.

ref=*<text>* (no default)
 Explicitly set the reference text, overriding what would be derived from **name**^{→ P.7}, **counter**^{→ P.7}, or **shorthand**^{→ P.7}.

label=*<label>* (no default)
 Equivalent to a trailing **\label{<label>}**.

reset=*<boolean>* (initially **true**)
 When **true** (the default), processing an **\item** resets the sub-level counter one nesting depth below the current level (e.g. **numprop***ii* at level 1). **reset**=**false** suppresses this behaviour, so that sub-item numbering continues from where it left off across consecutive parent items.

`crefname=<type>` (no default)

When `cleveref` is loaded, assigns an arbitrary reference type to this proposition. For example, `crefname=lemma` causes `\cref` to use the names defined by `\crefname{lemma}{...}{...}` instead of the default (private) `prop`^{P.5} type. The `<type>` must be known to `cleveref`; new types can be declared with `\crefname`.

Four of the list-dimension keys documented in the next section—`labelwidth`, `labelsep`, `itemindent` and `labelindent`^{P.11}—may also be given to an individual `\item`, where they reposition the label of that item alone, overriding the value in force for the rest of the list. (The other dimension keys have no effect at item level.)

6.2 Keys for prop environments

The keys in this section can be used in the following places:

- In the optional argument of `prop`^{P.5}: the key applies to that environment only, not to any other `prop`^{P.5} or `inlineprop`^{P.5} environments that may be nested within it.
- In the argument of `\proptions`^{P.5}: the key will apply to every subsequent `prop`^{P.5} environment (in the current group), unless overridden by that environment’s optional argument.
- In the optional argument of `\usepackage{propositions}`: equivalent to `\proptions`^{P.5}.
- With `\SetPropStyle`^{P.16} or `\DeclareNumberedStyle`^{P.16}, to add the key to a given style.

The keys can also be set in the optional argument of `\item`, `\ptag`^{P.5}, or `inlineprop`^{P.5}, or as part of a style used in one of those contexts, but will have no effect there, except for `labelwidth`, `labelsep`, `itemindent` and `labelindent`^{P.11} which will override the given dimensions for an individual `\item`.

`topsep=<length>`
`partopsep=<length>`
`itemsep=<length>`
`parsep=<length>`
`leftmargin=<length>`
`rightmargin=<length>`
`labelwidth=<length>`
`labelsep=<length>`
`itemindent=<length>`
`listparindent=<length>`

Override the standard L^AT_EX list dimensions. Accept the same values as `\setlength`, including rubber lengths (e.g. `itemsep=4pt plus 2pt`).

Each also accepts the value `*`, which means *as if the key had not been set*: the dimension takes the document class’s default, or—where `labelindent`^{P.11}

makes the five label-area dimensions over-determined—is left free for the package to derive from the others. This is the same convention `enumitem` uses, and it is chiefly useful for confining an override to some levels of nesting, since a value is resolved afresh at each level:

```
\propoptions{leftmargin = \proplevelchoice{2.5em, 0em, *}}
```

gives level 1 2.5em, level 2 0em, and every deeper level the class default. Without the `*` the last entry would apply at every level below the second, since `\proplevelchoice`^{P. 17} clamps rather than running out.

When used with a `\prop`^{P. 5} environment, the values of these keys can contain the special `\propformlabel` macro: see below.

`\propformlabel`

Expands to the formatted label of the (approximately) `items`-th item in this environment, computed at `\begin{prop}` *before* the list dimensions are applied, so it can be used directly in dimension expressions. It keeps that value for the whole environment: a dimension key is read again for each item’s label area, and a prediction that changed as the list went along would size each item’s label box to its predecessor’s label. Typical use:

```
\begin{prop}[items=20,
leftmargin=\widthof{\propformlabel}+0.5em]
```

sizes the left margin to accommodate labels up to the 20th item.

`\propwidestlabel`

`\propformlabel` with every digit replaced by the digit that makes the label widest (an 8 in the usual case, where all digits have the same width). Using it in place of `\propformlabel` in a dimension expression makes the dimension depend on how many digits the label has rather than on which digits they are, so that a run of numbered environments keeps a steady margin instead of shifting at every change of number: (9) and (10) differ in width by 5pt in the default font, where (8) and (88) differ only by as much as an extra digit requires. (The substitution is used for measurement only; the labels themselves are untouched.) This is what the `fitmargin` style measures.

`\propwidest{⟨label⟩}`

The filter that `\propwidestlabel` applies: expands `⟨label⟩` and replaces all of its digits by whichever single digit makes it widest, leaving formatting, letters and spaces alone. Use it on a label of your own, e.g. `\widthof{\propwidest{(\ref{lastitem})}}`.

The widest digit is found by measurement rather than assumed, since it depends on the font: with tabular figures every digit has the same width and the choice is immaterial, but with proportional (usually `oldstyle`) figures it is not, and 8 is then often not the widest—in EB Garamond’s `oldstyle` figures it is only the sixth widest, narrower than 0 by half a point per digit, enough for a margin reserved for (88) to let (00) overflow it. The measurement costs eleven boxes, incurred only where `\propwidest` is used.

`items=⟨n⟩`

(initially 1)

Indicates that approximately $\langle n \rangle$ items are expected in this environment. The only effect of this key is in conjunction with `\propformlabel`, to compute a preview label wide enough for the $\langle n \rangle$ th expected item, so that dimension expressions such as `leftmargin=\widthof{\propformlabel}+0.5em` reserve enough space for the widest label. Has no effect on actual item processing or counter stepping.

`labelindent`= $\langle length \rangle$ (no default)

Positions the left edge of the label box at $\langle length \rangle$ from the enclosing margin, adjusting `\labelwidth`, `\leftmargin`, `\labelsep`, or `\itemindent` as needed. (Since the value of any one of these dimensions can be derived from those of the other four, it never makes sense to set all five.)

`tightspacing` (no value)

Sets all vertical spacing to the compact defaults that the standard document classes use for level-three lists (`topsep`^{→P.9} and `itemsep`^{→P.9} to 2pt with stretch/shrink, `parsep`^{→P.9} to 0pt, `partopsep`^{→P.9} to 1pt).

`nosep` (no value)

Sets `\topsep`, `\itemsep`, and `\parsep` all to zero.

`continue`= $\langle boolean \rangle$ (initially true)

When true, a `prop`^{→P.5} environment that immediately follows another `prop`^{→P.5} (with no intervening paragraph text) replaces the normal `\topsep`-based inter-list space with `\itemsep` + `\parsep`, giving the visual appearance of a single continuous list.

6.3 Keys for prop and inlineprop environments

The keys in this section have effect in both the `prop`^{→P.5} and `inlineprop`^{→P.5} environments. They can also be used with `\propoptions`^{→P.5}, `\usepackage`, and `\SetPropStyle`^{→P.16}, just like the keys in the previous subsection.

`named style`= $\langle style \rangle$ (initially proposition)

The style when an `\item` or `\ptag`^{→P.5} has a value for `name`^{→P.7} but no explicit `style`^{→P.6}.

`named ptag style`= $\langle style \rangle$ (initially empty)

If set, overrides `named style` for `\ptag`^{→P.5} items only.

`nameless style`= $\langle style \rangle$ (initially numbered)

The style used when `\item` or `\ptag`^{→P.5} has no value for `name`^{→P.7} and no explicit `style`^{→P.6}. A `counter`^{→P.7} does not affect the choice: it says how the item is numbered, and this is the style meant to look right around a number.

`nameless ptag style`= $\langle style \rangle$ (initially empty)

If set, overrides `nameless style` for `\ptag`^{→P.5} items only.

The choice between them turns on `name`^{→P.7} alone, read from the whole key list—`\propoptions`^{→P.5}, then the environment argument, then the item's own argument. An item counts as named if a name reaches it from any of those, so `\begin{prop}[name=foo]\item bar` gives the same result as `\begin{prop}\item[name=foo] bar`. An explicit `style`^{→P.6} overrides the choice wherever it is set.

```

wrapper begin=<code>
wrapper end=<code>

```

Insert arbitrary *<code>* immediately before the beginning and after the end of the environment, so that the whole list can (for example) be wrapped in another environment.

Any value that contains a comma (such as a comma-separated list of options to an environment) must be enclosed in braces, so that the comma is not read as a key separator:

```

\begin{prop}[
  wrapper begin = {\begin{tcolorbox}[
    colframe = red, colback = white]},
  wrapper end   = {\end{tcolorbox}}]
  \item[Red] A proposition in a red frame.
  \item And a second one, in the same frame.
\end{prop}

```

Red A proposition in a red frame.
 (7) And a second one, in the same frame.

The wrapping environment must be one that can be split into separate begin and end code—that is, it must not read its body as a macro argument via `\collect@body` or similar.

The following command is provided for use with `wrapper begin`:

`\propoperativeleftmargin`

A read-only length giving the `leftmargin`^{→P.9} a `prop`^{→P.5} environment (with no optional argument) would use, given the current defaults set by `\propoptions`^{→P.5} and the current nesting level. It is recomputed at every `\begin{prop}`, so it is valid inside a wrapper (before the environment’s own `leftmargin`^{→P.9} has taken effect). For example, the built-in `framed` style uses this command in the value of `wrapper begin` to make the margins of framed environments match those of regular environments.

6.4 Global key

The following key can only be set in the optional argument of `\usepackage`, or in the preamble with `\propoptions`^{→P.5}.

`equations`

(no value, **global only**)

Installs hooks so that the L^AT_EX and `amstex` displayed equation environments (such as `equation` and `align`) use the same formatting as the special `equation prop` style. The `equation` style’s `display format`^{→P.7} and `ref format`^{→P.7} keys are used for generating equation numbers and cross-references to them.

Redefining the `equation` style, e.g. with

```
\SetPropStyle{equation}{format = [#1]}
```

will automatically update the hooks.

The `equations`^{P.12} key also sets `nameless style=eqnum`, so that top-level `\items` with no name will also use the `equation` style, while lower-level `\items` will use other kinds of numbering: for details, see section 9 below.

7 Cross-referencing commands

Labels placed after `\item` items (within `prop`^{P.5}) work with the standard `\label/\ref` mechanism. The key difference from ordinary L^AT_EX references is that `\ref` produces *formatted* output: for example, `\textbf` might be applied to the name, or the number might be wrapped in parentheses. The formatting is controlled by the `format` key (or separately by `display format` and `ref format`).

```
\Ref{<label>}
```

```
\Ref*{<label>}
```

Titlecase variants of `\ref` and `\ref*`: uppercases the first letter of the formatted output. (For example, if `\ref{thesis}` produces ‘the Identity Theory’, then `\Ref{thesis}` produces ‘The Identity Theory’.) The starred form suppresses the hyperlink. Note: `\Ref` only affects references produced by this package (which are stored via `\propapply`^{P.15}); for other references, it behaves like `\ref`.

```
\nref{<label>}
```

```
\nref*{<label>}
```

```
\Nref{<label>}
```

```
\Nref*{<label>}
```

“Naked ref.” Outputs the bare reference content with all formatting stripped. If `\ref{premise}` produces ‘(P1)’, then `\nref{premise}` produces ‘P1’. The starred form suppresses the hyperlink. `\Nref` is the titlecase variant: it uppercases the first letter of the bare content.

`\nref` can be useful in the argument of `\item`, when the the name of one proposition should depend on that of another:

```
\SetPropStyle{proposition}{format=(\textbf{#1})}
\begin{prop}
  \item[Phys] Everything is physical. \label{phys2}
  \item[\nref{phys2}*] Almost everything is physical.
  \label{newphys2}
  \item[\ref{phys2}*] This one has two sets of parentheses,
  which is probably not desired! Note that
  the previous proposition \ref{newphys2} avoided this by using
  |\nref| in the optional argument
  of |\item|.
\end{prop}
```

(**Phys**) Everything is physical.

(**Phys***) Almost everything is physical.

((**Phys***) This one has two sets of parentheses, which is probably not desired!
 Note that the previous proposition (**Phys***) avoided this by using `\nref` in the optional argument of `\item`.

Warning: documents where the name of one item includes a reference to that of another, and there are further references to that item, will require multiple L^AT_EX runs to resolve all references. To save time, it is better to avoid long chains of dependencies of this sort.

```
\oref[⟨prefix⟩][⟨suffix⟩]{⟨label⟩}
\oref*[⟨prefix⟩][⟨suffix⟩]{⟨label⟩}
\Oref[⟨prefix⟩][⟨suffix⟩]{⟨label⟩}
\Oref*[⟨prefix⟩][⟨suffix⟩]{⟨label⟩}
```

“Ref with options.” Extends `\ref` by injecting a prefix and/or suffix *inside* the formatting. With one optional argument, `⟨suffix⟩` is appended; with two, `⟨prefix⟩` is prepended and `⟨suffix⟩` appended. For instance, if `\ref{premise}` produces ‘(P1)’, then `\oref[*]{premise}` produces ‘(P1*)’ and `\oref[old~][*]{premise}` produces ‘(old~P1*)’.

`\Oref` is the titlecase variant; the starred forms suppress the hyperlink.

`\oref` can also be useful in the name of `\items`, if one wants the display format for the modified item to depend on that originally used

```
\begin{prop}
  \item[style=plain, name=\oref[$^\dag$]{phys2}]
  This will use boldface and parentheses because the
  original referenced item did.
\end{prop}
```

(**Phys**[†]) This will use boldface and parentheses because the original referenced item did.

Another handy use for `\oref` is in combination with `\nref` to refer to ranges:

```
The first two numbered examples in this document
were \oref[--\nref{atomism}]{atoms}.
```

The first two numbered examples in this document were (1–2).

```
\lastref[⟨prefix⟩]{⟨suffix⟩}
\Lastref[⟨prefix⟩]{⟨suffix⟩}
```

Produces a reference (with no hyperlink) to the most recently processed `\item` or `\ptag`^{→P.5}, even without a `\label`. Useful for back-references in running text. With one argument, `⟨suffix⟩` is appended; with two, `⟨prefix⟩` is also prepended. Use `\lastref{}` for a plain reference. `\Lastref` is the titlecase variant.

```
\nlastref
\NLastref
```

Like `\lastref{}`, but returns the bare content without formatting. `\NLastref` is the titlecase variant.

`\parentref[⟨prefix⟩]{⟨suffix⟩}`
`\Parentref[⟨prefix⟩]{⟨suffix⟩}`

Inside a nested `\prop`^{P.5} (or `\inlineprop`^{P.5}), produces a formatted reference to the most recent item of the enclosing level. Same argument convention as `\lastref`^{P.14}. `\Parentref` is the titlecase variant.

`\nparentref`
`\nParentref`

Like `\parentref{}` but returns the bare content without formatting. Takes no arguments; simply output any desired suffix directly afterwards. `\nParentref` is the titlecase variant.

`\parentref` and `\nparentref` are useful for making subitems whose names derive from their parent's:

```
\begin{prop}
  \item[P1, ref format=(#1)] \label{claim}
  \begin{prop}[counter format=\alph{#1},
    display format=\textit{#1.}, ref format=\parentref{#1}]
    \item \label{positive}
      Some things are physical.
    \item \label{negative}
      Some things are not physical.
  \end{prop}
\end{prop}
```

Of the two parts of `\ref{claim}`, `\ref{positive}` is far more controversial than `\ref{negative}`

P1 *a.* Some things are physical.
 b. Some things are not physical.

Of the two parts of (P1), (P1a) is far more controversial than (P1b). Thus, we will mostly be considering part b.

Many of the built-in numbered styles use `\parentref` in their `ref format`^{P.7}, to achieve this sort of composite effect.

7.1 How cross-referencing works

`\propapply{⟨template⟩}{⟨content⟩}`

Internally, each reference is stored in the `.aux` file as `\propapply{⟨template⟩}{⟨content⟩}`.

The `⟨template⟩` contains formatting with the placeholder `\propfmtarg` where content appears. At reference time, `\propapply` evaluates the template with `\propfmtarg` bound to `⟨content⟩`. The `\oref`^{P.14} and `\nref`^{P.13} commands work by locally redefining `\propapply`.

In normal use, you need not interact with `\propapply` directly.

`\propfmtarg`

Placeholder used inside templates; expands to the content argument of the enclosing `\propapply`.

8 Defining and modifying styles

Styles, equivalent to bundles of key-value settings, can be defined, and used freely in the optional arguments of `\item`, `\ptag`^{P.5}, `prop`^{P.5}, `inlineprop`^{P.5}, and the argument of `\propoptions`^{P.5}. Styles can freely be combined, and the definition of one style can reference another (in which case redefining the latter style will change the effect of the former style.)

\SetPropStyle{*<name>*}{*<keys>*}

Defines or modifies a prop style for use with the `style`^{P.6} key. All item-level keys (subsection 6.1) are accepted, plus the following:

`style`=*<parent>* (no default)

Inherit from a parent style. When an item is created, the parent's settings are loaded first (recursively, if the parent itself has a parent), then this style's own keys are applied on top.

The argument may be a macro which is expanded when the item is created: for example, a style with `style=\{<style1>\},\{<style2>\},\{<style3>\}` will resolve to `\{<style1>\}, \{<style2>\}, \{<style2>\}` depending on the nesting depth. The built-in `numbered` and `eqnum` styles use this mechanism.

`macro`=*<command>* (no default)

A new user macro, equivalent to `\item[style=<name>]`. Any further keys given to the macro are passed to `\item`.

If the style *<name>* already exists, `\SetPropStyle` modifies or adds keys. For example, `\SetPropStyle{proposition}{align=flush}` changes the alignment of the built-in `proposition` style while preserving its other settings.

```
\SetPropStyle{angle}{
  labelindent = 0em,
  display format = \textbf{$\angle\#\1$\rangle$},
  ref format = $\angle\#\1$\rangle$,
  macro = \angitem
}
\begin{prop}
  \angitem[Angle thesis] Everything is angular.
\end{prop}
No further discussion of \lastref{} is needed.
```

<Angle thesis> Everything is angular.

No further discussion of *<Angle thesis>* is needed.

\DeclareNumberedStyle{*<name>*}[*<keys>*]

Creates a new L^AT_EX counter named *<name>* and a matching prop style with `counter=<name>`. All `\SetPropStyle` keys are accepted, plus:

`parent`=*<counter>* (no default)

A parent counter; the new counter resets when the parent steps (same mechanism as `numberwithin`). A dedicated `prop` counter (stepped by each `prop`^{P.5} and `inlineprop`^{P.5}) is available for non-persistent numbering.


```

\DeclareNumberedStyle{P}
\begin{prop}
  \item[counter=P] First premise. \label{p1}
  \item[counter=P] Second premise. \label{p2}
\end{prop}
From \ref{p1} and \ref{p2}\ldots

```

```

(P1) First premise.
(P2) Second premise.

From (P1) and (P2)...

```

`\proplevelchoice{⟨item1, item2, ...⟩}`

Picks the entry from the list depending on the current nesting depth (1-indexed, last element will be used if the list is too short). At depth 0 (outside any `\prop`^{P.5} environment), returns the first entry. This macro is expandable, and designed to be used within `\SetPropStyle`^{P.16} to create styles that produce different results depending on the nesting depth of the `\item` in which they are used.

In a dimension key, an entry of `*` leaves that depth untouched (see section 6). A *blank* entry will not serve, and does not do what it looks like: the argument is read as a comma list, and comma lists discard empty items, so `\proplevelchoice{2em, , 1em}` has two entries rather than three and puts 1em at depth 2.

Special counters `leveltwo`, `levelthree`, `levelfour`, `levelfive` are provided, whose values are automatically reset each time an `\item` is processed at a lower nesting level. These are especially useful in combination with `\proplevelchoice`, to generate hierarchically numbered styles: for examples, see the built-in `numbered`, `eqnum`, and `hierarchical` styles in the next section.

9 Built-in styles

The following prop styles are predefined. Each entry shows the defining code (using user-facing commands), and each group of styles ends with a live example. All styles can be modified with `\SetPropStyle`^{P.16}; the definitions are reproduced here to facilitate modification.

Text styles

`plain` Unformatted text label.

```
\SetPropStyle{plain}{format = #1}
```

`proposition` The standard style assigned to named propositions. By default, uses boldface for both the label and references.

```
\SetPropStyle{proposition}{format = \textbf{#1}}
```

thesis Intended for named propositions with a longer name. The name begins at the text margin (flush alignment), and is set in small caps; references use plain font. Shortcut: `\titem`.

```
\SetPropStyle{thesis}{display format = \textsc{#1},
  ref format=#1, align = flush, macro = \titem}
```

vignette Intended for things like example vignettes and comments. Italic name at the text margin, and italic references, separated from the text by a colon.

```
\SetPropStyle{vignette}{ref format = \textit{#1},
  align = flush, label format = \textit{#1:}}
```

bullet Bullet symbol varying by depth (like `\itemize`). Shortcut: `\bitem`.

```
\SetPropStyle{bullet}{align = center,
  name = \proplevelchoice{\textbullet,
    {\normalfont\textendash}, \textasteriskcentered,
    \textperiodcentered},
  display format = #1, macro = \bitem}
```

```
\begin{prop}
  \item[One, style=plain] \label{bs:plain}
  A proposition in style |plain|, cited as \ref{bs:plain}.
  \item[Two, style=proposition] \label{bs:prop}
  A proposition in style |proposition|, cited as \ref{bs:prop}.
  \titem[Three] \label{bs:thesis}
  A proposition in style |thesis|, cited as \ref{bs:thesis}.
  \item[Four, style=vignette] \label{bs:vignette}
  A proposition in style |vignette|, cited as \ref{bs:vignette}.
  \bitem \label{bs:bullet}
  A proposition in style |bullet|, cited as \ref{bs:bullet}---though
  it is not often that one would want to cite an item in this style.
\end{prop}
```

One A proposition in style `plain`, cited as `One`.

Two A proposition in style `proposition`, cited as `Two`.

THREE A proposition in style `thesis`, cited as `Three`.

Four: A proposition in style `vignette`, cited as *Four*.

- A proposition in style `bullet`, cited as (•)—though it is not often that one would want to cite an item in this style.

Numbered styles

numbered The default nameless style. Selects one of the helper styles `levelone`–`levelfive`, depending on nesting depth.

```
\SetPropStyle{levelone}{counter = numpropi, format = (#1)}
\SetPropStyle{leveltwo}{counter = numpropii,
```

```

display format = #1., ref format = \parentref{#1}}
\SetPropStyle{levelthree}{counter = numpropiii,
display format = (#1), ref format = \parentref{.#1}}
\SetPropStyle{levelfour}{counter = numpropiv,
display format = #1., ref format = \parentref{#1}}
\SetPropStyle{levelfive}{counter = numpropv,
display format = (#1), ref format = \parentref{.#1}}
\SetPropStyle{numbered}{style = \proplevelchoice{
levelone, leveltwo, levelthree, levelfour, levelfive}}

```

equation Uses the equation counter. Note that this style has a special behavior when the `equations` option is active: changing its `display format`^{→P.7} and `ref format`^{→P.7} keys (or both, by setting `format`^{→P.7}) will also change the corresponding hooks used to create the tags for numbered equations make the `equation` environment and `amstex` environments like `gather`.

```

\SetPropStyle{equation}{counter = equation, format = (#1)}

```

eqnum Like `numbered`, but uses `equation` instead of `levelone` at the outer level. The `equations` package option sets default `nameless style = eqnum`. Since this manual uses this option, its outer-level nameless items use the `equation` style.

```

\SetPropStyle{eqnum}{style = \proplevelchoice{
equation, leveltwo, levelthree, levelfour, levelfive}}

```

```

\begin{prop}
\item \label{outer}
This is an outermost numbered item. Since the default style for
nameless items is |eqnum|, it uses the |equation| style.
\begin{prop}
\item \label{second}
This is a second level item, using |leveltwo|.
\begin{prop}
\item \label{third}
This is a third level item, using |levelthree|.
\begin{prop}
\item \label{fourth}
This is a fourth level item, using |levelfour|.
\begin{prop}
\item \label{fifth}
This is a fifth level item, using |levelfive|.
\end{prop}
\item Another fourth level item.
\end{prop}
\item Another third level item.
\end{prop}
\item Another second level item.
\end{prop}
\end{prop}
We hope you enjoyed reading \ref{outer}, \ref{second}, \ref{third},

```

`\ref{fourth}`, and `\ref{fifth}`.

- (8) This is an outermost numbered item. Since the default style for nameless items is `eqnum`, it uses the `equation` style.
 - a. This is a second level item, using `leveltwo`.
 - (i) This is a third level item, using `levelthree`.
 - A. This is a fourth level item, using `levelfour`.
 - (I) This is a fifth level item, using `levelfive`.
 - B. Another fourth level item.
 - (ii) Another third level item.
 - b. Another second level item.

We hope you enjoyed reading (8), (8a), (8a.i), (8a.iA), and (8a.iA.I).

roman Roman numerals. At the outer level, they use their own counter (reset every section); inside nested lists, they use the counter appropriate to the nesting level, so one can easily make roman-numbered sublists. Shortcut: `\ritem`.

```
\DeclareNumberedStyle{roman}[parent = section,
  counter format = \roman{#1}, format = (#1), macro = \ritem]
\SetPropStyle{roman}{counter = \proplevelchoice{
  roman, numpropii, numpropiii, numpropiv, numpropv}}
```

alph Letters. Works the same as `roman`, but with letters. Uses its own dedicated counter at the outer level. Shortcut: `\aitem`.

```
\DeclareNumberedStyle{alph}[parent = section,
  counter format = \alph{#1}, display format=#1.,
  ref format = (#1), macro = \aitem]
\SetPropStyle{alph}{counter = \proplevelchoice{
  alph, numpropii, numpropiii, numpropiv, numpropv}}
```

```
\begin{prop}
  \item[Basic classification, ref format={the \textit{#1}}]
  There are three different kinds of people. \label{complex}
  \begin{prop}
    \ritem \label{partone} Those who know how to count,
    comprising in turn:
    \begin{prop}
      \aitem \label{parta} Those who know how to count up to
      some number, but not beyond.
      \aitem \label{partb} Those who can keep going indefinitely.
    \end{prop}
    \ritem \label{parttwo} Those who do not know how to count.
  \end{prop}
\end{prop}
For \ref{complex} to serve its purpose, both \ref{partone} (and
its two components \ref{parta} and \ref{partb}) and
\ref{parttwo} are needed.
```

```

\begin{prop}
  \ritem
  The |roman| and |alph| styles are also useful for creating ad-hoc
  numbered lists at the outer level.
  \ritem
  Like this one.
\end{prop}

```

Basic classification There are three different kinds of people.

- (i) Those who know how to count, comprising in turn:
 - a. Those who know how to count up to some number, but not beyond.
 - b. Those who can keep going indefinitely.
- (ii) Those who do not know how to count.

For the *Basic classification* to serve its purpose, both (i) (and its two components (a) and (b)) and (ii) are needed.

- (i) The `roman` and `alph` styles are also useful for creating ad-hoc numbered lists at the outer level.
- (ii) Like this one.

`hierarchical` Produces 1, 1.1, 1.1.1... numbering. Defined via two helper styles:

```

\SetPropStyle{h-base}{counter = numpropi,
  counter format = \arabic{#1}, ref format = #1,
  display format = #1.}
\SetPropStyle{h-sub}{
  counter = \proplevelchoice{numpropi, numpropii,
    numpropiii, numpropiv, numpropv},
  counter format = \arabic{#1},
  format = \parentref{.#1}}
\SetPropStyle{hierarchical}{style = \proplevelchoice{
  h-base, h-sub}, tightspacing}

```

Note that since the optional arguments of the `prop`^{→P.5} and `inlineprop`^{→P.5} environment only affect the `\items` in the *immediate* scope of that environment (not of any nested environments), styles like `hierarchical` will need to be set using `\propoptions`^{→P.5} when one wants to apply the style to an environment and all its sub-environments, sub-sub-environments, etc. (The scope of `\propoptions` can be controlled by creating a `TeX` group.)

```

\begin{group}
\propoptions{style = hierarchical, leftmargin=3em, labelindent=0em}
\begin{prop}
  \item \label{theworld} The world is everything that is the case.
\end{prop}
\begin{prop}
  \item \label{totality}
  The world is the totality of facts, not of things.
\end{prop}
\item

```

```

    The world is determined by the facts, and by their being all the
    facts.
  \item
    For the totality of facts determines what is the case, and also
    whatever is not the case.
\end{prop}
\end{prop}
\end{prop}
Proposition \ref{totality} helps elucidate the meaning of
proposition \ref{theworld}.
\endgroup

```

1. The world is everything that is the case.
 - 1.1 The world is the totality of facts, not of things.
 - 1.1.1 The world is determined by the facts, and by their being all
 the facts.
 - 1.1.2 For the totality of facts determines what is the case, and also
 whatever is not the case.
- Proposition 1.1 helps elucidate the meaning of proposition 1.

Environment-level styles

These styles are designed to be used in the optional argument of `prop`^{→P.5} or `inlineprop`^{→P.5}.

`fitmargin` Fits the left margin to the predicted width of the label (computed using `\propwidestlabel`^{→P.10}), so that the label will never extend past the left margin of the following text.

```

\SetPropStyle{fitmargin}{
  labelindent = 0pt,
  leftmargin  = \widthof{\propwidestlabel} + \labelsep}

```

(Explanation: `\propwidestlabel`^{→P.10} computes the widest label the environment's items are expected to produce. By setting `labelindent`^{→P.11} to zero, we make sure that the `labelwidth`^{→P.9} will be sized to fit the computed `leftmargin`^{→P.9}.)

When a list will contain several numbered items, you can use the `items`^{→P.10} key to tell the environment how many `\items` it contains, so that it can properly anticipate how wide the widest label will be.

```

\begin{prop}[name=Fitted Margin, style=fitmargin]
  \item Notice that the |name| key needs to be set in the optional
  argument of |prop| rather than |item|, so that the style knows
  how much space needs to be reserved.
\end{prop}
\begin{prop}[items=2, style=fitmargin]
  \item
  The use of |items=2| is crucial here; without it, we would
  only reserve enough space for a one-digit number.

```

```

\item
  This happens to be where the |equation| counter hits value 10.
\end{prop}
The |hierarchical| style arguably looks better combined with |fitmargin|:
\begin{group}
\propoptions{style=hierarchical, style=fitmargin}
\begin{prop}
\item What is the case---a fact---is the existence of states of affairs.
\begin{prop}
\item A state of affairs (a state of things) is a combination
of objects (things).
\begin{prop}
\item
  It is essential to things that they should be possible
  constituents of states of affairs.
\item
  In logic nothing is accidental: if a thing can occur in a
  state of affairs, the possibility of the state of affairs
  must be written into the thing itself.
\end{prop}
\end{prop}
\end{prop}
\end{group}

```

Fitted Margin Notice that the `name` key needs to be set in the optional argument of `prop` rather than `item`, so that the style knows how much space needs to be reserved.

(9) The use of `items=2` is crucial here; without it, we would only reserve enough space for a one-digit number.

(10) This happens to be where the `equation` counter hits value 10.

The `hierarchical` style arguably looks better combined with `fitmargin`:

2. What is the case—a fact—is the existence of states of affairs.

2.1 A state of affairs (a state of things) is a combination of objects (things).

2.1.1 It is essential to things that they should be possible constituents of states of affairs.

2.1.2 In logic nothing is accidental: if a thing can occur in a state of affairs, the possibility of the state of affairs must be written into the thing itself.

outerfit This style behaves similar to `fitmargin` at the outer nesting level (with a bit more space between label and text), but does nothing at other levels. Intended to be set once using `\propoptionsP.5`, for a document that wants ‘fitmargin’-like behavior for its top-level propositions, but not for lower-level propositions (where adjusting to accommodate, e.g., roman numerals of different lengths would be a delicate task).

This matches the behaviour of the `\ex.` command in package `LINGUEX`, widely used in linguistics.

```
\SetPropStyle{outerfit}{
  labelindent = \proplevelchoice{0pt, *},
  leftmargin  = \proplevelchoice{
    \widthof{\propwidestlabel} + 1.3em, *}}

```

(Note the use of `*` in the argument of `\proplevelchoice`^{→P.17}, which leaves the deeper levels as though neither key had been set.)

framed Puts an outline around a list (requires the `tcolorbox` package to be loaded). Change the padding with `\setlength\propframepad{...}`.

```
\SetPropStyle{framed}{
  align = flush, leftmargin = 0pt, rightmargin = 0pt,
  labelindent = {}, continue = false,
  wrapper begin = {\begin{tcolorbox}[
    colback = white, colframe = black,
    boxrule = 0.4pt, arc = 0pt, boxsep = 0pt,
    left skip =
      \dimexpr\propoperativeleftmargin-\propframepad\relax,
    right skip =
      \dimexpr\propoperativeleftmargin-\propframepad\relax,
    left = \propframepad, right = \propframepad,
    top = \propframepad, bottom = \propframepad]},
  wrapper end = {\end{tcolorbox}}},
}
```

(Explanation: `leftmargin=0` means that the left margin *inside* the frame is zero. But the use of `\propoperativeleftmargin`^{→P.12} indents the whole `tcolorbox` environment by the right amount for the the left margin of the enclosed material to appear at the same position that would have been used for a list without the `frame` style, with the frame rule one `\propframepad` further out.)

```
\begin{prop}[style=framed]
  \item[Important Claim]
  This claim is so important that it deserves to
  put in a special box!
\end{prop}
```

Important Claim This claim is so important that it deserves to put in a special box!

standard A style that resets all the environment-level keys back to their default value. (This is useful, since there is otherwise no easy way to ‘unset’ a globally-set style.) Item-level keys like `align`^{→P.6} and `display format`^{→P.7} are not affected, so these will still be set by the the operative `named style`^{→P.11} or `nameless style`^{→P.11} defaults. (To reset `align` along with the other keys, just set `[style=standard, align=left]`.)

10 Compatibility

The `propositions` package is designed to work with `hyperref`, `cleveref`, `amsmath`, and `tcolorbox`.

- `amsmath` is required for `\ptagP.5` and the `equations` option.
- With `hyperref` loaded, all cross-referencing commands generate hyperlinks, as usual.
- With `cleveref` loaded, all proposition items are assigned to a private `prop` “reference type”, which by default has no special name, so `\cref` and `\ref` will generate the same output. The `crefname` key can override this.
- The built-in `framed` style requires `tcolorbox` to be loaded.

None of these packages has to be loaded in any particular order relative to `propositions`: each is detected either at load time or at `\begin{document}`, whichever is needed. The usual external conventions still apply—`hyperref` late, and `cleveref` after `hyperref`—which gives:

```
\usepackage{amsmath}      % if using \ptag or the equations option
\usepackage{tcolorbox}    % if using the framed style
\usepackage{hyperref}
\usepackage{propositions}
\usepackage{cleveref}     % if used
```

11 Known issues

When using `\ptagP.5` with a named counter (e.g. `\ptag[counter=P]`) inside an `amsmath` equation environment, `hyperref` may emit warnings of the form:

```
pdfTeX warning: destination with the same
identifier (name{equation.N}) has been already
used, duplicate ignored
```

These warnings are harmless and do not affect the correctness of cross-references.

12 Release notes

0.9 Initial public release.