

The propositions package

Cian Dorr
ciandorr@gmail.com

v0.91: 2026/08/07

Abstract

The **propositions** package provides a key-value driven system for labelling propositions, theses, and premises in academic papers. Items may be given names like ‘(P)’ or ‘Physicalism’, or auto-numbered using different counters; all carry robust cross-references with configurable formatting. The package integrates with **amsmath**, **hyperref**, **cleveref**, and **zref-clever**.

Contents

1	Introduction	2
2	History	2
3	Basic usage	2
4	Advanced usage	3
5	Basic environments and commands	5
6	Keys	6
6.1	Item-level keys	6
6.2	Keys for changing the list geometry	10
6.3	Other environment-level keys	13
6.4	Global key	15
7	Cross-referencing commands	15
7.1	How cross-referencing works	18
8	Defining and modifying styles	18
9	Built-in styles	20
10	Compatibility	28
10.1	Beamer	29
11	Known issues	29
12	Release notes	30

1 Introduction

In some academic disciplines (such as philosophy), it is common to have displayed propositions (examples, theses, premises, . . .) with various kinds of labels. A thesis might be referred to as ‘(P)’ or ‘Physicalism’; the premises of an argument might be numbered as ‘P1’, ‘P2’, ‘P3’, . . . ; or examples might be numbered consecutively over the course of a whole article. Standard L^AT_EX environments like `enumerate` can handle some of these cases, but cross-referencing is awkward: `\ref` produces a bare number or letter, and the author must manually add parentheses or other formatting at every point of reference. The standard `description` environment, meanwhile, does not allow cross-referencing at all.

The `propositions` package solves this by attaching formatting information to each label. With an appropriate choice of style, `\item[P]` (inside `prop`^{P.5}) is displayed as “(P)” and `\ref` automatically produces “(P)” as well—complete with parentheses and hyperlink. The full key-value interface supports named items, numbered items, custom counters, glosses, shorthands, per-item format changes, changes to the list geometry, and styles.

The `\ptag`^{P.6} command (which requires `amsmath`) extends this to displayed math environments: an equation can be tagged with a proposition label instead of (or using) its equation number, and `\ref` to an equation will pick up its name or number with specified formatting.

2 History

I wrote the ancestor to this package in the 90s while finishing my Ph.D. thesis, and used it in my own work but never documented or shared it. This new version is a thorough re-implementation in L^AT_EX3, written in 2026 with very extensive help from Claude Code. I hope others will find it as useful as I have.

3 Basic usage

Load with `\usepackage{propositions}` (see subsection 6.4 below for valid package options).

The `prop` environment generates a list of propositions, each introduced by `\item`. `\item` with an optional argument gives a `description`-like label:

```
\begin{prop}
  \item[Physicalism] Everything is physical. \label{phys}
  \item[Idealism] Everything is mental. \label{ideal}
\end{prop}
```

Physicalism Everything is physical.

Idealism Everything is mental.

Unlike the standard `description` environment, one can refer back to these propositions using the standard `\ref` command (or with new cross-referencing commands described in section 7):

```
\ref{phys} is more plausible than \ref{ideal}.
```

Physicalism is more plausible than **Idealism**.

With no optional argument, `\item` will by default generate numbered items similar to `enumerate`, but with numbering that persists across the document:

```
\begin{prop}
  \item Every atom is physical. \label{atoms}
\end{prop}
\ref{phys} follows from the conjunction of \ref{atoms} and
\begin{prop}
  \item Everything is an atom. \label{atomism}
\end{prop}
```

(1) Every atom is physical.

Physicalism follows from the conjunction of (1) and

(2) Everything is an atom.

As with `enumerate`, the counter and formatting depend on the nesting level:

```
\begin{prop}
  \item \label{dual}
  \begin{prop}
    \item Some things are physical. \label{some}
    \item Some things are not physical. \label{notall}
  \end{prop}
\end{prop}
Without \ref{some}, \ref{dual} would be consistent
with \ref{ideal}.
```

(3) a. Some things are physical.

b. Some things are not physical.

Without (3a), (3) would be consistent with **Idealism**.

4 Advanced usage

The format of the proposition labels, and of subsequent references, are both configurable using a key=value syntax (see [section 6](#) for the possible keys):

```
\begin{prop}
  \item[No Overlap,
        align=flush,
        display format=\textsc{#1},
        ref format=\textit{#1}]
    Nothing mental is physical. \label{incomp}
\end{prop}
Is \ref{incomp} consistent with \ref{phys}?
```

No OVERLAP Nothing mental is physical.
 Is *No Overlap* consistent with **Physicalism**?

The prop environment can also take an optional argument with a list of keys:

```
\begin{prop}[leftmargin=5em, format=#1]
  \item Every mental thing is physical.
\end{prop}
```

[4] Every mental thing is physical.

Preset styles can be declared and used in place of a set of key-value pairs. The package loads with a range of predefined styles (see section 9).

```
\begin{prop}
  \item[Nihilism, style=thesis] There is nothing. \label{nihilism}
\end{prop}
Does \ref{nihilism} imply \ref{phys}, \ref{dual}, or both? Discuss.
```

NIHILISM There is nothing.
 Does *Nihilism* imply **Physicalism**, (3), or both? Discuss.

Additional cross-referencing commands (see section 7) include `\nref`^{P.16} (strips formatting from reference) and `\lastref`^{P.17} (refers to the most recent proposition, even if it lacked a label):

```
\begin{prop}
  \item[Mentality] \label{mental} Everything is mental.
  \item[\nref{mental}*] Many things are mental.
\end{prop}
One may think \lastref\ more reasonable than \ref{mental}.
```

Mentality Everything is mental.
Mentality* Many things are mental.
 One may think **Mentality*** more reasonable than **Mentality**.

When the package is loaded with `\usepackage[equations]{propositions}`, a first-level `\item` within `prop`^{P.5} will use the counter as equations. (This looks better with the `leqno` option to `\documentclass`.)

```
\begin{equation}
  \exists x (\text{Mental}(x) \wedge \text{Physical}(x)) \label{overlap}
\end{equation}
\ref{overlap} can be stated in English as \ref{overlap2}:
\begin{prop}
  \item Some things are both mental and physical. \label{overlap2}
\end{prop}
```

$$(5) \quad \exists x(\text{Mental}(x) \wedge \text{Physical}(x))$$

(5) can be stated in English as (6):

(6) Some things are both mental and physical.

The `\ptag→P.6` command (requires `amsmath`) is a replacement for the standard `\tag` command that behaves just like an `\item` in a `prop` environment.

```
\begin{equation}
  \ptag[Monism, \format=\textsc{\#1}] \label{mon}
  \exists x \forall y (y = x)
\end{equation}
Is \ref{mon} compatible with \ref{dual}?
```

Monism $\exists x \forall y (y = x)$

Is **Monism** compatible with (3)?

5 Basic environments and commands

```
\begin{prop}[<keys>]
  <environment content>
\end{prop}
```

Creates a displayed list of propositions. It is a standard L^AT_EX list, so by default its formatting will depend on the standard length parameters like `\itemsep` and `\topsep`, although these can be overridden by setting keys.

Within `prop`, `\item` creates the propositions (see below).

The optional `<keys>` argument can contain a list of keys, which will affect only the given environment (not any other `prop` environments that may be nested within it).

```
\begin{inlineprop}[<keys>]
  <environment content>
\end{inlineprop}
```

Like `prop`, but does not create a list. Allows `\item` to be used outside list environments, e.g. for generating numbers at the beginning of paragraphs. Resets the `enumprop` counter and increments the nesting level. Accepts the same optional `<keys>` as `prop`.

Here the label is set in running text, and the space between it and the body is the source's own—except after an `\item` given no optional argument, where the scan for that argument has already consumed it. Such an `\item` is followed by an interword space of its own, so that `\item Alpha` sets like `\item[P] Alpha` rather than running the label into the word. `\item[]` asks for the other thing: an item with no argument to speak of, whose body follows immediately.

Within `prop` and `inlineprop`, `\item` is redefined to act as the proposition-

item command. Its optional argument is a comma-separated list of $\langle key \rangle = \langle value \rangle$ pairs (see section 6). A bare string without = is treated as a proposition name.

When used without an optional argument (or without setting `name`^{→P.7}, `counter`^{→P.7}, or `style`^{→P.7}), the style is determined by the `nameless style`^{→P.13} key (section 6). By default this is `numbered`, which dispatches by nesting depth to `levelone`, `leveltwo`, ... via `\proplevelchoice`.

`\ptag[ $\langle keys \rangle$ ]`

(Available only when `amsmath` is loaded.) Works inside displayed math environments like `equation` and `align`. Accepts the same keys as `\item` within `prop`^{→P.5}, except that `align`^{→P.10} has no effect (since positioning is controlled by the tag placement system).

Any display math environment (`equation`, `align`, etc.) used inside `prop`^{→P.5} or `inlineprop`^{→P.5} automatically increments the nesting level for its duration, so that `\ptag` inside such an environment behaves as if it were one level deeper.

`\propoptions{ $\langle keys \rangle$ }`

Sets default keys (see section 6), which take effect for all subsequent uses of `prop`^{→P.5}, `inlineprop`^{→P.5}, `\item`, and `\ptag` (within the current scope).

`\proplevelchoice{ $\langle item1, item2, \dots \rangle$ }`

Picks the entry from the comma-separated list depending on the current nesting depth (1-indexed; last element will be used if the list is too short; empty entries are skipped). At depth 0 (outside any `prop`^{→P.5} environment), returns the first entry.

This macro can be used, for example, to set different list dimensions for different nesting levels (see section 6.2) or to create styles that produce different results depending on the nesting depth where they are used (see section 8).

`\propfootnotechoice{ $\langle outside \rangle$ }{ $\langle inside \rangle$ }`

Expands to $\langle inside \rangle$ within the text of a footnote, and to $\langle outside \rangle$ anywhere else. The built-in `numbered` and `eqnum` styles use it to select `footnumprop` in footnotes (see section 8).

Further commands are described below, especially in section 7 (cross-referencing) and section 8 (defining styles).

6 Keys

6.1 Item-level keys

The keys listed in this subsection can be used in the following places:

- In the optional argument of `\item` or `\ptag`: the key applies to that item only.
- In the optional argument of `prop`^{→P.5} or `inlineprop`^{→P.5}: the key applies to every top-level `\item` within that environment, unless overridden by the `\item`'s own optional argument. (If another `prop`^{→P.5} or `inlineprop`^{→P.5} environment is used inside this one, the key will not apply to its `\items`.)

- In the argument of `\propoptions`: the key will apply to every subsequent `\item` or `\ptag` (in the current group), unless overridden by that `\item`'s optional argument, or that of its parent environment.
- In the optional argument of `\usepackage{propositions}`: equivalent to `\propoptions`^{P.6}, except that keys that require the # character cannot be set here, (due to a limitation in how L^AT_EX processes options)
- With `\SetPropStyle`^{P.18} or `\DeclareNumberedStyle`^{P.19}, to add the key to a given style.

`style=<style>` (no default)

A style, equivalent to a preset collection of keys: see section 8 for details.

`name=<text>` (no default)

The proposition's name. A bare string (without =) is equivalent to `name=<text>`. (To be precise: if the optional argument contains no = at all, the whole of it is the name; otherwise, it is read as a key list, and any entry of it without an = is the name, so a bare name can be combined with other keys, as in `\item[No Overlap, align=flush]`. In that case a name containing a comma must be braced—`\item[{Alpha, Beta}, align=flush]`—and a name containing an = needs the explicit `name={<text>}` form.)

`counter=<name>` (no default)

Counter to use. The counter is automatically stepped, and the item's `name` is set to `\the<name>` (though this can be overridden by `counter format` or `name`).

Any counter can be used with `counter format`. Special counters `numpropii`, `numpropiii`, `numpropiv`, `numpropv` are provided, whose values are automatically reset each time an `\item` is processed at a lower nesting level. There is also a counter `numpropi`, which resets at each chapter in classes that have them (use `\counterwithout*{numpropi}{chapter}` if you don't want this), and a counter `enumprop` which is reset at every *outermost* `prop`^{P.5} or `inlineprop`^{P.5} environment, so that lists using this counter behave like the standard `enumerate` environment. Finally, there is a counter `footprop`, reset at the beginning of every footnote.

The special value `counter=none` unsets the `counter` key (potentially useful if it would otherwise have been set by a style).

`counter format=<template>` (no default)

How to display the counter value. Use #1 for the counter name, e.g. `counter format=\roman{#1}`. When both this key and `counter` are set, this is used instead of `\the<counter>` for generating the item's `name`. The value `*` means "as if unset", as it does for a dimension key: the counter is displayed by its own `\the<counter>` again.

Along with the standard commands (`\arabic`, `\roman`, `\Roman`, `\alph`, `\Alph`, and `\fnsymbol`), the following command is available:

`\proprepeat{<counter>}{<token>}`

Prints `<token>` as many times as the value of `<counter>`.

```
\begin{prop}[counter = enumprop, format = (#1),
  counter format = \proprepeat{#1}{*}]
  \item An item labelled with one asterisk.
  \item And another, labelled with two.
\end{prop}
```

(*) An item labelled with one asterisk.
 (**) And another, labelled with two.

display format=*<template>* (no default)

Format for displaying the name or counter value in the proposition's label. Use #1 for the argument, e.g. `display format=\textbf{#1}`. Does not affect cross-references.

ref format=*<template>* (no default)

Format for subsequent cross-references to this proposition. Use #1 for the argument, e.g. `ref format=\{(#1)\}`. Does not affect the display.

format=*<template>* (no default)

Shorthand for setting both `display format` and `ref format`.

shorthand=*<text>* (no default)

An abbreviation displayed after the name. If present, the shorthand becomes the reference text: `\ref` produces the shorthand (formatted with `ref format`) rather than the full name.

```
\begin{prop}
  \item[Global Physical Supervenience, shorthand=GPS] \label{global}
  Every fact is entailed by some fact about
  the physical world.
\end{prop}
There are several interesting arguments for \ref{global}.
```

Global Physical Supervenience [GPS] Every fact is entailed by some fact about the physical world.

There are several interesting arguments for **GPS**.

shorthand format=*<template>* (initially ~[#1])

Format for displaying the shorthand in the label.

gloss=*<text>* (no default)

A parenthetical gloss displayed after the name. Does not affect cross-references.

```
\begin{prop}
  \item[Humean Supervenience, gloss=after David Lewis]
  Every fact is entailed by some fact about the
  fundamental properties and spatiotemporal relations
  of points.
```

`\end{prop}`

Humean Supervenience (after David Lewis) Every fact is entailed by some fact about the fundamental properties and spatiotemporal relations of points.

`gloss format`= $\langle template \rangle$ (initially $\sim(\#1)$)

Format for displaying the gloss in the label.

`label format`= $\langle template \rangle$ (no default)

Format applied to the *entire* assembled label, i.e. the name (after `display format`^{P.8}), shorthand, and gloss together. Use `#1` for the whole assembled text. For example, `label format=#1:` appends a colon after the complete label.

A label's weight and shape are normalised before any of these formats are applied, so that it reads the same wherever its item happens to sit rather than taking on the weight or shape of a block around it. (The kernel does as much for the equation number and the `description` label, and not for `enumerate`, whose label belongs to the running text.) Family is left alone, so a passage set in another family carries its labels with it. The formats are applied after the reset, so a style that wants the surrounding weight or shape need only ask: `label format={\bfseries #1}`.

`body begin`= $\langle material \rangle$ (no default)

`body end`= $\langle material \rangle$ (no default)

Material at the start and at the end of the item's *body*—the text after the label, as far as the next `\item` or the end of the environment. Unlike the format keys these take no `#1`: the body is not an argument, and cannot be handed to a command that would wrap it. What they can do is set a declaration over it, a font change being the case to have in mind: `body begin=\bfseries` on a level's style puts the items of that level in bold. The body is put in a group, so the declaration reaches the item's text and no further, and `body end` is set inside the group and before the body's last paragraph is ended. An item whose style sets neither key is not given a group at all.

A list nested in an item is part of that item's body, and so inside its group: a style that puts one level in bold puts the levels under it in bold too, unless their own `body begin` says otherwise.

`ref`= $\langle text \rangle$ (no default)

Explicitly set the reference text, overriding what would be derived from `name`^{P.7}, `counter`^{P.7}, or `shorthand`^{P.8}.

`label`= $\langle label \rangle$ (no default)

Equivalent to a trailing `\label{\langle label \rangle}`.

`reset`= $\langle boolean \rangle$ (initially `true`)

When `true` (the default), processing an `\item` resets the sub-level counter one nesting depth below the current level (e.g. `numpropii` at level 1).

`reset=false` suppresses this behaviour, so that sub-item numbering continues from where it left off across consecutive parent items.

An item that continues a run in this way does not become the parent of the sub-list that follows it: the run belongs, for referring purposes, to whatever item it began under. Taking each intervening item as the parent instead would give a run reading 1a, 1b, 2c, 2d, whose letters answer to one parent and whose prefixes to another. This is what lets an aside between two sub-lists—the `nolabel` style of section 9—interrupt a run of clauses without breaking it. An unlabelled item that should start a fresh sub-list instead wants `[style=nolabel, reset=true]`; its sub-items then refer with no prefix, having no parent reference to inherit.

`crefname=<type>` (no default)

When `cleveref` or `zref-clever` is loaded, assigns an arbitrary reference type to this proposition. For example, `crefname=lemma` on an item for which `\ref` would produce ‘(17)’ causes `\cref` (`cleveref`) or `\zcref` (`zref-clever`) to produce ‘lemma (17)’, and `\Cref` or `\zcref[cap]` to produce ‘Lemma (17)’. The `<type>` must be known to the package in use; new types can be declared with `\crefname` (with `cleveref`) or `\zcRefTypeSetup` (with `zref-clever`). (Bear in mind that a type carrying a format of its own will apply it to the reference this package has already formatted: `crefname=equation` turns ‘(17)’ into ‘eq. ((17))’, since both packages parenthesise references of that type.)

6.2 Keys for changing the list geometry

The keys in this section can be used in the following places:

- In the optional argument of `\item` (except for `topsep`^{P.11} and `partopsep`^{P.11} which only apply to complete lists), where they apply to that item alone.
- In the optional argument of `prop`^{P.5}: the key applies to that environment only, not to any other `prop`^{P.5} or `inlineprop`^{P.5} environments that may be nested within it.
- In the argument of `\proptoptions`^{P.6}: the key will apply to every subsequent `prop`^{P.5} environment (in the current group), unless overridden by that environment’s optional argument.
- In the optional argument of `\usepackage{propositions}`: equivalent to `\proptoptions`^{P.6}.
- With `\SetPropStyle`^{P.18} or `\DeclareNumberedStyle`^{P.19}, to add the key to a given style.

`align=left|right|center|flush|runin|nextline|flush-nextline` (initially `left`)

How the label should be positioned. `left` is the standard left-aligned label, its offset controlled by `labelwidth`^{P.11} and `labelsep`^{P.11}; `right` is right-aligned within the label box, like `enumerate`; `center` is centred within it; `flush` aligns the label with the left margin of the item text; `runin` does the same but reserves no label area at all: the label becomes the first word of

the item, separated from what follows by an ordinary interword space instead of a `labelsep`^{→P.11}, so that it stretches and breaks with the rest of the line; `nextline` puts the label on a line of its own, and `flush-nextline` does both. Has no effect inside `inlineprop`^{→P.5} or `\ptag`^{→P.6}. (Note that `runin`, `nextline` and `flush-nextline` put the label into the body rather than into the label box.)

```
\begin{prop}
  \item[L, align=left] Left aligned label.
  \item[C, align=center] Center aligned label.
  \item[R, align=right] Right aligned label.
  \item[Long label, align=center] As in standard \LaTeX\ lists,
    longer labels expand to fill the label box and then push
    the following text along to make room for themselves.
  \item[Flush label, align=flush] Flush aligned label.
  \item[Run-in label, align=runin] Run-in aligned label, which
    carries on as ordinary text after a single space.
  \item[Sometimes a long label will deserve its own line,
    align=nextline] Nextline aligned label.
  \item[Another rather long label,
    align=flush-nextline] Flush-nextline aligned label.
\end{prop}
```

L Left aligned label.

C Center aligned label.

R Right aligned label.

Long label As in standard L^AT_EX lists, longer labels expand to fill the label box and then push the following text along to make room for themselves.

Flush label Flush aligned label.

Run-in label Run-in aligned label, which carries on as ordinary text after a single space.

Sometimes a long label will deserve its own line

Nextline aligned label.

Another rather long label

Flush-nextline aligned label.

```
topsep=<length>
partopsep=<length>
itemsep=<length>
parsep=<length>
leftmargin=<length>
rightmargin=<length>
labelwidth=<length>
labelsep=<length>
itemindent=<length>
listparindent=<length>
labelindent=<length>
```

Override the standard L^AT_EX list dimensions. Accept the same values as `\setlength`, including rubber lengths (e.g. `itemsep=4pt plus 2pt`).

All but `topsep` and `partopsep` can be set for individual items as well as whole environments. For an item, `itemsep` determines the space *above* that item. `labelindent`^{→P.11} is not a standard L^AT_EX list dimension. It positions the left edge of the label box at $\langle length \rangle$ from the enclosing margin. This introduces a redundancy: any one of `labelindent`^{→P.11}, `labelwidth`^{→P.11}, `leftmargin`^{→P.11}, `labelsep`^{→P.11}, or `itemindent`^{→P.11} can be calculated from the four others, via the expression

$$\text{labelindent} + \text{labelwidth} + \text{labelsep} = \text{leftmargin} + \text{itemindent}$$

Whichever of these is not explicitly set will be computed from the ones that are explicitly set (or from the four most recently explicitly set) in such a way as to guarantee this identity. Each dimension key also accepts the value `*`, which means *behave as if the key had not been set*: the dimension takes the document class’s default, unless its value must shift to preserve the above identity. This behaviour is identical to that of package `enumitem`.

A dimension key can be set to any macro that expands to a dimension. For example, one can set different dimensions for different nesting levels by using `\proplevelchoice`^{→P.6}:

```
\proptoptions{leftmargin = \proplevelchoice{2.5em, 0em, *}}
```

(Note that without the `*`, the last entry `0em` would apply at every level below the second.)

`tightspacing` (no value)

Sets all vertical spacing to the compact defaults that the standard document classes use for level-three lists (`topsep`^{→P.11} and `itemsep`^{→P.11} to 2pt with stretch/shrink, `parsep`^{→P.11} to 0pt, `partopsep`^{→P.11} to 1pt).

`nosep` (no value)

Sets `\topsep`, `\itemsep`, and `\parsep` all to zero.

`continue`= $\langle boolean \rangle$ (initially `true`)

When a `prop`^{→P.5} environment with `continue=true` is immediately followed by another such environment (with no intervening paragraph text), the normal `\topsep`-based inter-list space is replaced with `\itemsep` + `\parsep`, giving the visual appearance of a single continuous list.

The following commands are intended for use in setting the values of dimension keys.

`\propformlabel`

Inside an item, this macro expands to the item’s formatted label.

```
\begin{prop}
  \item[This is a rather long label,
    labelindent=0pt,
    leftmargin=\widthof{\propformlabel}+\labelsep]
    Here we see that the left margin has been expanded to
    fit the label’s content.
```

`\end{prop}`

This is a rather long label Here we see that the left margin has been expanded to fit the label’s content.

At the beginning of the `\prop`^{P.5} environment, `\propformlabel`^{P.12} holds a “predicted” label text: whatever would be generated by an with no optional argument issued inside that environment (except that the relevant counter may be advanced by `items` key, see below).

`\proppredictedlabel`

Equivalent to `\propformlabel`^{P.12} at the beginning of an environment, but retains that “predicted” label throughout the environment, rather than being reset to hold the item’s actual label contents.

`items=<n>` (initially 1)

Indicates that (approximately) $\langle n \rangle$ items are expected in this environment. The only effect of this key is in conjunction with `\proppredictedlabel`, to compute a preview label wide enough for the $\langle n \rangle$ th expected item, so that dimension expressions such as `leftmargin=\widthof{\propformlabelP.12}+0.5em` reserve enough space for the widest label. Has no effect on actual item processing or counter stepping.

`\propwidest{<text>}`

Returns $\langle text \rangle$ with every digit replaced by the digit that makes it widest (an 8 in many fonts). The purpose is to enable styles which make `leftmargin`^{P.11} depend on the label contents (like the built in `fitmargin` and `outerfit` styles) to consider just how many digits the label has, rather than the specific digits, so that a run of numbered items can keep a steady margin instead of shifting slightly depending on the width of the digits.

6.3 Other environment-level keys

The keys in this section have effect in both the `\prop`^{P.5} and `\inlineprop`^{P.5} environments. They can also be used with `\proptoptions`^{P.6}, `\usepackage`, and `\SetPropStyle`^{P.18}, just like the keys in the previous subsection.

`named style=<style>` (initially proposition)

The base style when an `\item` or `\ptag`^{P.6} has a value for `name`^{P.7}. Explicitly given keys, including `style`^{P.7}, will override whatever is set by this style.

`nameless style=<style>` (initially numbered)

The base style used when an `\item` or `\ptag`^{P.6} has no value for `name`^{P.7}. The choice whether to assign an item `named style` or the `nameless style` turns on whether its `name`^{P.7} is set (either by its own optional argument, or by inheritance from its environment or `\proptoptions`^{P.6}).

`named ptag style=<style>`

`nameless ptag style=` $\langle style \rangle$

If set, override `named style` and `nameless style` for `\ptag`^{P.6} items only.

`wrapper begin=` $\langle code \rangle$

`wrapper end=` $\langle code \rangle$

Insert arbitrary $\langle code \rangle$ immediately before the beginning and after the end of the environment, so that the whole list can (for example) be wrapped in another environment.

Any value that contains a comma (such as a comma-separated list of options to an environment) must be enclosed in braces, so that the comma is not read as a key separator:

```
\begin{prop}[
  wrapper begin = {\begin{tcolorbox}[
    colframe = red, colback = white]},
  wrapper end   = {\end{tcolorbox}}]
  \item[Red] A proposition in a red frame.
  \item And a second one, in the same frame.
\end{prop}
```

Red A proposition in a red frame.
(7) And a second one, in the same frame.

The wrapping environment must be one that can be split into separate begin and end code—that is, it must not read its body as a macro argument via `\collect@body` or similar.

The following commands are provided for use with `wrapper begin` and `wrapper end`:

`\propoperativeleftmargin`

A read-only length giving the `leftmargin`^{P.11} a `prop`^{P.5} environment (with no optional argument) would use, given the current defaults set by `\propoptions`^{P.6} and the current nesting level. It is recomputed at every `\begin{prop}`, so it is valid inside a wrapper (before the environment's own `leftmargin`^{P.11} has taken effect). For example, the built-in `framed` style uses this command in the value of `wrapper begin` to make the margins of framed environments match those of regular environments.

`\propsetabove` $[\langle space\ above \rangle][\langle space\ below \rangle]\{\langle material \rangle\}$

`\propsetbelow` $[\langle space\ above \rangle][\langle space\ below \rangle]\{\langle material \rangle\}$

`\propsetaboveitem` $[\langle space\ above \rangle][\langle space\ below \rangle]\{\langle material \rangle\}$

For use in `wrapper begin` and `wrapper end` (respectively): sets $\langle material \rangle$ in the gap above or below the list, at the list's own left margin, and vertically centred between the adjacent line of the list and the line before or after it. The two optional arguments add vertical space on either side of it, and either may be negative.

`\propsetaboveitem` is the same for the gap above a single `\item`, and goes in `body begin`^{P.9}. It places $\langle material \rangle$ at that item's own left margin, where

`\propsetabove`, running outside the list, places it at the enclosing one; the `conclusion` style shows how a rule reaches back from there to where the label begins.

```
\begin{prop}[
  wrapper begin = \propsetabove[0.2em][0.2em]{%
    \rule{\linewidth}{0.4pt}},
  wrapper end   = \propsetbelow[0.2em][0.2em]{%
    \rule{\linewidth}{0.4pt}}]
  \item A proposition bracketed by rules.
  \item And a second one.
\end{prop}
```

-
- (8) A proposition bracketed by rules.
- (9) And a second one.
-

6.4 Global key

The following key can only be set in the optional argument of `\usepackage`, or in the preamble with `\propoptions`^{P.6}.

`equations`

(no value, **global only**)

Installs hooks so that the $\text{\LaTeX}$ and `amstex` displayed equation environments (such as `equation` and `align`) use the same formatting as the special `equation` prop style. The `equation` style's `display format`^{P.8} and `ref format`^{P.8} keys are used for generating equation numbers and cross-references to them.

Redefining the `equation` style, e.g. with

```
\SetPropStyle{equation}{format = [#1]}
```

will automatically update the hooks.

The `equations` key also sets `nameless style=eqnum`, so that top-level `\items` with no name will also use the `equation` style, while lower-level `\items` will use other kinds of numbering: for details, see section 9 below.

7 Cross-referencing commands

Labels placed after `\item` items (within `prop`^{P.5}) work with the standard `\label/\ref` mechanism. The key difference from ordinary $\text{\LaTeX}$ references is that `\ref` produces *formatted* output: for example, `\textbf` might be applied to the name, or the number might be wrapped in parentheses. The formatting is controlled by the `format` key (or separately by `display format` and `ref format`).

`\Ref{\label}`

`\Ref*{\label}`

Titlecase variants of `\ref` and `\ref*`: uppercases the first character of the formatted output, doing nothing if it has no uppercase form. (For example, if

`\ref{thesis}` produces ‘the Identity Theory’, then `\Ref{thesis}` produces ‘The Identity Theory’.) The starred form suppresses the hyperlink. Note: `\Ref` only affects references produced by this package (which are stored via `\propapply`^{→ P. 18}); for other references, it behaves like `\ref`.

`\nref{<label>}`
`\nref*{<label>}`
`\Nref{<label>}`
`\Nref*{<label>}`

“Naked ref.” Outputs the bare reference content with all formatting stripped. If `\ref{premise}` produces ‘(P1)’, then `\nref{premise}` produces ‘P1’. The starred form suppresses the hyperlink. `\Nref` is the titlecase variant: it up-percases the first character of the bare content.

`\nref` can be useful in the argument of `\item`, when the the name of one proposition should depend on that of another:

```
\SetPropStyle{proposition}{format=(\textbf{#1})}
\begin{prop}
  \item[Phys] Everything is physical. \label{phys2}
  \item[\nref{phys2}*] Almost everything is physical.
  \label{newphys2}
  \item[\ref{phys2}*] This one has two sets of parentheses,
  which is probably not desired! Note that
  the previous proposition \ref{newphys2} avoided this by using
  |\nref| in the optional argument
    of |\item|.
\end{prop}
```

(**Phys**) Everything is physical.
 (**Phys***) Almost everything is physical.
 ((**Phys***) This one has two sets of parentheses, which is probably not desired!
 Note that the previous proposition (**Phys***) avoided this by using `\nref` in
 the optional argument of `\item`.

Warning: documents where the name of one item includes a reference to that of another, and there are further references to that item, will require multiple $\LaTeX$ runs to resolve all references. To save time, it is better to avoid long chains of dependencies of this sort.

`\oref[<prefix>][<suffix>]{<label>}`
`\oref*[<prefix>][<suffix>]{<label>}`
`\Oref[<prefix>][<suffix>]{<label>}`
`\Oref*[<prefix>][<suffix>]{<label>}`

“Ref with options.” Extends `\ref` by injecting a prefix and/or suffix *inside* the formatting. With one optional argument, `<suffix>` is appended; with two, `<prefix>` is prepended and `<suffix>` appended. For instance, if `\ref{premise}` produces ‘(P1)’, then `\oref[*]{premise}` produces ‘(P1*)’ and `\oref[old~][*]{premise}` produces ‘(old~P1*)’.
`\Oref` is the titlecase variant; the starred forms suppress the hyperlink.

`\oref` can also be useful in the name of `\items`, if one wants the display format for the modified item to depend on that originally used

```
\begin{prop}
  \item[style=plain, name=\oref[$^\dag$]{phys2}]
    This will use boldface and parentheses because the
    original referenced item did.
\end{prop}
```

(**Phys[†]**) This will use boldface and parentheses because the original referenced item did.

Another handy use for `\oref` is in combination with `\nref` to refer to ranges:

```
The first two numbered examples in this document
were \oref[--\nref{atomism}]{atoms}.
```

The first two numbered examples in this document were (1–2).

`\lastref` [*prefix*] {*suffix*}

`\Lastref` [*prefix*] {*suffix*}

Produces a reference (with no hyperlink) to the most recently processed `\item` or `\ptag`^{P.6}, even without a `\label`. Useful for back-references in running text. With one argument, *suffix* is appended; with two, *prefix* is also prepended. Use `\lastref{}` for a plain reference. `\Lastref` is the titlecase variant.

`\nlastref`

`\nLastref`

Like `\lastref{}`, but returns the bare content without formatting. `\nLastref` is the titlecase variant.

`\parentref` [*prefix*] {*suffix*}

`\Parentref` [*prefix*] {*suffix*}

Inside a nested `prop`^{P.5} (or `inlineprop`^{P.5}), produces a formatted reference to the most recent item of the enclosing level. Same argument convention as `\lastref`. `\Parentref` is the titlecase variant.

`\nparentref`

`\nParentref`

Like `\parentref{}` but returns the bare content without formatting. Takes no arguments; simply output any desired suffix directly afterwards. `\nParentref` is the titlecase variant.

`\parentref` and `\nparentref` are useful for making subitems whose names derive from their parent's:

```
\begin{prop}
  \item[P1, ref format=(#1)] \label{claim}
  \begin{prop}[counter format=\alph{#1},
    display format=\textit{#1.}, ref format=\parentref{#1}]
```

```

\item \label{positive}
Some things are physical.
\item \label{negative}
Some things are not physical.
\end{prop}
\end{prop}
Of the two parts of \ref{claim}, \ref{positive} is far more controversial than \ref{negative}.

P1 a. Some things are physical.
    b. Some things are not physical.

Of the two parts of (P1), (P1a) is far more controversial than (P1b). Thus, we
will mostly be considering part b.

```

Many of the built-in numbered styles use `\parentref→P.17` in their `ref format→P.8`, to achieve this sort of composite effect.

7.1 How cross-referencing works

`\propapply{<template>}{<content>}`

Internally, each reference is stored in the .aux file as `\propapply{<template>}{<content>}`. The `<template>` contains formatting with the placeholder `\propfmtarg` where content appears. At reference time, `\propapply` evaluates the template with `\propfmtarg` bound to `<content>`. The `\oref→P.16` and `\nref→P.16` commands work by locally redefining `\propapply`. In normal use, you need not interact with `\propapply` directly.

`\propfmtarg`

Placeholder used inside templates; expands to the content argument of the enclosing `\propapply`.

8 Defining and modifying styles

Styles, equivalent to bundles of key-value settings, can be defined, and used freely in the optional arguments of `\item`, `\ptag→P.6`, `prop→P.5`, `inlineprop→P.5`, and the argument of `\proptoptions→P.6`.

`\SetPropStyle{<name>}{<keys>}`

Defines or modifies a prop style for use with the `style→P.7` key. All item-level keys (subsection 6.1) are accepted, plus the following:

`style=<parent>` (no default)

Inherit from a parent style. When an item is created, the parent's settings are loaded first (recursively, if the parent itself has a parent), then this style's own keys are applied on top.

The argument may be a macro which is expanded when the item is created: for example, a style with `style=\{<style1>\},\{<style2>\},\{<style3>\}` will resolve to `\{<style1>\}, \{<style2>\}, \{<style2>\}` depending on the nesting depth. The built-in `numbered` and `eqnum` styles use this mechanism.

macro=*<command>* (no default)

A new user macro, equivalent to `\item[style=<name>]`. Any further keys given to the macro are passed to `\item`.

If the style *<name>* already exists, `\SetPropStyle`^{P.18} modifies or adds keys. For example, `\SetPropStyle{proposition}{align=flush}` changes the alignment of the built-in `proposition` style while preserving its other settings.

Styles can freely be combined, and the definition of one style can reference another (in which case redefining the latter style will change the effect of the former style.) If you want to ensure that your style will reset appearance keys like `format`^{P.8}, include `style=plain`, which specifies as parent the built-in `plain` which resets all appearance keys to their default values.

```
\SetPropStyle{angle}{
  labelindent = 0em,
  display format = \textbf{$\langle\angle\#\!1\rangle$},
  ref format = $\langle\angle\#\!1\rangle$,
  macro = \angitem
}
\begin{prop}
  \angitem[Angle thesis] Everything is angular.
\end{prop}
No further discussion of \lastref{} is needed.
```

<Angle thesis> Everything is angular.
No further discussion of *<Angle thesis>* is needed.

\DeclareNumberedStyle{*<name>*}[*<keys>*]

Creates a new L^AT_EX counter named *<name>* and a matching prop style with `counter=<name>` and parent style `plain` (so appearance keys are reset). All `\SetPropStyle`^{P.18} keys are accepted, plus:

parent=*<counter>* (no default)

A parent counter; the new counter resets when the parent steps (same mechanism as `\numberwithin`). For numbering that begins again at each list rather than running through the document, see `enumprop` under `counter`^{P.7}.

```
\DeclareNumberedStyle{P}
\begin{prop}
  \item[counter=P] First premise. \label{p1}
  \item[counter=P] Second premise. \label{p2}
\end{prop}
From \ref{p1} and \ref{p2}\ldots
```

(P1) First premise.
(P2) Second premise.
From (P1) and (P2)...

9 Built-in styles

The following prop styles are predefined. Each entry shows the defining code (using user-facing commands), and each group of styles ends with a live example. All styles can be modified with `\SetPropStyle`^{P.18}; the definitions are reproduced here to facilitate modification.

Text styles

plain Unformatted text label.

```
\SetPropStyle{plain}{format = #1}
```

proposition The standard style assigned to named propositions. By default, uses boldface for both the label and references.

```
\SetPropStyle{proposition}{format = \textbf{#1}}
```

thesis Intended for named propositions with a longer name. The name begins at the text margin (flush alignment), and is set in small caps; references use plain font.

```
\SetPropStyle{thesis}{display format = \textsc{#1},  
  ref format=#1, align = flush}
```

vignette Intended for things like example vignettes and comments. Italic name at the text margin, and italic references, separated from the text by a colon and ordinary space space.

```
\SetPropStyle{vignette}{ref format = \textit{#1},  
  align = runin, label format = \textit{#1:}}
```

bullet Bullet symbol varying by depth (like `\itemize`).

```
\SetPropStyle{bullet}{align = center,  
  name = \proplevelchoice{\textbullet,  
    {\normalfont\textendash}, \textasteriskcentered,  
    \textperiodcentered},  
  display format = #1}
```

nolabel A special style for creating items with no labels. Also sets `reset`^{P.9}=`false`, so these items will not disrupt the numbering of sub-lists.

```
\SetPropStyle{nolabel}{counter = none, name = {},  
  reset = false}
```

```
\begin{prop}  
  \item[One, style=plain] \label{bs:plain}  
  A proposition in style |plain|, cited as \ref{bs:plain}.
```

```

\item[Two, style=proposition] \label{bs:prop}
A proposition in style |proposition|, cited as \ref{bs:prop}.
\item[Three, style=thesis] \label{bs:thesis}
A proposition in style |thesis|, cited as \ref{bs:thesis}.
\item[Four, style=vignette] \label{bs:vignette}
A proposition in style |vignette|, cited as \ref{bs:vignette}.
\item[style=bullet] \label{bs:bullet}
A proposition in style |bullet|, cited as \ref{bs:bullet}---though
it is not often that one would want to cite an item in this style.
\item[style=nolabel]
A proposition in style |nolabel|.
\end{prop}

```

One A proposition in style plain, cited as *One*.

Two A proposition in style **proposition**, cited as **Two**.

THREE A proposition in style **thesis**, cited as *Three*.

Four: A proposition in style *vignette*, cited as *Four*.

- A proposition in style **bullet**, cited as •—though it is not often that one would want to cite an item in this style.

A proposition in style **nolabel**.

Numbered styles

numbered The default nameless style. Selects one of the helper styles **levelone**–**levelfive**, depending on nesting depth, or **footnumprop** if in a footnote (and not nested).

```

\SetPropStyle{numbered}{style = \proplevelchoice{
  \propfootnotechoice{levelone}{footnumprop},
  leveltwo, levelthree, levelfour, levelfive}}
\SetPropStyle{levelone}{counter = numpropi, format = (#1)}
\SetPropStyle{leveltwo}{counter = numpropii,
  display format = #1., ref format = \parentref{#1}}
\SetPropStyle{levelthree}{counter = numpropiii,
  display format = (#1), ref format = \parentref{.#1}}
\SetPropStyle{levelfour}{counter = numpropiv,
  display format = #1., ref format = \parentref{#1}}
\SetPropStyle{levelfive}{counter = numpropv,
  display format = (#1), ref format = \parentref{.#1}}

```

footnumprop The counter is displayed as a string of asterisks. This style is designed to be used for numbered propositions in footnotes, which should not interrupt the numbering in the main text. Note that the nesting level resets to zero inside footnotes, so a **numbered** (or **eqnum**) proposition immediately inside a footnote will always use this style.

```

\SetPropStyle{footnumprop}{counter = footprop,
  counter format = \proprepeat{#1}{*}, format = (#1)}

```

equation Uses the `equation` counter. Note that this style has a special behavior when the `equations` option is active: changing its `display format`^{→P.8} and `ref format`^{→P.8} keys (or both, by setting `format`^{→P.8}) will also change the corresponding hooks used to create the tags for numbered equations make the `equation` environment and `amstex` environments like `gather`.

```
\SetPropStyle{equation}{counter = equation, format = (#1)}
```

eqnum Like `numbered`, but uses `equation` instead of `levelone` at the outer level. The `equations` package option sets default `nameless style = eqnum`.

```
\SetPropStyle{eqnum}{style = \proplevelchoice{
\propfootnotechoice{equation}{footnumprop},
leveltwo, levelthree, levelfour, levelfive}}
```

enum Like `numbered` again, but at the outer level it uses `enumprop`, which restarts at every outermost `prop`^{→P.5}, so that the list is numbered from one however many have gone before. This is the style for a one-off lists—the behaviour of `enumerate`—where `numbered/eqnum` is for numbered propositions that carry on through the document.

```
\SetPropStyle{enumprop}{counter = enumprop, format = (#1)}
\SetPropStyle{enum}{style = \proplevelchoice{
enumprop, leveltwo, levelthree, levelfour, levelfive}}
```

```
\begin{prop}
\item \label{outer}
This is an outermost numbered item. Since the default style for
nameless items is |eqnum|, it uses the |equation| style.
\begin{prop}
\item \label{second}
This is a second level item, using |leveltwo|.
\begin{prop}
\item \label{third}
This is a third level item, using |levelthree|.
\begin{prop}
\item \label{fourth}
This is a fourth level item, using |levelfour|.
\begin{prop}
\item \label{fifth}
This is a fifth level item, using |levelfive|.
\end{prop}
\item Another fourth level item.
\end{prop}
\item Another third level item.
\end{prop}
\item Another second level item.
\end{prop}
\end{prop}
We hope you enjoyed reading \ref{outer}, \ref{second}, \ref{third},
\ref{fourth}, and \ref{fifth}.
```

```

\begin{prop}[style=enum]
  \item This list will be numbered from one.
  \item If both kinds of lists are used in the same
    document, they had better be formatted differently
    so readers don't get confused.
\end{prop}

```

(10) This is an outermost numbered item. Since the default style for nameless items is `eqnum`, it uses the `equation` style.

- a. This is a second level item, using `leveltwo`.
 - (i) This is a third level item, using `levelthree`.
 - A. This is a fourth level item, using `levelfour`.
 - (I) This is a fifth level item, using `levelfive`.
 - B. Another fourth level item.
 - (ii) Another third level item.
 - b. Another second level item.

We hope you enjoyed reading (10), (10a), (10a.i), (10a.iA), and (10a.iA.I).

- (1) This list will be numbered from one.
- (2) If both kinds of lists are used in the same document, they had better be formatted differently so readers don't get confused.

roman Roman numerals. At the outer level, they use their own counter (reset every section); inside nested lists, they use the counter appropriate to the nesting level, so one can easily make roman-numbered sublists.

```

\DeclareNumberedStyle{roman}[parent = section,
  counter format = \roman{#1}, format = (#1)]
\SetPropStyle{roman}{counter = \proplevelchoice{
  roman, numpropii, numpropiii, numpropiv, numpropv}}

```

alph Letters. Works the same as `roman`, but with letters. Uses its own dedicated counter at the outer level.

```

\DeclareNumberedStyle{alph}[parent = section,
  counter format = \alph{#1}, display format=#1.,
  ref format = (#1)]
\SetPropStyle{alph}{counter = \proplevelchoice{
  alph, numpropii, numpropiii, numpropiv, numpropv}}

```

```

\begin{prop}
  \item[Basic classification, ref format={the \textit{#1}}]
    There are three kinds of people. \label{complex}
  \begin{prop}
    \item[style=roman] \label{partone} Those who know how to
      count, comprising in turn:
    \begin{prop}
      \item[style=alph] \label{parta} Those who know how to count
        up to some number, but not beyond.
    \end{prop}
  \end{prop}
\end{prop}

```

```

\item[style=alph] \label{partb} Those who can keep going
indefinitely.
\end{prop}
\item[style=roman] \label{parttwo} Those who do not know how
to count.
\end{prop}
\end{prop}
For \ref{complex} to serve its purpose, both \ref{partone} (and
its two components \ref{parta} and \ref{partb}) and
\ref{parttwo} are needed.
\begin{prop}
\item[style=roman]
The |roman| and |alph| styles are also useful for creating ad-hoc
numbered lists at the outer level.
\item[style=roman]
Like this one.
\end{prop}

```

Basic classification There are three kinds of people.

- (i) Those who know how to count, comprising in turn:
 - a. Those who know how to count up to some number, but not beyond.
 - b. Those who can keep going indefinitely.
- (ii) Those who do not know how to count.

For the *Basic classification* to serve its purpose, both (i) (and its two components (a) and (b)) and (ii) are needed.

- (i) The **roman** and **alph** styles are also useful for creating ad-hoc numbered lists at the outer level.
- (ii) Like this one.

hierarchical Produces 1, 1.1, 1.1.1... numbering. Defined via two helper styles:

```

\SetPropStyle{h-base}{counter = numpropi,
counter format = \arabic{#1}, ref format = #1,
display format = #1.}
\SetPropStyle{h-sub}{
counter = \proplevelchoice{numpropi, numpropii,
numpropiii, numpropiv, numpropv},
counter format = \arabic{#1},
format = \parentref{.#1}}
\SetPropStyle{hierarchical}{style = \proplevelchoice{
h-base, h-sub}, tightspacing}

```

Note that since the optional arguments of `prop`^{P.5} and `inlineprop`^{P.5} only affect the `\items` in the *immediate* scope of that environment (not of any nested environments), styles like **hierarchical**, which one presumably wants to apply to apply an environment along with all its sub-environments, sub-sub-environments, etc., will need to be set using `\propoptions`^{P.6}. (The scope of `\propoptions` can be controlled by creating a TeX group.)

```

\begin{group}
\propoptions{style = hierarchical, leftmargin=3em, labelindent=0em}
\begin{prop}
\item \label{theworld} The world is everything that is the case.
\begin{prop}
\item \label{totality}
The world is the totality of facts, not of things.
\begin{prop}
\item
The world is determined by the facts, and by their being all the
facts.
\item
For the totality of facts determines what is the case, and also
whatever is not the case.
\end{prop}
\end{prop}
\end{prop}
\end{group}
Proposition \ref{totality} helps elucidate the meaning of
proposition \ref{theworld}.

```

1. The world is everything that is the case.
 - 1.1 The world is the totality of facts, not of things.
 - 1.1.1 The world is determined by the facts, and by their being all the facts.
 - 1.1.2 For the totality of facts determines what is the case, and also whatever is not the case.
- Proposition 1.1 helps elucidate the meaning of proposition 1.

Environment-level styles

These styles are designed to be used in the optional argument of `prop`^{P.5} or `inlineprop`^{P.5}.

`fitmargin` Fits the left margin to the predicted width of the label, so that the label will never extend past the left margin of the following text. An item whose own label outgrows the prediction takes more room than the list settled on, never less.

```

\SetPropStyle{fitmargin}{
  labelindent = 0pt,
  leftmargin = \maxof
    {\widthof{\propwidest{\proppredictedlabel}}}
    {\widthof{\propwidest{\propformlabel}}}
  + \labelsep
}

```

(Explanation: at the start of an environment `\propformlabel`^{P.12} and `\proppredictedlabel`^{P.13} are identical, so the margin is set to the prediction. At each item, the left margin will be expanded further to fit that item's label, now stored in `\propformlabel`^{P.12}, if this is greater than the predicted one.)

When a list will contain several numbered items, you can use the `items` ^{→ P. 13} key to tell the environment how many `\items` it contains, so that it can properly anticipate how wide the widest label will be.

```
\begin{prop}[name=Fitted Margin, style=fitmargin]
  \item Notice that the |name| key needs to be set in the optional
    argument of |prop| rather than |item|, so that the style knows
    how much space needs to be reserved.
\end{prop}
\begin{prop}[items=2, style=fitmargin]
  \item
    The use of |items=2| is crucial here; without it, we would
    only reserve enough space for a one-digit number.
  \item
    This happens to be where the |equation| counter hits value 10.
\end{prop}
The |hierarchical| style arguably looks better combined with |fitmargin|:
\begin{group}
\propoptions{style=hierarchical, style=fitmargin}
\begin{prop}
  \item What is the case---a fact---is the existence of states of affairs.
\begin{prop}
  \item A state of affairs (a state of things) is a combination
    of objects (things).
\begin{prop}
  \item
    It is essential to things that they should be possible
    constituents of states of affairs.
  \item
    In logic nothing is accidental: if a thing can occur in a
    state of affairs, the possibility of the state of affairs
    must be written into the thing itself.
\end{prop}
\end{prop}
\end{prop}
\end{group}
```

Fitted Margin Notice that the `name` key needs to be set in the optional argument of `prop` rather than `item`, so that the style knows how much space needs to be reserved.

(11) The use of `items=2` is crucial here; without it, we would only reserve enough space for a one-digit number.

(12) This happens to be where the `equation` counter hits value 10.

The `hierarchical` style arguably looks better combined with `fitmargin`:

2. What is the case—a fact—is the existence of states of affairs.

2.1 A state of affairs (a state of things) is a combination of objects (things).

2.1.1 It is essential to things that they should be possible constituents of states of affairs.

2.1.2 In logic nothing is accidental: if a thing can occur in a state of affairs, the possibility of the state of affairs must be written into the thing itself.

outerfit This style behaves similar to **fitmargin** at the outer nesting level (with a bit more space between label and text), but does nothing at other levels. Intended to be set once using `\propoptions`^{P.6}, for a document that wants ‘fitmargin’-like behavior for its top-level propositions, but not for lower-level propositions (where adjusting to accommodate, e.g., roman numerals of different lengths would be a delicate task).

This matches the behaviour of the `\ex.` command in package LINGUEX, widely used in linguistics.

```
\SetPropStyle{outerfit}{
  labelindent = \proplevelchoice{0pt, *},
  leftmargin = \proplevelchoice{\maxof
    {\widthof{\propwidest{\proppredictedlabel}}}
    {\widthof{\propwidest{\propformlabel}}}}
    + 1.3em, *}}
```

(Note the use of `*` in the argument of `\proplevelchoice`^{P.6}, which leaves the deeper levels as though neither key had been set.)

framed Puts an outline around a list (requires the `tcolorbox` package to be loaded). Change the padding with `\setlength\propframepad{...}`.

```
\SetPropStyle{framed}{
  align = flush, leftmargin = 0pt, rightmargin = 0pt,
  labelindent = {}, continue = false,
  wrapper begin = {\begin{tcolorbox}[
    colback = white, colframe = black,
    boxrule = 0.4pt, arc = 0pt, boxsep = 0pt,
    left skip =
      \dimexpr\propoperativeleftmargin-\propframepad\relax,
    right skip =
      \dimexpr\propoperativeleftmargin-\propframepad\relax,
    left = \propframepad, right = \propframepad,
    top = \propframepad, bottom = \propframepad]},
  wrapper end = {\end{tcolorbox}}},
}
```

(Explanation: `leftmargin=0` means that the left margin *inside* the frame is zero. But the use of `\propoperativeleftmargin`^{P.14} indents the whole `tcolorbox` environment by the right amount for the the left margin of the enclosed material to appear at the same position that would have been used for a list without the frame style, with the frame rule one `\propframepad` further out.)

```
\begin{prop}[style=framed]
  \item[Important Claim]
  This claim is so important that it deserves to
  put in a special box!
\end{prop}
```

Important Claim This claim is so important that it deserves to put in a special box!

conclusion Draws a rule immediately before the item: intended to be used to display the conclusion of an argument whose premises have just been stated. Being an item-level style, it can mark the conclusion of an argument whose premises are items of the same list, or—applied to a one-item environment, as it always could be—of the list before it.

```
\SetPropStyle{conclusion}{body begin =
\propsetaboveitem[0.2em][0.2em]{\smash{%
\hspace*{-\labelwidth-\labelsep+\itemindent}%
\rule{\linewidth+\labelwidth+\labelsep
-\itemindent}{0.4pt}}}}
```

(The rule reaches back from where the body begins to where the label begins, and is that much wider to keep its right-hand end; with the standard dimensions that reach is exactly `leftmargin`^{→P.11}, so the rule starts at the enclosing text margin. Drop the `\hspace` and the two adjustments to start it at the body instead.)

```
\begin{prop}[counter=enumprop, format=\textbf{P#1}]
\item Everything mental has physical effects.
\item Everything that has physical effects is physical.
\end{prop}
\begin{prop}[style=conclusion]
\item[C] Everything mental is physical.
\end{prop}
```

```
P1 Everything mental has physical effects.
P2 Everything that has physical effects is physical.
C Everything mental is physical.
```

standard Resets all the environment-level keys back to their default values—potentially useful, since there is otherwise no easy way to ‘unset’ a globally-set style. Item-level keys like `align`^{→P.10} and `display format`^{→P.8} are not affected, so these will still be set by the the operative `named style`^{→P.13} or `nameless style`^{→P.13} defaults. (To reset `align` along with the other keys, just set `[style=standard, align=left]`.)

10 Compatibility

The `propositions` package is designed to work with `hyperref`, `cleveref`, `zref-clever`, `amsmath`, `tclobox`, and `beamer`.

- `amsmath` is required for `\ptag`^{→P.6} and the `equations` option.

- With `hyperref` loaded, all cross-referencing commands generate hyperlinks, as usual.
- With `cleveref` or `zref-clever` loaded, all proposition items are assigned to a private `prop` “reference type”, which by default has no special name, so `\cref` (with `cleveref`) or `\zcref` (with `zref-clever`) will generate the same output as `\ref`. The `crefname` key can override this and set a different reference type..
- The built-in `framed` style requires `tcolorbox` to be loaded.
- The integration with `beamer` is described below.

None of these packages has to be loaded in any particular order relative to `propositions`: each is detected either at load time or at `\begin{document}`, whichever is needed. The usual external conventions still apply—`hyperref` late, and `cleveref` after `hyperref`.

10.1 Beamer

Under `beamer`, `prop`^{P.5} and its `\items` take overlay specifications in the same places `beamer`’s own environments do:

- `\item<2->`, and `\item<2->[Premise]` or `\item[Premise]<2->`, for one item;
- `\begin{prop}[<+>]`, for the default specification of that environment’s items, followed by keys as usual if wanted: `[<+>, align=runin]`;
- `\begin{prop}<2->`, for the environment itself (analogous to `beamer` environments like `block`.)

Specifications compose as they always do in `beamer`: an item appears where its own and its environment’s are both satisfied.

`inlineprop`^{P.5} takes the same three. An item not yet reached is covered rather than removed, exactly as in a `prop`^{P.5}, so it holds its width and the running text does not reflow as the overlays advance—and a `\label` written inside such an item still works, which one hidden with `\only` would not.

11 Known issues

When using `\ptag`^{P.6} with a named counter (e.g. `\ptag[counter=P]`) inside an `amsmath` equation environment, `hyperref` may emit warnings of the form:

```
pdfTeX warning: destination with the same
identifier (name{equation.N}) has been already
used, duplicate ignored
```

These warnings are harmless and do not affect the correctness of cross-references.

12 Release notes

0.92 (unreleased) [Change] `conclusion` is now an item-level style, so an argument’s premises and its conclusion can be items of one list. New `\propsetaboveitem`^{→P.14}. A style that redefined `conclusion` by re-setting its wrapper `begin`^{→P.14} must now clear that key, since `\SetPropStyle`^{→P.18} adds to a style rather than replacing it and the two rules would both be drawn.

[New] The list-geometry keys work in an `\item`’s argument too, where they apply to that item alone: `leftmargin`^{→P.11}, `rightmargin`^{→P.11}, `parsep`^{→P.11}, `listparindent`^{→P.11} and `itemsep`^{→P.11} join the four that already did.

[Change] `\propformlabel`^{→P.12} follows each item inside a `prop`^{→P.5}; `\proppredictedlabel`^{→P.13} is still the environment’s prediction. `\propwidestlabel` is retired in favour of `\propwidest`^{→P.13}{*label*}. `fitmargin` and `outerfit` now let an item whose label outgrows the prediction take more room.

[Bug fix] A dimension given in a `prop`^{→P.5}’s argument is no longer defeated by a style named earlier in the same argument.

[Change] `counter format`^{→P.7} now allows the argument `*` for “as if unset”.

[Change] Styles meant to settle an item’s whole appearance now start from `plain`, so that switching style resets the appearance keys the new style does not mention instead of leaving them as an earlier layer had them. `nolabel` now clears an inherited `shorthand`^{→P.8} and `gloss`^{→P.8} as it already cleared an inherited `name`^{→P.7}.

[Change] Item labels now normalise weight and shape, so that a label in a bold or italic block is no longer set in bold or italic. Family is unaffected, as is reference text. A style can ask for the old behaviour with `label format`^{→P.9} = `{\bfseries #1}`.

[New] `body begin`^{→P.9} and `body end`^{→P.9} keys, for material at either end of an item’s body.

[New] beamer overlay specifications on `prop`^{→P.5}, `inlineprop`^{→P.5} and their `\items`. See subsection 10.1.

[Change] Inside `inlineprop`^{→P.5}, an `\item` used without an optional argument is now followed by an interword space, so that `\item Alpha` sets like `\item[P] Alpha`. Use `\item[]` if you don’t want the space.

[Change] `numropi` now resets at each chapter under `book` and `report`, as `equation` does. (Undo with `\counterwithout*{numropi}{chapter}`.)

[Bug fix] A list dimension written in terms of another—`rightmargin`^{→P.11} = `\leftmargin` for a list symmetric like `quote`—is now computed after `labelindent`^{→P.11} resolution, not before, so it sees the value the list ends up with.

[Bug fix] `\Ref`^{→P.15} and the other titlecase variants uppercase the first character only, where they used to look ahead for the first letter: a reference reading ‘(2a)’ came back as ‘(2A)’.

[Bug fix] An `inlineprop`^{→P.5} nested inside a `prop`^{→P.5} now sets its items inline, and a `prop`^{→P.5} inside an `inlineprop`^{→P.5} creates a list.

0.91 New `align`^{→P.10} value `runin`, and the built-in style `vignette` changed to use it.

New style `enum` and counter `enumprop`.

`zref-clever` is now supported alongside `cleveref`, through the same `crefname`^{→P.10} key.

New style `conclusion`, which uses new commands `\propsetabove`^{→P.14} and `\propsetbelow`^{→P.14} that place material in the gap above or below a list.

New style `nolabel`, for an item with no label at all, and `counter`^{→P.7} = `none` is now documented. An item with nothing to refer to no longer takes a `ref format`^{→P.8}: `\ref` to it printed `()` rather than nothing.

An item carrying `reset`^{→P.9} = `false` no longer becomes the parent of the sub-list that follows it, so a run of sub-items interrupted by an aside keeps the prefix it began with instead of picking up the aside's. (This is a change: such sub-references used to take each intervening item as their parent, giving runs like 1a, 1b, 2c.)

Propositions in footnotes are numbered with asterisks by the new style `footnumprop` and counter `footprop`, and the nesting level now resets inside a footnote. New commands `\proprepeat`^{→P.7} and `\propfootnotechoice`^{→P.6}.

The `prop` counter, stepped by every `prop`^{→P.5} and `inlineprop`^{→P.5} but never displayed, has been withdrawn.

Stray spaces around a `name`^{→P.7} are trimmed, so that `\item[ Alpha ]` places its label like `\item[Alpha]`.

Equation tags hand `display format`^{→P.8} a bare number, rather than one wrapped in `amsmath`'s spacing guards.

0.9 Initial public release.