

The propositions package*

Cian Dorr (with help from Claude Code)
ciandorr@gmail.com

2026/02/13

Abstract

The `propositions` package provides a key-value driven system for labelling propositions, theses, and premises in academic papers. Items may be given names like ‘(P)’ or ‘Physicalism’, or auto-numbered using different counters; all carry robust cross-references with configurable formatting. The package integrates with `amsmath`, `hyperref`, and `cleveref`.

Contents

1	Introduction	2
2	History	2
3	Basic usage	2
4	Advanced usage	3
5	The prop environment and <code>\pitem</code>	4
6	Item types	7
6.1	Built-in types	8
7	Cross-referencing	10
7.1	How it works: <code>\propapply</code>	13
8	Package options	13
8.1	List dimensions	14
8.2	Default types	14
8.3	Equation numbering	15
9	Compatibility	15
10	Known issues	15

*This document describes version v0.2, dated 2026/02/13.

1 Introduction

In some academic disciplines (such as philosophy), it is common to have displayed propositions (examples, theses, premises, . . .) with various kinds of labels. A thesis might be referred to as ‘(P)’ or ‘Physicalism’; the premises of an argument might be numbered as ‘P1’, ‘P2’, ‘P3’, . . . ; or examples might be numbered consecutively over the course of a whole article. Standard $\text{\LaTeX}$ environments like `enumerate` can handle some of these cases, but cross-referencing is awkward: `\ref` produces a bare number or letter, and the author must manually add parentheses or other formatting at every point of reference. The standard `description` environment does not allow cross-referencing at all.

The `propositions` package solves this by attaching formatting information to each label. A short item like `\item[P]` (inside `prop`) is displayed as “(P)” and `\ref` automatically produces “(P)” as well—complete with parentheses, hyperlinks, and `cleveref` support. The full key-value interface supports named items, numbered items, custom counters, glosses, shorthands, and per-item format overrides.

The `\ptag` command (which requires `amsmath`) extends this to displayed math environments: an equation can be tagged with a proposition label instead of (or using) its equation number.

2 History

I wrote the ancestor to this package in the 90s while finishing my Ph.D. thesis, but never documented it or shared it with the world. This new version is a thorough re-implementation in $\text{\LaTeX}3$, written in 2026 with extensive help from Claude Code. I hope others will find it as useful as I have.

3 Basic usage

Load the package with `\usepackage{propositions}` or `\usepackage[options]{propositions}` (see [section 8](#) below for valid package options).

The `prop` environment generates a list of propositions, each introduced by `\item`. `\item` with an optional argument gives a `description`-like label:

<pre>\begin{prop} \item[Physicalism] Everything is physical. \label{phys} \item[Idealism] Everything is mental. \label{ideal} \end{prop}</pre>	Physicalism Everything is physi- cal. Idealism Everything is mental.
--	--

Unlike the standard `description` environment, one can refer back to these propositions using the standard `\ref` command:

<pre>\ref{phys} is more plausible than \ref{ideal}.</pre>	Physicalism is more plausible than Idealism.
---	---

With no optional argument, `\item` will by default generate numbered items similar to `enumerate`, but with numbering that persists across the document:

<pre> \begin{prop} \item Every atom is physical. \label{atoms} \end{prop} \ref{phys} follows from the conjunction of \ref{atoms} and \begin{prop} \item Everything is an atom. \label{atomism} \end{prop} </pre>	(1) Every atom is physical. Physicalism follows from the conjunction of (1) and (2) Everything is an atom.
--	--

As with `enumerate`, the counter and formatting depend on the nesting level:

<pre> \begin{prop} \item \label{dual} \begin{prop} \item Some things are physical. \label{some} \item Some things are not physical. \label{notall} \end{prop} \end{prop} </pre>	(3) a. Some things are physical. b. Some things are not physical. Without (3a), (3) would be consistent with Idealism.
---	---

Without `\ref{some}`, `\ref{dual}` would be consistent with `\ref{ideal}`.

4 Advanced usage

The format of the proposition labels, and of subsequent references, are both configurable using a key=value syntax (see [section 5](#) for the possible keys):

<pre> \begin{prop} \item[No Overlap, align=flush, display format=\textsc{#1}, ref format=\textit{#1}] Nothing mental is physical. \label{incomp} \end{prop} </pre>	No OVERLAP Nothing mental is physical. Is <i>No Overlap</i> consistent with Physicalism?
--	---

Is `\ref{incomp}` consistent with `\ref{phys}`?

Preset *item types* can be declared and used instead of configuring the `\items` one at a time:

<pre> \begin{prop} \item[Nihilism, type=thesis] There is nothing. \label{nihilism} \end{prop} </pre>	NIHILISM There is nothing. Does NIHILISM imply Physicalism, (3), or both? Discuss.
--	---

Does `\ref{nihilism}` imply `\ref{phys}`, `\ref{dual}`, or both? Discuss.

Shortcut commands—e.g., `\titem[⟨keys⟩]` for `\item[type=thesis, ⟨keys⟩]` (within `prop`)—can also be defined. The package loads with a range of predefined types.

When the package is loaded with `\usepackage[equations]{propositions}`, first-level `\items` within `prop` use the same counter as equations. (This looks better with the `leqno` option to `\documentclass`.)

<pre>\begin{equation} \exists x (\text{Mental}(x) \wedge \text{Physical}(x)) \end{equation} \begin{prop} \item There is overlap between the mental and the physical. \end{prop}</pre>	$(4) \quad \exists x(\text{Mental}(x) \wedge \text{Physical}(x))$ $(5) \quad \text{There is overlap between the mental and the physical.}$
---	--

The `\ptag` command (requires `amsmath`) is an analogue of `\item` (within `prop`) that works inside displayed math environments.

<pre>\begin{equation} \ptag{Monism} \label{mon} \exists x \forall y (y = x) \end{equation} Is \ref{mon} compatible with \ref{dual}?</pre>	$\text{Monism} \quad \exists x \forall y (y = x)$ $\text{Is Monism compatible with (3)?}$
---	---

5 The `prop` environment and `\pitem`

```
\begin{prop}[⟨keys⟩]
  ⟨environment content⟩
\end{prop}
```

Creates a displayed list of propositions. It is a standard L^AT_EX list, so by default its formatting will depend on the standard length parameters like `\itemsep` and `\topsep`, although these can be overridden by setting package keys.

Within `prop`, `\pitem` (see below) creates labelled items. The ordinary `\item` command is still available for unlabelled items.

Any display math environment (`\equation`, `align`, etc.) used inside `prop` or `inlineprop` automatically increments the nesting level for its duration, so that `\ptag` inside such an environment behaves as if it were one level deeper. The optional `⟨keys⟩` argument accepts the same keys as `\proppositions`^{P.13} (section 8), with effects local to this environment.

```
\begin{inlineprop}[⟨keys⟩]
  ⟨environment content⟩
\end{inlineprop}
```

Like `prop`, but does not create a list. Allows `\pitem` to be used outside list environments, e.g. for generating numbers at the beginning of paragraphs. Steps the `prop` counter and increments the nesting level. Accepts the same optional `⟨keys⟩` as `prop`.

Within `prop` and `inlineprop`, `\item` is redefined to act as the proposition-item command. Its optional argument is a comma-separated list of $\langle key \rangle = \langle value \rangle$ pairs (the keys are described below). A bare string without `=` is treated as a proposition name.

When used without an optional argument (or without setting `name`, `counter`, or `type`), the type is determined by the `default nameless type` key (section 8). By default this is `numbered`, which dispatches by nesting depth to `levelone`, `leveltwo`, ... via `\proplevelchoice`.

`\pitem[ $\langle keys \rangle$ ]` (deprecated)

Deprecated alias for `\item` within `prop` or `inlineprop`. Issues a warning on each use. Replace with `\item`.

`\ptag[ $\langle keys \rangle$ ]`

(Available only when `amsmath` is loaded.) Works inside displayed math environments like `equation` and `align`. Accepts the same keys as `\item` within `prop`, except that `align` has no effect (since positioning is controlled by the tag placement system).

The following keys can be used in the optional argument of `\item` (within `prop` or `inlineprop`) or the argument of `\ptag`:

`name= $\langle text \rangle$` (no default)

The proposition's name. A bare string (without `=`) in the key list is equivalent to `name= $\langle text \rangle$` .

`type= $\langle type \rangle$` (no default)

An item type, equivalent to a preset collection of keys. Types can be declared using `\SetItemTypeP.7` or `\DeclareNumberedTypeP.7`, and several come predefined (section 6).

`counter= $\langle name \rangle$` (no default)

Counter to use. The counter is automatically stepped, and the item's `name` is set to `\the $\langle name \rangle$` (though this can be overridden by `counter format` or `name`).

`counter format= $\langle template \rangle$` (no default)

How to display the counter value. Use `#1` for the counter name, e.g. `counter format=\roman{#1}`. When set, this is used instead of `\the $\langle counter \rangle$` for generating the item's name.

`format= $\langle template \rangle$` (no default)

Formatting applied to the `name`: use `#1` for the argument, e.g. `format=\textbf{(#1)}`. Shorthand for setting both `display format` and `ref format`.

`display format= $\langle template \rangle$` (no default)

Format for displaying the name in the proposition's label. Does not affect cross-references.

`label format= $\langle template \rangle$` (no default)

Format applied to the *entire* assembled label, i.e. the name (after `display format`), shorthand, and gloss together. Use `#1` for the whole assembled text. For example, `label format=#1`: appends a colon after the complete label. Does not affect cross-references.

ref format= $\langle template \rangle$ (no default)
Format for subsequent cross-references to this proposition. Does not affect the display.

shorthand= $\langle text \rangle$ (no default)
An abbreviation displayed after the name. If present, the shorthand becomes the reference text: `\ref` produces the shorthand (formatted with **ref format**) rather than the full name.

shorthand format= $\langle template \rangle$ (initially $\sim[\#1]$)
Format for displaying the shorthand in the label.

gloss= $\langle text \rangle$ (no default)
A parenthetical gloss displayed after the name. Does not affect cross-references.

gloss format= $\langle template \rangle$ (initially $\sim(\#1)$)
Format for displaying the gloss in the label.

ref= $\langle text \rangle$ (no default)
Explicitly set the reference text, overriding what would be derived from **name**, **counter**, or **shorthand**.

label= $\langle label \rangle$ (no default)
Equivalent to a trailing `\label{\langle label \rangle}`.

crefname= $\langle type \rangle$ (no default)
When **cleveref** is loaded, assigns an arbitrary reference type to this proposition. For example, **crefname=lemma** causes `\cref` to use the names defined by `\crefname{lemma}{...}{...}` instead of the default **proposition** type. The $\langle type \rangle$ must be known to **cleveref**; new types can be declared with `\crefname`.

reset= $\langle boolean \rangle$ (initially **true**)
When **true** (the default), processing this `\pitem` resets the sub-level counter one nesting depth below the current level (e.g. **numpropii** at level 1). Set **reset=false** to suppress this reset, so that sub-item numbering continues from where it left off across consecutive parent items. Can also be set in a type definition via `\SetItemType`^{P. 7}.

align= $\langle type \rangle$ (no default)
How the label should be positioned. Possible values: **left** (standard left-aligned label, offset controlled by `\labelwidth` and `\labelsep`), **right** (right-aligned, like **enumerate**), **center** (centered within the label box), **flush** (aligned with left margin of item text), **nextline** (label on its own line), and **flush-nextline**. Has no effect inside `inlineprop` or `\ptag`. For left-margin alignment, use `labelindent=0em` instead.

labelsep= $\langle length \rangle$
itemindent= $\langle length \rangle$
listparindent= $\langle length \rangle$
labelindent= $\langle length \rangle$

These keys override the settings of the corresponding list dimensions just for the relevant `\pitem`. For the role of `labelindent` (which determines the distance from enclosing left margin to the left edge of the label box), see the corresponding package option.

6 Item types

`\SetItemType{<name>}{<keys>}`

Defines or modifies an item type for use with the `type` key. All `\pitem`^{P.5} keys are accepted, plus the following:

`type=<parent>` (no default)

Inherit from a parent type. When an item is created, the parent's settings are loaded first (recursively, if the parent itself has a parent), then this type's own keys are applied on top.

The argument may be a macro which is expanded when the item is created: for example, a type with `type=\{<type1>\},\{<type2>\},\{<type3>\}` will resolve to `\{<type1>\}`, `\{<type2>\}`, `\{<type2>\}` depending on the nesting depth. The built-in `numbered` and `eqnum` types use this mechanism.

`macro=<command>` (no default)

A new user macro, equivalent to `\pitem[type=<name>]`. Any further keys given to the macro are passed to `\pitem`.

If the type `<name>` already exists, `\SetItemType` modifies or adds keys. For example, `\SetItemType{proposition}{align=flush}` changes the alignment of the built-in `proposition` type while preserving its other settings.

<pre> \SetItemType{angle}{ labelindent = 0em, display format = \textbf{<\angle\$#1\$\rangle\$}, ref format = <\angle\$#1\$\rangle\$, macro = \angitem } \begin{prop} \angitem[Angle thesis] Everything is angular. \end{prop} No further discussion of \lastref{} is needed.</pre>	<Angle thesis> Everything is angular. No further discussion of <Angle thesis> is needed.
--	--

`\DeclareNumberedType{<name>}[<keys>]`

Creates a new L^AT_EX counter named `<name>` and a matching item type with `counter=<name>`. All `\SetItemType` keys are accepted, plus:

`parent=<counter>` (no default)

A parent counter; the new counter resets when the parent steps (same mechanism as `\numberwithin`). A dedicated `prop` counter (stepped by each `prop` and `inlineprop`) is available for non-persistent numbering.

<code>\DeclareNumberedType{P}</code>	P1 First premise.
<code>\begin{prop}</code>	P2 Second premise.
<code>\item[counter=P] First premise.</code>	From P1 and P2 ...
<code>\label{p1}</code>	
<code>\item[counter=P] Second premise.</code>	
<code>\label{p2}</code>	
<code>\end{prop}</code>	
<code>From \ref{p1} and \ref{p2}\ldots</code>	

`\proplevelchoice{⟨item1, item2, ...⟩}`

Picks the entry at the current nesting depth (1-indexed, clamped to the list length). At depth 0 (outside any `prop` environment), returns the first entry. This macro is fully expandable and can be used in the `name`, `format`, and `type` keys of `\SetItemType` to create depth-dependent types.

6.1 Built-in types

The following item types are predefined. Each entry shows the defining code (using user-facing commands) and a live example. All types can be modified with `\SetItemType` ^{P.7}.

Text types

plain Unformatted text label.

	<code>\SetItemType{plain}{format = #1}</code>
--	---

Claim An unformatted item.

proposition Bold text label. Auto-selected when `\item` has a name but no `type`.

	<code>\SetItemType{proposition}{format = \textbf{#1}}</code>
--	--

Thesis A bold-formatted item.

thesis Small-caps name at the text margin (flush alignment). Shortcut: `\titem`.

	<code>\SetItemType{thesis}{format = \textsc{#1},</code> <code>align = flush, macro = \titem}</code>
--	--

HYPOTHESIS A flush-aligned item.

vignette Italic name at the text margin with a colon in the label.

	<code>\SetItemType{vignette}{ref format = \textit{#1},</code> <code>align = flush, label format = \textit{#1:}}</code>
--	---

Example: A vignette item.

bullet Bullet symbol varying by depth (like `\itemize`). Shortcut: `\bitem`.

```
| \SetItemType{bullet}{align = center,  
|   name = \proplevelchoice{\textbullet,  
|     {\normalfont\textendash}, \textasteriskcentered,  
|     \textperiodcentered},  
|   display format = #1, macro = \bitem}
```

- A bullet item.

Numbered types with dedicated counters

roman Roman-numeral counter, resets per section. Shortcut: `\ritem`.

```
| \DeclareNumberedType{roman}[parent = section,  
|   counter format = \roman{#1}, format = (#1), macro = \ritem]
```

- (i) A roman-numbered item.

alph Alphabetic counter, resets per section. Shortcut: `\aitem`.

```
| \DeclareNumberedType{alph}[parent = section,  
|   counter format = \alph{#1}, format = (#1), macro = \aitem]
```

- (a) An alphabetic item.

Level-specific types

These types are used by the `numbered` and `eqnum` dispatcher types (below). They share the counters `numpropi`–`numpropv`, which reset automatically when an `\item` at the next lower level is processed.

levelone Level-1 numbered items: arabic in parentheses.

```
| \SetItemType{levelone}{counter = numpropi, format = (#1)}
```

leveltwo Level-2: lowercase alphabetic with dot.

```
| \SetItemType{leveltwo}{counter = numpropii,  
|   display format = #1., ref format = \parentref{#1}}
```

levelthree Level-3: lowercase roman in parentheses.

```
| \SetItemType{levelthree}{counter = numpropiii,  
|   display format = (#1), ref format = \parentref{.#1}}
```

levelfour Level-4: uppercase alphabetic with dot.

```
| \SetItemType{levelfour}{counter = numpropiv,  
|   display format = #1., ref format = \parentref{#1}}
```

levelfive Level-5: uppercase roman in parentheses.

```
| \SetItemType{levelfive}{counter = numpropv,  
|   display format = (#1), ref format = \parentref{.#1}}
```

equation Uses the `equation` counter. When the `equations` option is active, `\SetItemType{equation}{...}` automatically updates the `\tagform@` and `\ref` hooks for all equations.

```
| \SetItemType{equation}{counter = equation, format = (#1)}
```

Dispatcher types

These types use `type` with `\proplevelchoice` to dispatch to a level-specific type at resolution time.

numbered The default nameless type. Dispatches to `levelone`–`levelfive` by nesting depth.

```
| \SetItemType{numbered}{type = \proplevelchoice{  
|   levelone, leveltwo, levelthree, levelfour, levelfive}}
```

eqnum Like `numbered`, but uses `equation` at level 1. Activated by the `equations` package option (which sets `default nameless type = eqnum`).

```
| \SetItemType{eqnum}{type = \proplevelchoice{  
|   equation, leveltwo, levelthree, levelfour, levelfive}}
```

hierarchical Produces 1, 1.1, 1.1.1... numbering using `\parentref` and `counter format`. Defined via two helper types:

```
| \SetItemType{h-base}{counter = numpropi,  
|   counter format = \arabic{#1}, format = #1}  
| \SetItemType{h-sub}{  
|   counter = \proplevelchoice{numpropi, numpropii,  
|     numpropiii, numpropiv, numpropv},  
|   counter format = \arabic{#1},  
|   format = \parentref{.#1}}  
| \SetItemType{hierarchical}{type = \proplevelchoice{  
|   h-base, h-sub}}
```

7 Cross-referencing

Labels placed after `\item` items (within `prop`) work with the standard `\label/\ref` mechanism. The key difference from ordinary L^AT_EX references is that `\ref` produces *formatted* output: for example, `\textbf` might be applied to the name, or the number might be wrapped in parentheses. The formatting is controlled by the `format` key (or separately by `display format` and `ref format`).

`\Ref{<label>}`
`\Ref*{<label>}`

Titlecase variants of `\ref` and `\ref*`: uppercases the first letter of the formatted output. (For example, if `\ref{thesis}` produces ‘the Identity Theory’, then `\Ref{thesis}` produces ‘The Identity Theory’.) The starred form suppresses the hyperlink. Note: `\Ref` only affects references produced by this package (which are stored via `\propapply`); for other references, it behaves like `\ref`.

`\nref{<label>}`
`\nref*{<label>}`
`\Nref{<label>}`
`\Nref*{<label>}`

“Naked ref.” Outputs the bare reference content with all formatting stripped. If `\ref{premise}` produces ‘(P1)’, then `\nref{premise}` produces ‘P1’. The starred form suppresses the hyperlink. `\Nref` is the titlecase variant: it uppercases the first letter of the bare content.

`\nref` can be useful in the argument of `\item`, when the the name of one proposition should depend on that of another:

<code>\SetItemType{proposition}{format=(#1)}</code>	
<code>\begin{prop}</code>	(Phys) Everything is physical.
<code>\item[Phys]</code>	(Phys*) Almost everything is physical.
Everything is physical.	
<code>\label{phys2}</code>	((Phys*)) This one has two sets
<code>\item[\nref{phys2}*]</code>	of parentheses, which is probably
Almost everything is physical.	not desired. (Phys*) avoided this
<code>\label{newphys2}</code>	by using <code>\nref</code> .
<code>\item[\ref{phys2}*]</code>	
This one has two sets of parentheses,	
which is probably not desired.	
<code>\ref{newphys2}</code> avoided this by using	
<code> \nref </code> .	
<code>\end{prop}</code>	

Warning: documents where the name of one item includes a reference to that of another, and there are further references to that item, will require multiple $\LaTeX$ runs to resolve all references. To save time, it is better to avoid long chains of dependencies of this sort.

`\oref[<prefix>][<suffix>]{<label>}`
`\oref*[<prefix>][<suffix>]{<label>}`
`\Oref[<prefix>][<suffix>]{<label>}`
`\Oref*[<prefix>][<suffix>]{<label>}`

“Ref with options.” Extends `\ref` by injecting a prefix and/or suffix *inside* the formatting. With one optional argument, `<suffix>` is appended; with two, `<prefix>` is prepended and `<suffix>` appended. For instance, if `\ref{premise}` produces ‘(P1)’, then `\oref[*]{premise}` produces ‘(P1*)’ and `\oref[old~][*]{premise}` produces ‘(old~P1*)’.
`\Oref` is the titlecase variant; the starred forms suppress the hyperlink.

`\oref` can also be useful in the name of `\items`, if one wants the display format for the modified item to depend on that originally used

<pre> \begin{prop} \label{premise} \item[type=plain,name=\oref[*]{phys2}] This will use boldface and parentheses because the original referenced item did. \end{prop> </pre>	<pre> (Phys*) This will use boldface and parentheses because the original referenced item did. </pre>
---	---

Another handy use for `\oref` is in combination with `\nref` to refer to ranges:

<pre> The first two numbered examples in this document were were \oref[--\nref{atomism}]{atoms}. </pre>	<pre> The first two numbered examples in this document were were (1–2). </pre>
---	--

`\lastref` [*prefix*] {*suffix*}

`\Lastref` [*prefix*] {*suffix*}

Produces a reference (with no hyperlink) to the most recently processed `\pitem` or `\ptag`, even without a `\label`. Useful for back-references in running text. With one argument, *suffix* is appended; with two, *prefix* is also prepended. Use `\lastref{}` for a plain reference. `\Lastref` is the titlecase variant.

`\nlastref`

`\nLastref`

Like `\lastref{}`, but returns the bare content without formatting. `\nLastref` is the titlecase variant.

`\parentref` [*prefix*] {*suffix*}

`\Parentref` [*prefix*] {*suffix*}

Inside a nested `prop` (or `inlineprop`), produces a formatted reference to the most recent item of the enclosing level. Same argument convention as `\lastref`. `\Parentref` is the titlecase variant.

`\nparentref`

`\nParentref`

Like `\parentref{}` but returns the bare content without formatting. Takes no arguments; simply output any desired suffix directly afterwards. `\nParentref` is the titlecase variant.

`\parentref` and `\nparentref` are useful for making subitems whose names derive from their parent's:

```

\DeclareNumberedType{inner}[
  counter format=\alph{inner},
  display format=#1.]
\begin{prop}
\item[OI] Outer item.
\label{outer2}
\begin{prop}
\item[type=inner,
  format=\parentref{.#1}]
\label{dsub1}
Ref: \ref{dsub1},
naked: \nref{dsub1}.
\item[type=inner,
  display format=#1.,
  ref format=\parentref{.#1}]
\label{dsub2}
Ref: \ref{dsub2},
naked: \nref{dsub2}.
\end{prop}
\end{prop}

```

OI Outer item.

OI.a Ref: **OI.a**, naked: a.

b. Ref: **OI.b**, naked: b.

The built-in `leveltwo` and `levelthree` types have `ref format=\parentref{#1}` and `ref format=\parentref{.#1}`, respectively, so that if the parent references as ‘(P1)’, a `leveltwo` sub-item references as ‘(P1a)’ and `\nref` returns just ‘a’.

7.1 How it works: `\propapply`

`\propapply{<template>}{<content>}`

Internally, each reference is stored in the `.aux` file as `\propapply{<template>}{<content>}`.

The `<template>` contains formatting with the placeholder `\propfmtarg` where content appears. At reference time, `\propapply` evaluates the template with `\propfmtarg` bound to `<content>`. The `\oref`^{P.11} and `\nref`^{P.11} commands work by locally redefining `\propapply`.

In normal use, you need not interact with `\propapply` directly.

`\propfmtarg`

Placeholder used inside templates; expands to the content argument of the enclosing `\propapply`.

8 Package options

`\proppositions{<keys>}`

Sets package-level keys. These can also be set:

- In the optional argument of `prop` and `inlineprop` (local to that environment).
- In the preamble with `\usepackage[<options>]{propositions}` (global).

Exception: `equations` is a global key; it cannot be used in the optional argument of `prop` or `inlineprop`.

8.1 List dimensions

`topsep`= $\langle length / length list \rangle$
`partopsep`= $\langle length / length list \rangle$
`itemsep`= $\langle length / length list \rangle$
`parsep`= $\langle length / length list \rangle$
`leftmargin`= $\langle length / length list \rangle$
`rightmargin`= $\langle length / length list \rangle$
`labelwidth`= $\langle length / length list \rangle$
`labelsep`= $\langle length / length list \rangle$
`itemindent`= $\langle length / length list \rangle$
`listparindent`= $\langle length / length list \rangle$

Override the standard L^AT_EX list dimensions. Accept the same values as `\setlength`, including rubber lengths (e.g. `itemsep=4pt plus 2pt`). Each key may also take a comma-separated list of per-level values: e.g. `leftmargin={2.5em, 0em}`. The first value applies at level 1, the second at level 2, etc. Gaps in the list (e.g. `leftmargin={, 0em}`) cause the class default to be used for that level.

`labelindent`= $\langle length / length list \rangle$ (no default)

Positions the left edge of the label box at $\langle length \rangle$ from the enclosing margin, adjusting `\labelwidth`, `\leftmargin`, `\labelsep`, or `\itemindent` as needed. (Since the value of any one of these dimensions can be derived from those of the other four, it never makes sense to set all five.)

`tightspacing` (no value)

Sets all vertical spacing to the compact defaults that the standard document classes use for level-three lists (`topsep` and `itemsep` to 2pt with stretch/shrink, `parsep` to 0pt, `partopsep` to 1pt). Individual dimension keys set afterward override.

`nosep` (no value)

Sets `\topsep`, `\itemsep`, and `\parsep` all to zero.

`continue`= $\langle boolean \rangle$ (initially `true`)

When `true`, a `prop` environment that immediately follows another `prop` (with no intervening paragraph text) replaces the normal `\topsep`-based inter-list space with `\itemsep` + `\parsep`, giving the visual appearance of a single continuous list.

8.2 Default types

When `\pitem` or `\ptag` is used without an explicit `type`, one of the following defaults is selected based on whether a name/counter was given and whether `ptag` mode is active.

`default type`= $\langle type \rangle$ (initially `proposition`)

The type used when a `name` or `counter` is given but no explicit `type`.

`default ptag type`= $\langle type \rangle$ (initially empty)

If set, overrides `default type` for `\ptag` items only.

`default nameless type=<type>` (initially `numbered`)

The type used when `\pitem` or `\ptag` has no optional argument (no name, counter, or type).

`default ptag nameless type=<type>` (initially empty)

If set, overrides `default nameless type` for `\ptag` items only.

8.3 Equation numbering

`equations` (no value, **global only**)

Sets `default nameless type=eqnum` and installs hooks so that the $\text{\LaTeX}$ and `amstex` displayed equation environments (such as `equation` and `align`) use the same formatting as the `equation` item type. The `equation` type's `display format` and `ref format` keys are used for generating equation numbers and cross-references to them. Redefining the `equation` type, e.g. with

```
| \SetItemType{equation}{format = [#1]}
```

will automatically update the hooks.

9 Compatibility

The `propositions` package is designed to work with `hyperref`, `cleveref`, and `amsmath`. `amsmath` is required for `\ptag` and the `equations` option. With `cleveref` loaded, all proposition items are assigned to a default `proposition` “reference type”; the `crefname` key can override this.

Recommended load order:

```
\usepackage{hyperref}  
\usepackage{amsmath} % if using \ptag  
\usepackage{propositions}  
\usepackage{cleveref} % if used
```

10 Known issues

When using `\ptag` with a named counter (e.g. `\ptag[counter=P]`) inside an `amsmath` equation environment, `hyperref` may emit warnings of the form:

```
pdfTeX warning: destination with the same  
identifier (name{equation.N}) has been already  
used, duplicate ignored
```

These warnings are harmless and do not affect the correctness of cross-references.