



AL-KAWTHAR

U N I V E R S I T Y

Department of Computer Science

CS 121 L – Programming Fundamentals (PF)

Lab # 05

Objective:

To introduce students to the concept of nested loops in C programming. Students will learn how to use nested loops to solve problems involving patterns, palindromes, and other iterative tasks.

Name of Student	Muhammad Hashir Rafique
Student ID	BSCS24101023
Date of Lab Conducted	
Marks Obtained	
Remarks	
Signature	

LAB 5 - ACTIVITY 1

Drawing 2D Patterns using Nested Loops

Objective:

- Demonstrate the use of nested loops to print 2D patterns.

Activities:

1. Write a C program to print the following pattern using nested loops:

```
*  
* *  
* * *  
* * * *  
* * * * *
```

Example Code:

```
#include <stdio.h>  
  
int main() {  
    int rows = 5;  
  
    for (int i = 1; i <= rows; i++) {  
        for (int j = 1; j <= i; j++) {  
            printf("* ");  
        }  
        printf("\n");  
    }  
  
    return 0;  
}
```

2. Modify the program to print the following inverted pattern:

```
* * * * *  
* * * *  
* * *  
* *  
*
```

3. Dry-run the programs with sample values and explain the logic.

1. Pattern Printing

```
#include <stdio.h>

int main() {
    int rows = 5;

    for (int i = 1; i <= rows; i++) {
        for (int j = 1; j <= i; j++) {
            printf("* ");
        }
        printf("\n");
    }

    return 0;
}
```

Dry Run:

```
*
* *
* * *
* * * *
* * * * *
```

Logic - In this pattern, we use two nested loops.

- The outer loop runs from 1 to the number of rows (which is 5), and it controls the number of lines printed.
- The inner loop is responsible for printing the asterisks.
- For each row *i*, the inner loop runs from 1 to *i*, printing one * followed by a space each time. So, in the first row, it prints one star, in the second row two stars, and so on.
- After each row is printed, a newline character `\n` moves the cursor to the next line. This creates the right-angled triangle growing downward.

2. Inverted Pattern Printing

```
#include <stdio.h>

int main() {
    int rows = 5;

    for (int i = rows; i >= 1; i--) {
        for (int j = 1; j <= i; j++) {
            printf("* ");
        }
        printf("\n");
    }

    return 0;
}
```

```
}
```

Dry Run:

```
* * * * *  
* * * *  
* * *  
* *  
*
```

Logic - In this inverted pattern, the structure is similar, but the outer loop counts down instead of up.

- It starts from 5 and decreases to 1, which controls how many lines will be printed.
- The inner loop again prints the asterisks, but this time it prints fewer stars with each row.
- In the first iteration, it prints five stars because `i` is 5. In the next iteration, `i` becomes 4, so it prints four stars, and this continues until it reaches 1 star.
- After each set of stars, a newline is printed to move to the next line.
- This creates an upside-down right-angled triangle.

LAB 5 - ACTIVITY 2

Palindrome Checker using Nested Loops

Objective:

- Use nested loops to check if a given string is a palindrome.

Activities:

1. Define a palindrome (a word that reads the same backward as forward, e.g., "madam").

Example Code:

```
#include <stdio.h>
#include <string.h>

int main() {
    char str[100];

    printf("Enter a string: ");
    scanf("%s", str);

    int len = strlen(str);
    int is_palindrome = 1;

    for (int i = 0, j = len - 1; i < j; i++, j--) {
        if (str[i] != str[j]) {
            is_palindrome = 0;
            break;
        }
    }

    if (is_palindrome) {
        printf("%s is a palindrome.\n", str);
    } else {
        printf("%s is NOT a palindrome.\n", str);
    }

    return 0;}
```

2. Write a C program to check if a user-input string is a palindrome using nested loops.
 3. Test the program with sample inputs (e.g., "racecar", "hello").
-

C Language Code

```
#include <stdio.h>
#include <string.h>

int main() {
    char str[100];
    int is_palindrome = 1;

    printf("Enter a string: ");
    scanf("%s", str);

    int len = strlen(str);

    // comparing front and back characters
    for (int i = 0, j = len - 1; i < j; i++, j--) {
        if (str[i] != str[j]) {
            is_palindrome = 0;
            break;
        }
    }

    if (is_palindrome) {
        printf("%s is a palindrome.\n", str);
    } else {
        printf("%s is NOT a palindrome.\n", str);
    }

    return 0;
}
```

Dry Run:

```
Enter a string: civic
civic is a palindrome.
```

LAB 5 - ACTIVITY 3

Multiplication Table using Nested Loops

Objective:

- Generate a multiplication table using nested loops.

Activities:

1. Write a C program to print the multiplication table from 1 to 10 using nested loops.
2. Format the output neatly, like below:

```
1 x 1 = 1
1 x 2 = 2
...
10 x 10 = 100
```

3. Dry-run the program and explain the loop iterations.

Example Code:

```
#include <stdio.h>

int main() {
    for (int i = 1; i <= 10; i++) {
        for (int j = 1; j <= 10; j++) {
            printf("%d x %d = %d\n", i, j, i * j);
        }
        printf("\n");
    }

    return 0;
}
```

C Language program

```
#include <stdio.h>

int main() {
    for (int i = 1; i <= 10; i++) {
        for (int j = 1; j <= 10; j++) {
            printf("%d x %d = %d\n", i, j, i * j);
        }
        printf("\n"); // Adds a blank line after each table
    }

    return 0;
}
```

Dry Run:

```
1 x 1 = 1
1 x 2 = 2
1 x 3 = 3
1 x 4 = 4
1 x 5 = 5
1 x 6 = 6
1 x 7 = 7
1 x 8 = 8

...
...
...

10 x 5 = 50
10 x 6 = 60
10 x 7 = 70
10 x 8 = 80
10 x 9 = 90
10 x 10 = 100
```


LAB 5 - ASSIGNMENT

Prepare a document that includes the following:

1. Definition: Nested loops involve loops inside another loop, useful for grids/multi-level iterations.
2. Programs in C language:
 - Pattern: Print a pyramid using *.
 - Palindrome: Check if a number (e.g., 121) is a palindrome.
 - Grid: Print a 5x5 grid of numbers (1 to 25).
3. Flowcharts: Hand-drawn for each program.

(1)

Definition: Nested Loops in C

A nested loop means using one loop inside another loop. It's commonly used when you need to work with multi-dimensional patterns, such as printing grids, patterns, or handling rows and columns. For example, to print a 5x5 grid, you use an outer loop for rows and an inner loop for columns.

(2)

Pyramid Code:

```
#include <stdio.h>

int main() {
    int rows = 5;

    for (int i = 1; i <= rows; i++) {
        // Print spaces
        for (int space = 1; space <= rows - i; space++) {
            printf(" ");
        }
        // Print stars
        for (int j = 1; j <= 2 * i - 1; j++) {
            printf("*");
        }
        printf("\n");
    }

    return 0;
}
```

FLOWCHART OF THE PREVIOUS PROGRAM

Palindrome checker:

```
#include <stdio.h>

int main() {
    int num, original, reversed = 0, digit;

    printf("Enter a number: ");
    scanf("%d", &num);

    original = num;

    while (num != 0) {
        digit = num % 10;
        reversed = reversed * 10 + digit;
        num = num / 10;
    }

    if (original == reversed) {
        printf("%d is a palindrome.\n", original);
    } else {
        printf("%d is NOT a palindrome.\n", original);
    }

    return 0;
}
```

Dry Run:

```
Enter a number: 678
678 is NOT a palindrome.
```

FLOWCHART OF THE PREVIOUS PROGRAM

Grid:

```
#include <stdio.h>

int main() {
    int count = 1;

    for (int i = 1; i <= 5; i++) {
        for (int j = 1; j <= 5; j++) {
            printf("%2d ", count);
            count++;
        }
        printf("\n");
    }

    return 0;
}
```

Dry Run:

```
1  2  3  4  5
6  7  8  9 10
11 12 13 14 15
16 17 18 19 20
21 22 23 24 25
```

FLOWCHART OF THE PREVIOUS PROGRAM