

No.	Time	Source	Destination	Protocol	Length	Info
32	4.301003	192.168.100.26	128.119.245.12	TCP	66	52934 → 443 [SYN] Seq=0 Win=64240 Len=0

MSS=1460 WS=256 SACK_PERM

Frame 32: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface \Device\NPF_{ED91EC35-9F79-4616-A8EC-EE34DDA67C15}, id 0

Ethernet II, Src: LiteonTechno_52:c1:e7 (9c:2f:9d:52:c1:e7), Dst: GuangzhouVSo_35:dd:98 (6c:68:a4:35:dd:98)

Internet Protocol Version 4, Src: 192.168.100.26, Dst: 128.119.245.12

Transmission Control Protocol, Src Port: 52934, Dst Port: 443, Seq: 0, Len: 0

No.	Time	Source	Destination	Protocol	Length	Info
37	4.403958	128.119.245.12	192.168.100.26	TCP	66	443 → 52934 [SYN, ACK] Seq=0 Ack=1 Win=29200

Len=0 MSS=1300 SACK_PERM WS=128

Frame 37: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface \Device\NPF_{ED91EC35-9F79-4616-A8EC-EE34DDA67C15}, id 0

Ethernet II, Src: GuangzhouVSo_35:dd:98 (6c:68:a4:35:dd:98), Dst: LiteonTechno_52:c1:e7 (9c:2f:9d:52:c1:e7)

Internet Protocol Version 4, Src: 128.119.245.12, Dst: 192.168.100.26

Transmission Control Protocol, Src Port: 443, Dst Port: 52934, Seq: 0, Ack: 1, Len: 0