

MacPhersons Envy Voicemail Database Definition

Thursday, December 06, 2012

6:35 AM

voicemail=# \d mailbox

		Table "public.mailbox"	
Column	Type	Modifiers	
mailboxid	integer	not null	default nextval('public.mailbox_mailboxid_seq'::text)
uniqueid	integer	not null	default nextval('public.mailbox_uniqueid_seq'::text)
context	character varying(50)	not null	default 'default'::character varying
mailbox	character varying(11)	not null	default '0'::character varying
password	character varying(5)	not null	default '0'::character varying
fullname	character varying(150)	not null	default ''::character varying
email	character varying(50)	not null	default ''::character varying
pager	character varying(50)	not null	default ''::character varying
tz	character varying(10)	not null	default 'pacific'::character varying
attach	character varying(4)	not null	default 'yes'::character varying
saycid	character varying(4)	not null	default 'yes'::character varying
dialout	character varying(10)	not null	default ''::character varying
callback	character varying(10)	not null	default ''::character varying
review	character varying(4)	not null	default 'no'::character varying
operator	character varying(4)	not null	default 'no'::character varying
envelope	character varying(4)	not null	default 'no'::character varying
sayduration	character varying(4)	not null	default 'no'::character varying
saydurationm	integer	not null	default 1
sendvoicemail	character varying(4)	not null	default 'no'::character varying
delete	character varying(4)	not null	default 'no'::character varying
nextaftercmd	character varying(4)	not null	default 'yes'::character varying
forcename	character varying(4)	not null	default 'no'::character varying
forcegreetings	character varying(4)	not null	default 'no'::character varying
hidefromdir	character varying(4)	not null	default 'yes'::character varying
stamp	timestamp without time zone	not null	default now()
usermanid	integer	not null	default 0
active	integer	not null	default 1
deleted	integer	not null	default 0

Indexes:

"mailbox_pkey" primary key, btree (mailboxid)
"mailbox_uniqueid_key" unique, btree (uniqueid)
"mailbox_idx_context" btree (context)
"mailbox_idx_mailbox" btree (mailbox)
"mailbox_idx_mailboxid" btree (mailboxid)
"mailbox_idx_uniqueid" btree (uniqueid)
"mailbox_idx_usermanid" btree (usermanid)

voicemail=# \d mailbox_flag

		Table "public.mailbox_flag"	
Column	Type	Modifiers	
mailboxflagid	integer	not null	default nextval('public.mailbox_flag_mailboxflagid_seq'::text)
mailboxid	integer	not null	default 0
mailbox	character varying(11)	not null	
fromnumber	character varying(32)		
autoroute	integer	not null	default 0
autologin	integer	not null	default 0
created	timestamp without time zone		default now()
active	integer	not null	default 1
deleted	integer	not null	default 0

Indexes:

"mailbox_flag_pkey" primary key, btree (mailboxflagid)
"mailbox_flag_idx_fromnumber" btree (fromnumber)
"mailbox_flag_idx_mailbox" btree (mailbox)
"mailbox_flag_idx_mailboxflagid" btree (mailboxflagid)
"mailbox_flag_idx_mailboxid" btree (mailboxid)

voicemail=# \d list

		Table "public.list"	
Column	Type	Modifiers	
listid	integer	not null	default nextval('public.list_listid_seq'::text)
mailbox	character varying(11)	not null	default ''::character varying
name	character varying(32)	not null	
description	character varying(128)		
keycode	character varying(32)	not null	
global	integer	not null	default 1
active	integer	not null	default 1
deleted	integer	not null	default 0

Indexes:

"list_pkey" primary key, btree (listid)
"list_idx_keycode" btree (keycode)

```
"list_idx_listid" btree (listid)
"list_idx_mailbox" btree (mailbox)
```

voicemail=# \d listitem

Table "public.listitem"			
Column	Type	Modifiers	
listitemid	integer	not null	default nextval('public.listitem_listitemid_seq'::text)
listid	integer	not null	
mailbox	character varying(11)	not null	

Indexes:

```
"listitem_pkey" primary key, btree (listitemid)
"listitem_idx_listid" btree (listid)
"listitem_idx_listitemid" btree (listitemid)
"listitem_idx_mailbox" btree (mailbox)
```

voicemail=# \d userman

Table "public.userman"			
Column	Type	Modifiers	
userid	integer	not null	default nextval('public.userman_userid_seq'::text)
fullname	character varying(64)	not null	
username	character varying(32)	not null	
password	character varying(32)	not null	
comments	character varying(128)		
accesslevelid	integer	not null	
active	integer	not null	default 1
deleted	integer	not null	default 0

Indexes:

```
"userman_pkey" primary key, btree (userid)
"userman_idx_userid" btree (userid)
"userman_idx_username" btree (username)
```

voicemail=# \d vmmessage

Table "public.vmmessage"			
Column	Type	Modifiers	
uniqueid	integer	not null	default nextval('public.vmmessage_uniqueid_seq'::text)
msgnum	integer	default 0	
mailbox	character varying(80)		
origmailbox	character varying(80)		
context	character varying(80)	default ''	character varying
callerchan	character varying(128)	default ''	character varying
callerid	character varying(80)		
origdate	character varying(40)	default ''	character varying
origtime	character varying(40)		
category	character varying(80)	default ''	character varying
duration	integer	default 0	
folder	integer	default 0	
heard	integer	default 0	
path	character varying(128)	default ''	character varying
filename	character varying(64)	default ''	character varying
created	timestamp without time zone	default now()	
active	integer	default 1	
deleted	integer	default 0	

Indexes:

```
"vmmessage_pkey" primary key, btree (uniqueid)
"vmmessage_idx_mailbox" btree (mailbox)
"vmmessage_idx_msgnum" btree (msgnum)
"vmmessage_idx_uniqueid" btree (uniqueid)
```