

Rule Driven Query Expansion

Xinze Lyu and Wei Hu

¹ State Key Laboratory for Novel Software Technology, Nanjing University, China

² Department of Computer Science and Technology, Nanjing University, China
xzlv.nju@gmail.com, whu@nju.edu.cn

Abstract. Empty answers problem exists when we use SPARQL to access RDF knowledge graph data. Put situations that querying facts in-existent to the real world aside, one reason is that users lack enough knowledge for a particular RDF knowledge graph, that leads to SPARQL queries with wrong formats or inaccurate expressions. However, due to the schema-free nature of RDF data and incompleteness of particular RDF knowledge graphs, even a SPARQL query with correct format can reflect users' intentions accurately, it may fail to get any results. Researches going on in translating the natural language to SPARQL help a lot to address the first problem, but these are inconducive for the second problem which was caused by the faults in structure and content of RDF knowledge graphs. We design a rule-driven framework to alleviate the obstacles caused by the structure and content of RDF knowledge graphs. Specifically, given a SPARQL query, we use knowledge graph oriented rule-learning procedure to take reasoning rules, with the help of these rules, our system return possible results. More importantly, our system shows detailed information with similarity score and rules to explain why our system chooses particular possible answers.

Keywords: SPARQL · Empty Answer · Rule Learning.

1 Problem Statement

1.1 Empty Answer Problem for SPARQL query

Users use SPARQL queries reflecting their intentions to access the data from RDF knowledge graph, reasons for Empty Answer Problem are various, three of which are main ones, 1)the facts that users want to query do not exist in the real world, this may be caused by the wrong mapping of entities or relations, the misplace of subjects or objects; 2)the formats of SPARQL is wrong, including the namespace, operators and so on; 3)SPARQL queries are accurate and well-formatted, but they do not have exact matches in particular RDF knowledge graphs.

The problem 1) and 2) can be regarded as users can not use SPARQL language describe their intentions, there are lots of works being done to solve this problem, including entity linking [7], relation linking [1] and more sophisticated work, translating natural language into SPARQL [6]. These works are done under the situation that users lack the full knowledge of particular RDF knowledge

graph, they aim to help users to generate well-formatted SPARQL query to reflect their intentions accurately, however, it is not enough. Even a SPARQL query can avoid the problem 1) and 2), it may still has to face problem 3). For example, when a user want to know “Who is the advisor of Newton?”, he makes a SPARQL “***SELECT ?advisor WHERE {dbr:Issac_Newton dbo:academicAdvisor ?advisor}***” to access Dbpedia, this is a correct SPARQL query, but it gets no answer because there is not an entity that exists explicit relation “*dbo:academicAdvisor*” with “*dbr:Issac_Newton*”. But Newton really has advisors, it is “*dbr:Isaac_Barrow*”, this fact is recorded as “*dbr:Issac_Newton dbo:doctoralAdvisor dbr:Isaac_Barrow*” in Dbpeida. This seems that we can make some “magic operations” to link word “advisor” to “*dbo:doctoralAdvisor*” instead of “*dbo:academicAdvisor*”, we also prepare another example in table 1. We construct this query to get Asian directors and their films. It gets no answer, too. Although some directors’ birthplaces are connected to “*dbr:China*”, “*dbr:Japan*” and so on, they are Asian directors absolutely, but no one’s birthplace is connected to “*dbr:Asia*” directly.

Table 1. SPARQL to get Asian films and their films.

	SELECT ?film ?director WHERE
(1)	?film dbo:director ?director.
(2)	?director dbo:birthPlace dbr:Asia.

In this paper, we assume that our SPARQL queries are not related to problem 1) and 2) and focus on problem 3). Problem 1) and 2) are more related to Natural Language Processing, Problem 3) is different, it is caused by the inherent limits(or features) of RDF knowledge graph. RDF knowledge graph is schema-free, there are often several similar predicates to describe the same relation, this leads to the problem about “Newton’s advisors” above; RDF knowledge graph is incomplete, it is also impossible to make a single complete RDF knowledge graph now, so it leads to the problem about “Asian” presented above.

More clearly, Problem 3) has 2 typical kinds of expressions. One is the SPARQL queries have a high level of constraints, we get an instance from the released resource of [8], there are three constraints for the SPARQL query in table 2. This query gets no answers, in fact, the constraints (1) and (2) are redundant, we can infer that “?company” is “dbr:Apple_Inc” only with constraints (3). It seems good to relax or delete the unnecessary constraints. Some works tried to solve it by Query Relaxation techniques, including replacement with similar entities and predicates [2], relaxation with ontology rule [5] and approximation for related results with representation learning in vector space [3, 8, 9]. Some works try to find which parts of a SPARQL query should be deleted, but it is a NP-hard problem and do not get good results. Also, there are works [4] that try to construct this problem as a complete document IR problem, which needs extra text sources. We will detail these methods later.

Besides high level constraints query, there are many simple and plain SPARQL queries, like “***SELECT ?advisor WHERE {dbr:Issac_Newton dbo:academicAdvisor***

?advisor}”, relaxation techniques are not proper for these simple queries, because relaxation will change the meaning of simple SPARQL queries easily.

Table 2. SPARQL with high constraints.

SELECT ?company WHERE		
(1)	?company rdfs:type	dbo:Company.
(2)	?company dbo:industry	dbr:Electronics.
(3)	dbr:IPhone dbp:developer	?company.

1.2 Semantic Parsing

1.3 Paraphrasing

1.4 Similarity Based Method

1.5 Ontology Rule Based Method

1.6 Embedding Based Method

Table 3. Table captions should be placed above the tables.

Heading level	Example	Font size and style
Title (centered)	Lecture Notes	14 point, bold
1st-level heading	1 Introduction	12 point, bold
2nd-level heading	2.1 Printing Area	10 point, bold
3rd-level heading	Run-in Heading in Bold. Text follows	10 point, bold
4th-level heading	<i>Lowest Level Heading.</i> Text follows	10 point, italic

Displayed equations are centered and set on a separate line.

$$x + y = z \quad (1)$$

Please try to avoid rasterized images for line-art diagrams and schemas. Whenever possible, use vector graphics instead (see Fig. 1).

Theorem 1. *This is a sample theorem. The run-in heading is set in bold, while the following text appears in italics. Definitions, lemmas, propositions, and corollaries are styled the same way.*

Proof. Proofs, examples, and remarks have the initial word in italics, while the following text appears in normal font.

For citations of references, we prefer the use of square brackets and consecutive numbers. Citations using labels or the author/year convention are also acceptable. The following bibliography provides a sample reference list with entries for journal articles [?], an LNCS chapter [?], a book [?], proceedings without editors [?], and a homepage [?]. Multiple citations are grouped [?, ?, ?], [?, ?, ?, ?].




Fig. 1. A figure caption is always placed below the illustration. Please note that short captions are centered, while long ones are justified by the macro package automatically.

References

1. Dubey, M., Banerjee, D., Chaudhuri, D., Lehmann, J.: Earl: Joint entity and relation linking for question answering over knowledge graphs. arXiv preprint arXiv:1801.03825 (2018)
2. Elbassuoni, S., Ramanath, M., Weikum, G.: Query relaxation for entity-relationship search. In: Extended Semantic Web Conference. pp. 62–76. Springer (2011)
3. Hamilton, W., Bajaj, P., Zitnik, M., Jurafsky, D., Leskovec, J.: Embedding logical queries on knowledge graphs. In: Advances in Neural Information Processing Systems. pp. 2030–2041 (2018)
4. Huang, H., Liu, C., Zhou, X.: Approximating query answering on rdf databases. World Wide Web **15**(1), 89–114 (2012)
5. Poulouassilis, A., Wood, P.T.: Combining approximation and relaxation in semantic web path queries. In: International Semantic Web Conference. pp. 631–646. Springer (2010)
6. Sander, M., Waltinger, U., Roshchin, M., Runkler, T.: Ontology-based translation of natural language queries to sparql. In: NLABD: AAAI Fall Symposium (2014)
7. Shen, W., Wang, J., Han, J.: Entity linking with a knowledge base: Issues, techniques, and solutions. IEEE Transactions on Knowledge and Data Engineering **27**(2), 443–460 (2015)
8. Wang, M., Wang, R., Liu, J., Chen, Y., Zhang, L., Qi, G.: Towards empty answers in sparql: Approximating querying with rdf embedding. In: International Semantic Web Conference. pp. 513–529. Springer (2018)
9. Zhang, L., Zhang, X., Feng, Z.: Trquery: An embedding-based framework for recommending sparql queries. arXiv preprint arXiv:1806.06205 (2018)