Comment	Description	Designator	Footprint	LibRef	Quantity
Button	PUSH BUTTON	B2, B3, B4	PUSH BUTTON 4 PIN SMD 5	PUSH BUTTON 4 PIN	3
Battery		BT1	Bat	Battery	1
100nf	Capacitor	C1, C3, C5, C6, C7, C12, C14, C15	CAP0805	CAP SMD	8
10uf	Capacitor	C2, C4	CAP0805	CAP SMD	2
Capacitor Tantalum SMD	Capacitor Tantalum SMD	C8, C9	Tan 1206 (3216X18L) Size A	Capacitor Tantalum SMD	2
10uf	Capacitor	C10, C11	CAP 1206 (3216X15L)	CAP SMD	2
LED RGB WS2812	LED	D1, D2	LED 5050 WS2812B	LED RGB WS2812	2
TP4056	Complete single cell Li-Ion battery with a constant current / constant voltage linear charger	IC1	SOP-8	TP4056	1
TYPE-C-31-M-12	USB Connectors 24 Receptacle 1 8.94*7.3mm RoHS	J1	HRO_TYPE-C-31-M- 12	TYPE-C-31-M-12	1
Header 3X2	Header, 3-Pin, Dual row	P1	HDR2X3	Header 3X2	1
S8050	Bipolar (BJT) Transistor NPN 25 V 500 mA 150MHz 300 mW Surface Mount SOT-23	Q1, Q2	SOT-23	SMD-TRANSISTORS- NPN-25V- 500MW(SOT-23)	2
4.7k	RESISTOR	R1, R3	RES 0805	RES	2
470	RESISTOR	R2	RES 0805	RES	1
12k	RESISTOR	R4, R6	RES 0805	RES	2
1k	RESISTOR	R5, R20	RES 0805 (2012X06L)	RES	2
5.1k	RESISTOR	R8, R9	RES 0805	RES	2
1k	RESISTOR	R11, R12, R13	RES 0805	RES	3
0R	RESISTOR	R14, R15	RES 0805	RES	2
1437566-3		S1	Subminiator SPDT switch	Subminiator SPDT switch	1
B3U-1000P	Switch Tactile N.O. SPST Round Button Gull Wing 0.05A 12VDC 1.5N SMD Embossed T/R	S2, S3	SW_B3U-1000P	B3U-1000P	2
LED	LED	STD3, STD4	L0805	LED	2
Test Point	Test Point	TP1	Test Point SMD	Test Point	1
ESP32-WROOM-32U	Bluetooth, WiFi 802.11b/g/n, Bluetooth v4.2 +EDR, Class 1, 2 and 3 Transceiver Module 2.4GHz ~ 2.5GHz Antenna Not Included, U.FL Surface Mount	U1	XCVR_ESP32- WROOM-32U	ESP32-WROOM-32U	1
CP2102	USB Bridge, USB to UART USB 2.0 UART Interface 28-QFN _5x5_	U2	QFN28G_0.5-5X5MM	INTERFACE-CP2102- GMR(QFN28)	1
Buzzer small	5-12v small buzzer (12mm)	U3	BUZZER	Buzzer	1
LF33	3.3V VOLTAGE REGULATOR	U5	D-PACK	LF33	1
LCDTFT_1.69IN	LCD TFT Color, 1.69", 240X280, ST7789V Driver	U6	LCDTFT_1.69IN_ST7 789V_MOD	LCDTFT_1.69IN_ST7 789V_MOD	1