



THERMOMETER CALIBRATION LOG

SQF NO. 11.2.3

| Thermometer ID: | | | THERMOMETER ACTUAL READING | | | | | |
|-----------------|------|------|----------------------------|-----|------|-----------|------------|-------------------|
| NO. | DATE | TIME | THERMOMETER ID | HOT | COLD | PASS/FAIL | CHECKED BY | CORRECTIVE ACTION |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |

Critical Limits: Each thermometer must be within +/- 2 OF of the certified thermometer.

Hot Calibration: Verify the boiling point of water based on the location's altitude. (Jarrell, TX BP = 210.4OF or 99OC)

Corrective Action: Difference of >/= -2 OF results in recalibration of thermometer.

Broken thermometers will be taken out of service and documented in the corrective action column. (When found during the calibration process)

Monitoring: Each thermometer will be calibrated on a daily basis.

Verification: Owner or designated employee will review this record prior to shipment of product.

| | | | |
|--------------|-------|-------|--|
| Verified By: | Date: | Time: | |
|--------------|-------|-------|--|