
Lists

Processing Variable-Length Sequences of Elements



SoftUni Team Technical Trainers







Software University

https://softuni.bg

Questions?





#fund-java

Table of Contents



- 1. Lists Overview
- 2. List Manipulating
- 3. Reading Lists from the Console
- 4. Sorting Lists and Arrays





List<E> - Overview



List<E> holds a list of elements of any type


```
List<String> names = new ArrayList<>();
//Create a list of strings
names.add("Peter");
names.add("Maria");
names.add("George");
names.remove("Maria");
for (String name : names)
  System.out.println(name);
//Peter, George
```



List<E> - Overview



```
List<Integer> nums = new ArrayList<>(
           Arrays.asList(10, 20, 30, 40, 50, 60));
nums.remove(2); Remove by index
                                    Remove by value
nums.remove(Integer.valueOf(40));
nums.add(100); Inserts an element to index
nums.add(0, -100);
                              Items count
for (int i = 0; i < nums.size(); i++)
  System.out.print(nums.get(i) + " ");
```




List<E> — Data Structure



- List<E> holds a list of elements (like array, but extendable)
- Provides operations to add / insert / remove / find elements:
 - size() number of elements in the List<E>
 - add(element) adds an element to the List<E>
 - add(index, element) inserts an element to given position
 - remove(element) removes an element (returns true / false)
 - remove(index) removes element at index
 - contains(element) determines whether an element is in the list
 - set(index, item) replaces the element at the given index


Add – Appends an Element






Remove – Deletes an Element






Add (Index, El) – Inserts an Element at Position







Reading Lists from the Console

Using for Loop or String.split()

Reading Lists from the Console



First, read from the console the array length:

```
Scanner sc = new Scanner(System.in);
int n = Integer.parseInt(sc.nextLine());
```

Next, create a list of given size n and read its elements:

```
List<Integer> list = new ArrayList<>();
for (int i = 0; i < n; i++) {
  int number = Integer.parseInt(sc.nextLine());
  list.add(number);
}</pre>
```

Reading List Values from a Single Line



Lists can be read from a single line of space separated values:

```
2 8 30 25 40 72 -2 44 56
```

```
List<Integer> items = Arrays.stream(values.split(" "))
.map(Integer::parseInt).collect(Collectors.toList());
```

Printing Lists On the Console



Printing a list using a for-loop:

Printing a list using a String.join():


Gets an element at given index


```
List<String> list = new ArrayList<>(Arrays.asList(
   "one", "two", "three", "four", "five", "six"));
System.out.println(String.join("; ", list));
```

Problem: Gauss' Trick



- Write a program that sum all numbers in a list in the following order:
 - first + last, first + 1 + last 1, first + 2 + last 2, ... first + n, last n
- Examples:





Solution: Gauss' Trick



```
Scanner sc = new Scanner(System.in);
List<Integer> numbers = Arrays.stream(sc.nextLine().split(" "))
       .map(Integer::parseInt).collect(Collectors.toList());
int size = numbers.size();
for (int i = 0; i < size / 2; i++) {
  numbers.set(i, numbers.get(i) + numbers.get(numbers.size() - 1));
  numbers.remove(numbers.size() - 1);
System.out.println(numbers.toString().replaceAll("[\\[\\],]", ""));
```


Problem: Merging Lists



- You receive two lists with numbers. Print a result list which contains the numbers from both of the lists
 - If the length of the two lists is not equal, just add the remaining elements at the end of the list
 - list1[0], list2[0], list1[1], list2[1], ...

```
1 2 3 4 5
6 7 8

1 6 2 7 3 8 4 5
```



Solution: Merging Lists



```
//TODO: Read the input
List<Integer> resultNums = new ArrayList<>();
for (int i = 0; i < Math.min(nums1.size(), nums2.size()); i++) {</pre>
 //TODO: Add numbers in resultNums
if (nums1.size() > nums2.size())
  resultNums.addAll(getRemainingElements(nums1, nums2));
else if (nums2.size() > nums1.size())
  resultNums.addAll(getRemainingElements(nums2, nums1));
System.out.println(resultNums.toString().replaceAll("[\\[\\],]", ""));
```

Solution: Merging Lists



```
public static List<Integer> getRemainingElements
       (List<Integer> longerList, List<Integer> shorterList) {
  List<Integer> nums = new ArrayList<>();
  for (int i = shorterList.size(); i < longerList.size(); i++)</pre>
    nums.add(longerList.get(i));
  return nums;
```



Sorting Lists and Arrays

Sorting Lists



- Sorting a list == reorder its elements incrementally: Sort()
 - List items should be comparable, e.g. numbers, strings, dates, ...


```
List<String> names = new ArrayList<>(Arrays.asList())
"Peter", "Michael", "George", "Victor", "John"));
Collections.sort(names); Sort in natural (ascending) order
System.out.println(String.join(", ", names));
// George, John, Michael, Peter, Victor
Collections.sort(names);
                               Reverse the sorted result
Collections.reverse(names);
System.out.println(String.join(", ", names));
// Victor, Peter, Michael, John, George
```

Problem: List of Products



 Read a number n and n lines of products. Print a numbered list of all the products ordered by name

Examples:



Check your solution here: https://judge.softuni.org/Contests/1295/

Solution: List of Products




```
int n = Integer.parseInt(sc.nextLine());
List<String> products = new ArrayList<>();
for (int i = 0; i < n; i++) {
  String currentProduct = sc.nextLine();
  products.add(currentProduct);
Collections.sort(products);
for (int i = 0; i < products.size(); i++)</pre>
  System.out.printf("%d.%s%n", i + 1, products.get(i));
```

Problem: Remove Negatives and Reverse



- Read a list of integers, remove all negative numbers from it
 - Print the remaining elements in reversed order
 - In case of no elements left in the list, print "empty"



Solution: Remove Negatives and Reverse



```
List<Integer> nums = Arrays.stream(sc.nextLine().split(" "))
       .map(Integer::parseInt).collect(Collectors.toList());
for (int i = 0; i < nums.size(); i++)</pre>
  if (nums.get(i) < 0)</pre>
    nums.remove(i--);
Collections.reverse(nums);
if (nums.size() == 0)
  System.out.println("empty");
else
  System.out.println(nums.toString().replaceAll("[\\[\\],]",
""));
```

Summary



- Lists hold a sequence of elements (variable-length)
- Can add / remove / insert elements at runtime
- Creating (allocating) a list: new ArrayList<E>()
- Accessing list elements by index
- Printing list elements: String.join(...)





Questions?

















SoftUni Diamond Partners







Coca-Cola HBC Bulgaria









Решения за твоето утре













Trainings @ Software University (SoftUni)



- Software University High-Quality Education,
 Profession and Job for Software Developers
 - softuni.bg, about.softuni.bg
- Software University Foundation
 - softuni.foundation
- Software University @ Facebook
 - facebook.com/SoftwareUniversity
- Software University Forums
 - forum.softuni.bg









License



- This course (slides, examples, demos, exercises, homework, documents, videos and other assets) is copyrighted content
- Unauthorized copy, reproduction or use is illegal
- © SoftUni https://about.softuni.bg/
- © Software University https://softuni.bg

