

A Preliminary Analysis of Syntax-Semantics Separation and Sense Selection in Word Embedding

QiPeng Guo¹ ShuaiChen Chang¹ Quan Gan² Xing
Tian³ XiangYang Xue¹ Zheng Zhang³

¹Fudan University, China

²NYU

³NYU Shanghai

April 19, 2017

Goals and Their Intuition

- Separate syntax and semantics

Goals and Their Intuition

- Separate syntax and semantics
 - We will have a syntactic embedding (which we don't really care in qualitative analysis) and a semantic embedding for each word.
 - Syntax sends structural input to semantics and phonology (Chomsky, 1995)
 - Semantic-syntactic separation is also suggested by receptive aphasia (speaking grammatically without semantic significance) and expressive aphasia (in reverse).

Goals and Their Intuition

- Separate syntax and semantics
 - We will have a syntactic embedding (which we don't really care in qualitative analysis) and a semantic embedding for each word.
 - Syntax sends structural input to semantics and phonology (Chomsky, 1995)
 - Semantic-syntactic separation is also suggested by receptive aphasia (speaking grammatically without semantic significance) and expressive aphasia (in reverse).
- Select senses for a word given its context to deal with polysemous words.


Goals and Their Intuition

- Separate syntax and semantics
 - We will have a syntactic embedding (which we don't really care in qualitative analysis) and a semantic embedding for each word.
 - Syntax sends structural input to semantics and phonology (Chomsky, 1995)
 - Semantic-syntactic separation is also suggested by receptive aphasia (speaking grammatically without semantic significance) and expressive aphasia (in reverse).
- Select senses for a word given its context to deal with polysemous words.
 - More favorably, use a single embedding to start with, and obtain the "context-dependent" embedding by *selecting* the senses from it.

Goals and Their Intuition

- Separate syntax and semantics
 - We will have a syntactic embedding (which we don't really care in qualitative analysis) and a semantic embedding for each word.
 - Syntax sends structural input to semantics and phonology (Chomsky, 1995)
 - Semantic-syntactic separation is also suggested by receptive aphasia (speaking grammatically without semantic significance) and expressive aphasia (in reverse).
- Select senses for a word given its context to deal with polysemous words.
 - More favorably, use a single embedding to start with, and obtain the "context-dependent" embedding by *selecting* the senses from it.
 - Contrary to one-sense-per-word approach.


Two-stream Model (Figure)



Baseline:

$$\mathbf{h}_t = \text{GRU}(\mathbf{h}_{t-1}, \tanh(\mathbf{W}_x \mathbf{x}_t); \boldsymbol{\theta}_{\text{GRU}})$$

$$\mathbf{y}_t = \text{Softmax}(\mathbf{h}_t; \boldsymbol{\theta}_{\text{Softmax}})$$



Two-stream Model

- Train a recurrent net to predict part-of-speech for the next word (syntactic stream).

$$\mathbf{d}_t^y = \psi(\mathbf{h}_{t-1}^y, \mathbf{x}_t^y; \mathbf{W}_c^y, \mathbf{W}_x^y)$$

$$\mathbf{h}_t^y = \text{GRU}(\mathbf{h}_{t-1}^y, \mathbf{d}_t^y; \boldsymbol{\theta}_{\text{GRU}}^y)$$

$$\mathbf{y}_t^{\text{pos}} = \text{Softmax}(\mathbf{h}_t^y; \boldsymbol{\theta}_{\text{Softmax}}^y)$$

$$\psi(\mathbf{h}_{t-1}, \mathbf{x}_t; \mathbf{W}_c, \mathbf{W}_x) = g(\mathbf{W}_c \mathbf{h}_{t-1}) \odot \tanh(\mathbf{W}_x \mathbf{x}_t)$$

$$g(x) = \begin{cases} 0 & x \leq 0 \\ 1/(1 + e^{-x}) & x > 0 \end{cases}$$

Two-stream Model

- Train a recurrent net to predict part-of-speech for the next word (syntactic stream).

$$\mathbf{d}_t^e = \psi(\mathbf{h}_{t-1}^e, \mathbf{x}_t^e; \mathbf{W}_c^e, \mathbf{W}_x^e)$$

$$\mathbf{h}_t^e = \text{GRU}(\mathbf{h}_{t-1}^e, [\mathbf{d}_t^e; \mathbf{h}_t^y]; \boldsymbol{\theta}_{\text{GRU}}^e)$$

$$\mathbf{y}_t^{\text{sem}} = \text{Softmax}(\mathbf{h}_t^e; \boldsymbol{\theta}_{\text{Softmax}}^e)$$

$$\psi(\mathbf{h}_{t-1}, \mathbf{x}_t; \mathbf{W}_c, \mathbf{W}_x) = g(\mathbf{W}_c \mathbf{h}_{t-1}) \odot \tanh(\mathbf{W}_x \mathbf{x}_t)$$

$$g(x) = \begin{cases} 0 & x \leq 0 \\ 1/(1 + e^{-x}) & x > 0 \end{cases}$$

- Fix the syntactic stream and train another recurrent net to predict the next actual word, with syntactic information (semantic stream).
- Minimize the negative log-likelihood for both part-of-speech and words.

Two-stream Model

- Train a recurrent net to predict part-of-speech for the next word (syntactic stream).

$$\begin{aligned}\vec{d}_t^y &= \psi(\vec{h}_{t-1}^y, \mathbf{x}_t^y; \vec{W}_c^y, \vec{W}_x^y) \\ \overleftarrow{d}_t^y &= \psi(\overleftarrow{h}_{t-1}^y, \mathbf{x}_t^y; \overleftarrow{W}_c^y, \overleftarrow{W}_x^y) \\ \vec{h}_t^y &= \text{GRU}(\vec{h}_{t-1}^y, \vec{d}_t^y; \theta_{\text{GRU}}^y) \\ \overleftarrow{h}_t^y &= \text{GRU}(\overleftarrow{h}_{t+1}^y, \overleftarrow{d}_t^y; \overleftarrow{\theta}_{\text{GRU}}^y) \\ \mathbf{y}_t^{\text{pos}} &= \text{Softmax}([\vec{h}_t^y; \overleftarrow{h}_{t+2}^y]; \theta_{\text{Softmax}}^y)\end{aligned}$$

- Fix the syntactic stream and train another recurrent net to predict the next actual word, with syntactic information (semantic stream).
- Minimize the negative log-likelihood for both part-of-speech and words.

Two-stream Model

- Train a recurrent net to predict part-of-speech for the next word (syntactic stream).

$$\vec{d}_t^e = \psi(\vec{h}_{t-1}^e, x_t^e; \vec{W}_c^e, \vec{W}_x^e)$$

$$\overleftarrow{d}_t^e = \psi(\overleftarrow{h}_{t-1}^e, x_t^e; \overleftarrow{W}_c^e, \overleftarrow{W}_x^e)$$

$$\vec{h}_t^e = \text{GRU}(\vec{h}_{t-1}^e, [\vec{d}_t^e; \vec{h}_t^y]; \vec{\theta}_{\text{GRU}}^e)$$

$$\overleftarrow{h}_t^e = \text{GRU}(\overleftarrow{h}_{t+1}^e, [\overleftarrow{d}_t^e; \overleftarrow{h}_t^y]; \overleftarrow{\theta}_{\text{GRU}}^e)$$

$$y_t^{\text{sem}} = \text{Softmax}([\vec{h}_t^e; \overleftarrow{h}_{t+2}^e]; \theta_{\text{Softmax}}^e)$$

- Fix the syntactic stream and train another recurrent net to predict the next actual word, with syntactic information (semantic stream).
- Minimize the negative log-likelihood for both part-of-speech and words.

Sense Selection

- Recall that we want to select only a subset of the dynamic embeddings:

$$\psi(\mathbf{h}_{t-1}, \mathbf{x}_t; \mathbf{W}_c, \mathbf{W}_x) = \mathbf{g}(\mathbf{W}_c \mathbf{h}_{t-1}) \odot \tanh(\mathbf{W}_x \mathbf{x}_t)$$


- We want $\mathbf{g} = \mathbf{g}(\mathbf{W}_c \mathbf{h}_{t-1})$ to be sparse.
- Additional penalty for each gating function output:

$$\mathcal{L}_s = \rho \log(\rho/\bar{g}) + (1 - \rho) \log(1 - \rho/\bar{g})$$

$$\bar{g} = \sum_{i=1}^{|\mathbf{g}|} g_i$$


Purging Syntactic Information

- How to ensure that there is no syntactic information left in semantic embedding \mathbf{x}^e ?




Purging Syntactic Information

- How to ensure that there is no syntactic information left in semantic embedding \mathbf{x}^e ?
 - Idea: use an *adversary* to predict the part-of-speech directly from \mathbf{x}^e ;
 - Then the model tries to fool the adversary .



Purging Syntactic Information


- How to ensure that there is no syntactic information left in semantic embedding \mathbf{x}^e ?
 - Idea: use an *adversary* to **minimize** $\sum_t -\log P(\text{POS}_t^e \mid \mathbf{x}_t^e; \theta_{\text{adv}})$ w.r.t. θ_{adv} ;
 - Then the model tries to **additionally minimize the penalty** $\mathcal{L}_{\text{adv}} = -H(\text{pos} \mid \mathbf{x}_t^e; \theta_{\text{adv}})$ w.r.t. \mathbf{x}_t^e , freezing everything else .




Sparsity (Results)

- Visualization (next frame): Pick a sentence and a word there, replace the word with every word in the vocabulary, and search the nearest neighbor of \mathbf{d}_t^e :


Sparsity (Results)



Sparsity (Results)



Sparsity (Results)



Measuring Cleanness

- Assumption: if separated successfully, given a word w and its embedding, the word of the nearby embedding should have more varied syntactic roles different from that of w .

$$\frac{1}{K} \sum_{w' \in NN_K(w)} 1_{POS(w)=POS(w')}$$

- Result of this quantity:

Model	Top-5	Top-10	Top-15	Top-20
Baseline	64.9%	69.8%	72.1%	73.1%
SynSem	60.7%	64.9%	66.7%	67.5%
SynSem + adv	48.4%	52.9%	54.8%	55.7%

Measuring Cleanness

- Assumption: if separated successfully, given a word w and its embedding, the word of the nearby embedding should have more varied syntactic roles different from that of w .


$$\frac{1}{|V|} \sum_{w \in V} \frac{1}{K} \sum_{w' \in NN_K(w)} 1_{POS(w)=POS(w')}$$

- Result of this quantity:

Model	Top-5	Top-10	Top-15	Top-20
Baseline	64.9%	69.8%	72.1%	73.1%
SynSem	60.7%	64.9%	66.7%	67.5%
SynSem + adv	48.4%	52.9%	54.8%	55.7%


Word Association

- Start from a word embedding, find the K-nearest neighbors and repeat:




Word Association

- Start from a word embedding, find the K-nearest neighbors and repeat:




Word Association

- Start from a word embedding, find the K-nearest neighbors and repeat:



Word Association

- Start from a word embedding, find the K-nearest neighbors and repeat:



More Results: Language Modeling

Model	Dataset	PPL	$ \theta $	POS PPL
Zaremba et al., 2014	PTB	78.4	66M	-
Merity et al., 2016	PTB	70.9	21M	-
Zilly et al., 2016	PTB	66.0	24M	-
Baseline Uni	PTB	74.4	6.7M	-
Baseline Uni + POS	PTB	71.7		-
SynSem Uni	PTB	73.1	7.1M	6.35
Baseline Uni	Wiki	70.3	98M	-
SynSem Uni	Wiki	67.0	100M	5.47
Baseline Bi	Wiki	39.0	149M	-
SynSem Bi	Wiki	25.5	150M	3.15

More Results: SCWS

- Stanford Contextual Word Similarities (SCWS) Dataset:
 - ... majority decisions are not binding on the **minority** ...
... the signatories was subject to **minor** reservations ...
10 humans rated an average score of 5.3

More Results: SCWS

- Stanford Contextual Word Similarities (SCWS) Dataset:
 - ...Polymers with microcrystalline regions are generally tougher (can be **bent** more without breaking)...
 - ...Sigismund was **bent** on strengthening the power of the monarchy...
 - 10 humans rated an average score of 1.7

More Results: SCWS

- Stanford Contextual Word Similarities (SCWS) Dataset:
 - ...Polymers with microcrystalline regions are generally tougher (can be **bent** more without breaking)...
 - ...Sigismund was **bent** on strengthening the power of the monarchy...
 - 10 humans rated an average score of 1.7
- We can also take a subset where each pair of queried words are identical.
 - But apparently nobody has done this before (to our best knowledge).

More Results: SCWS

- Stanford Contextual Word Similarities (SCWS) Dataset:
 - ...Polymers with microcrystalline regions are generally tougher (can be **bent** more without breaking)...
 - ...Sigismund was **bent** on strengthening the power of the monarchy...
 - 10 humans rated an average score of 1.7
- We can also take a subset where each pair of queried words are identical.
 - But apparently nobody has done this before (to our best knowledge).
- We give score by scaling the embedding (either [\mathbf{d}^y ; \mathbf{d}^e] or \mathbf{d}^e only) to norm 1 and computing the cosine distance.

More Results: SCWS

Model	w/o Ctxt	with Ctxt	Polysemous
Skip-gram-300d	65.2	-	-
Huang	62.8	65.7	-
Chen	66.2	68.9	-
Neelakantan-50d	64.0	66.1	-
Neelakantan-300d	67.3	69.3	17.2 ¹
Li et al	-	69.7	-
Qiu et al	-	66.1	-
Baseline	62.0	-	-
SynSem(400)	64.3	61.9	22.4
SynSem(600)	66.2	63.1	-
SynSem(800)	66.6	66.2	-

¹Our reproduction

Discussion & Future Work

- In terms of performance in language modeling and SCWS, it does not seem worth such hassle...
 - Do we really need to explicitly separate & select for downstream tasks (e.g. language modeling, machine translation)?
 - Likely not, but still needs investigation.