

PCTMC_methods

April 28, 2022

```
[1]: import sympy as sp
import numpy as np
import time
from scipy.integrate import odeint
import matplotlib.pyplot as plt
import numpy.random as rnd
from math import ceil
```

```
[2]: class Symbols:

    def __init__(self):
        # initialize
        self.reference = []
        self.values = []
        # initialize map from string to int and back
        self.reference2id = {}
        self.names2id = {}
        self.id2reference = {}
        self.dimension = 0

    #Adds a new symbol to the symbol array, creating a sympy object
    def add(self, name, value):
        symbol = sp.symbols(name)
        index = len(self.reference)
        self.reference.append(symbol)
        self.values.append(value)
        self.reference2id[symbol] = index
        self.names2id[name] = index
        self.id2reference[index] = symbol
        self.dimension += 1
        return symbol

    # sets the value of a symbol
    def set(self, name, value):
        try:
            index = self.names2id[name]
            self.values[index] = value
```

```

    except:
        print("Symbol " + name + " is not defined")

def get_value(self,name):
    try:
        index = self.names2id[name]
        return self.values[index]
    except:
        print("Symbol " + name + " is not defined")

#finalizes the symbol array, generating a numpy array for values
def finalize(self):
    self.values = np.array(self.values)

def get_id(self, name):
    return self.names2id[name]

```

[3]: `class Transition:`

```

def __init__(self, update, rate, sympy_symbols):
    #this will convert rate into a sympy expression.

    self.update = None
    self.update_dictionary = update
    try:
        self.rate = sp.sympify(rate, sympy_symbols, evaluate=False)
    except sp.SympifyError as e:
        print("An error happened while parsing expression", rate, ":", e)

# finalizes transition by turning the update list into a numpy array
def finalize(self, variables):
    self.update = np.zeros(variables.dimension)
    for var_name in self.update_dictionary:
        index = variables.get_id(var_name)
        self.update[index] = self.update_dictionary[var_name]
    self.update = np.reshape(self.update, (1,variables.dimension))

```

[5]: `class Model:`

```

def __init__(self):
    #init variables and parameters
    self.variables = Symbols()
    self.parameters = Symbols()
    # this contains a map of names to sympy variables, to be used later for
    ↪ parsing expressions
    self.names2sym = {}
    # init transition list

```

```

self.transitions = []
self.transition_number = 0
self.system_size = 0;
self.system_size_reference = None
self.system_size_name = ''
self.variables_names = []

def set_system_size(self, name, value):
    self.add_parameter(name, value)
    self.system_size_reference = self.names2sym[name]
    self.system_size_name = name
    self.system_size = value

def add_variable(self, name, value):
    if name in self.names2sym:
        raise ModelError("Name " + name + " already defined!")
    var = self.variables.add(name, value)
    self.variables_names.append(name)
    self.names2sym[name] = var

def add_parameter(self, name, value):
    if name in self.names2sym:
        raise ModelError("Name " + name + " already defined!")
    par = self.parameters.add(name, value)
    self.names2sym[name] = par

# Changes the initial value of a variable
def set_variable(self, name, value):
    self.variables.set(name, value)

# Changes the value of a parameter
def set_parameter(self, name, value):
    if self.system_size_name == name:
        self.parameters.set(name, value)
        self.system_size = value
    else:
        self.parameters.set(name, value)

def get_parameter_value(self, name):
    return self.parameters.get_value(name)

# Adds a transition to the model
def add_transition(self, update, rate):
    t = Transition(update, rate, self.names2sym)
    self.transitions.append(t)
    self.transition_number += 1

```

```

# Finalizes the initialization
def finalize_initialization(self):
    self.variables.finalize()
    self.parameters.finalize()
    for t in self.transitions:
        t.finalize(self.variables)

    self.__generate_vector_field()
    self.__generate_diffusion()
    self.__generate_jacobian()
    self.__generate_numpy_functions()

#generates the mean field vector field
def __generate_vector_field(self):
    self._vector_field_sympy = np.zeros(self.transitions[0].update.shape,
    ↪dtype=object)

    '''

    CODE HERE: fluid equation

    '''

    self._vector_field_sympy = sp.simplify(self._vector_field_sympy)

#generates the diffusion term
def __generate_diffusion(self):
    self._diffusion_sympy = 0

    '''

    CODE HERE: diffusion term

    '''

# computes symbolically the jacobian of the vector field
def __generate_jacobian(self):
    n = self.variables.dimension
    f = self._vector_field_sympy
    x = self.variables.reference
    J = np.zeros((n, n), dtype=object)

    '''

```

```

    CODE HERE: jacobian (sympy.diff)

    """

    self._jacobian_sympy = J

    # generate numpy expressions and the mean field VF
    def __generate_numpy_functions(self):
        sympy_ref = self.variables.reference + self.parameters.reference
        self.rates = sp.lambdify(sympy_ref, [t.rate for t in self.transitions],
        ↪ "numpy")
        self.vector_field = sp.lambdify(sympy_ref, self._vector_field_sympy,
        ↪ "numpy")
        self.diffusion = sp.lambdify(sympy_ref, self._diffusion_sympy, "numpy")
        self.jacobian = sp.lambdify(sympy_ref, self._jacobian_sympy, "numpy")

    #evaluates and returns vector field, diffusion, ...
    def evaluate_all_vector_fields(self, var_values):
        f = self.vector_field(*var_values, *self.parameters.values)
        D = self.diffusion(*var_values, *self.parameters.values)
        J = self.jacobian(*var_values, *self.parameters.values)
        return np.asarray(f), np.asarray(D), np.asarray(J)

    def evaluate_MF_vector_field(self, var_values):
        f = self.vector_field(*var_values, *self.parameters.values)
        return np.asarray(f)

    def evaluate_rates(self, var_values):
        r = self.rates(*var_values, *self.parameters.values)
        return np.asarray(r)

```

```

[6]: class Simulator:
    def __init__(self, model):
        self.model = model
        self.t0 = 0
        self.x0 = model.variables.values

    def _unpack(self, z):
        n = self.model.variables.dimension
        phi = z[0:n] # mean field
        c = np.reshape(z[n:], (n, n)) # c term
        return phi, c

```

```

def _pack(self, f, dc):
    z = np.concatenate((f.flatten(), dc.flatten()))
    return z

# computes the full vector field for the linear noise ODE
def _linear_noise_ODE(self, z, t):
    x_t, c_t = self._unpack(z)

    '''

    CODE HERE: linear noise eq

    '''

    dz = self._pack(dx_dt, dc_dt)
    return dz

# computes the vector field for the classic mean field
def _mean_field_ODE(self, x, t):

    '''

    CODE HERE: mean field eq

    '''

    return dx.flatten()

def _generate_time_stamp(self, final_time, points):
    """
    Generates a time stamp from time self.t0 to final_time,
    with points+1 number of points.

    :param final_time: final time of the simulation
    :param points: number of points
    :return: a time stamp numpy array
    """

    step = (final_time - self.t0) / points
    time = np.arange(self.t0, final_time + step, step)
    return time

def _SSA_single_simulation(self, final_time, time_stamp, model_dimension,
    ↪trans_number):
    """
    A single SSA simulation run

```

```

:param final_time: final simulation time
:param time_stamp: time array containing time points to save
:param model_dimension: dimension of the model
:param trans_number: transitions' number
:return: the variables computed along the trajectory
"""

# tracks simulation time and state
time = 0
state = self.x0
# tracks index of the time stamp vector, to save the array
print_index = 1
x = np.zeros((len(time_stamp), model_dimension))
# save initial state
x[0, :] = self.x0
# main SSA loop
trans_code = range(trans_number)
while time < final_time:
    # compute rates and total rate

    # sanity check, to avoid negative numbers close to zero

    # COMPLETE HERE

    # check if total rate is non zero.

    # store values in the output array
    while print_index < len(time_stamp) and time_stamp[print_index] <=
→time:
        x[print_index, :] = state
        print_index += 1

return x

def SSA_simulation(self, final_time, runs=100, points=1000, update=1):
    """
    Runs SSA simulation for a given number of runs and returns the average

    :param final_time: final simulation time
    :param runs: number of runs, default is 100
    :param points: number of points to be saved, default is 1000
    :param update: percentage step to update simulation time on screen
    :return: a Trajectory object, containing the average
    """

```

```

time_stamp = self._generate_time_stamp(final_time, points)
n = self.model.variables.dimension
m = self.model.transition_number
average = np.zeros((len(time_stamp), n))
# LOOP ON RUNS, count from 1
update_runs = ceil(runs * update / 100.0)
c = 0
for i in range(1, runs + 1):
    c = c + 1
    # updates every 1% of simulation time
    if c == update_runs:
        print(ceil(i * 100.0 / runs), "% done")
        c = 0
    y = self._SSA_single_simulation(final_time, time_stamp, n, m)
    # WARNING, works with python 3 only.
    # updating average
    average = (i - 1) / i * average + y / i
    time_stamp = np.reshape(time_stamp, (len(time_stamp), 1))
    trajectory = Trajectory(time_stamp, average, "SSA average", self.model.
→variables_names)
    return trajectory

def MF_simulation(self, final_time, points=1000):
    """
    Numerically integrates standard mean field equations

    :param final_time: final simulation time
    :param points: number of points to be saved
    :return: a trajectory object for model observables
    """
    t = self._generate_time_stamp(final_time, points)

    """

    CODE HERE: mean field solution

    """

    t = np.reshape(t, (len(t), 1))
    trajectory = Trajectory(t, x, "Mean Field", self.model.variables_names)
    return trajectory

def LN_simulation(self, final_time, points=1000):
    """
    Numerically integrates the linear noise equations

    :param final_time: final simulation time

```



```

: param points: number of points to be saved
: return: a trajectory object for corrected model observables
"""
n = self.model.variables.dimension
t = self._generate_time_stamp(final_time, points)

'''

CODE HERE: linear noise solution

'''

return

```

```

[7]: class Trajectory:
    def __init__(self, t, x, desc, labels):
        self.time = t
        self.data = x
        self.labels = labels
        self.description = desc

    def plot(self, var_to_plot=None):
        if var_to_plot is None:
            var_to_plot = self.labels
        fig = plt.figure()
        ax = fig.add_subplot(111)
        ax.set_prop_cycle(plt.cycler('color', ['r', 'g', 'b', 'c', 'm', 'y', 'k']))
        handles = []
        labels = []
        for v in var_to_plot:
            try:
                i = self.labels.index(v)
                h, = ax.plot(self.time, self.data[:, i])
                handles.append(h)
                labels.append(v)
            except:
                print("Variable", v, "not found")
        fig.legend(handles, labels)
        plt.title(self.description)
        plt.xlabel('Time')
        plt.show()

    def plot_comparing_to(self, trajectory, var_to_plot=None):
        if var_to_plot is None:
            var_to_plot = self.labels
        fig = plt.figure()

```

```

ax = fig.add_subplot(111)
ax.set_prop_cycle(plt.cycler('color', ['r', 'r', 'g', 'g', 'b', 'b', 'c',
↪ 'c', 'm', 'm', 'y', 'y', 'k', 'k']))
handles = []
labels = []
for v in var_to_plot:
    try:
        i = self.labels.index(v)
        h, = ax.plot(self.time, self.data[:, i])
        handles.append(h)
        labels.append(self.description + " " + v)
        h, = ax.plot(trajjectory.time, trajjectory.data[:, i], '--')
        handles.append(h)
        labels.append(trajjectory.description + " " + v)
    except Exception as e:
        print("Probably variable", v, "not found")
        print("Exception is", e)
fig.legend(handles, labels)
plt.title(self.description + " vs " + trajjectory.description)
plt.xlabel('Time')
plt.show()

```

[]: