```
No.     Time           Source                Destination           Protocol Length Info
   358 60.788411666   128.119.245.12        192.168.0.4           TCP      74     80 → 53278 [SYN, ACK] Seq=0 Ack=1
Win=28960 Len=0 MSS=1460 SACK_PERM=1 TSval=3498533228 TSecr=1086734120 WS=128
Frame 358: 74 bytes on wire (592 bits), 74 bytes captured (592 bits) on interface 0
Ethernet II, Src: Technico_06:60:74 (b4:2a:0e:06:60:74), Dst: AskeyCom_49:ad:62 (e8:d1:1b:49:ad:62)
Internet Protocol Version 4, Src: 128.119.245.12, Dst: 192.168.0.4
Transmission Control Protocol, Src Port: 80, Dst Port: 53278, Seq: 0, Ack: 1, Len: 0
    Source Port: 80
    Destination Port: 53278
    [Stream index: 28]
    [TCP Segment Len: 0]
    Sequence number: 0    (relative sequence number)
    [Next sequence number: 0    (relative sequence number)]
    Acknowledgment number: 1    (relative ack number)
    1010 .... = Header Length: 40 bytes (10)
    Flags: 0x012 (SYN, ACK)
    Window size value: 28960
    [Calculated window size: 28960]
    Checksum: 0xad88 [unverified]
    [Checksum Status: Unverified]
    Urgent pointer: 0
    Options: (20 bytes), Maximum segment size, SACK permitted, Timestamps, No-Operation (NOP), Window scale
    [SEQ/ACK analysis]
    [Timestamps]
```