

Protein Circuit Topology Plugin - Complete API Documentation

Total Callable Entry Points: 180 **Python Files With Callables:** 41

Table of Contents

1. [Calculating Functions](#) (7 functions)
2. [Plotting Functions](#) (8 functions)
3. [Importing Functions](#) (2 functions)
4. [Exporting Functions](#) (3 functions)
5. [Analysis Functions](#) (14 functions)
6. [Utility Functions](#) (65 functions)
7. [GUI Functions](#) (67 functions)
8. [Initialization Functions](#) (14 functions)

Calculating Functions

```
energy_cmap(index, numbering, res_names, protid, potential_sign='-')
```

Module: functions/calculating/energy_cmap.py

Applies an energy filter to an existing residue contact map based on a potential matrix.

```
_atoms_for_search(atoms, include_hydrogens)
```

Module: functions/calculating/get_cmap.py

Heavy atoms only, unless the caller asked for ProteinCT-identical all-atom counting.

```
get_cmap(chain, level='chain', cutoff_distance=4.5, cutoff_numcontacts=5,  
exclude_neighbour=3, include_hydrogens=False)
```

Module: functions/calculating/get_cmap.py

Creates a residue-residue contact map (as a list of contacts) for a single chain or a whole model.

Two residues are in contact when at least `cutoff_numcontacts` atom-atom pairs lie within `cutoff_distance`. Hydrogen atoms are ignored by default, so models with and without hydrogens give the same contacts; `include_hydrogens=True` counts every atom present, which is what the reference ProteinCT implementation does. At level 'model' the whole model is searched, so inter-chain contact pairs are included, and the neighbour exclusion is applied on the concatenated residue index (it therefore also spans a chain boundary).

```
get_matrix(index, protid)
```

Module: functions/calculating/get_matrix.py

Creates a topological relationship matrix for a residue contact map.

Single chain (two-column index): every pair of contact pairs is classified as Series (S), Parallel (P, P-1), Cross (X) or one of the concerted classes (CP, CP-1, CS). Whole model (four-column index, chain IDs attached): P, S and X are assigned only to two intra-chain contact pairs of the same chain. Pairs

involving inter-chain contact pairs use the multi-chain vocabulary of Heidari et al. (2022): Independent (I) when the two contact pairs involve disjoint sets of chains, Tandem (T) when they share exactly one chain, and Loop (L) when both connect the same two chains; the subscript in the statistics (I2, I3, I4, T2, T3) is the number of chains involved.

get_stats(mat)

Module: functions/calculating/get_stats.py

Calculates the fraction of Parallel and Cross (non-Series) relations on each diagonal of the relation matrix, i.e. as a function of the distance between two contact pairs in the contact list. This is the quantity ProteinCT calls the "entangled" fraction.

length_filter(index, distance, mode='<')

Module: functions/calculating/length_filter.py

Filters contact indices based on sequence separation distance.

local_ct(index, mat, numbering)

Module: functions/calculating/local_ct.py

Calculates local circuit topology statistics for each residue.

Plotting Functions

show(fig)

Module: functions/plots/_display.py

Display a figure without blocking PyMOL, regardless of what ran before it.

discrete_cmap(colors)

Module: functions/plots/_palette.py

Return (cmap, norm) mapping integer code *i* to colors[*i*], for any subset of codes.

circuit_plot(index, protid, numbering)

Module: functions/plots/circuit_plot.py

Plots the circuit topology of a protein as a series of arcs.

local_topology_plot(index, mat, numbering, siteid, relation)

Module: functions/plots/local_topology_plot.py

matrix_plot(mat, protid)

Module: functions/plots/matrix_plot.py

Plots the topological relationship matrix for a single chain.

matrix_plot_model(mat, protid)

Module: functions/plots/matrix_plot_model.py

Plots the topological relationship matrix for a whole model (multiple chains).

```
stats_plot(px_fraction, psx, protid)
```

Module: functions/plots/stats_plot.py

Plots the fraction of Parallel and Cross (non-Series) relations versus distance from the diagonal of the relation matrix, and a pie chart of the relation types.

ProteinCT calls the left-hand quantity the "entangled" fraction; it is a statement about relation types, not about geometric entanglement.

```
autopct_funct(pct)
```

Module: functions/plots/stats_plot.py

Importing Functions

```
retrieve_chain(input_file, chainid=0)
```

Module: functions/importing/retrieve_chain.py

Retrieves a specific chain from a PDB or MMCIF file.

```
warn_about_numbering(chain, protid)
```

Module: functions/importing/retrieve_chain.py

Report the two residue-numbering situations that contact detection handles imprecisely.

Exporting Functions

```
export_cmap3(index, protid, numbering, output_dir)
```

Module: functions/exporting/export_cmap3.py

Exports a residue contact map (as a binary matrix) to a CSV file.

```
export_mat(index, mat, protid, output_dir)
```

Module: functions/exporting/export_mat.py

Exports the topological relationship matrix to a CSV file.

```
export_psx(psxlist, output_dir)
```

Module: functions/exporting/export_psx.py

Exports the counts of Parallel (P), Series (S) and Cross (X) relations (and, for multi-chain models, I/T/L) to a CSV file.

A batch run accumulates every input's row into one psxlist and calls this once, so a single output file is correct - there is nothing to disambiguate with a per-input name.

Analysis Functions

```
run_local_ct(self)
```

Module: analysis/local_ct_analysis.py

Runs the local circuit topology analysis based on user-selected parameters. Handles data retrieval, calculation, plotting, and exporting.

_states_of(traj_obj, n_states)

Module: analysis/multiple_file_analysis.py

One work item per trajectory state, read straight from the loaded object.

run_multi_analysis(self)

Module: analysis/multiple_file_analysis.py

Runs the multi-file circuit topology analysis. Iterates through files in the selected directory, performs analysis, and generates plots/exports.

run_standard_analysis(self)

Module: analysis/single_file_analysis.py

Runs the standard single-file circuit topology analysis. Handles data retrieval, calculation, plotting, and exporting.

run_single_frame_analysis(self)

Module: analysis/single_frame_analysis.py

Runs circuit topology analysis for a single frame of a trajectory or a single PDB file from a directory.

toggle_frame_controls(self, enabled)

Module: analysis/single_frame_analysis.py

Toggles the enabled state of the frame selector and run button.

_safe_delete(*names)

Module: analysis/visualization.py

Delete PyMOL objects/selections, ignoring names that do not exist.

_analyse_chains(target_obj, relation_type, vals, state)

Module: analysis/visualization.py

Run the circuit topology analysis for every chain of a single-state object.

Kept separate from the colouring so that every chain - and every frame of a trajectory - can be measured first and then coloured against one shared scale.

_shared_bounds(analyses)

Module: analysis/visualization.py

One set of bucket bounds covering every chain and frame, so colours are comparable.

_apply_colours(analyses, relation_type, bounds)

Module: analysis/visualization.py

Paint each analysed chain against the shared scale.

_color_chains_by_topology(target_obj, relation_type, vals, state, *, scale_bar=True)

Module: analysis/visualization.py

Analyse and colour every chain of a single-state object against one shared scale.

`_color_every_state(state_objs, relation_type, vals, split_prefix)`

Module: analysis/visualization.py

Colour each per-state object, quietly and without repainting the scene N times.

`_visualize_trajectory(self, relation_type, selected_obj, vals, n_states)`

Module: analysis/visualization.py

Colors every state of a trajectory object by its own circuit topology.

`visualize_molecule(self, relation_type)`

Module: analysis/visualization.py

Visualizes the circuit topology on the selected molecule in PyMOL by colouring residues by their participation in the selected relation type.

Utility Functions

`clear_selected_single_file(self)`

Module: utils/clear_file.py

Clears the currently selected single file and updates the UI.

`clear_selected_local_file(self)`

Module: utils/clear_file.py

Clears the currently selected local file and updates the UI.

`_ensure_object_loaded(obj_name)`

Module: utils/directory.py

`_load_structure_file(self, label, attr_file, attr_obj)`

Module: utils/directory.py

Shared helper: open a file dialog, load into PyMOL, check for non-polymer atoms.

`_choose_output_dir(self, attr_name, label)`

Module: utils/directory.py

Shared helper: open a directory dialog and store the result.

`choose_file(self)`

Module: utils/directory.py

`choose_local_file(self)`

Module: utils/directory.py

`choose_local_output_dir(self)`

Module: utils/directory.py

`choose_output_dir(self)`

Module: utils/directory.py

choose_output_dir_multi(self)

Module: `utils/directory.py`

choose_input_dir_multi(self)

Module: `utils/directory.py`

Opens directory dialog to select the input directory containing PDBs for multi-file analysis. Updates the frame selector spinbox based on the number of PDB files found.

set_label_text_elided(file_path, label)

Module: `utils/directory.py`

Sets the text of a QLabel to an elided version of the file path if it's too long.

get_folding_score(mat, index, numbering)

Module: `utils/folding_score.py`

Calculate the folding score based on the given relations, using topology data.

The score is the sum of the mean per-residue participation in Parallel, Series and Cross relations.

get_vis_vals(self)

Module: `utils/get_values.py`

Retrieves visualization parameters from the GUI.

get_values(self)

Module: `utils/get_values.py`

Retrieves parameters for single-file analysis from the GUI.

get_local_values(self)

Module: `utils/get_values.py`

Retrieves parameters for local analysis from the GUI.

get_multiple_values(self)

Module: `utils/get_values.py`

Retrieves parameters for multi-file analysis from the GUI.

update_chain_combo_box(self)

Module: `utils/helpers.py`

Updates the chain combo box with the chains available in the currently selected object.

make_info_button(tooltip)

Module: `utils/helpers.py`

Creates a small info button with a tooltip.

temp_pdb_export(selection, state=None, label=None)

Module: `utils/helpers.py`

Save a PyMOL selection to a temporary PDB file, yield the path, then clean up.

notify(message)

Module: `utils/helpers.py`

Put a message on PyMOL's command line.

make_note_row(text, tooltip)

Module: `utils/helpers.py`

A quiet grey caption with its info button pinned to the right.

make_param_row(label_text, tooltip, spinbox)

Module: `utils/helpers.py`

Create a standard parameter row layout with label, info button, and spinbox.

show_folding_score_dialog(parent, chain, folding_score)

Module: `utils/helpers.py`

Show the CT folding score for a chain in a small, auto-sized pop-up dialog.

resolve_output_path(self, output_dir)

Module: `utils/helpers.py`

Validates and creates the output directory. Returns the Path on success, None on failure.

report_empty_local_result(idx, mat, residue_id, residue_number, contact)

Module: `utils/local_ct_report.py`

Print a notice when the plot will highlight nothing; return "" when it will.

`residue_id` is a POSITION into `numbering`; `residue_number` is what the user typed.

non_polymer_counts(obj_name)

Module: `utils/non_polymer.py`

Residue-name histogram of the non-polymer atoms in one object. Empty when there are none.

report_excluded_atoms(obj_name)

Module: `utils/non_polymer.py`

Log what analysis will ignore. Returns the message or empty string.

__init__(self, parent=None)

Module: `utils/pymol_objects.py`

Type: `PymolObjects` method

objects(self)

Module: `utils/pymol_objects.py`

Type: `PymolObjects` method

The object list as of the last poll.

refresh(self)

Module: `utils/pymol_objects.py`

Type: PymolObjects method

Re-read PyMOL's object list and emit `changed` if it moved.

stop(self)

Module: `utils/pymol_objects.py`

Type: PymolObjects method

Stop polling. Called from CTDIALOG.closeEvent so a hidden dialog leaves no live timer.

get_relation_type_vector(mat, index, relation_type, numbering)

Module: `utils/relations.py`

Per-residue participation in one class of contact-contact relation.

bucket_bounds(relation_vector, n_buckets=BUCKETS)

Module: `utils/relations.py`

Upper bounds of the colour buckets, taken from the quantiles of the non-zero values. Zero is excluded because it gets its own white level and never shares a bucket.

register_shades()

Module: `utils/relations.py`

Define every shade colour, blended from white towards each relation-type hue (once per session).

_shade_levels(n_bounds)

Module: `utils/relations.py`

Pick `n_bounds` shades spread across the registered range, so the top is always full.

_shade_fraction(level, of)

Module: `utils/relations.py`

How far towards the hue a given level sits. Level 0 is white; the rest start at MIN_SHADE.

color_by_relation(molecule_name, relation_vector, numbering, relation_type, bounds=None)

Module: `utils/relations.py`

Colour a PyMOL object by a relation vector, in discrete levels.

make_scale_bar(topo_obj, relation_type, bounds)

Module: `utils/relations.py`

Put a stepped, labelled colour bar in the viewer so the numbers behind the colours show.

Stepped because the colouring is, so what the legend shows is what the structure got.

get_residue_range(self, obj_name)

Module: `utils/residues.py`

Retrieves the residue range for each chain in the specified object. Updates the chain combo box and residue range spinbox.

update_residue_range(self)

Module: `utils/residues.py`

Updates the residue range spinbox based on the currently selected chain.

_refresh_objects(self)

Module: `utils/trajectory.py`

Ask the shared object model to re-poll. Fallback to `update_list()`.

select_mol_file(self)

Module: `utils/trajectory.py`

Opens a file dialog to select a structure file (PDB or CIF) for trajectory analysis. Loads the file into PyMOL.

select_xtc_file(self)

Module: `utils/trajectory.py`

Opens a file dialog to select a trajectory file (XTC). Loads the trajectory into PyMOL and reports the non-polymer atoms the analysis will ignore.

export_frames_from_traj(self)

Module: `utils/trajectory.py`

Exports each frame of the loaded trajectory as a separate PDB file. Prompts the user for confirmation and an output directory.

update_output_widgets_multi(self)

Module: `utils/updates.py`

Updates the visibility of output widgets in the multi-file analysis tab based on checkbox states.

update_output_widgets_local(self)

Module: `utils/updates.py`

Updates the visibility of output widgets in the local analysis tab based on checkbox states.

update_output_widgets(self)

Module: `utils/updates.py`

Update visibility of output widgets for single-file export options.

update_local_list(self, new_objects=None)

Module: `utils/updates.py`

Updates the list of available objects in the local analysis dropdown.

update_list(self, new_objects=None)

Module: `utils/updates.py`

Updates the list of available objects in the single-file analysis dropdown.

is_placeholder_object(obj_name)

Module: `utils/validation.py`

Return True when a combo-box value is not a real PyMOL object.

legalize_object_name(raw_name)

Module: `utils/validation.py`

Return a PyMOL-safe object name for explicit load operations.

object_exists(obj_name)

Module: `utils/validation.py`

Return True when the named object exists in the current PyMOL session.

object_selection(obj_name)

Module: `utils/validation.py`

Return an exact object selection for a PyMOL object name.

polymer_selection(obj_name)

Module: `utils/validation.py`

Return the analysable part of an object: its polymer atoms only (replaces the old 'remove non-polymer' step).

chain_selection(obj_name, chain_id)

Module: `utils/validation.py`

Return a PyMOL selection for one polymer chain of an object.

selection_has_atoms(selection)

Module: `utils/validation.py`

Return True when a PyMOL selection currently contains atoms.

get_object_chains(obj_name)

Module: `utils/validation.py`

Return the polymer chains of an existing object, or an empty list on failure.

count_object_states(obj_name)

Module: `utils/validation.py`

Return the number of coordinate states for an object (0 if it doesn't exist).

is_trajectory(obj_name)

Module: `utils/validation.py`

Return True when an object has more than one state (a trajectory or NMR ensemble).

validate_structure_file(path_like)

Module: `utils/validation.py`

Validate a PDB/CIF file path and return it as a Path.

validate_trajectory_file(path_like)

Module: `utils/validation.py`

Validate a supported trajectory file path and return it as a Path.

list_structure_files(directory)

Module: `utils/validation.py`

Return sorted PDB/CIF files from a directory.

set_frame_spinbox_bounds(spinbox, file_count)

Module: `utils/validation.py`

Set a 1-based frame spinbox range without creating invalid Qt ranges.

selected_frame_file(files, frame_index)

Module: `utils/validation.py`

Return the file for a 1-based frame index or raise a clear error.

GUI Functions

_show_admin_required_dialog()

Module: `__init__.py`

Show a Qt message box explaining that elevated privileges are required.

_show_restart_required_dialog()

Module: `__init__.py`

Tell the user dependencies were installed but PyMOL must be restarted.

_try_register()

Module: `__init__.py`

Attempt to register plugin functions and add the GUI menu item.

__init_plugin__(app=None)

Module: `__init__.py`

Initialize the plugin within PyMOL.

Invoked by PyMOL when the plugin is loaded. The flow is:

1. Register PyMOL commands if dependencies are already present.
2. Otherwise, if PyMOL is installed system-wide and this session lacks administrator/root privileges, show guidance and stop (a writable environment is required to install).
3. Install the missing dependencies into PyMOL's own conda environment.
4. Invalidate the import cache and re-register. If the freshly installed packages are not importable in this live session, ask the user to restart PyMOL.

run_plugin_gui()

Module: `__init__.py`

Create or raise the plugin GUI dialog.

This function is bound as the menu action entrypoint and returns the singleton dialog instance so callers (and tests) can interact with it.

`__init__(self, parent=None)`

Module: `gui_class.py`

Type: `CTDialog` method

Construct the dialog: window chrome, the three tabs, then the shared object model.

`_on_objects_changed(self, objects)`

Module: `gui_class.py`

Type: `CTDialog` method

Refresh both object dropdowns from one polled list.

`closeEvent(self, event)`

Module: `gui_class.py`

Type: `CTDialog` method

Stop polling when the dialog closes.

`init_ui(self)`

Module: `gui_class.py`

Type: `CTDialog` method

Create the top-level tab widget and initialize each feature tab.

`__init__(self, dialog, parent=None)`

Module: `tabs/local_tab.py`

Type: `LocalTab` method

`pymol_objects(self)`

Module: `tabs/local_tab.py`

Type: `LocalTab` method

`get_local_values(self)`

Module: `tabs/local_tab.py`

Type: `LocalTab` method

Every setting this tab exposes.

`clear_selected_local_file(self)`

Module: `tabs/local_tab.py`

Type: `LocalTab` method

`choose_local_file(self)`

Module: `tabs/local_tab.py`

Type: `LocalTab` method

`choose_local_output_dir(self)`

Module: `tabs/local_tab.py`

Type: LocalTab method

`handle_local_object_change(self, obj_name=None)`

Module: tabs/local_tab.py

Type: LocalTab method

Log what analysis will ignore, then refresh the chain/residue controls.

`get_residue_range(self, obj_name=None)`

Module: tabs/local_tab.py

Type: LocalTab method

`update_residue_range(self)`

Module: tabs/local_tab.py

Type: LocalTab method

`update_chain_combo_box(self)`

Module: tabs/local_tab.py

Type: LocalTab method

`update_output_widgets_local(self)`

Module: tabs/local_tab.py

Type: LocalTab method

`run_local_ct(self)`

Module: tabs/local_tab.py

Type: LocalTab method

`update_local_list(self)`

Module: tabs/local_tab.py

Type: LocalTab method

`_build_local_input_group(self)`

Module: tabs/local_tab.py

`_build_local_params_group(self)`

Module: tabs/local_tab.py

`_build_local_analysis_group(self)`

Module: tabs/local_tab.py

`_build_local_export_group(self)`

Module: tabs/local_tab.py

`init_local_tab(self)`

Module: tabs/local_tab.py

Initializes the 'Local Circuit Topology' tab in the GUI. Sets up widgets for file selection, parameter input, analysis options, and exporting.

`__init__(self, dialog, parent=None)`

Module: tabs/multiple_file_tab.py

Type: MultiFileTab method

`pymol_objects(self)`

Module: tabs/multiple_file_tab.py

Type: MultiFileTab method

The shared object model, so utils.trajectory can request a refresh.

`get_multiple_values(self)`

Module: tabs/multiple_file_tab.py

Type: MultiFileTab method

Every setting this tab exposes.

`choose_input_dir_multi(self)`

Module: tabs/multiple_file_tab.py

Type: MultiFileTab method

`choose_output_dir_multi(self)`

Module: tabs/multiple_file_tab.py

Type: MultiFileTab method

`select_mol_file(self)`

Module: tabs/multiple_file_tab.py

Type: MultiFileTab method

`select_xtc_file(self)`

Module: tabs/multiple_file_tab.py

Type: MultiFileTab method

`export_frames_from_traj(self)`

Module: tabs/multiple_file_tab.py

Type: MultiFileTab method

`update_output_widgets_multi(self)`

Module: tabs/multiple_file_tab.py

Type: MultiFileTab method

`run_multi_analysis(self)`

Module: tabs/multiple_file_tab.py

Type: MultiFileTab method

run_single_frame_analysis(self)

Module: tabs/multiple_file_tab.py

Type: MultiFileTab method

toggle_frame_controls(self, enabled)

Module: tabs/multiple_file_tab.py

Type: MultiFileTab method

update_list(self)

Module: tabs/multiple_file_tab.py

Type: MultiFileTab method

Legacy name still called by helper code; routes through the shared model.

_build_multi_dir_group(self)

Module: tabs/multiple_file_tab.py

_build_multi_traj_group(self)

Module: tabs/multiple_file_tab.py

_build_multi_params_group(self)

Module: tabs/multiple_file_tab.py

_build_multi_frame_widgets(self, layout)

Module: tabs/multiple_file_tab.py

_build_multi_filters_group(self)

Module: tabs/multiple_file_tab.py

_build_multi_plot_group(self)

Module: tabs/multiple_file_tab.py

_build_multi_export_group(self)

Module: tabs/multiple_file_tab.py

init_multi_file_tab(self)

Module: tabs/multiple_file_tab.py

Initializes the 'Multi-File Analysis' tab in the GUI. Sets up widgets for directory selection, trajectory handling, parameter input, analysis options, and exporting.

__init__(self, dialog, parent=None)

Module: tabs/single_file_tab.py

Type: SingleFileTab method

pymol_objects(self)

Module: tabs/single_file_tab.py

Type: SingleFileTab method

get_values(self)

Module: tabs/single_file_tab.py

Type: SingleFileTab method

Every setting this tab exposes.

get_vis_vals(self)

Module: tabs/single_file_tab.py

Type: SingleFileTab method

clear_selected_single_file(self)

Module: tabs/single_file_tab.py

Type: SingleFileTab method

choose_file(self)

Module: tabs/single_file_tab.py

Type: SingleFileTab method

choose_output_dir(self)

Module: tabs/single_file_tab.py

Type: SingleFileTab method

handle_standard_object_change(self, obj_name=None)

Module: tabs/single_file_tab.py

Type: SingleFileTab method

Log what analysis will ignore. Non-polymer atoms need no action from the user.

update_output_widgets(self)

Module: tabs/single_file_tab.py

Type: SingleFileTab method

visualize_molecule(self, contact_type)

Module: tabs/single_file_tab.py

Type: SingleFileTab method

run_standard_analysis(self)

Module: tabs/single_file_tab.py

Type: SingleFileTab method

update_list(self)

Module: tabs/single_file_tab.py

Type: SingleFileTab method

_build_input_group(self)

Module: tabs/single_file_tab.py

`_build_params_group(self)`

Module: tabs/single_file_tab.py

`_build_plot_group(self)`

Module: tabs/single_file_tab.py

`_build_vis_group(self)`

Module: tabs/single_file_tab.py

`_build_export_group(self)`

Module: tabs/single_file_tab.py

`_build_folding_group(self)`

Module: tabs/single_file_tab.py

`init_single_file_tab(self)`

Module: tabs/single_file_tab.py

Initializes the 'Single-File Analysis' tab in the GUI. Sets up widgets for file selection, parameter input, analysis options, visualization, and exporting.

Initialization Functions

`is_path_user(path)`

Module: initialization_checks.py

Checks if a given path is within the user's home directory.

`is_running_as_admin()`

Module: initialization_checks.py

Returns True if the current process has administrator / root privileges.

On Windows this calls `IsUserAnAdmin()`; on POSIX it checks `effective uid == 0`. Returns False on any error so callers can treat the result conservatively.

`install_failed(reqs=REQUIREMENTS_FILE)`

Module: initialization_checks.py

Prints instructions for manual installation of dependencies if automated installation fails.

`_normalize_requirement_name(requirement)`

Module: initialization_checks.py

Convert a conda-style dependency entry into its package name.

`requirement_specs(req_path)`

Module: initialization_checks.py

Parse requirements.yml into package name -> the exact spec the file declares.

check_installed_packages(requirements_list)

Module: initialization_checks.py

Checks if the required packages are installed in the current environment.

_is_package_available(pack)

Module: initialization_checks.py

Check whether a conda-named package is importable in this interpreter.

is_conda_installed()

Module: initialization_checks.py

Checks if conda is discoverable on the system PATH.

_find_conda_executable()

Module: initialization_checks.py

Locate the conda executable that owns the running PyMOL environment.

_installed_spec(package)

Module: initialization_checks.py

Pin `package` to the version already installed in this prefix, read from conda-meta.

_run_conda(command)

Module: initialization_checks.py

Run a conda command, returning None if it could not be launched at all.

_retry_without_broken_pins(command)

Module: initialization_checks.py

Retry a conda command with a malformed `conda-meta/pinned` moved out of the way.

install_dependencies(reqs=REQUIREMENTS_FILE, missing=None)

Module: initialization_checks.py

Install plugin dependencies into PyMOL's own conda environment.

register_pymol_functions()

Module: initialization_checks.py

Register the plugin's core functions as PyMOL commands.

This function imports the plugin's modular command wrappers and extends the PyMOL `cmd` object so that the commands become available to users as top-level PyMOL commands.

Last Updated: September 14, 2026 (plugin v0.0.3)