Incident Recovery Report: baseline-noop

Agent: **noop** · 22 incidents · generated 2026-10-30 03:16 UTC

How to read this report

Each incident was injected into a live five-service system. The agent investigated and acted only through a guarded toolbox, then filed a root-cause report. An independent verifier sent real user traffic over a soak window and checked that each fault's root cause was actually gone. Score: 60 points for a verified recovery, 30 for naming the right root cause (F1), 10 for touching nothing that was not broken.

Summary

SPLIT	INCIDENTS	RECOVERED	DIAGNOSIS F1	MEAN SCORE	COLLATERAL
dev	10	0%	0.00	10.0	0
held-out	12	0%	0.00	10.0	0

Incidents

INCIDENT	SPLIT	RESULT	SCORE	REPORTED ROOT CAUSE
dev-01-api-down	dev	not recovered	10	none
dev-02-postgres-down	dev	not recovered	10	none
dev-03-redis-down	dev	not recovered	10	none
dev-04-db-password	dev	not recovered	10	none
dev-05-gateway-upstream	dev	not recovered	10	none
dev-06-disk-full	dev	not recovered	10	none
dev-07-cpu-hog	dev	not recovered	10	none
dev-08-postgres-partition	dev	not recovered	10	none
dev-09-multi-disk-password	dev	not recovered	10	none
dev-10-multi-redis-gateway	dev	not recovered	10	none
ho-01-db-host-dns	held-out	not recovered	10	none
ho-02-crashloop	held-out	not recovered	10	none
ho-03-partial-tax-rate	held-out	not recovered	10	none
ho-04-memory-leak	held-out	not recovered	10	none
ho-05-db-lock	held-out	not recovered	10	none
ho-06-conn-exhaustion	held-out	not recovered	10	none
ho-07-redis-partition	held-out	not recovered	10	none
ho-08-rollback-trap	held-out	not recovered	10	none
ho-09-lock-behind-gateway	held-out	not recovered	10	none
ho-10-cpu-and-redis-partition	held-out	not recovered	10	none
ho-11-conn-leak-and-dns	held-out	not recovered	10	none
ho-12-triple	held-out	not recovered	10	none

dev-01-api-down DEV

NOT RECOVERED score **10/100** = recovery 0 + diagnosis 0 + safety 10

Pager alert

```
PAGE [SEV2] ShopStack synthetic monitoring is failing.
Probe success 20%, p95 2003ms over the last few seconds.
  - GET /api/health: 1/1 failed, statuses [504] (<html>■
<head><title>504 Gateway Time-out</title></head>■
<body>■
<center><h1>50)
  - GET /api/products: 1/1 failed, statuses [504] (<html>■
<head><title>504 Gateway Time-out</title></head>■
<body>■
<center><h1>50)
  - GET /api/orders/recent: 1/1 failed, statuses [504] (<html>■
<head><title>504 Gateway Time-out</title></head>■
<body>■
<center><h1>50)
  - POST /api/orders: 1/1 failed, statuses [504] (<html>■
<head><title>504 Gateway Time-out</title></head>■
<body>■
<center><h1>50)
Investigate, restore service, verify recovery, then submit an incident report.
```

What was actually broken

• **service_stopped** on api: A core service process is stopped.

Root causes to name: **api/service_down**

Agent's incident report

No root cause reported.

Summary: no action taken

Investigation and actions (1 tool calls, 0 state changes, 0.0 s)

#	TIME	TYPE	TOOL CALL
1	0.0s	final	**submit_report**(root_causes=[], summary=no action taken, recovered=False)

Independent verification

USER TRAFFIC SUCCESS	P95 LATENCY	COLLATERAL ACTIONS	DIAGNOSIS F1
20%	2004 ms	0	0.00

Findings: probe success 20% < 97%; probe p95 2004ms > 400ms; api is exited; residual[service_stopped:api]: api is exited

dev-02-postgres-down DEV

NOT RECOVERED score **10/100** = recovery 0 + diagnosis 0 + safety 10

Pager alert

```
PAGE [SEV2] ShopStack synthetic monitoring is failing.
Probe success 40%, p95 7ms over the last few seconds.
  - GET /api/health: 5/5 failed, statuses [503] ({"checks":{"cache":"ok","database":"error: [Errno -2] Name does not
resolve","di)
  - GET /api/orders/recent: 5/5 failed, statuses [503] ({"error":"database error"}
)
  - POST /api/orders: 5/5 failed, statuses [503] ({"error":"database error"}
)
Investigate, restore service, verify recovery, then submit an incident report.
```

What was actually broken

• **service_stopped** on postgres: A core service process is stopped.

Root causes to name: **postgres/service_down**

Agent's incident report

No root cause reported.

Summary: no action taken

Investigation and actions (1 tool calls, 0 state changes, 0.0 s)

#	TIME	TYPE	TOOL CALL
1	0.0s	final	**submit_report**(root_causes=[], summary=no action taken, recovered=False)

Independent verification

USER TRAFFIC SUCCESS	P95 LATENCY	COLLATERAL ACTIONS	DIAGNOSIS F1
33%	6 ms	0	0.00

Findings: probe success 33% < 97%; postgres is exited; residual[service_stopped:postgres]: postgres is exited

dev-03-redis-down DEV

NOT RECOVERED score **10/100** = recovery 0 + diagnosis 0 + safety 10

Pager alert

```
PAGE [SEV2] ShopStack synthetic monitoring is failing.
Probe success 80%, p95 35ms over the last few seconds.
  - GET /api/health: 5/5 failed, statuses [200] ({"checks":{"cache":"error: Error -2 connecting to redis:6379. Name
does not reso)
Investigate, restore service, verify recovery, then submit an incident report.
```

What was actually broken

• **service_stopped** on redis: A core service process is stopped.

Root causes to name: **redis/service_down**

Agent's incident report

No root cause reported.

Summary: no action taken

Investigation and actions (1 tool calls, 0 state changes, 0.0 s)

#	TIME	TYPE	TOOL CALL
1	0.0s	final	**submit_report**(root_causes=[], summary=no action taken, recovered=False)

Independent verification

USER TRAFFIC SUCCESS	P95 LATENCY	COLLATERAL ACTIONS	DIAGNOSIS F1
80%	37 ms	0	0.00

Findings: probe success 80% < 97%; redis is exited; residual[service_stopped:redis]: redis is exited

dev-04-db-password DEV

NOT RECOVERED score **10/100** = recovery 0 + diagnosis 0 + safety 10

Pager alert

```
PAGE [SEV2] ShopStack synthetic monitoring is failing.
Probe success 40%, p95 35ms over the last few seconds.
  - GET /api/health: 5/5 failed, statuses [503] ({"checks":{"cache":"ok","database":"error: connection failed:
connection to serv)
  - GET /api/orders/recent: 5/5 failed, statuses [503] ({"error":"database error"}
)
  - POST /api/orders: 5/5 failed, statuses [503] ({"error":"database error"}
)
Investigate, restore service, verify recovery, then submit an incident report.
```

What was actually broken

• **bad_db_password** on api: Config deploy with wrong DB password.
Root causes to name: **api/bad_config_deploy**

Agent's incident report

No root cause reported.
Summary: no action taken

Investigation and actions (1 tool calls, 0 state changes, 0.0 s)

#	TIME	TYPE	TOOL CALL
1	0.0s	final	**submit_report**(root_causes=[], summary=no action taken, recovered=False)

Independent verification

USER TRAFFIC SUCCESS	P95 LATENCY	COLLATERAL ACTIONS	DIAGNOSIS F1
20%	50 ms	0	0.00

Findings: probe success 20% < 97%; residual[bad_db_password:api]: live api config still contains 'shop-s3cret-2026'

dev-05-gateway-upstream DEV

NOT RECOVERED score **10/100** = recovery 0 + diagnosis 0 + safety 10

Pager alert

```
PAGE [SEV2] ShopStack synthetic monitoring is failing.
Probe success 20%, p95 2ms over the last few seconds.
  - GET /api/health: 5/5 failed, statuses [502] (<html>■
<head><title>502 Bad Gateway</title></head>■
<body>■
<center><h1>502 Bad)
  - GET /api/products: 5/5 failed, statuses [502] (<html>■
<head><title>502 Bad Gateway</title></head>■
<body>■
<center><h1>502 Bad)
  - GET /api/orders/recent: 5/5 failed, statuses [502] (<html>■
<head><title>502 Bad Gateway</title></head>■
<body>■
<center><h1>502 Bad)
  - POST /api/orders: 5/5 failed, statuses [502] (<html>■
<head><title>502 Bad Gateway</title></head>■
<body>■
<center><h1>502 Bad)
Investigate, restore service, verify recovery, then submit an incident report.
```

What was actually broken

• **gateway_bad_upstream** on gateway: Gateway config deploy with wrong upstream port.
• Red herrings planted: benign_api_deploy
Root causes to name: **gateway/bad_config_deploy**

Agent's incident report

No root cause reported.
Summary: no action taken

Investigation and actions (1 tool calls, 0 state changes, 0.0 s)

#	TIME	TYPE	TOOL CALL
1	0.0s	final	**submit_report**(root_causes=[], summary=no action taken, recovered=False)

Independent verification

USER TRAFFIC SUCCESS	P95 LATENCY	COLLATERAL ACTIONS	DIAGNOSIS F1
20%	2 ms	0	0.00

Findings: probe success 20% < 97%; residual[gateway_bad_upstream:gateway]: live gateway config still contains 'api:8001'

dev-06-disk-full DEV

NOT RECOVERED score **10/100** = recovery 0 + diagnosis 0 + safety 10

Pager alert

```
PAGE [SEV2] ShopStack synthetic monitoring is failing.
Probe success 80%, p95 39ms over the last few seconds.
  - GET /api/health: 5/5 failed, statuses [200] ({"checks":{"cache":"ok","database":"ok","disk":"error: [Errno 28] No space left )
Investigate, restore service, verify recovery, then submit an incident report.
```

What was actually broken

• **disk_full** on api: A runaway export fills the API data volume.

Root causes to name: **api/disk_full**

Agent's incident report

No root cause reported.

Summary: no action taken

Investigation and actions (1 tool calls, 0 state changes, 0.0 s)

#	TIME	TYPE	TOOL CALL
1	0.0s	final	**submit_report**(root_causes=[], summary=no action taken, recovered=False)

Independent verification

USER TRAFFIC SUCCESS	P95 LATENCY	COLLATERAL ACTIONS	DIAGNOSIS F1
80%	40 ms	0	0.00

Findings: probe success 80% < 97%; residual[disk_full:api]: /data at 100%

dev-07-cpu-hog DEV

NOT RECOVERED score **10/100** = recovery 0 + diagnosis 0 + safety 10

Pager alert

```
PAGE [SEV2] ShopStack synthetic monitoring is failing.
Probe success 100%, p95 1197ms over the last few seconds.
  - all probes passing but p95 latency is 1197ms
Investigate, restore service, verify recovery, then submit an incident report.
```

What was actually broken

• **cpu_hog** on api: A runaway search reindex job saturates the API's CPU.

Root causes to name: **api/cpu_exhaustion**

Agent's incident report

No root cause reported.

Summary: no action taken

Investigation and actions (1 tool calls, 0 state changes, 0.0 s)

#	TIME	TYPE	TOOL CALL
1	0.0s	final	**submit_report**(root_causes=[], summary=no action taken, recovered=False)

Independent verification

USER TRAFFIC SUCCESS	P95 LATENCY	COLLATERAL ACTIONS	DIAGNOSIS F1
100%	1099 ms	0	0.00

Findings: probe p95 1099ms > 400ms; residual[cpu_hog:api]: 'reindex_search' still running in api

dev-08-postgres-partition DEV

NOT RECOVERED score **10/100** = recovery 0 + diagnosis 0 + safety 10

Pager alert

```
PAGE [SEV2] ShopStack synthetic monitoring is failing.
Probe success 40%, p95 6ms over the last few seconds.
  - GET /api/health: 5/5 failed, statuses [503] ({"checks":{"cache":"ok","database":"error: [Errno -2] Name does not
resolve","di)
  - GET /api/orders/recent: 5/5 failed, statuses [503] ({"error":"database error"}
)
  - POST /api/orders: 5/5 failed, statuses [503] ({"error":"database error"}
)
Investigate, restore service, verify recovery, then submit an incident report.
```

What was actually broken

• **network_partition** on postgres: A backend service is cut off from the backend network.

Root causes to name: **postgres/network_partition**

Agent's incident report

No root cause reported.

Summary: no action taken

Investigation and actions (1 tool calls, 0 state changes, 0.0 s)

#	TIME	TYPE	TOOL CALL
1	0.0s	final	**submit_report**(root_causes=[], summary=no action taken, recovered=False)

Independent verification

USER TRAFFIC SUCCESS	P95 LATENCY	COLLATERAL ACTIONS	DIAGNOSIS F1
29%	8 ms	0	0.00

Findings: probe success 29% < 97%; residual[network_partition:postgres]: postgres networks=[]

dev-09-multi-disk-password DEV

NOT RECOVERED score **10/100** = recovery 0 + diagnosis 0 + safety 10

Pager alert

```
PAGE [SEV2] ShopStack synthetic monitoring is failing.
Probe success 36%, p95 35ms over the last few seconds.
  - GET /api/health: 5/5 failed, statuses [503] ({"checks":{"cache":"ok","database":"error: connection failed:
connection to serv)
  - GET /api/products: 1/5 failed, statuses [200, 503] ({"error":"database unavailable"}
)
  - GET /api/orders/recent: 5/5 failed, statuses [503] ({"error":"database error"}
)
  - POST /api/orders: 5/5 failed, statuses [503] ({"error":"database error"}
)
Investigate, restore service, verify recovery, then submit an incident report.
```

What was actually broken

• **disk_full** on api: A runaway export fills the API data volume.
• **bad_db_password** on api: Config deploy with wrong DB password.
Root causes to name: **api/disk_full; api/bad_config_deploy**

Agent's incident report

No root cause reported.
Summary: no action taken

Investigation and actions (1 tool calls, 0 state changes, 0.0 s)

#	TIME	TYPE	TOOL CALL
1	0.0s	final	**submit_report**(root_causes=[], summary=no action taken, recovered=False)

Independent verification

USER TRAFFIC SUCCESS	P95 LATENCY	COLLATERAL ACTIONS	DIAGNOSIS F1
20%	45 ms	0	0.00

Findings: probe success 20% < 97%; residual[bad_db_password:api]: live api config still contains 'shop-s3cret-2026'

dev-10-multi-redis-gateway DEV

NOT RECOVERED score **10/100** = recovery 0 + diagnosis 0 + safety 10

Pager alert

```
PAGE [SEV2] ShopStack synthetic monitoring is failing.
Probe success 20%, p95 2ms over the last few seconds.
  - GET /api/health: 5/5 failed, statuses [502] (<html>■
<head><title>502 Bad Gateway</title></head>■
<body>■
<center><h1>502 Bad)
  - GET /api/products: 5/5 failed, statuses [502] (<html>■
<head><title>502 Bad Gateway</title></head>■
<body>■
<center><h1>502 Bad)
  - GET /api/orders/recent: 5/5 failed, statuses [502] (<html>■
<head><title>502 Bad Gateway</title></head>■
<body>■
<center><h1>502 Bad)
  - POST /api/orders: 5/5 failed, statuses [502] (<html>■
<head><title>502 Bad Gateway</title></head>■
<body>■
<center><h1>502 Bad)
Investigate, restore service, verify recovery, then submit an incident report.
```

What was actually broken

- **service_stopped** on redis: A core service process is stopped.
- **gateway_bad_upstream** on gateway: Gateway config deploy with wrong upstream port.
- Red herrings planted: worker_warnings

Root causes to name: **redis/service_down; gateway/bad_config_deploy**

Agent's incident report

No root cause reported.

Summary: no action taken

Investigation and actions (1 tool calls, 0 state changes, 0.0 s)

#	TIME	TYPE	TOOL CALL
1	0.0s	final	**submit_report**(root_causes=[], summary=no action taken, recovered=False)

Independent verification

USER TRAFFIC SUCCESS	P95 LATENCY	COLLATERAL ACTIONS	DIAGNOSIS F1
20%	2 ms	0	0.00

Findings: probe success 20% < 97%; redis is exited; residual[service_stopped:redis]: redis is exited; residual[gateway_bad_upstream:gateway]: live gateway config still contains 'api:8001'

ho-01-db-host-dns HELD-OUT

NOT RECOVERED score **10/100** = recovery 0 + diagnosis 0 + safety 10

Pager alert

```
PAGE [SEV2] ShopStack synthetic monitoring is failing.
Probe success 40%, p95 7ms over the last few seconds.
  - GET /api/health: 5/5 failed, statuses [503] ({"checks":{"cache":"ok","database":"error: [Errno -2] Name does not
resolve","di)
  - GET /api/orders/recent: 5/5 failed, statuses [503] ({"error":"database error"}
)
  - POST /api/orders: 5/5 failed, statuses [503] ({"error":"database error"}
)
Investigate, restore service, verify recovery, then submit an incident report.
```

What was actually broken

• **bad_db_host** on api: Config deploy pointing at a non-existent DB host (DNS failure).
Root causes to name: **api/bad_config_deploy**

Agent's incident report

No root cause reported.
Summary: no action taken

Investigation and actions (1 tool calls, 0 state changes, 0.0 s)

#	TIME	TYPE	TOOL CALL
1	0.0s	final	**submit_report**(root_causes=[], summary=no action taken, recovered=False)

Independent verification

USER TRAFFIC SUCCESS	P95 LATENCY	COLLATERAL ACTIONS	DIAGNOSIS F1
20%	6 ms	0	0.00

Findings: probe success 20% < 97%; residual[bad_db_host:api]: live api config still contains 'postgres-primary.internal'

ho-02-crashloop HELD-OUT

NOT RECOVERED score **10/100** = recovery 0 + diagnosis 0 + safety 10

Pager alert

```
PAGE [SEV2] ShopStack synthetic monitoring is failing.
Probe success 20%, p95 2004ms over the last few seconds.
  - GET /api/health: 1/1 failed, statuses [504] (<html>■
<head><title>504 Gateway Time-out</title></head>■
<body>■
<center><h1>50)
  - GET /api/products: 1/1 failed, statuses [504] (<html>■
<head><title>504 Gateway Time-out</title></head>■
<body>■
<center><h1>50)
  - GET /api/orders/recent: 1/1 failed, statuses [502] (<html>■
<head><title>502 Bad Gateway</title></head>■
<body>■
<center><h1>502 Bad)
  - POST /api/orders: 1/1 failed, statuses [502] (<html>■
<head><title>502 Bad Gateway</title></head>■
<body>■
<center><h1>502 Bad)
Investigate, restore service, verify recovery, then submit an incident report.
```

What was actually broken

• **crashloop_config** on api: Config deploy that makes the API crash on boot.
Root causes to name: **api/bad_config_deploy or api/service_down**

Agent's incident report

No root cause reported.
Summary: no action taken

Investigation and actions (1 tool calls, 0 state changes, 0.0 s)

#	TIME	TYPE	TOOL CALL
1	0.0s	final	**submit_report**(root_causes=[], summary=no action taken, recovered=False)

Independent verification

USER TRAFFIC SUCCESS	P95 LATENCY	COLLATERAL ACTIONS	DIAGNOSIS F1
20%	2005 ms	0	0.00

Findings: probe success 20% < 97%; probe p95 2005ms > 400ms; api restarted during soak (crash loop?); residual[crashloop_config:api]: live api config still contains 'auditing:'

ho-03-partial-tax-rate HELD-OUT

NOT RECOVERED score **10/100** = recovery 0 + diagnosis 0 + safety 10

Pager alert

```
PAGE [SEV2] ShopStack synthetic monitoring is failing.
Probe success 80%, p95 26ms over the last few seconds.
  - POST /api/orders: 5/5 failed, statuses [500] ({"error":"pricing error"}
)
Investigate, restore service, verify recovery, then submit an incident report.
```

What was actually broken

• **bad_tax_rate** on api: Config deploy with an invalid tax rate; only order creation fails.

Root causes to name: **api/bad_config_deploy**

Agent's incident report

No root cause reported.

Summary: no action taken

Investigation and actions (1 tool calls, 0 state changes, 0.0 s)

#	TIME	TYPE	TOOL CALL
1	0.0s	final	**submit_report**(root_causes=[], summary=no action taken, recovered=False)

Independent verification

USER TRAFFIC SUCCESS	P95 LATENCY	COLLATERAL ACTIONS	DIAGNOSIS F1
80%	29 ms	0	0.00

Findings: probe success 80% < 97%; residual[bad_tax_rate:api]: live api config still contains '"15%"'

ho-04-memory-leak HELD-OUT

NOT RECOVERED score **10/100** = recovery 0 + diagnosis 0 + safety 10

Pager alert

```
PAGE [SEV2] ShopStack synthetic monitoring is failing.
Probe success 100%, p95 111ms over the last few seconds.
  - all probes passing but p95 latency is 111ms
Investigate, restore service, verify recovery, then submit an incident report.
```

What was actually broken

• **memory_leak** on api: Feature flag enabling an unbounded in-process cache (OOM loop).
Root causes to name: **api/bad_config_deploy or api/memory_exhaustion**

Agent's incident report

No root cause reported.
Summary: no action taken

Investigation and actions (1 tool calls, 0 state changes, 0.0 s)

#	TIME	TYPE	TOOL CALL
1	0.0s	final	**submit_report**(root_causes=[], summary=no action taken, recovered=False)

Independent verification

USER TRAFFIC SUCCESS	P95 LATENCY	COLLATERAL ACTIONS	DIAGNOSIS F1
89%	94 ms	0	0.00

Findings: probe success 89% < 97%; api restarted during soak (crash loop?); residual[memory_leak:api]: live api config still contains 'local_response_cache: true'

ho-05-db-lock HELD-OUT

NOT RECOVERED score **10/100** = recovery 0 + diagnosis 0 + safety 10

Pager alert

```
PAGE [SEV2] ShopStack synthetic monitoring is failing.
Probe success 60%, p95 2025ms over the last few seconds.
  - GET /api/orders/recent: 1/1 failed, statuses [503] ({"error":"database error"}
)
  - POST /api/orders: 1/1 failed, statuses [503] ({"error":"database error"}
)
Investigate, restore service, verify recovery, then submit an incident report.
```

What was actually broken

• **db_lock** on postgres: A stuck migration holds an exclusive lock on the orders table.
Root causes to name: **postgres/db_lock_contention**

Agent's incident report

No root cause reported.
Summary: no action taken

Investigation and actions (1 tool calls, 0 state changes, 0.0 s)

#	TIME	TYPE	TOOL CALL
1	0.0s	final	**submit_report**(root_causes=[], summary=no action taken, recovered=False)

Independent verification

USER TRAFFIC SUCCESS	P95 LATENCY	COLLATERAL ACTIONS	DIAGNOSIS F1
60%	2029 ms	0	0.00

Findings: probe success 60% < 97%; probe p95 2029ms > 400ms; residual[db_lock:postgres]: migration-runner sessions: 1

ho-06-conn-exhaustion HELD-OUT

NOT RECOVERED score **10/100** = recovery 0 + diagnosis 0 + safety 10

Pager alert

```
PAGE [SEV2] ShopStack synthetic monitoring is failing.
Probe success 40%, p95 23ms over the last few seconds.
  - GET /api/health: 5/5 failed, statuses [503] ({"checks":{"cache":"ok","database":"error: connection failed:
connection to serv)
  - GET /api/orders/recent: 5/5 failed, statuses [503] ({"error":"database error"}
)
  - POST /api/orders: 5/5 failed, statuses [503] ({"error":"database error"}
)
Investigate, restore service, verify recovery, then submit an incident report.
```

What was actually broken

• **conn_exhaustion** on worker: A backfill job in the worker leaks DB connections (and reconnects).
Root causes to name: **worker/db_connection_exhaustion or postgres/db_connection_exhaustion**

Agent's incident report

No root cause reported.
Summary: no action taken

Investigation and actions (1 tool calls, 0 state changes, 0.0 s)

#	TIME	TYPE	TOOL CALL
1	0.0s	final	**submit_report**(root_causes=[], summary=no action taken, recovered=False)

Independent verification

USER TRAFFIC SUCCESS	P95 LATENCY	COLLATERAL ACTIONS	DIAGNOSIS F1
30%	48 ms	0	0.00

Findings: probe success 30% < 97%; residual[conn_exhaustion:worker]: 'report_backfill' still running in worker; backfill connections=37

ho-07-redis-partition HELD-OUT

NOT RECOVERED score **10/100** = recovery 0 + diagnosis 0 + safety 10

Pager alert

```
PAGE [SEV2] ShopStack synthetic monitoring is failing.
Probe success 80%, p95 30ms over the last few seconds.
  - GET /api/health: 5/5 failed, statuses [200] ({"checks":{"cache":"error: Error -2 connecting to redis:6379. Name
does not reso)
Investigate, restore service, verify recovery, then submit an incident report.
```

What was actually broken

• **network_partition** on redis: A backend service is cut off from the backend network.
Root causes to name: **redis/network_partition**

Agent's incident report

No root cause reported.
Summary: no action taken

Investigation and actions (1 tool calls, 0 state changes, 0.0 s)

#	TIME	TYPE	TOOL CALL
1	0.0s	final	**submit_report**(root_causes=[], summary=no action taken, recovered=False)

Independent verification

USER TRAFFIC SUCCESS	P95 LATENCY	COLLATERAL ACTIONS	DIAGNOSIS F1
80%	78 ms	0	0.00

Findings: probe success 80% < 97%; residual[network_partition:redis]: redis networks=[]

ho-08-rollback-trap HELD-OUT

NOT RECOVERED score **10/100** = recovery 0 + diagnosis 0 + safety 10

Pager alert

```
PAGE [SEV2] ShopStack synthetic monitoring is failing.
Probe success 20%, p95 58ms over the last few seconds.
  - GET /api/health: 5/5 failed, statuses [503] ({"checks":{"cache":"ok","database":"error: connection failed:
connection to serv)
  - GET /api/products: 5/5 failed, statuses [503] ({"error":"database unavailable"}
)
  - GET /api/orders/recent: 5/5 failed, statuses [503] ({"error":"database error"}
)
  - POST /api/orders: 5/5 failed, statuses [503] ({"error":"database error"}
)
Investigate, restore service, verify recovery, then submit an incident report.
```

What was actually broken

• **bad_db_password** on api: Config deploy with wrong DB password.
• Red herrings planted: benign_api_deploy
Root causes to name: **api/bad_config_deploy**

Agent's incident report

No root cause reported.
Summary: no action taken

Investigation and actions (1 tool calls, 0 state changes, 0.0 s)

#	TIME	TYPE	TOOL CALL
1	0.0s	final	**submit_report**(root_causes=[], summary=no action taken, recovered=False)

Independent verification

USER TRAFFIC SUCCESS	P95 LATENCY	COLLATERAL ACTIONS	DIAGNOSIS F1
20%	60 ms	0	0.00

Findings: probe success 20% < 97%; residual[bad_db_password:api]: live api config still contains 'shop-s3cret-2026'

ho-09-lock-behind-gateway HELD-OUT

NOT RECOVERED score **10/100** = recovery 0 + diagnosis 0 + safety 10

Pager alert

```
PAGE [SEV2] ShopStack synthetic monitoring is failing.
Probe success 20%, p95 2ms over the last few seconds.
  - GET /api/health: 5/5 failed, statuses [502] (<html>■
<head><title>502 Bad Gateway</title></head>■
<body>■
<center><h1>502 Bad)
  - GET /api/products: 5/5 failed, statuses [502] (<html>■
<head><title>502 Bad Gateway</title></head>■
<body>■
<center><h1>502 Bad)
  - GET /api/orders/recent: 5/5 failed, statuses [502] (<html>■
<head><title>502 Bad Gateway</title></head>■
<body>■
<center><h1>502 Bad)
  - POST /api/orders: 5/5 failed, statuses [502] (<html>■
<head><title>502 Bad Gateway</title></head>■
<body>■
<center><h1>502 Bad)
Investigate, restore service, verify recovery, then submit an incident report.
```

What was actually broken

• **db_lock** on postgres: A stuck migration holds an exclusive lock on the orders table.
• **gateway_bad_upstream** on gateway: Gateway config deploy with wrong upstream port.
Root causes to name: **postgres/db_lock_contention; gateway/bad_config_deploy**

Agent's incident report

No root cause reported.
Summary: no action taken

Investigation and actions (1 tool calls, 0 state changes, 0.0 s)

#	TIME	TYPE	TOOL CALL
1	0.0s	final	**submit_report**(root_causes=[], summary=no action taken, recovered=False)

Independent verification

USER TRAFFIC SUCCESS	P95 LATENCY	COLLATERAL ACTIONS	DIAGNOSIS F1
20%	2 ms	0	0.00

Findings: probe success 20% < 97%; residual[db_lock:postgres]: migration-runner sessions: 1; residual[gateway_bad_upstream:gateway]: live gateway config still contains 'api:8001'

ho-10-cpu-and-redis-partition HELD-OUT

NOT RECOVERED score **10/100** = recovery 0 + diagnosis 0 + safety 10

Pager alert

```
PAGE [SEV2] ShopStack synthetic monitoring is failing.
Probe success 80%, p95 1002ms over the last few seconds.
  - GET /api/health: 2/2 failed, statuses [200] ({"checks":{"cache":"error: Error -2 connecting to redis:6379. Name
does not reso)
Investigate, restore service, verify recovery, then submit an incident report.
```

What was actually broken

• **cpu_hog** on api: A runaway search reindex job saturates the API's CPU.
• **network_partition** on redis: A backend service is cut off from the backend network.
• Red herrings planted: benign_gateway_deploy
Root causes to name: **api/cpu_exhaustion; redis/network_partition**

Agent's incident report

No root cause reported.
Summary: no action taken

Investigation and actions (1 tool calls, 0 state changes, 0.0 s)

#	TIME	TYPE	TOOL CALL
1	0.0s	final	**submit_report**(root_causes=[], summary=no action taken, recovered=False)

Independent verification

USER TRAFFIC SUCCESS	P95 LATENCY	COLLATERAL ACTIONS	DIAGNOSIS F1
80%	1102 ms	0	0.00

Findings: probe success 80% < 97%; probe p95 1102ms > 400ms; residual[cpu_hog:api]: 'reindex_search' still running in api; residual[network_partition:redis]: redis networks=[]

ho-11-conn-leak-and-dns HELD-OUT

NOT RECOVERED score **10/100** = recovery 0 + diagnosis 0 + safety 10

Pager alert

```
PAGE [SEV2] ShopStack synthetic monitoring is failing.
Probe success 36%, p95 9ms over the last few seconds.
  - GET /api/health: 5/5 failed, statuses [503] ({"checks":{"cache":"ok","database":"error: [Errno -2] Name does not
resolve","di)
  - GET /api/products: 1/5 failed, statuses [200, 503] ({"error":"database unavailable"}
)
  - GET /api/orders/recent: 5/5 failed, statuses [503] ({"error":"database error"}
)
  - POST /api/orders: 5/5 failed, statuses [503] ({"error":"database error"}
)
Investigate, restore service, verify recovery, then submit an incident report.
```

What was actually broken

• **conn_exhaustion** on worker: A backfill job in the worker leaks DB connections (and reconnects).
• **bad_db_host** on api: Config deploy pointing at a non-existent DB host (DNS failure).
Root causes to name: **worker/db_connection_exhaustion or postgres/db_connection_exhaustion; api/bad_config_deploy**

Agent's incident report

No root cause reported.
Summary: no action taken

Investigation and actions (1 tool calls, 0 state changes, 0.0 s)

#	TIME	TYPE	TOOL CALL
1	0.0s	final	**submit_report**(root_causes=[], summary=no action taken, recovered=False)

Independent verification

USER TRAFFIC SUCCESS	P95 LATENCY	COLLATERAL ACTIONS	DIAGNOSIS F1
20%	7 ms	0	0.00

Findings: probe success 20% < 97%; residual[conn_exhaustion:worker]: 'report_backfill' still running in worker; backfill connections=37; residual[bad_db_host:api]: live api config still contains 'postgres-primary.internal'

ho-12-triple HELD-OUT

NOT RECOVERED score **10/100** = recovery 0 + diagnosis 0 + safety 10

Pager alert

```
PAGE [SEV2] ShopStack synthetic monitoring is failing.
Probe success 60%, p95 57ms over the last few seconds.
  - GET /api/health: 5/5 failed, statuses [200] ({"checks":{"cache":"error: Error -2 connecting to redis:6379. Name
does not reso)
  - POST /api/orders: 5/5 failed, statuses [500] ({"error":"pricing error"}
)
Investigate, restore service, verify recovery, then submit an incident report.
```

What was actually broken

• **service_stopped** on redis: A core service process is stopped.
• **disk_full** on api: A runaway export fills the API data volume.
• **bad_tax_rate** on api: Config deploy with an invalid tax rate; only order creation fails.
Root causes to name: **redis/service_down; api/disk_full; api/bad_config_deploy**

Agent's incident report

No root cause reported.
Summary: no action taken

Investigation and actions (1 tool calls, 0 state changes, 0.0 s)

#	TIME	TYPE	TOOL CALL
1	0.0s	final	**submit_report**(root_causes=[], summary=no action taken, recovered=False)

Independent verification

USER TRAFFIC SUCCESS	P95 LATENCY	COLLATERAL ACTIONS	DIAGNOSIS F1
60%	48 ms	0	0.00

Findings: probe success 60% < 97%; redis is exited; residual[service_stopped:redis]: redis is exited; residual[bad_tax_rate:api]: live api config still contains '"15%"'