


# One-Time Passwords

Gianluca Dini  
Dept. of Ingegneria dell'Informazione  
University of Pisa  
Email: [gianluca.dini@unipi.it](mailto:gianluca.dini@unipi.it)  
Version: 2024-04-08

1

## One-Time Password



UNIVERSITÀ DI PISA

- One-Time Password (OTP)
  - A password that is valid for only one login session or transaction
  - A.k.a. dynamic password, dynamic pin
- Pros
  - Not vulnerable to replay attack
  - Not vulnerable to password-reuse attack
- Cons
  - Hard to remember, so you need additional technology

11/04/2024

One-time passwords

2

2

## Methods



UNIVERSITÀ DI PISA

- Based on time-synchronization
- Based on the previous password
- Based on a challenge

11/04/2024

One-time passwords

3

3

## Time synchronization (→)



UNIVERSITÀ DI PISA

- Prover
  - Token,  $\text{clock}_p$
- Verifier:
  - Authentication server,  $\text{clock}_v$
- Problems
  - Clocks of prover and verifier are roughly synchronised
  - Network latency, user delay, clock skews


11/04/2024

One-time passwords

4

4

# Time synchronization (→)



UNIVERSITÀ DI PISA

- Time Parameters
  - $T_0$  = initial time
  - $T$  = current time
  - $X$  = time steps in a second
  - $C$  = # of time-steps between  $T_0$  and  $T$ 
    - $C = (T - T_0)/X$
  - $W$  = acceptance window
- Key
  - Key  $k$  shared between prover and verifier


11/04/2024

One-time passwords

5

5

# Time synchronization



UNIVERSITÀ DI PISA

- The protocol
  - **Prover**
    - $T_p \leftarrow \text{clock}_p()$
    - $C_p = (T_p - T_0)/X$
    - $\text{HOTP} = \text{HMAC}_k(C_p)$
  - **Authenticator**
    - $T_v \leftarrow \text{clock}_v()$
    - for all  $t$  in  $[T_v - W/2, T_v + W/2]$  {
      - $C_v = (t - T_0)/X$ ;
      - if  $(\text{HOTP} == \text{H}_k(C_v))$  return TRUE;
  - } return FALSE

< -----TRUE|FALSE-----

11/04/2024

One-time passwords

6

6

## Time synchronization



UNIVERSITÀ DI PISA

- For more details
  - D. M'Raihi, S. Machani, M. Pei, J. Rydell. TOTP: Time-Based One-Time Password Algorithm, [RFC 6238](#), IETF, May 2011

11/04/2024

One-time passwords

7

7

## Lamport's scheme



UNIVERSITÀ DI PISA

- Hash List
  - Setup
    - Seed  $p_0 \leftarrow \text{random}()$
    - $p_i = H(p_{i-1})$ ,  $i = 1, \dots, n$
    - $p_n$  is stored at the verifier by *offline means*
  - Password verification
    - Prover sends  $p_{n-1}$  to Verifier
    - Verifier returns  $(p_n == H(p_{n-1}))$
    - *More in general*
      - Verifier returns  $(p_i == H(p_{i-1}))$  or  $(p_i == H^i(p_0))$
      - 2<sup>nd</sup> form in case  $p_i$  are not verified sequentially


11/04/2024

One-time passwords

8

8

# Challenge-response



- Prover and Verifier share a key  $K$

– **Verifier**

$chl \leftarrow \text{random}()$

$\text{send}(\text{Prover}, chl)$

----->

<-----

$\text{return } (res == H_k(ch))$

**Prover**

$res = H_k(chl)$

$\text{send}(\text{Verifier}, res)$

11/04/2024

One-time passwords

9