Object Oriented Programming

LAB-01 - Solutions (C++)

University of Fallujah - College of IT - AI Department

Task 01: resizeArray

```
#include <iostream>
using namespace std;

// Returns new array of double size:
// first half = original, second half = 2x
int* resizeArray(int inArray[], const int size)
{
    int* newArr = new int[size * 2];
    for (int i = 0; i < size; i++)
    {
        newArr[i] = inArray[i];
        newArr[i + size] = inArray[i] * 2;
    }
    return newArr;
}

int main()
{
    int size;
    cout << "Enter size of the array: ";
    cin >> size;

    int* arr = new int[size];
    cout << "Enter elements of array: ";
    for (int i = 0; i < size; i++)
        cin >> arr[i];

    int* res = resizeArray(arr, size);

    cout << "Resized array: ";
    for (int i = 0; i < size * 2; i++)
    {
        cout << res[i];
        if (i < size * 2 - 1)
            cout << ", ";
    }
    cout << endl;

    delete[] arr;
    delete[] res;
    arr = res = nullptr;
    return 0;
}
```

Task 02: Diagonal Matrix

```
#include <iostream>
using namespace std;

// true if all entries outside main diagonal are 0
bool isDiagonal(int** m, int n)
{
    for (int i = 0; i < n; i++)
        for (int j = 0; j < n; j++)
            if (i != j && m[i][j] != 0)
                return false;
    return true;
}

int main()
{
    int n;
    cout << "Enter matrix size: ";
    cin >> n;

    // allocate n x n matrix
    int** m = new int*[n];
    for (int i = 0; i < n; i++)
        m[i] = new int[n];

    cout << "Enter matrix values:\n";
    for (int i = 0; i < n; i++)
        for (int j = 0; j < n; j++)
            cin >> m[i][j];

    if (isDiagonal(m, n))
        cout << "Diagonal matrix\n";
    else
        cout << "Not a diagonal matrix\n";

    // free memory
    for (int i = 0; i < n; i++)
        delete[] m[i];
    delete[] m;
    m = nullptr;
    return 0;
}
```

Task 03: left() and Destructor()

```
#include <iostream>
#include <cstring>
using namespace std;

// copies first 'count' chars of target
char* left(const char* target, const int count)
{
    char* sub = new char[count + 1];
    for (int i = 0; i < count; i++)
        sub[i] = target[i];
    sub[count] = '\0';
    return sub;
}

// frees the dynamic memory
void Destructor(char* p)
{
    delete[] p;
}

int main()
{
    char str[30];
    int count;

    cout << "Enter a string: ";
    cin.getline(str, 30);
    if (cin.fail())          // input longer than 29
    {
        cin.clear();
        cin.ignore(1000, '\n');
    }

    cout << "Enter count: ";
    cin >> count;

    if (count < 0 || count > (int)strlen(str))
        cout << "Count is out of range!\n";
    else
    {
        char* sub = left(str, count);
        cout << "Left substring: " << sub << endl;
        Destructor(sub);
        sub = nullptr;
    }
    return 0;
}
```

Task 04: Students Marks Statistics

```
#include <iostream>
using namespace std;

int findMin(int inArray[], const int size)
{
    int min = inArray[0];
    for (int i = 1; i < size; i++)
        if (inArray[i] < min)
            min = inArray[i];
    return min;
}

int findMax(int inArray[], const int size)
{
    int max = inArray[0];
    for (int i = 1; i < size; i++)
        if (inArray[i] > max)
            max = inArray[i];
    return max;
}

int computeAverage(int inArray[], const int size)
{
    int sum = 0;
    for (int i = 0; i < size; i++)
        sum += inArray[i];
    return sum / size;
}

int computeMedian(int inArray[], const int size)
{
    // sort a copy (bubble sort)
    int* t = new int[size];
    for (int i = 0; i < size; i++)
        t[i] = inArray[i];
    for (int i = 0; i < size - 1; i++)
        for (int j = 0; j < size - i - 1; j++)
            if (t[j] > t[j + 1])
            {
                int tmp = t[j];
                t[j] = t[j + 1];
                t[j + 1] = tmp;
            }

    int med;
    if (size % 2 == 1)
        med = t[size / 2];
    else
        med = (t[size / 2 - 1] + t[size / 2]) / 2;

    delete[] t;
    return med;
}

int main()
{
    int n;
```

```
    cout << "Number of students: ";
    cin >> n;
    while (n <= 0)
    {
        cout << "Enter a positive number: ";
        cin >> n;
    }

    int* marks = new int[n];
    for (int i = 0; i < n; i++)
    {
        cout << "Marks of student " << i + 1 << ": ";
        cin >> marks[i];
        while (marks[i] < 0)   // no negatives
        {
            cout << "Invalid! Re-enter: ";
            cin >> marks[i];
        }
    }

    cout << "Maximum: " << findMax(marks, n) << endl;
    cout << "Minimum: " << findMin(marks, n) << endl;
    cout << "Average: " << computeAverage(marks, n) << endl;
    cout << "Median : " << computeMedian(marks, n) << endl;

    delete[] marks;
    marks = nullptr;
    return 0;
}
```