Object Oriented Programming

LAB-03 - Solutions(C++)

UniversityofFallujah - Collegeof IT - AI Department

Task 01 (Part 1): Inventory with int code

```
#include <iostream>
#include <iomanip>
#include <cstdlib>
#include <ctime>
#include <string>
using namespace std;

const int SIZE = 10;

struct InventoryItem
{
    int     code;
    string  name;
    double  cost;
    double price;
};

InventoryItem insertItem()
{
    InventoryItem item;
    item.code = 3123 + rand() % 9000;   // auto code

    cout << "Item name: ";
    getline(cin >> ws, item.name);
    cout << "Item cost: ";
    cin >> item.cost;

    item.price = item.cost * 1.40;      // 40% profit
    return item;
}

void displayStock(const InventoryItem* item)
{
    cout << left << setw(8) << item->code
         << setw(18) << item->name
         << setw(12) << item->cost
         << setw(12) << item->price << endl;
}

int main()
{
    srand(time(0));
    InventoryItem stock[SIZE];

    for (int i = 0; i < SIZE; i++)
        stock[i] = insertItem();

    cout<< left << setw(8) << "Code"
         << setw(18) << "Name"
```

```
         << setw(12) << "Cost"
         << setw(12) << "Price" << endl;
    cout<< string(50, '-') << endl;

    for (int i = 0; i < SIZE; i++)
        displayStock(&stock[i]);
    return 0;
}
```

Task 01 (Part 2): Code as string (e.g. COM_31203)

SameasPart1,butcodeisastring:first3letters(uppercase)+_+running number.

```
#include  <iostream>
#include   <iomanip>
#include    <cctype>
#include    <string>
using namespace std;

const int SIZE = 10;
int counter = 31203;   // running integer

struct InventoryItem
{
    string  code;      // now a string
    string  name;
    double  cost;
    double price;
};

// builds code like COM_31203
string makeCode(const string& name)
{
    string pre = name.substr(0, 3);
    for (int i = 0; i < (int)pre.size(); i++)
        pre[i] = toupper(pre[i]);
    return pre + "_" + to_string(counter++);
}

InventoryItem insertItem()
{
    InventoryItem item;
    cout << "Item name: ";
    getline(cin >> ws, item.name);
    cout << "Item cost: ";
    cin >> item.cost;

    item.code = makeCode(item.name);
    item.price = item.cost * 1.40;
    return item;
}

void displayStock(const InventoryItem* item)
{
    cout << left << setw(12) << item->code
         << setw(18) << item->name
         << setw(12) << item->cost
         << setw(12) << item->price << endl;
}

int main()
{
    InventoryItem stock[SIZE];
    for (int i = 0; i < SIZE; i++)
        stock[i] = insertItem();

    cout<< left << setw(12) << "Code"
         << setw(18) << "Name"
         << setw(12) << "Cost"
```

```
         << setw(12) << "Price" << endl;
    cout<< string(54, '-') << endl;

    for (int i = 0; i < SIZE; i++)
        displayStock(&stock[i]);
    return 0;
}
```

Task 02: Carpet Cost

Pricepersqft=Rs.18.Inchesare converted to feet (inches / 12).

```
#include <iostream>
using namespace std;

const int PRICE_PER_SQFT = 18;   // Rs. per sq ft

struct FeetInches
{
    int feet;
    int inches;
};

struct RoomDimension
{
    FeetInches length;
    FeetInches Width;
};

// converts feet + inches to feet
double toFeet(const FeetInches& f)
{
    return f.feet + f.inches / 12.0;
}

// cost of carpet for one room
int computeTheCarpetingCost(const RoomDimension& room)
{
    double area = toFeet(room.length) * toFeet(room.Width);
    return (int)(area * PRICE_PER_SQFT);
}

int main()
{
    int n;
    cout << "Number of rooms: ";
    cin >> n;

    RoomDimension* rooms = new RoomDimension[n];
    for (int i = 0; i < n; i++)
    {
        cout << "Room " << i + 1 << endl;
        cout << " Length (feet inches): ";
        cin >> rooms[i].length.feet >> rooms[i].length.inches;
        cout << " Width (feet inches): ";
        cin >> rooms[i].Width.feet >> rooms[i].Width.inches;
    }

    int choice;
    do
    {
        cout<<"\n1. Total cost of house\n"
             <<"2. Cost of each room\n"
             <<"0. Exit\n"
             <<"Choice: ";
        cin >> choice;

        if (choice == 1)
```

```
        {
            int total = 0;
            for (int i = 0; i < n; i++)
                total+=computeTheCarpetingCost(rooms[i]);
            cout<<"Totalcost:Rs."<<total << endl;
        }
        else if (choice == 2)
        {
            for (int i = 0; i < n; i++)
                cout<<"Room"<<        i+1<<": Rs. "
                      <<computeTheCarpetingCost(rooms[i]) << endl;
        }
    } while (choice != 0);

    delete[] rooms;
    rooms = nullptr;
    return 0;
}
```