

Manual for setting up the sensors of the Monitoring Box

Mick Nieman
Amsterdam University of Applied Sciences

Pjotr Scholtze
Amsterdam University of Applied Sciences

Heeyeon Joung
Seoul National University of Science and Technology

November 2017

Abstract

This has not been written yet and still needs content to be placed here.

Contents

1	Introduction	2
2	Requirements	3
3	Glossary	5
4	Global Positioning System (GPS) sensor	6
5	Temperature and humidity sensor	7
6	Heartrate sensor	8
7	Regular carbon dioxide (CO ₂) sensor	9
8	Advanced carbon dioxide (CO ₂) sensor	10
9	Raspberry Pi Camera	11
10	Galvanic skin response sensor	12
11	Development issued example sensor	13
12	Developemnt issued unknown sensor	14

Chapter 1

Introduction

Chapter 2

Requirements

For every sensor added there is need for an Arduino Nano. The Arduino Nano is a programmable microprocessor. Advanced users may be able to connect multiple sensors to a single Arduino Nano, note that this requires advanced knowledge of the communication protocols between the Raspberry Pi 3 b+ and Arduino Nano. Along with every Arduino Nano you need an USB A to Mini-USB B cable.

The first item needed for the GPS sensor is the Global Positioning System (GPS) module. We have used the Digilent 410-237 GPS-receiverboard.

For the temperature and humidity sensor we have used the DHT22 module, this is a digital temperature- and humidity sensor. the DHT22 is more accurate (0,5° accuracy) than the previous, DHT11. It has a temperature reach from -40 to +80 °C. and has a humidity reach from 10% to 90% with an accuracy of 2,0 %.

The heartrate sensor consists of the MAXREFDES117# Reference Design Board with optical heart rate and pulse-oximetry monitor. It has integrated Red and Infrared LEDs. This works best on a person's fingertip or earlobe.

The CO₂ sensor comes in two varieties, the regular sensor which is affordable but less accurate and the advanced which has a higher costs and comes with higher accuracy.

The 'Regular CO₂ sensor' uses the MIKROE-1630 Daughter Board from Air Quality Click. It's an MQ-135 High sensitivity air quality sensor and potentiometer.

The 'Advanced CO₂ sensor' uses CO2meter.com its K-30 sensor. The K-30 sensor is an accurate gas sensing up to 5000ppm (CO₂) with an accuracy of 3%. Note that the advanced CO₂ meter does not work on the Arduino Nano and is only tested on the Arduino Uno.

The raspberry Pi Cam doesn't require to be connected to an Arduino and

can be plugged directly in to the Raspberry Pi its camera-port. For this project we used Sony's IMX219 8-Megapixel Pi Camera Board. It is able for taking photographs of 3280x2464 pixels or video's at 1080p at 30 frames per second.

The galvanic skin response sensor, or short GSR, measures the galvanic skin response based on the electrical conductance of the skin. For the Monitoring Box we have used the Grove-GSR sensor from seeed studio.

Chapter 3

Glossary

Chapter 4

Global Positioning System (GPS) sensor

Chapter 5

Temperature and humidity sensor

Chapter 6

Heartrate sensor

Chapter 7

Regular carbon dioxide (CO₂) sensor

Chapter 8

Advanced carbon dioxide (CO₂) sensor

Chapter 9

Raspberry Pi Camera

Chapter 10

Galvanic skin response sensor

Chapter 11

Development issued example sensor

Chapter 12

Development issued unknown sensor