P-channel -30 V, 12 mΩ typ., -9 A STripFET™ H6 Power MOSFET in a PowerFLAT™ 3.3x3.3 package



PowerFLAT™ 3.3x3.3



AM01475v4

Features

Order code	V_{DS}	$R_{DS(on)}$ max	I_D
STL9P3LLH6	-30 V	15 mΩ	-9 A

- Very low on-resistance
- Very low gate charge
- High avalanche ruggedness
- Low gate drive power loss

Applications

- Switching applications

Description

This device is a P-channel Power MOSFET developed using the STripFET™ H6 technology with a new trench gate structure. The resulting Power MOSFET exhibits very low $R_{DS(on)}$ in all packages.

Product status
STL9P3LLH6

Product summary	
Order code	STL9P3LLH6
Marking	9P3L
Package	PowerFLAT™ 3.3x3.3
Packing	Tape and reel

1 Electrical ratings

Table 1. Absolute maximum ratings

Symbol	Parameter	Value	Unit
V_{DS}	Drain-source voltage	-30	V
V_{GS}	Gate-source voltage	± 20	V
I_D	Drain current (continuous) at T_{pcb} = 25 °C	-9	A
I_D	Drain current (continuous) at T_{pcb} = 100 °C	-5.9	A
I_{DM} (1)	Drain current (pulsed)	-36	A
P_{TOT}	Total dissipation at T_{pcb}=25 °C	3	W
T_{stg}	Storage temperature range	- 55 to 150	°C
T_j	Operating junction temperature range		

1. *Pulse width limited by safe operating area.*

Table 2. Thermal data

Symbol	Parameter	Value	Unit
$R_{thj\text{-}case}$	Thermal resistance junction-case	2.5	°C/W
$R_{thj\text{-}pcb}$ (1)	Thermal resistance junction-pcb	42	°C/W

1. *When mounted on FR-4 board of 1inch², 2oz Cu t < 10 s*

2 Electrical characteristics

(T_C = 25 °C unless otherwise specified)

Table 3. On /off states

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$V_{(BR)DSS}$	Drain-source breakdown voltage	V_{GS} = 0 V, I_D = -1 mA	-30			V
I_{DSS}	Zero gate voltage drain current	V_{GS} = 0 V, V_{DS} = -30 V			-1	µA
		V_{GS} = 0 V, V_{DS} = -30 V, T_C = 125 °C (1)			-10	µA
I_{GSS}	Gate-body leakage current	V_{DS} = 0 V, V_{GS} = ± 20 V			±100	nA
$V_{GS(th)}$	Gate threshold voltage	V_{DS} = V_{GS}, I_D = -250 µA	-1			V
$R_{DS(on)}$	Static drain-source on-resistance	V_{GS} = -10 V, I_D =-4.5 A		12	15	mΩ
		V_{GS} = -4.5 V, I_D = -4.5 A		18	22.5	mΩ

1. *Defined by design, not subject to production test.*

Table 4. Dynamic

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
C_{iss}	Input capacitance	V_{DS} = -25 V, f = 1 MHz, V_{GS} = 0 V	-	2615	-	pF
C_{oss}	Output capacitance		-	340	-	pF
C_{rss}	Reverse transfer capacitance		-	235	-	pF
Q_g	Total gate charge	V_{DD} = -15 V, I_D = -9 A, V_{GS} = -4.5 to 0 V (see Figure 13. Gate charge test circuit)	-	24	-	nC
Q_{gs}	Gate-source charge		-	9	-	nC
Q_{gd}	Gate-drain charge		-	8	-	nC

Table 5. Switching times

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$t_{d(on)}$	Turn-on delay time	V_{DD} = -15 V, I_D = -4.5 A, R_G = 4.7 Ω, V_{GS} = -10 V (see Figure 12. Switching times test circuit for resistive load)	-	13.2	-	ns
t_r	Rise time		-	93	-	ns
$t_{d(off)}$	Turn-off delay time		-	50	-	ns
t_f	Fall time		-	18	-	ns

Table 6. Source drain diode

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
V_{SD} (1)	Forward on voltage	I_{SD} = -9 A, V_{GS} = 0 V	-		-1.1	V

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
t_{rr}	Reverse recovery time	I_{SD} = -9 A, di/dt = 100 A/µs	-	20		ns
Q_{rr}	Reverse recovery charge	V_{DD} = -24 V, T_j=150 °C	-	16		nC
I_{RRM}	Reverse recovery current	(see Figure 14. Test circuit for inductive load switching and diode recovery times)	-	-1.6		A

1. *Pulsed: pulse duration = 300 µs, duty cycle 1.5%*

2.1 Electrical characteristics (curves)

Note: Note: For the P-channel Power MOSFET, current and voltage polarities are reversed.

Figure 1. Safe operating area



Figure 2. Thermal impedance



Figure 3. Output characteristics



Figure 4. Transfer characteristics



Figure 5. Gate charge vs gate-source voltage



Figure 6. Static drain-source on-resistance



Figure 7. Capacitance variations



Figure 8. Normalized gate threshold voltage vs temperature



Figure 9. Normalized on-resistance vs temperature



Figure 10. Normalized $V_{(BR)DSS}$ vs temperature



Figure 11. Source-drain diode forward characteristics



3 Test circuits

Figure 12. Switching times test circuit for resistive load



Figure 13. Gate charge test circuit



Figure 14. Test circuit for inductive load switching and diode recovery times



4 Package information

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: www.st.com. ECOPACK® is an ST trademark.

4.1 PowerFLAT™ 3.3x3.3 package information

Figure 15. **PowerFLAT™ 3.3x3.3 package outline**



Table 7. **PowerFLAT™ 3.3x3.3 package mechanical data**

Dim.	mm		
	Min.	Typ.	Max.
A	0.70	0.80	0.90
b	0.25	0.30	0.39
c	0.14	0.15	0.20
D	3.10	3.30	3.50
D1	3.05	3.15	3.25
D2	2.15	2.25	2.35
e	0.55	0.65	0.75
E	3.10	3.30	3.50
E1	2.90	3.00	3.10
E2	1.60	1.70	1.80
H	0.25	0.40	0.55
K	0.65	0.75	0.85
L	0.30	0.45	0.60
L1	0.05	0.15	0.25
L2			0.15
θ	8°	10°	12°

Figure 16. **PowerFLAT™ 3.3x3.3 recommended footprint (dimensions are in mm)**



Revision history

Table 8. **Document revision history**

Date	Revision	Changes
23-Jan-2014	1	First release.
07-Mar-2016	2	Modified: title and $R_{DS(on)}$ max value Modified: *Table 2: "Absolute maximum ratings"*, *Table 4: "On /off states"*, *Table 5: "Dynamic"*, *Table 6: "Switching times"* and *Table 7: "Source drain diode"* Minor text changes.
20-Feb-2018	3	Updated Figure 1. Safe operating area and Figure 2. Thermal impedance. Removed maturity status indication from cover page. The document status is production data.

Contents

1 **Electrical ratings** 2
2 **Electrical characteristics** 3
2.1 Electrical characteristics (curves) 5
3 **Test circuits** 8
4 **Package information** 9
4.1 PowerFLAT™ 3.3x3.3 package information 9
Revision history 13
Contents 14
Disclaimer 15

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

STMicroelectronics:

STL9P3LLH6