




Introduction to Computer Graphics with WebGL

Ed Angel

Professor Emeritus of Computer Science

Founding Director, Arts, Research,
Technology and Science Laboratory

University of New Mexico



The University of New Mexico


Programming with WebGL

Part 1: Background

Ed Angel

Professor Emeritus of Computer Science

University of New Mexico



The University of New Mexico


Objectives

- Development of the OpenGL API
- OpenGL Architecture
 - OpenGL as a state machine
 - OpenGL as a data flow machine
- Functions
 - Types
 - Formats
- Simple program



Early History of APIs


- IFIPS (1973) formed two committees to come up with a standard graphics API
 - Graphical Kernel System (GKS)
 - 2D but contained good workstation model
 - Core
 - Both 2D and 3D
 - GKS adopted as ISO and later ANSI standard (1980s)
- GKS not easily extended to 3D (GKS-3D)
 - Far behind hardware development



The University of New Mexico

PHIGS and X

-
- Programmers Hierarchical Graphics System (PHIGS)
 - Arose from CAD community
 - Database model with retained graphics (structures)
 - X Window System
 - DEC/MIT effort
 - Client-server architecture with graphics
 - PEX combined the two
 - Not easy to use (all the defects of each)



SGI and GL

-
- Silicon Graphics (SGI) revolutionized the graphics workstation by implementing the pipeline in hardware (1982)
 - To access the system, application programmers used a library called GL
 - With GL, it was relatively simple to program three dimensional interactive applications



The University of New Mexico

OpenGL

The success of GL lead to OpenGL (1992), a platform-independent API that was

- Easy to use
- Close enough to the hardware to get excellent performance
- Focus on rendering
- Omitted windowing and input to avoid window system dependencies



The University of New Mexico

OpenGL Evolution


- Originally controlled by an Architectural Review Board (ARB)
 - Members included SGI, Microsoft, Nvidia, HP, 3DLabs, IBM,.....
 - Now Kronos Group
 - Was relatively stable (through version 2.5)
 - Backward compatible
 - Evolution reflected new hardware capabilities
 - 3D texture mapping and texture objects
 - Vertex and fragment programs
 - Allows platform specific features through extensions



The University of New Mexico

Modern OpenGL

- Performance is achieved by using GPU rather than CPU
- Control GPU through programs called shaders
- Application's job is to send data to GPU
- GPU does all rendering





Immediate Mode Graphics

- Geometry specified by vertices
 - Locations in space(2 or 3 dimensional)
 - Points, lines, circles, polygons, curves, surfaces
- Immediate mode
 - Each time a vertex is specified in application, its location is sent to the GPU
 - Old style uses **glVertex**
 - Creates bottleneck between CPU and GPU
 - Removed from OpenGL 3.1 and OpenGL ES 2.0




Retained Mode Graphics

- Put all vertex attribute data in array
- Send array to GPU to be rendered immediately
- Almost OK but problem is we would have to send array over each time we need another render of it
- Better to send array over and store on GPU for multiple renderings



OpenGL 3.1

- Totally shader-based
 - No default shaders
 - Each application must provide both a vertex and a fragment shader
- No immediate mode
- Few state variables
- Most 2.5 functions deprecated
- Backward compatibility not required
 - Exists a compatibility extension



The University of New Mexico

Other Versions

- OpenGL ES
 - Embedded systems
 - Version 1.0 simplified OpenGL 2.1
 - Version 2.0 simplified OpenGL 3.1
 - Shader based
- WebGL
 - Javascript implementation of ES 2.0
 - Supported on newer browsers
- OpenGL 4.1, 4.2,
 - Add geometry, tessellation, compute shaders