

RRFB CONSTRUCTION NOTES:

1. PRIOR APPROVAL FOR THE USE OF RRFBS MUST BE OBTAINED FROM THE CITY OF AUSTIN TRANSPORTATION ENGINEERING DIVISION.
2. REFER TO "MUTCD INTERIM APPROVAL 21 - RECTANGULAR RAPID FLASHING BEACONS AT CROSSWALKS" FOR THE LATEST REQUIREMENTS AND GUIDANCE.
3. ADA COMPLIANT PEDESTRIAN FACILITIES, INCLUDING RAMPS AND SIDEWALKS, MUST BE INSTALLED PRIOR TO RRFB ACTIVATION.
4. FINAL POLE/BUTTON LOCATION SHALL MEET THE ADA REQUIREMENT FOR USER REACH AND HEIGHT FROM THE ADJACENT LANDING.
5. RECTANGULAR RAPID FLASHING BEACONS (RRFBS) ARE SUPPLEMENTAL TO THE CROSSWALK, THEREFORE, THE CROSSWALK MUST BE MARKED BEFORE RRFBS ARE OPERATIONAL. THE RRFB MUST BE READY FOR ACTIVATION IMMEDIATELY UPON INSTALLATION OF THE CROSSWALK
6. RRFB INSTALLATIONS MUST BE INSPECTED AND APPROVED BY THE AUSTIN TRANSPORTATION DEPARTMENT ARTERIAL MANAGEMENT DIVISION PRIOR TO ACTIVATION.
7. THE REQUIREMENT FOR PROVIDING ADVANCE WARNING SIGNS WILL BE DETERMINED BY THE TRANSPORTATION ENGINEERING DIVISION
8. THE NEED FOR AND PLACEMENT OF STOP BARS WILL BE DETERMINED BY THE TRANSPORTATION ENGINEERING DIVISION

CITY OF AUSTIN DEPARTMENT OF PUBLIC WORKS	RECTANGULAR RAPID FLASHING BEACON PLACEMENT	
<hr/> ADOPTED	THE ARCHITECT/ENGINEER ASSUMES RESPONSIBILITY FOR APPROPRIATE USE OF THIS STANDARD.	STANDARD NO. <b>832-2</b> 2 OF 2