

City Scan Technical Reference

World Bank - City Resilience Program

2026-05-05

Table of contents

Welcome	6
In this technical reference	6
About City Resilience Program (CRP)	6
 I City Scan Overview	 7
1 What is City Scan?	8
1.1 What can the City Scan tell me?	9
1.2 Guiding questions to keep in mind	9
1.3 Why invest in urban resilience	9
 2 City Scan Examples	 10
2.1 Example 1: Standalone Images - Dakar, Senegal	10
2.2 Example 2: Comprehensive Analytical PDF Report - Bitung, Indonesia	11
2.3 Example 3: Interactive HTML website - City, Country	11
 II Standard Workflow	 12
3 General Workflow	13
3.1 Part 1. Basic Setup	13
3.2 Part 2. Configuring Inputs	14
3.3 Part 3. Running a Scan	14
 4 Setup Instructions	 16
4.1 Authentication	16
4.2 Git	17
4.3 Python	17
4.3.1 <i>Option 1: Via Conda (Recommended for Mac, Windows, Linux)</i>	17
4.3.2 <i>Option 2: Via Bootstrap Script (Alternative Setup – only for Mac, Linux)</i>	18
4.4 R	19
4.5 Quarto	20
4.6 VS Code	20
4.6.1 Docker	21

5	Inputs Configuration	22
6	Running a Scan	23
6.1	Collecting and analyzing the dataset	23
6.1.1	Step 1: Configure Setup	23
6.1.2	Step 2: Clone the Repository	23
6.1.3	Step 3: Configure Inputs	24
6.1.4	Step 4: Running Tasks	24
6.1.5	Step 4b: Multi-analysis	25
6.2	Rendering Maps and Charts	25
6.2.1	Step 5: Rendering Maps and Charts	25
6.2.2	Step 6: Scan Calculations Reference Sheet	26
III	Advanced Workflow	27
7	Running Multiple City Scans	28
7.1	Overview	28
7.2	Batch Configuration	28
7.3	Running the Batch	29
7.4	Progress Tracking	31
7.5	Output Structure	32
8	Running a Custom City Scan	33
8.1	When to Customize	33
8.2	Selecting Tasks	33
8.3	Overriding Default Parameters	33
8.4	Adding a Custom Data Source	34
8.5	Custom Output Directory Layout	35
IV	Tasks & Data Layers	37
9	Tasks & Structure Overview	38
9.1	What Is a Task?	38
9.2	Task Anatomy	38
9.2.1	Inputs, Processing, Outputs	38
9.2.2	Task Metadata	39
9.3	Task Categories	41
9.4	Execution Model	42
10	Data Layer References	43
10.1	Population	43
10.2	Land Use & Environment	43

10.3	Infrastructure	44
10.4	Risk & Hazard	46
10.5	Adding a Custom Data Layer	47
V	Understanding the Repo	48
11	Repository Structure	49
11.1	Top-level Layout	49
11.2	Core Package: <code>cityscan/</code>	49
11.2.1	Key Modules	50
11.3	Tasks Directory: <code>tasks/</code>	50
11.4	Inputs & Outputs	50
11.5	Tests	52
12	Task Dependency	53
12.1	Dependency Graph	55
12.2	How Dependencies Are Declared	56
12.3	Execution Order Example	56
12.4	Dependency Table	56
12.5	Handling Failures	57
12.6	Visualizing the DAG	57
VI	Case Studies & Galleries	58
13	Case Study: Standard Scan — Rabat, Morocco	59
13.1	City Context	59
13.2	AOI Definition	61
13.3	Running the Scan	62
13.4	Key Findings	62
13.4.1	Population Distribution	62
13.4.2	Flood Risk	64
13.4.3	Land Use	64
13.5	Outputs	64
14	Case Study: Multiple Scans — Philippines	65
14.1	Project Context	65
14.2	Cities Covered	65
14.3	Batch Configuration	65
14.4	Running the Batch	66
14.5	Key Findings Across Cities	68
14.5.1	Coastal Flood Risk	69
14.5.2	Urban Heat Islands	69

14.6 Lessons Learned	69
VII Collaborating	70
15 Git Guide	71
15.1 Branching Strategy	71
15.2 Cloning the Repository	71
15.3 Commit Message Conventions	71
15.3.1 Examples	72
15.4 Pull Request Workflow	72
15.5 Keeping Your Branch Up to Date	74
16 Reporting Issues	75
16.1 Where to Report	75
16.2 Before You Open an Issue	75
16.3 Bug Reports	75
16.4 Feature Requests	76
16.5 Sharing Log Files	78
16.6 Issue Labels	78
17 Contributing	79
17.1 Types of Contributions	79
17.2 Development Setup	79
17.3 Code Style	79
17.4 Writing a New Task	80
17.5 Pull Request Checklist	82
17.6 Review Process	83
18 Sharing the Guide	84
18.1 Rendered Formats	84
18.2 Publishing to GitHub Pages	84
18.3 Publishing to Quarto Pub	85
18.4 Sharing the PDF	85
18.5 Embedding in Other Sites	86
18.6 Keeping the Guide Up to Date	86
References	88

Welcome

The City Scan is a diagnostic tool designed to equip cities with the early insights needed to address risk by:

- Providing a rapid, data-driven snapshot of a city's demographic, economic, climate, and risk landscape.
- Leveraging remote sensing and geospatial analysis of any city in the world, using global datasets.
- Revealing the interaction between the urban built and natural environments.

In this technical reference

This reference book is a structured technical documentation to use and operate City Scan as a diagnostic tool. Here, you will find documentations on City Scan overview, getting started, running a City Scan, tasks and data layers, repository structure, case studies & galleries, as well as contributing guides.

About City Resilience Program (CRP)

The City Resilience Program is housed within the Global Facility for Disaster Reduction and Recovery (GFDRR) at the World Bank. CRP is a global initiative supported by the Swiss State Secretariat for Economic Affairs, the Austrian Federal Ministry of Finance, the Italian Ministry of Foreign Affairs, the Italian Agency for Development Cooperation, and the Gates Foundation.

To learn more about CRP and GFDRR visit <https://www.gfdr.org/en/crp>.

Part I

City Scan Overview

1 What is City Scan?



Figure 1.1: City Scan Concept

A City Scan is a rapid geospatial assessment of a city's demographic, socioeconomic, climate, and risk conditions. It is a collection of maps and charts made from global and publicly available datasets that provide quick high-level insights into resilience-related topics for a city. The output is a package of maps, data visualizations and insights that integrate features of both the built and natural environments. These scans are especially useful for grounding early-stage conversations in geospatial data.

1.1 What can the City Scan tell me?

This City Scan is intended to support operational teams in building dialogue around a city's most pressing resilience challenges. It is designed as a conversation starter rather than a specific decision making tool. Thinking spatially about how urbanization affects the resilience of various urban forces, networks, and people helps equip officials to develop risk informed investment proposals, identify opportunities and barriers to unlocking private capital, and prioritize and coordinate future investments.

1.2 Guiding questions to keep in mind

- How might investment priorities differ in different parts of the city based on this data?
- What spatial relationships are surprising?
- What questions does this spatial pattern spur?
- Where else have you worked that is reminiscent of these findings?
- What might be applicable from there? What might not be?

1.3 Why invest in urban resilience

Investing in urban resilience boosts long-term economic, social, and physical sustainability by safeguarding the gains from current developments for future generations. Greater urban resilience builds the capacity of local governments to help households, communities, and enterprises manage and avoid shocks and stresses, for example by damage-proofing infrastructure before a disaster or maintaining critical services afterward. This approach represents a significant shift from prior development trends, which concentrated investments on post-disaster reconstruction and recovery.

Note

For a hands-on introduction, see [Running Your First City Scan](#).

2 City Scan Examples

City Scan output is a collection of maps and charts made from global and publicly available datasets that provide quick high-level insights into resilience-related topics for a city. The output is a package of maps, data visualizations and insights that integrate features of both the built and natural environments. It is available as standalone images, compiled PDF, and interactive Quarto HTML.

2.1 Example 1: Standalone Images - Dakar, Senegal

This format is useful if you'd like to combine City Scan outputs with your own analysis. See examples from our analysis for Dakar, Senegal




Figure 2.1: Examples of maps & charts generated by City Scan

2.2 Example 2: Comprehensive Analytical PDF Report - Bitung, Indonesia

The generated maps and charts are compiled according to relevant themes, along with data interpretation and considerations. See examples below from our analysis in Bitung, Indonesia.

Note

The final PDF output is compiled and designed via Adobe InDesign and not yet automatically generated by the code. Automated PDF generation will be part of future updates.

2.3 Example 3: Interactive HTML website - City, Country

Nemo enim ipsam voluptatem quia voluptas sit aspernatur aut odit aut fugit, sed quia consequuntur magni dolores eos qui ratione voluptatem sequi nesciunt.

Tip


Full case studies for Rabat and the Philippines are in [Part 6. Case Studies & Galleries](#).

Part II

Standard Workflow

3 General Workflow

This chapter provides a three-part walkthrough of the City Scan repo for new users. The diagram below illustrates the general workflow of performing a standard City Scan.



3.1 Part 1. Basic Setup

i Note

See [Part 4. Getting Started/ Setup Instructions](#) for full details of prerequisites and installations

City Scan uses multiple programming languages and software to run, including Git, Python, R, Quarto, and Google Cloud. The steps required for setups are below:

- Clone the repo
- Create conda env + activate cityscan
- Installing City Scan as Python Package via `pip install -e .` for the scan CLI

- GCS and GEE authentication via `gcloud auth application-default login`
- Install Quarto
- Run `scan --check` to verify everything passes

3.2 Part 2. Configuring Inputs

Inputs folder is where you can specify your area of interests (AOI), types of analysis to conduct, and certain global analysis parameters.

- Drop AOI shapefile into `inputs/AOI/`
- Edit `inputs/city_inputs.yml`
- Edit `inputs/menu.yml`

3.3 Part 3. Running a Scan

When running a scan, we are essentially going through several phases. The general flow is collect → analyze → multianalysis → render.

1. **Collect** stage is retrieving specified datasets as indicated in inputs configuration from various publicly available sources for the specified AOI. As an output, you will retrieve TIFFs, GeoJSONs, or Geopackages in your output folder.

To conduct **collect** stage, run in your terminal

```
scan --collect
```

2. **Analyze** stage is conducting various analysis on a single task, such as seeing the statistical distribution, applying threshold, extracting median/mean values, etc. As an output, you will retrieve various CSVs in your output folder.

To conduct **analyze** stage, run in your terminal

```
scan --analyze
```

3. Alternatively, you can **batch data collection and data analysis together by looping over tasks** by running:

```
scan --all
```

Or, you can leverage your computer memory and **parallelizing data collection and data analysis together per tasks** by running:

```
scan --all --parallel
```

 Warning

[**Internal Note**] Perhaps in the future, `scan --all` and `scan --all --parallel` should be reserved to orchestrate the whole process, including multianalysis, render, and scan-calculations

4. **Multianalysis** stage is performing cross-task analysis after single tasks analysis have been executed. For example, this stage executes analysis of flood-exposed population, which requires both flood analysis and population analysis to have been conducted. To do this, run in your terminal:

```
scan --multianalysis
```

5. **Render** stage is generating various visualizations as results of previous stages. This includes rendering maps and charts as PNGs or HTMLs.

```
# Static maps - applies styling from source/layers.yml, writes PNGs to 03-render-output/  
scan --render maps
```

```
# Charts for a specific task - writes HTML to tasks/{name}/charts/index.html  
scan --render charts elevation
```

To generate a compiled interactive quarto document and HTML of all tasks, run:

```
scan --render scan-calculations
```

4 Setup Instructions

City Scan repo is multilingual: Python is used for data collection and analysis, R for mapping and charting, and Quarto for report compilation and web visualization.

All City Scan tasks can be accessed through terminal with the required tools configured:

- [Git](#)
- [Python](#)
- [R](#)
- [Quarto](#)
- gcloud

Recommended: - [Visual Studio Code](#)

The following sections describe the recommended setup configuration and best practices.

4.1 Authentication

Authentication is managed in `core/config/`:

- **auth.py** — initializes Google Earth Engine (GEE) and Google Cloud Storage (GCS) credentials
- **scan.py** — the Scan class that loads AOI, city config, and creates city output folders
- **paths.py** — auto-detects input/output directories based on project structure
- **gdal_auth.py** — configures GDAL for authenticated access to private GCS buckets via `/vsigs/`

Tasks that need GEE (forest, landcover, LST, NDVI, nightlight) or private GCS (WSF, fathom, landcover burn, basic info) are automatically authenticated before running. If auth fails, those tasks are skipped with a warning.

See [google cloud setup](#) for more details.

4.2 Git

Git is a version control system. It's a timewarpy quantum tool that lets multiple dimensions and times exist at once. It lets you keep multiple versions of your files, and keep track of changes. It also makes it easier to collaborate with each other, as a conduit for “pulling” and “pushing” and “pulling” code from and to GitHub. Instead of downloading a repo from GitHub, you can “clone” it – which is still downloading, but with the added benefit of keeping a live connection to future changes (at your discretion).

Git is already installed on most macOS and Linux systems. You can install it from [Git for Windows](#). If git is not installed, see the GitHub's [git installation guide](#)

4.3 Python

We recommend creating a python environment to run City Scan Tasks. Here are the options:

4.3.1 *Option 1: Via Conda (Recommended for Mac, Windows, Linux)*

4.3.1.1 Step 1: Install Anaconda

Download and install Anaconda from the [official Anaconda website](#):

- Visit <https://www.anaconda.com/download> and select your operating system
- Follow the installation wizard and accept the default settings
- Restart your terminal after installation completes
- Verify installation by running: `conda --version`

If `conda --version` returns command not found (especially in the VS Code integrated terminal), conda was installed but not initialized for your shell. Run once:

```
conda init zsh      # macOS / Linux (zsh - default on modern macOS)
conda init bash     # Linux / older macOS / WSL
conda init powershell # Windows PowerShell
```

Then close and reopen the terminal. You should see `(base)` in your prompt and `conda` should resolve.

4.3.1.2 Step 2: Create and Activate the Environment

```
conda create -n cityscan python=3.11.8 -y
conda activate cityscan
```

4.3.1.3 Step 3: Install Dependencies

```
python -m pip install --upgrade pip
pip install -r requirements.txt
```

4.3.1.4 Step 4: Register Jupyter Kernel (Optional, for notebook use)

```
python -m ipykernel install --user --name cityscan --display-name "Cityscan"
```

4.3.2 Option 2: Via Bootstrap Script (Alternative Setup – only for Mac, Linux)

If you prefer automated system setup or Python is not installed, use the bootstrap approach:

4.3.2.1 Step 1: Clone the Repository

```
git clone --single-branch --branch unified https://github.com/varinaldi/city-scan-automation
cd city-scan-automation
```

4.3.2.2 Step 2: Run Bootstrap Script

This script prepares your system and installs Python 3.11.8 via pyenv:

```
bash bootstrap.sh
```

If you need to manually activate the environment later, use:

```
source venv/bin/activate
```

Note: Review the `bootstrap.sh` script first to ensure it meets your system requirements. It will: - Install system dependencies - Install and configure pyenv - Install Python 3.11.8 - Update your shell configuration

If pyenv is installed for the first time, restart your terminal and run the script again.

4.3.2.3 Step 3: Run Setup Script

This script creates the virtual environment, installs dependencies, and registers the Jupyter kernel:

```
bash orchestrator.sh
```

When setup is successful, you should see: - Python 3.11.8 ready via pyenv - A new virtual environment created - A Jupyter kernel registered: “Cityscan (Python 3.11)”

4.4 R

R is used for the maps, charts, and scan-calculations report, and also for several data collection tasks (earthquake, oxford, cyclones, flood_events, gdp_gridded, coastal_erosion, sea_level_rise). You can download R [here](#). **Use the latest stable R release** (currently 4.5.x) — the repo depends on a current `ggplot2`, `terra`, `sf`, and `tidyterra` stack that won’t install cleanly on older R. If you already have R, run `R --version` and upgrade if you’re behind. To use R in VS Code, we recommend installing the [R extension](#): follow the instructions at the link; we also recommend installing [radian](#).

If you have used R in the past, you likely used RStudio as your editor. For the City Scan workflow and development, we recommend VS Code as it supports multiple languages and has a better terminal and Git integration. Still, RStudio can still be useful, and can be downloaded [here](#).

4.5 Quarto

Quarto is a publishing system that lets you create documents and websites with R, Python, JavaScript, and Julia. If you are familiar with R Markdown, Jupyter notebooks, or Observable notebooks, Quarto is similar but allows for the use of multiple languages in the same document. It is used to create the City Scan reports and website.

A Quarto file is a markdown document with code chunks that can be rendered into HTML, PDF, or other formats. The Python and R code is executed at the time of rendering and the output is included in the final document.

To install Quarto, follow the instructions at [Quarto's installation page](#).

4.6 VS Code

VS Code isn't strictly necessary, but it makes working with multiple files and filetypes much easier. It also makes working with [Git](#) much clearer. VS Code is a free code editor with an integrated terminal and near endless extensions. (If you're coming from R, you've probably been using RStudio; VS Code is like RStudio but for all languages, a better terminal, easier Git integration and better handling of multiple windows. If you're coming from Python, I'm not and don't know what you're probably using.)

Install VS Code from [Visual Studio Code](#).

Recommended extensions for working with this repo:

- [Python](#) — Python language support
- [R](#) — R language support
- [Quarto](#) — Quarto rendering + preview
- [Rainbow CSV](#) — color-coded columns for the many CSVs under `02-process-output/tabular/`
- [Color Highlight](#) — inline color swatches for hex codes in `source/layers.yml`
- [Geo Data Viewer](#) — preview `.geojson`, `.shp`, and other vector files on a map
- [GeoTIFF Viewer](#) — preview `.tif` rasters directly in the editor `<!-- ### gcloud`

The Google Cloud SDK, `gcloud`, is a command line tool for interacting with Google Cloud Platform. It lets us download and upload files from and to Cloud Storage, run Jobs, and so forth. You can do most of these things in the browser, but `gcloud` is often much more convenient.

The standard install instructions are [here](#); slightly simpler instructions are [here](#)

4.6.1 Docker

Docker lets all of us, with our different devices, operating systems and softwares, pretend we all have the same setup. It lets us define and run *containers*, essentially mini virtual machines that can run anywhere Docker is installed. Docker is most important for us because it's how we package code up to run on Google Cloud, but it's also helpful for running code locally.

With Docker, we write instructions (a Dockerfile) that define a Docker *image*. This image defines the operating system, software, libraries, and code that will ... TK

To install, follow the instructions at <https://docs.docker.com/desktop>. ->

5 Inputs Configuration

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Duis sagittis posuere ligula sit amet lacinia. Duis dignissim pellentesque magna, rhoncus congue sapien finibus mollis. Ut eu sem laoreet, vehicula ipsum in, convallis erat. Vestibulum magna sem, blandit pulvinar augue sit amet, auctor malesuada sapien. Nullam faucibus leo eget eros hendrerit, non laoreet ipsum lacinia. Curabitur cursus diam elit, non tempus ante volutpat a. Quisque hendrerit blandit purus non fringilla. Integer sit amet elit viverra ante dapibus semper. Vestibulum viverra rutrum enim, at luctus enim posuere eu. Orci varius natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus.

Nunc ac dignissim magna. Vestibulum vitae egestas elit. Proin feugiat leo quis ante condimentum, eu ornare mauris feugiat. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris cursus laoreet ex, dignissim bibendum est posuere iaculis. Suspendisse et maximus elit. In fringilla gravida ornare. Aenean id lectus pulvinar, sagittis felis nec, rutrum risus. Nam vel neque eu arcu blandit fringilla et in quam. Aliquam luctus est sit amet vestibulum eleifend. Phasellus elementum sagittis molestie. Proin tempor lorem arcu, at condimentum purus volutpat eu. Fusce et pellentesque ligula. Pellentesque id tellus at erat luctus fringilla. Suspendisse potenti.

6 Running a Scan

6.1 Collecting and analyzing the dataset

6.1.1 Step 1: Configure Setup

City Scan uses multiple programming languages and software to run, including:

- [Git](#)
- [Python](#)
- [R](#)
- [Quarto](#)
- Google Cloud - for accessing data, see [authentication](#) details.

See [setup.md](#) for detailed instruction.

6.1.2 Step 2: Clone the Repository

```
git clone -b unified https://github.com/varinaldi/city-scan-automation.git
cd city-scan-automation
```

Install the `scan` CLI (one-time):

```
pip install -e .
```

This gives you the `scan` command as a shortcut for `python -m tasks` — both work interchangeably.

Verify your environment is ready:

```
scan --check
```

Runs a preflight on R, Python, GEE, GCS, Quarto, and inputs. Targets a subset with e.g. `scan --check r gee`.

6.1.3 Step 3: Configure Inputs

Adjust the files in the `inputs/` folder for your specific project: - Use `AOI/` folder and store your AOI boundary file there - Modify `city_inputs.yml` and `menu.yml` with your analysis parameters

6.1.4 Step 4: Running Tasks

Make sure the Python environment is activated.

Executing tasks can be done from the `city-scan` directory or from within `mnt/scan-id`. General form:

```
scan {TASKNAME} {FLAG}
```

Each task is divided into different steps, defined by `{FLAG}`: - `--collect` runs data collection and saves outputs in `02-process-outputs/spatial` or `/tabular` - `--analyze` runs data analysis and creates output CSVs in `02-process-outputs/tabular` - `--all` runs both `--collect` and `--analyze`, reads `menu.yml` - `--multianalysis` runs cross-task analysis (currently only for fathom)

To run all tasks set to true in `menu.yml` in parallel (recommended):

```
scan --all
```

This opens a Terminal UI (TUI) showing per-task progress and logs.

When running the above from - `city-scan` root — initializes `mnt/scan-id` and copies all necessary folders. - For an existing scan, target it with `--scan-id`: `scan --all --parallel --scan-id 2026-02-malta-malta` - Inside `mnt/scan-id` — outputs files into the local `02-process-outputs/`.

To run an individual task or a set of tasks:

```
# Individual task
scan wsf

# Multiple tasks
scan wsf population forest
```

Run specific steps with `{FLAG}`:


```
# Collect step only
scan wsf --collect
```

```
# Analyze step only for multiple tasks
scan wsf population green --analyze
```

Other available flags:

```
# Show available tasks
scan --list
```

```
# Re-run using the city's existing code (no resync from root)
scan --all -k --scan-id 2026-02-malta-malta
```

6.1.5 Step 4b: Multi-analysis

Some tasks have cross-task analysis scripts (e.g. flood exposure calculations that combine flood and WSF data). Run these after all individual tasks have completed:

```
scan --all --multianalysis
```

6.2 Rendering Maps and Charts

6.2.1 Step 5: Rendering Maps and Charts

After data collection and analysis, generate maps and charts via the `--render` flag:

```
# Static maps - applies styling from source/layers.yml, writes PNGs to 03-
render-output/maps/
scan --render maps --scan-id 2026-02-malta-malta
```

```
# Charts for a specific task - writes HTML to tasks/{name}/charts/index.html
scan --render charts elevation --scan-id 2026-02-malta-malta
```

Maps read spatial data from `02-process-output/spatial/`. Charts read CSVs from `02-process-output/tabular/`.

6.2.2 Step 6: Scan Calculations Reference Sheet

The `scan-calculations` reads `sections.yml` to determine section order, then assembles all per-task `charts/index.qmd` into a single combined HTML report:

```
scan --render scan-calculations --scan-id 2026-02-malta-malta
```

The compiled report is saved to `scan-calculations/scan-calculations.html`.

If `scan_calculations: True` is set in `menu.yml`, the `scan-calculations` folder is automatically copied to the city folder when running `scan --all`.

See [scan-calculations/README.md](#) for details.

Part III

Advanced Workflow

7 Running Multiple City Scans

City Scan supports batch execution across multiple cities using a single configuration file.

7.1 Overview

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Batch mode iterates over a list of city configurations, running each scan sequentially or in parallel depending on available compute resources.

7.2 Batch Configuration

```
# batch_config.yml
scan_type: batch
output_base_dir: "outputs/"
year: 2024

cities:
  - city: "Nairobi"
    country: "KE"
    aoi: "inputs/AOI/nairobi.geojson"

  - city: "Kampala"
    country: "UG"
    aoi: "inputs/AOI/kampala.geojson"

  - city: "Dar es Salaam"
    country: "TZ"
    aoi: "inputs/AOI/dar_es_salaam.geojson"
```

7.3 Running the Batch

```
python run.py --config batch_config.yml --batch
```

Sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Scans run sequentially by default. To enable parallel execution:

```
python run.py --config batch_config.yml --batch --workers 3
```


7.4 Progress Tracking




Figure 7.1: Batch scan progress terminal output

Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla pariatur. A progress summary is printed after all scans complete:

```
Batch complete: 3/3 cities succeeded
  Nairobi      (58m 12s)
  Kampala      (1h 03m 47s)
  Dar es Salaam (1h 11m 02s)
```

7.5 Output Structure

```
outputs/
  nairobi/
    maps/
    stats/
    report.html
  kampala/
  ...
  dar_es_salaam/
  ...
```

Table 7.1: Batch run options

Parameter	Default	Description
<code>--workers</code>	1	Number of parallel scans
<code>--retry</code>	0	Retry failed scans N times
<code>--skip-existing</code>	false	Skip cities with existing outputs

Warning

Running too many parallel workers may hit Google Earth Engine API rate limits. Start with `--workers 2` and scale up cautiously.

8 Running a Custom City Scan

A custom scan lets you select specific tasks, override default parameters, and plug in additional data sources beyond the standard suite.

8.1 When to Customize

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Consider a custom scan when:

- You only need a subset of data layers to save time
- You have proprietary or local data to incorporate
- You want non-default resolution or time periods

8.2 Selecting Tasks

```
# custom_config.yml
city: "Jakarta"
country: "ID"
aoi: "inputs/AOI/jakarta.geojson"
output_dir: "outputs/jakarta_custom"
scan_type: custom

tasks:
  - population
  - flood_risk
  - coastal_erosion
```

8.3 Overriding Default Parameters

```

task_overrides:
  population:
    year: 2020
    resolution: 100

  flood_risk:
    return_period: 50 # 50-year flood instead of 100-year
    source: "fathom_v3"

```

Sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Overrides are merged with the task defaults, so only specified fields are changed.

8.4 Adding a Custom Data Source

```

# tasks/custom/my_sensor_data.py
from cityscan.registry import register_task

@register_task
class MySensorDataTask:
    name = "sensor_data"
    inputs = ["aoi"]
    outputs = ["sensor_data.tif"]

    def run(self, config):
        aoi = self.load_aoi(config["aoi"])
        data = self.load_local_raster("data/sensor_grid.tif")
        clipped = self.clip(data, aoi)
        self.write_raster(clipped, "sensor_data.tif")

```

Then reference it in your config:

```

tasks:
  - population
  - sensor_data # your custom task

```

8.5 Custom Output Directory Layout




Figure 8.1: Custom scan output structure

Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla pariatur.

Table 8.1: Custom scan configuration options

Config Key	Type	Description
<code>tasks</code>	<code>list[str]</code>	Tasks to include
<code>task_overrides</code>	<code>dict</code>	Per-task parameter overrides
<code>extra_task_dirs</code>	<code>list[str]</code>	Paths to custom task modules

 Tip

Use `--dry-run` to preview which tasks will execute and in what order before committing to a full run.

Part IV

Tasks & Data Layers

9 Tasks & Structure Overview

City Scan is organized around modular **tasks** — each responsible for computing a single data layer. This chapter explains how tasks are structured and how they interact.

9.1 What Is a Task?

Lorem ipsum dolor sit amet, consectetur adipiscing elit. A task is a self-contained Python module that ingests raw data, performs spatial analysis, and writes output files. Each task is independently runnable and cacheable.

```
tasks/  
  population.py  
  landuse.py  
  roads.py  
  flood_risk.py  
  ...
```

9.2 Task Anatomy

9.2.1 Inputs, Processing, Outputs

```
# Typical task structure  
class PopulationTask:  
    name = "population"  
    inputs = ["aoi", "worldpop"]  
    outputs = ["population_density.tif", "pop_stats.csv"]  
  
    def run(self, config):  
        aoi = self.load_aoi(config["aoi"])  
        data = self.fetch_worldpop(aoi, config["year"])  
        result = self.clip_and_resample(data, aoi)  
        self.write_outputs(result, config["output_dir"])
```

9.2.2 Task Metadata

Each task declares metadata used by the orchestrator:

Table 9.1: Task metadata fields

Field	Type	Description
<code>name</code>	<code>str</code>	Unique task identifier
<code>inputs</code>	<code>list[str]</code>	Required input data sources
<code>outputs</code>	<code>list[str]</code>	Files this task produces
<code>depends_on</code>	<code>list[str]</code>	Tasks that must run first

9.3 Task Categories




Figure 9.1: Task category overview

Sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Tasks fall into four broad categories:

- **Population** — WorldPop-based density and count estimates
- **Environment** — NDVI, NDWI, land use, and urban heat
- **Infrastructure** — roads, buildings, and accessibility
- **Risk** — flood, coastal erosion, and seismic exposure

9.4 Execution Model

Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla pariatur. The orchestrator resolves task dependencies and runs tasks in topological order, parallelizing independent tasks where possible.

```
# Run all tasks
python run.py --config config.yml

# Run a specific task
python run.py --config config.yml --task population
```

Note

See [Data Layer References](#) for a complete list of tasks and their data sources.

10 Data Layer References

Complete reference for all data layers available in City Scan, including source datasets, resolution, and output descriptions.

10.1 Population

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Population layers are derived from WorldPop and LandScan datasets.

Table 10.1: Population data layers

Task ID	Description	Source	Resolution
population	Total population count per grid cell	WorldPop	100m
population_density	People per km ²	WorldPop	100m
pop_growth	Annual population growth rate	WorldPop (multi-year)	100m

10.2 Land Use & Environment

```
# Example: computing NDVI
def compute_ndvi(red_band, nir_band):
    return (nir_band - red_band) / (nir_band + red_band)
```

Table 10.2: Land use and environment data layers

Task ID	Description	Source	Resolution
landuse	Land use / land cover classification	Dynamic World (GEE)	10m

Task ID	Description	Source	Resolution
ndvi	Normalized Difference Vegetation Index	Sentinel-2	10m
ndwi	Normalized Difference Water Index	Sentinel-2	10m
urban_heat	Land surface temperature	Landsat 8/9	30m

10.3 Infrastructure

Sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Infrastructure layers use OpenStreetMap as the primary source.

Table 10.3: Infrastructure data layers

Task ID	Description	Source	Resolution
roads	Road network density	OpenStreetMap	Vector
buildings	Building footprints & density	OpenStreetMap	Vector
accessibility	Travel time to services	OpenStreetMap + OTP	100m

10.4 Risk & Hazard




Figure 10.1: Risk layer visualization

Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla pariatur.

Table 10.4: Risk and hazard data layers

Task ID	Description	Source	Resolution
flood_risk	100-year flood extent	Fathom / MERIT Hydro	90m
coastal_erosion	Shoreline change rate	CoastalDEM + Sentinel-1	30m
seismic	Peak ground acceleration	GSHAP	~10km

10.5 Adding a Custom Data Layer

```
# Register a new task
from cityscan.registry import register_task

@register_task
class MyCustomTask:
    name = "my_custom_layer"
    inputs = ["aoi"]
    outputs = ["my_custom_layer.tif"]

    def run(self, config):
        # implementation here
        pass
```

Tip

Custom tasks can be placed in the `tasks/custom/` directory and will be auto-discovered at runtime.

Part V

Understanding the Repo

11 Repository Structure

An orientation to the City Scan codebase — what lives where and why.

11.1 Top-level Layout

```
city-scan/  
  cityscan/          # core Python package  
  tasks/             # task modules  
  inputs/            # user-supplied inputs (AOI, local data)  
  outputs/           # generated scan outputs (git-ignored)  
  scripts/           # utility scripts  
  tests/             # test suite  
  docs/              # this documentation  
  pyproject.toml     # package metadata & dependencies  
  run.py             # CLI entry point  
  orchestrator.sh    # shell-based orchestrator (legacy)
```

11.2 Core Package: cityscan/

Lorem ipsum dolor sit amet, consectetur adipiscing elit.

```
cityscan/  
  __init__.py  
  config.py          # config loading and validation  
  registry.py        # task registration and discovery  
  runner.py          # task execution and dependency resolution  
  gee.py             # Google Earth Engine helpers  
  io.py              # file I/O utilities  
  report.py          # HTML report generation
```

11.2.1 Key Modules

Table 11.1: Core module responsibilities

Module	Responsibility
<code>config.py</code>	Load and validate <code>config.yml</code>
<code>registry.py</code>	Discover and register task classes
<code>runner.py</code>	Resolve dependencies, schedule, and run tasks
<code>gee.py</code>	Authenticate and interact with GEE

11.3 Tasks Directory: `tasks/`

```
tasks/  
  population.py  
  landuse.py  
  roads.py  
  flood_risk.py  
  coastal_erosion.py  
  custom/          # user-defined custom tasks
```

Sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Each file in `tasks/` is a self-contained module that is auto-discovered by the registry at startup.

11.4 Inputs & Outputs

```
inputs/  
  AOI/              # place your GeoJSON boundary files here  
  
outputs/            # created automatically; git-ignored  
  <city_name>/  
    maps/  
    stats/  
    report.html
```




Figure 11.1: Repository structure diagram

11.5 Tests

```
pytest tests/          # run the full test suite
pytest tests/unit/      # unit tests only
pytest tests/integration/ # integration tests (requires GEE)
```

Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla pariatur.

Note

For how tasks connect to each other, see [Task Dependency](#).

12 Task Dependency

City Scan tasks form a directed acyclic graph (DAG). Understanding dependencies helps you predict execution order and debug failures.

12.1 Dependency Graph




Figure 12.1: Task dependency DAG

Lorem ipsum dolor sit amet, consectetur adipiscing elit. The orchestrator builds this graph at startup by reading each task's `depends_on` declaration.

12.2 How Dependencies Are Declared

```
class AccessibilityTask:
    name = "accessibility"
    depends_on = ["roads", "population"] # must run after these

    def run(self, config):
        roads = self.load_output("roads")
        pop   = self.load_output("population")
        # ... compute accessibility
```

12.3 Execution Order Example

For the default task suite, the orchestrator produces the following topological order:

- | | |
|------------------|---------------------------------|
| 1. aoi_prep | |
| 2. population | (depends on: aoi_prep) |
| 3. landuse | (depends on: aoi_prep) |
| 4. roads | (depends on: aoi_prep) |
| 5. ndvi | (depends on: aoi_prep) |
| 6. flood_risk | (depends on: aoi_prep) |
| 7. accessibility | (depends on: roads, population) |
| 8. urban_heat | (depends on: landuse, ndvi) |
| 9. report | (depends on: all above) |

Sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Tasks at the same level can be parallelized.

12.4 Dependency Table

Table 12.1: Task dependency matrix

Task	Depends On
population	aoi_prep
roads	aoi_prep
landuse	aoi_prep
flood_risk	aoi_prep
accessibility	roads, population
urban_heat	landuse, ndvi
report	all tasks

12.5 Handling Failures

```
# Resume a scan after a failed task
python run.py --config config.yml --resume
```

Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla pariatur. With `--resume`, the runner skips tasks whose output files already exist and only re-runs tasks downstream of the failure point.

12.6 Visualizing the DAG

```
from cityscan.runner import Runner

runner = Runner.from_config("config.yml")
runner.visualize_dag("dag.png") # saves a PNG of the dependency graph
```

Tip

Use `python run.py --dry-run --config config.yml` to print the resolved execution order without running any tasks.

Part VI

Case Studies & Galleries

13 Case Study: Standard Scan — Rabat, Morocco

This case study walks through a complete standard City Scan for Rabat, Morocco, demonstrating the end-to-end workflow and key findings.

13.1 City Context

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Rabat is the capital of Morocco, with a metropolitan population of approximately 1.9 million. The city faces urban growth pressures, coastal flood risk, and heat island effects.

Table 13.1: Rabat scan metadata

Attribute	Value
Country	Morocco
Population	~1.9 million
Area (AOI)	~117 km ²
Scan date	March 2024
Tasks run	14

13.2 AOI Definition




Figure 13.1: Rabat area of interest

Sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. The AOI was defined using the official administrative boundary of the Rabat-Salé-Kénitra region, clipped to the primary urban core.

```
# AOI file used
inputs/AOI/rabat_urban_core.geojson
```

13.3 Running the Scan

```
python run.py --config configs/rabat.yml
```

```
# configs/rabat.yml
city: "Rabat"
country: "MA"
aoi: "inputs/AOI/rabat_urban_core.geojson"
output_dir: "outputs/rabat"
year: 2024
scan_type: standard
```

13.4 Key Findings

13.4.1 Population Distribution

Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla pariatur. Population is concentrated in the Agdal and Hassan neighborhoods, with density exceeding 15,000 people/km².




Figure 13.2: Rabat population density map

13.4.2 Flood Risk

Excepteur sint occaecat cupidatat non proident, sunt in culpa qui officia deserunt mollit anim id est laborum. Approximately 8% of the built environment falls within the 100-year flood extent, concentrated along the Bouregreg River corridor.

13.4.3 Land Use

```
# Summary statistics from outputs/rabat/stats/landuse_stats.csv
landuse_summary = {
  "Urban/Built-up": 62.3,
  "Vegetation": 18.7,
  "Bare soil": 11.4,
  "Water": 7.6,
}
```

13.5 Outputs

All scan outputs are available at `outputs/rabat/`. The interactive report can be viewed at `outputs/rabat/report.html`.

Note

For a multi-city batch scan case study, see [Case Study: Multiple Scans — Philippines](#).

14 Case Study: Multiple Scans — Philippines

This case study demonstrates running City Scan across multiple Philippine cities simultaneously using batch mode.

14.1 Project Context

Lorem ipsum dolor sit amet, consectetur adipiscing elit. The World Bank Philippines office requested City Scans for five secondary cities to support climate resilience planning. Batch mode was used to process all cities in a single run.

14.2 Cities Covered

Table 14.1: Philippine cities included in the batch scan

City	Region	Population	AOI Area
Cebu	Central Visayas	964,169	315 km ²
Davao	Davao Region	1,776,949	2,444 km ²
Iloilo	Western Visayas	457,626	78 km ²
Cagayan de Oro	Northern Mindanao	728,402	488 km ²
Zamboanga	Zamboanga Peninsula	977,234	1,483 km ²

14.3 Batch Configuration

```
# configs/philippines_batch.yml
scan_type: batch
output_base_dir: "outputs/philippines"
year: 2023

cities:
  - city: "Cebu"
```


```
country: "PH"
aoi: "inputs/AOI/cebu.geojson"
- city: "Davao"
  country: "PH"
  aoi: "inputs/AOI/davao.geojson"
- city: "Iloilo"
  country: "PH"
  aoi: "inputs/AOI/iloilo.geojson"
- city: "Cagayan de Oro"
  country: "PH"
  aoi: "inputs/AOI/cdo.geojson"
- city: "Zamboanga"
  country: "PH"
  aoi: "inputs/AOI/zamboanga.geojson"
```

14.4 Running the Batch

```
python run.py --config configs/philippines_batch.yml --batch --workers 2
```

Sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Two parallel workers were used to balance GEE API rate limits with execution speed. Total batch runtime was approximately 6 hours.

14.5 Key Findings Across Cities



68
Figure 14.1: Flood risk comparison across Philippine cities

Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla pariatur.

14.5.1 Coastal Flood Risk

All five cities have significant coastal exposure. Zamboanga showed the highest percentage of built-up area within the 100-year flood extent at 23%.

14.5.2 Urban Heat Islands

```
# Comparative heat island intensity (°C above rural baseline)
heat_island = {
    "Cebu": 3.2,
    "Davao": 2.8,
    "Iloilo": 2.1,
    "Cagayan de Oro": 2.6,
    "Zamboanga": 3.5,
}
```

14.6 Lessons Learned

Excepteur sint occaecat cupidatat non proident, sunt in culpa qui officia deserunt mollit anim id est laborum. Key takeaways from this multi-city deployment:

- Pre-validate all AOI files before starting the batch to avoid mid-run failures.
- Use `--workers 2` as the safe default for GEE-heavy task suites.
- Monitor GEE quota usage via the [GEE Console](#) during long runs.

i Note

Configuration files for all five cities are available in `configs/examples/philippines/`.

Part VII

Collaborating

15 Git Guide

A practical Git reference for City Scan contributors, covering branching strategy, commit conventions, and common workflows.

15.1 Branching Strategy

Lorem ipsum dolor sit amet, consectetur adipiscing elit. City Scan uses a trunk-based development model with short-lived feature branches.

main	# stable, always deployable
feature/<name>	# new features or improvements
fix/<name>	# bug fixes
docs/<name>	# documentation-only changes

15.2 Cloning the Repository

```
git clone https://github.com/cityresilience/city-scan.git
cd city-scan
git checkout -b feature/my-new-feature
```

15.3 Commit Message Conventions

Sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Follow the [Conventional Commits](#) format:

<type>(<scope>): <short description>

[optional body]

[optional footer]

Table 15.1: Conventional commit types

Type	When to Use
feat	New feature or data layer
fix	Bug fix
docs	Documentation changes only
refactor	Code restructuring, no behavior change
test	Adding or updating tests
chore	Maintenance (deps, CI, config)

15.3.1 Examples

```
git commit -m "feat(tasks): add seismic hazard layer"
git commit -m "fix(gee): handle expired credentials gracefully"
git commit -m "docs(setup): clarify GEE authentication steps"
```

15.4 Pull Request Workflow

```
# 1. Create a branch
git checkout -b fix/flood-risk-clipping

# 2. Make changes and commit
git add tasks/flood_risk.py
git commit -m "fix(tasks): correct AOI clipping in flood risk task"

# 3. Push and open a PR
git push -u origin fix/flood-risk-clipping
gh pr create --fill
```





Figure 15.1: Pull request checklist on GitHub

15.5 Keeping Your Branch Up to Date

```
git fetch origin  
git rebase origin/main
```

Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla pariatur.

Warning

Avoid `git merge main` into feature branches — use rebase to keep a clean linear history.

Note

For opening issues, see [Reporting Issues](#). For contributing code, see [Contributing](#).

16 Reporting Issues

How to report bugs, request features, and ask questions about City Scan.

16.1 Where to Report

Lorem ipsum dolor sit amet, consectetur adipiscing elit. All issues are tracked on the GitHub repository:

GitHub Issues: <https://github.com/cityresilience/city-scan/issues>

16.2 Before You Open an Issue

Sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Before filing a new issue, please:

1. **Search existing issues** — your problem may already be reported or fixed.
2. **Check the documentation** — especially [Setting Up](#) for environment problems.
3. **Reproduce the issue** — confirm it happens on a clean install.

16.3 Bug Reports

Use the **Bug Report** template when something is broken. Include:

```
## Description
A clear description of what went wrong.

## Steps to Reproduce
1. Run `python run.py --config config.yml`
2. Observe error in `outputs/city/scan.log`

## Expected Behavior
The scan should complete successfully.
```

```
## Actual Behavior
Task `flood_risk` fails with `KeyError: 'return_period'`.

## Environment
- OS: macOS 14.4
- Python: 3.11.6
- City Scan version: 0.9.2
```

16.4 Feature Requests

Use the **Feature Request** template to propose new data layers, CLI options, or workflow improvements.




Figure 16.1: GitHub issue tracker showing a mix of bug reports and feature requests

16.5 Sharing Log Files

```
# Find your scan log
cat outputs/<city>/scan.log

# Or attach the whole log to the issue
```

Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla pariatur. Redact any sensitive paths or credentials before sharing logs.

16.6 Issue Labels

Table 16.1: GitHub issue labels

Label	Meaning
bug	Confirmed defect
enhancement	New feature or improvement
documentation	Docs gap or correction
good first issue	Suitable for new contributors
help wanted	Maintainers welcome external PRs

Tip

For quick questions, open a **Discussion** instead of an issue — discussions are better for open-ended conversations.

17 Contributing

We welcome contributions to City Scan — from new data layers to documentation improvements.

17.1 Types of Contributions

Lorem ipsum dolor sit amet, consectetur adipiscing elit:

- **New tasks** — add a data layer not currently in the suite
- **Bug fixes** — resolve issues in existing tasks or infrastructure
- **Documentation** — improve this cookbook
- **Tests** — expand test coverage
- **Performance** — optimize slow tasks or reduce GEE API calls

17.2 Development Setup

```
git clone https://github.com/cityresilience/city-scan.git
cd city-scan
python -m venv .venv && source .venv/bin/activate
pip install -e ".[dev]"
pre-commit install
```

Sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. The `[dev]` extras install linting, formatting, and test tools.

17.3 Code Style

City Scan uses [Ruff](#) for linting and formatting.

```
ruff check .          # lint
ruff format .         # format
```

Pre-commit hooks enforce these checks on every commit. To run manually:

```
pre-commit run --all-files
```

17.4 Writing a New Task

```
# tasks/my_new_layer.py
from cityscan.registry import register_task
from cityscan.base import BaseTask

@register_task
class MyNewLayerTask(BaseTask):
    name = "my_new_layer"
    description = "Computes lorem ipsum data layer."
    inputs = ["aoi"]
    outputs = ["my_new_layer.tif"]
    depends_on = []

    def run(self, config: dict) -> None:
        aoi = self.load_aoi(config["aoi"])
        result = self._compute(aoi)
        self.write_raster(result, "my_new_layer.tif")

    def _compute(self, aoi):
        # implementation here
        pass
```

Add a corresponding test in `tests/unit/test_my_new_layer.py`.

17.5 Pull Request Checklist




Figure 17.1: Pull request checklist

Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla pariatur.

- ☐ Tests pass: `pytest tests/`
- ☐ Linting passes: `ruff check .`
- ☐ New task is registered and documented in [Data Layer References](#)
- ☐ PR title follows Conventional Commits format
- ☐ No secrets or credentials committed

17.6 Review Process

Table 17.1: Pull request review stages

Stage	Who	Typical Duration
Automated checks (CI)	GitHub Actions	< 5 min
Code review	Core maintainer	1–3 days
Merge	Core maintainer	After approval

Note

See [Git Guide](#) for branching and commit conventions.

18 Sharing the Guide

How to share, publish, and distribute the City Scan Cookbook with your team and stakeholders.

18.1 Rendered Formats

Lorem ipsum dolor sit amet, consectetur adipiscing elit. The cookbook is built with [Quarto](#) and can be rendered to HTML, PDF, or both.

```
# Render HTML (default)
quarto render

# Render PDF
quarto render --to pdf

# Render both
quarto render --to html,pdf
```

Output is written to `_book/`.

18.2 Publishing to GitHub Pages

```
quarto publish gh-pages
```

Sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. This command builds the book and pushes the rendered HTML to the `gh-pages` branch. The site is then accessible at:

<https://cityresilience.github.io/city-scan/>

18.3 Publishing to Quarto Pub

```
quarto publish quarto-pub
```

Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla pariatur. You will be prompted to sign in to your Quarto Pub account on first use.

18.4 Sharing the PDF




Figure 18.1: PDF export of the City Scan Cookbook

After rendering to PDF:

```
open _book/City-Scan-Cook-Book.pdf # macOS
```

Table 18.1: Guide distribution options

Distribution Method	Audience	Notes
GitHub Pages (HTML)	Technical users	Free, auto-updates on push
Quarto Pub (HTML)	General stakeholders	Free, public URL
PDF via email	Partners / clients	Snapshot in time
PDF on SharePoint	Internal World Bank	Behind org auth

18.5 Embedding in Other Sites

```
<!-- Embed a specific chapter as an iframe -->
<iframe
  src="https://cityresilience.github.io/city-scan/setting-up.html"
  width="100%"
  height="600px"
  frameborder="0">
</iframe>
```

18.6 Keeping the Guide Up to Date

```
# Set up GitHub Actions to auto-publish on every push to main
# .github/workflows/publish.yml
```

```
on:
  push:
    branches: [main]

jobs:
  publish:
    runs-on: ubuntu-latest
    steps:
      - uses: actions/checkout@v4
```

```
- uses: quarto-dev/quarto-actions/publish@v2
  with:
    target: gh-pages
```

 Tip

For feedback on the guide itself, open a **documentation** issue on GitHub — see [Reporting Issues](#).

References