



Jean-Christophe Benoit
Rapport de projet Phase 2
LOG430 — Architecture logicielle
28 octobre 2025, Montréal
École de technologie supérieure

Run book

Prerequisites

To run this project locally, you need the following tools installed:

- [Go 1.21+](#)
- [Docker](#) & [Docker Compose](#)

Installation

1. Clone the repository

```
git clone https://github.com/cjayneb/log430-project.git
cd log430-project
```

2. Configure environment variables

Change the values in the `backend/services/{service-name}/config.go` files if you want to override defaults. Example:

```
Port string `env:"APP_PORT" envDefault:"8181"`
DBUrl string `env:"DATABASE_URL"
envDefault:"user:pass@tcp(127.0.0.1:3306)/brokerx"`
```

The variables in `config.go` are used when running the app locally. The environment variables set in the `docker-compose.yml` will override the values set in `backend/services/{service-name}/config.go` when running the project with Docker Compose.

Running the project

Run locally (without Docker)

From on of the `backend/services/{service-name}` directories:

```
go run .
```

This will start the microservice's API on `http://127.0.0.1:8080`.

- Health endpoint: `http://127.0.0.1:8080/health` (GET) (each microservice has one)

More examples

- Login endpoint: `http://127.0.0.1:8080/api/user/auth/login` (POST)
- Home page endpoint: `http://127.0.0.1:8080/` (GET)
- Orders page endpoint: `http://127.0.0.1:8080/api/order` (GET)

You must have a MySQL instance and a Redis instance running on your machine for all uses cases to work

Run with Docker Compose

From the project root:

```
docker compose down -v # To remove existing containers and their volumes
docker compose up --build -d
```

This starts:

- The Go backend microservices on <http://localhost/api>
- A MySQL database (`brokerx_db`) on port `3306`
- Nginx API Gateway
- Redis DB

Running tests

Important : Before running all tests, you must have the test database up, because some of the tests are integration tests needing a real database.

Run the following command to start the test database:

```
#From the root of the project
docker compose -f docker-compose.test.yml up -d
```

Running all tests (with coverage report)

Inside the `backend/services/{service-name}` folder of each micro-service:

```
go test ./... -coverprofile=coverage
```

Generate HTML coverage report

```
go tool cover -html=coverage
```

Deployment

At this stage, the application is deployed locally or remotely using Docker Compose. A production-ready deployment would likely use Kubernetes or cloud-based services, but that is outside the current scope.

Deploying locally

To deploy locally, you just have to run the following commands

```
docker compose down -v # Ensure Docker is clean with no previous
deployment
docker compose up --build -d # Build the Docker image and run docker
compose in detached mode
```

Deploying remotely

The GitHub Actions Workflow should take care of deploying the application to the ETS Virtual Machine self hosted runner automatically on every push. See [.github/workflows/ci_cd.yml](#)

The current deployment pipeline is broken because of issues with the storage on the ETS VM.

To access the remote deployment, you must be connected to the ETS Cisco Secure Client via accesvpn.etsmtl.ca

User Guide

This document show syou how to use BrokerX once it has been deployed either locally or remotely.

Access BrokerX

To access BrokerX, use your web browser and navigate to :

- Locally : <http://localhost/>
- Remotely : <http://10.194.32.206/>

Registering as a new user

Access the following link in your browser : <http://localhost/register.html>

Register

Enter you first and last name as well as an email and a password and submit :

Register

🌐 localhost

Registration successful. You can now login.

OK

Logging in

Enter the email and password and click on *Login* to access the account of a seller :

- Email : seller@email.com
- Password : password



 http://localhost

Login

Login

Placing an order

Logging in will bring you to this *Orders* page:

BrokerX - Orders

 [Wallet](#) | [Logout](#)

Place Order

Stock Symbol:

Quantity:



Order Action:

Buy 

Order Type:

Market 

Timing:

DAY ▾

Price per stock:

0.00 ▴ ▾

Submit Order

Your Orders

No orders yet.

Then you can fill the form to sell AAPL stocks at market price and click *Submit Order* :

Place Order

Stock Symbol:

Quantity:



Order Action:

Order Type:

Timing:

Price per stock:



Then you should see your order appear at the top of the page and this confirmation message at the bottom of the form.

Error messages will also appear at the bottom of the form.

Submit Order

Order placed successfully.

Your Orders

ID	Symbol	Quantity	Remaining	Action	Type	Timing	Unit Price	Status	Created At
1	AAPL	10	10	sell	market	day	0	open	2025-10-29, 12:06:03 a.m.

Next, if you refresh the page, you should see that your order status, and remaining quantity have been updated if a matching order has been found :

Submit Order

Your Orders

ID	Symbol	Quantity	Remaining	Action	Type	Timing	Unit Price	Status	Created At
1	AAPL	10	4	sell	market	day	0	partially_filled	2025-10-29, 12:06:03 a.m.

Other users (email and buyer@email.com) have different base positions, orders and wallet balances, which make for different outputs in results.

Adding funds to your wallet

After logging in, it is possible to add funds to your wallet by clicking on *Wallet*:

BrokerX - Orders

 [Wallet](#) | [Logout](#)

Then entering the amount you want to deposit and submitting :

Wallet

Balance: \$300

  Add Funds

The balance automatically updates itself and you will be able to make bigger purchases of stocks :

Wallet

Balance: \$700

  Add Funds

Arc42

1. Introduction and Goals

1.1 Requirements Overview

The BrokerX project is an online brokerage platform targeting individual investors, developed in response to the rapidly evolving financial services sector. It is made to allow retail investors to trade stocks securely and rapidly from the comfort of their home.

The system **must** support the following core functionalities:

- **Authentication** : Secure login with session cookies.
 - Justification: Secure access to the system is mandatory, especially considering the sensitivity of the data residing on BrokerX.
- **Order placement** : Allow users to place market or limit orders on various stocks.
 - Justification: This is a core business function. Without order placement, Brokerx has no reason to exist.
- **Matching & Execution** : Ensure matching of buy and sell orders using an internal matching engine, generating an execution report.

- **Justification:** This is another feature that is too important to be ignored, placing an order to buy stocks is a must, but it is not useful if the order cannot be matched with a corresponding selling order.

The system **should** support the following functionalities:

- **Market data subscription** : Realtime market data updates (top-of-book, trades, OHLC).
 - **Justification:** This feature should definitely be a part of BrokerX, so that users do not have to use another platform to consult stock prices, but it is not a necessity to have a brokerage system that works.
- **Registration** : Account creation and identity verification via an OTP sent by email.
 - **Justification:** For now, user accounts can be manually added to the system and tests of the whole system can still be done without a registration page.
- **Wallet funding** : Allow users to add money to their BrokerX wallet in order to buy stocks and get compensated for selling stocks.
 - **Justification:** For now, wallets can be also be manually created and given any amount as a test balance, since the system does not yet interact with the real stock market.
- **Order modification/cancellation** : Allow users to modify or cancel order that have been placed.
 - **Justification:** This is not a necessity as it does not pose any real risk to lack the ability to modify or cancel orders during this phase. However, a brokerage platform should definitely have this feature in order to rectify input errors.

The system **could** support the following functionalities:

- **Notifications** : Send email notifications to the user when an order is confirmed.
 - **Justification:** This is a nice-to-have and in no way necessary to a working brokerage platform.

These functions cover the core trading workflow and will be expanded in later iterations.

[LOG430 - 2025.3 - Projet - Cahier de Charge.pdf](#)

1.2 Quality Goals

Priority	Quality goal	Scenario
1	Latency	≤ 250 ms to get an acknowledgement after placing an order.
2	Throughput	≥ 800 orders successfully placed per second.
3	Availability	The system must be available at least 95.5% of the time.

These goals are to be met during the second iteration (micro-services architecture) of BrokerX.

Notes / roadmap: The project specification defines phased targets (monolith → microservices → event-driven) where the latency/throughput and availability targets tighten in later phases. Observability (logs + metrics) is required from phase 2 and distributed tracing from phase 3. These constraints drive the choice of architecture and incremental migration plan

1.3 Stakeholders

Contents.

Role/Name	Contact	Expectations
Clients (web users)	N/A	Fast, correct order handling; clear execution confirmations; accurate portfolio balances.
Developers of BrokerX	Jean-Christophe Benoit	Clear modular code structure (domain vs infra), testability, reproducible CI/CD, containerized deployment.
Back-Office Operations	N/A	Accurate execution records, trustworthy reports for accounting.
Compliance /Risk Employees	N/A	Control over pre-trade checks, post-trade surveillance, immutable logs, idempotency guarantees.
External Market Data Provider	N/A	Well-defined streaming API (subscribe/unsubscribe); order routing contracts for simulated exchanges.


2. Architecture Constraints

Constraint	Description
Technology	C#, Go, Rus or C++ permitted. Python or JavaScript/TypeScript are strongly discouraged for the backend part of the system.
Performance	The system must meet latency, throughput and availability targets.
Deployment	The system prototype must be containerized and deployed on a public or semi publicly accessible platform via an automatic CI/CD pipeline. Multiple artifacts must be deployed during phase 2.

3. System Scope and Context

Business Context

BrokerX - Bounded Contexts



Technical Context

\newpage


4. Solution Strategy


Problem	Solution
Maintainability and evolution	Internally, the system code is organized in a modular fashion using an architecture similar to hexagonal. This isolates the domain logic from infrastructure adapters. This allows the monolithic prototype to evolve somewhat easily in later phases.

Problem	Solution
Data consistency and integrity	A MySQL database is used to store all data as the one source of truth. Entities and data queries and commands are managed with repositories which abstract the database specific logic into interfaces. Transactions are used in critical flows like order executions to maintain consistency
Delivering data to client	The Go server supports multiple http endpoints for server rendered html templates and data retrieval.
Latency and throughput	Using the Go language because it is well-suited for high concurrency, low latency environments. Goroutines are easily implementable for asynchronous processing, making order acknowledgement faster.
Error Handling & Observability	The Go programming language is made for functions to return multiple return values, making it very easy to propagate errors from any layers back to the client. It also comes with a an integrated logging library, ensuring the system's behaviors and faults are observable at any point.


5. Building Block View


BrokerX - C4 Container Diagram






BrokerX - Domain Model





6. Runtime View

General Use Case Diagram



The use cases colored in green are the ones that are currently implemented in the system

UC-02 Login

Goal:

Allow a registered user to securely authenticate into the BrokerX system.

Actors:

- Primary: Client (user)
- Supporting: MySQL DB

Preconditions:

- The user is already registered in the system.
- Credentials (email, password hash) are stored in the database.

Main Flow:

1. The Client submits email and password to the system.
2. The system receives the credentials and validates them.
3. The system returns the home page, along with a signed session cookie to the client

Postconditions:


- User is authenticated and can call secured endpoints with the cookie.

Exceptions / Alternatives:

E2. Database unavailable → The system returns an error 500 Internal Server Error.

A3. Invalid credentials → The system returns an error 401 Unauthorized.

A3. Third failed authentication attempt → The system returns an error 401 Unauthorized and locks the account for 30 minutes.



UC-05 Place order

Goal:

Allow a user to place a buy or sell order on a stock.

Actors:

- Primary: Client (user)

- Supporting: Market Data Provider

Preconditions:

- The user is logged in.
- The Market Data Provider is up and running.
- The client is on the Orders page

Main Flow:

1. The Client completes the form to place an order containing the symbol, quantity, action, type, timing and unit price.
2. The system receives the order data and validates that the inputs are not empty.
3. The system starts verification the compliance of the order.
4. The system requests instrument and price data from the Market Data Provider.
5. The Market Data Provider responds with instrument tick size and price band.
6. The system finishes verifying the compliance of the order.
7. The system creates an order.
8. The system submits the order to the internal matching engine.
9. The system send an acknowledgement to the client that the order has been placed.
10. The client receives the acknowledgement.

Postconditions:

- The order is stored in the database with open status.
- The client can see the new placed order with all its information.

Exceptions / Alternatives:

- E3.** The order has an invalid quantity → The system propagates the error back to the client. The order is not created.
- E5.** The Market Data Provider does not respond → The system propagates the error back to the client. The order is not created.
- E5.** The user does not have enough funds → The system propagates the error back to the client. The order is not created.
- E5.** The user does not have enough stocks → The system propagates the error back to the client. The order is not created.
- E5.** The order tick size or price band does not match the instrument's required tick size or price band → The system propagates the error back to the client. The order is not created.



Actors:

- Preconditions:


- Main Flow:

- Postconditions:

- Exceptions / Alternatives:


A2. The system finds no match for the order → The order stays in the database. The order is not updated.
No execution records are saved.

- E5.** There is a database error when updating the order(s) → The system logs the error. The order stays in the database. The order is not updated. The execution records are not saved.
- E6.** There is a database error when saving the execution records → The system logs the error. The order stays in the database. The order is not updated. The execution records are not saved.



\newpage

7. Deployment View



\newpage

8. Cross-cutting Concepts

- Architecture semi-hexagonale
- Server-side HTML rendring
- Interfaces
- MySQL relational database
- Repository pattern
- Transaction pattern

\newpage

9. Design Decisions

ADR-01: Hexagonal architecture

Context

BrokerX must be evolvable across phases: from monolithic prototype to micro-services and eventually event-driven. A tightly coupled MVC design would limit flexibility. We need an architecture that clearly

separates domain logic from infrastructure to make refactoring manageable.

Decision

Adopt a hexagonal style architecture (ports and adapters):

- **Core domain layer:** entities, matching engine, business rules
- **Ports:** interfaces for any internal/external service, data access objects
- **Adapters:** implementations of the interfaces (REST API handlers, SQL repositories, mock data provider)

Status

Accepted

Consequences

- Domain logic is independent of delivery and persistence mechanisms
 - Easier to swap infrastructure (database, APIs) without touching core logic
 - Simplifies testing (domain logic can be tested in isolation)
 - Slightly higher complexity (more abstractions, interfaces, files)
 - May be over engineering for phase 1 but will most likely pay off in later phases
-

ADR-02: Persistence with MySQL and Repository/Transaction Manager Pattern

Context

BrokerX must maintain strong consistency for orders, executions and balances. Persistent storage was required by the project and we want to avoid spreading raw SQL queries across the codebase.

Decision

Use MySQL relational database as the system of record, accessed through repository interfaces in the ports layers. Repositories abstract database-specific logic into adapters. Transactions are applied for critical operations (order matching).

Status

Accepted

Consequences

- Centralized persistence logic, easier to maintain
 - Enforces data integrity using SQL constraints and transactions
 - Repository interfaces decouple domain logic from data access details, allowing easier replacement of persistent storage in the future.
 - Less flexibility in schema evolution if requirements change rapidly
-

ADR-03: Use of Go as Implementation Language

Context

The backend must support low latency and high throughput for order placement and matching. It must also be portable across environments (developer laptops, CI/CD pipelines, VMs). The following languages were considered :

- Java/C#
- Python/Node.js
- Rust/C

Decision

Implement BrokerX backend API server in Go (Golang)

Status

Accepted

Consequences

- Very fast compilation and deployment cycle.
- Excellent concurrency support for handling many requests/orders.
- Small memory footprint, portable binaries.
- Clean error handling via multiple return values.
- Newer language, meaning lack of libraries in certain domains

\newpage

10. Quality Requirements

Latency

Throughput

Data Integrity

Security

Testability

Interoperability

\newpage

11. Risks and Technical Debts

- Writing a lot of code in a short amount of time can lead to lack of unit testing and therefore, quality degradation.
- Lack of code review due to the project being individually developped.
- There is a risk of long refactoring time between phases depending on the evolvability of the system.

\newpage

12. Glossary

Term	Definition
ADR	Architecture Decision Record: a short document that captures an important architectural choice, its context, and consequences.
Broker	An intermediary that executes buy/sell orders on behalf of investors. BrokerX acts as an online broker for retail clients.
CI	Continuous Integration: automation of integrating new code into the main branch with quality checks and automated tests.
CD	Continuous Deployment: automation of delivering tested code to production environments.
Execution	The successful match of a buy and sell order, resulting in a trade and an execution report.
Execution Report	A message generated by the matching engine that details the outcome of an order execution (price, quantity, time).
Hexagonal Architecture	Also called Ports and Adapters: an architectural style that separates the domain logic (core) from external systems (DB, UI, APIs).
Latency	The time it takes for a user action (e.g., placing an order) to receive an acknowledgement from the system.
Limit Order	An order to buy or sell a stock at a specified price or better.
Market Data Provider	External or simulated service that supplies price and instrument data to BrokerX.
Market Order	An order to buy or sell immediately at the current market price.
Matching Engine	The core system component that pairs buy and sell orders and generates execution records.
Monolith	An application built as a single deployable unit. BrokerX phase 1 is implemented as a Go monolith.
MySQL	Relational database used by BrokerX to persist orders, executions, users, and balances.
Order	A request placed by a user to buy or sell a stock (can be market or limit, buy or sell, ioc or day).

Term	Definition
IOC	Immediate Or Cancel. Refers to the timing of an order that must be immediately fully filled, if not, it must be cancelled
DAY	Refers to the timing of an order that is open until the end of the trading day.
Order Book	The collection of all open buy and sell orders for a given instrument, managed by the matching engine.
Port	Interface in hexagonal architecture that represents an entry/exit point for the core domain logic (e.g., repository interface, service interface).
Adapter	Implementation of a port, connecting the domain logic to infrastructure (e.g., SQL repository, HTTP services).
Pre-trade Checks	Compliance rules applied before accepting an order (e.g., tick size validation, price bands, sufficient balance/holdings).
Session Cookie	Small piece of data stored on the client after login, used to authenticate subsequent requests.
Tick Size	The minimum price movement allowed for a given instrument.
Throughput	Number of orders the system can successfully handle per second.
Transaction	A group of one or more database operations executed as a single unit of work, ensuring atomicity and consistency.
Wallet	Virtual balance associated with a user account, used to fund purchases and receive proceeds from sales.