

REST Web Services

Week 11 Lecture

**COMMONWEALTH OF
Copyright Regulations 1969
WARNING**

This material has been reproduced and communicated to you by or on behalf of the University of Sydney pursuant to Part VB of the Copyright Act 1968 (**the Act**).

The material in this communication may be subject to copyright under the Act. Any further reproduction or communication of this material by you may be the subject of copyright protection under the Act.

Do not remove this notice.

Outline

- Examples of published public web services
- Creating REST web services in Expressjs Application
- Consuming REST web services in Expressjs application

What are web services

- Web services is a distributed architectural **paradigm** for applications
- It provides a simple and open way of **integrating** functions or data from various systems
- It can be used **within** an organization and/or **across** the public Internet
- When it was first proposed, it consists of several basic standards
 - SOAP: A messaging protocol for transferring information
 - WSDL: A model and an XML format for describing Web services
 - UDDI: A registry and protocol for publishing and discovering web services (**not really used!!**)
 - WSDL and UDDI are in tension with the idea of using URI to address web resources
 - Original design of Web Services is very **application centric** in contrast to the **resource centric** Web and REST style.
- The term web services has much broader meaning now
 - At least two implementations: SOAP based vs. RESTful

Typical Use Case of Web Services API

What web services technology achieve can be done using basic network programming


Web services provide a better way of integrating component

Standard communication protocol: HTTP

Relative standard message format: XML, JSON

Ability to utilize existing system/applications

Web services API also provides a convenient way of getting structured data for analysis purpose



Example Web Service APIs

- Twitter API
 - <https://dev.twitter.com/rest/public>
- MediaWiki API
 - https://www.mediawiki.org/wiki/API:Main_page
- Flickr API
 - <http://www.flickr.com/services/api/>
- Amazon product advertising API
 - <https://affiliate-program.amazon.com/gp/advertising/api/detail/main.html#details>
- New York Times API
 - <http://developer.nytimes.com/docs>
- Youtube API
 - https://developers.google.com/youtube/getting_started#data_api

MediaWiki API

- <https://en.wikipedia.org/w/api.php?action=query&prop=revisions&rvprop=ids|timestamp&rvstart=2016-12-01T00:00:00Z&rvend=2017-01-01T00:00:00Z&rvidir=newer&format=jsonfm&titles=cat&rqlimit=max>



```
{
  "batchcomplete": "",
  "query": {
    "normalized": [
      {
        "from": "cat",
        "to": "Cat"
      }
    ],
    "pages": {
      "6678": {
        "pageid": 6678,
        "ns": 0,
        "title": "Cat",
        "revisions": [
          {
            "revid": 752709621,
            "parentid": 752304215,
            "timestamp": "2016-12-02T20:51:06Z"
          },
          {
            "revid": 752713783,
            "parentid": 752709621,
            "timestamp": "2016-12-02T21:17:08Z"
          }
        ]
      }
    }
  }
}
```

What is REST

- **Representational State Transfer**
- REST-style architectures consist of clients and servers. Clients initiate requests to servers; servers process requests and return appropriate responses. Requests and responses are built around the transfer of representations of resources. A resource can be essentially any coherent and meaningful concept that may be addressed. A representation of a resource is typically a document that captures the current or **intended** state of a resource.

Based on Roy Fielding's doctoral dissertation, rephrased by wikipedia
http://en.wikipedia.org/wiki/Representational_State_Transfer

Early day REST API format


- REST is an architectural style rather than a strict protocol
- The commonly agreed format comes after many APIs have been published and used by large communities
- Many early days RESTful API's URL has a format consists of
 - API end point (a concept coming from SOAP)
 - a parameter to specify the action: query, update, etc..
 - and many action specific parameters
 - Most of which are expressed as query strings
- Many API providers provide API sandbox or API explorer to help developer build the request URL
- Example:  
 - <https://api.flickr.com/services/rest/?method=flickr.test.echo&name=value>
 - <https://en.wikipedia.org/w/api.php?action=query&name=value>

Commonly agreed REST API format

- The commonly agreed REST API URL format conforms to general web architecture
 - Using URI (or URL) to specify resources
 - Using HTTP method to indicate action
- A URI (Uniform Resource Identifier) as a resource identifier is one of the central concepts of WWW
 - A predominant use of the World Wide Web is pure information retrieval, where the representation of an available resource, identified by a URI, is fetched using a HTTP GET request without affecting the resource in any way.
- The simplicity and scalability of the Web is largely due to the fact that there are a few "generic" methods (GET, POST, PUT, DELETE) which can be used to interact with any resource made available on the Web via a URI.

Basic REST design principles

- Use HTTP methods explicitly
- Be stateless
 - Address the resources explicitly in the request message



- Expose directory structure-like URIs
 - <http://www.mysevice.org/discussion/topics/{topic}>
- Transfer XML, JSON, or both <http://www.ibm.com/developerworks/webservices/library/ws-restful/>

Resource types

- Most of the time we can differentiate between collection type of resources and individual resource
 - Revisions and revision
 - Articles and article
- The URL's directory structure is based on that
- This can be nested and it is up to developers to decide the nesting direction
 - /movies/ForrestGump/actors/TomHanks
 - /directors/AngLee/movies/LifeOfPi

Request URLs and methods

Action	URL path	Parameters	Example
Create new revision	/revisions		http://localhost:3000/revisions
Get all revisions	/revisions		http://localhost:3000/revisions
Get a revision	/revisions	revision_id	http://localhost:3000/revisions/123
Update a revision	/revisions	revision_id	http://localhost:3000/revisions/123
Delete a revision	/revisions	revision_id	http://localhost:3000/revisions/123

Request Method	Use case	Response
POST	Add new data in a collection	New data created
GET	Read data from data source	Data objects
PUT	Update existing data	Updated object
DELETE	Delete an object	NULL

Outline

- Examples of published public web services
- **Creating REST web services in Expressjs Application**
- Consume REST web services in Expressjs application

Create REST API in ExpressJs

- Additional express route feature: route parameters
 - Route parameters are named URL segments that are used to capture the values specified at their position in the URL
 - The values are populated in **req.params** object
 - Example
 - Route path: `/users/:userId/books/:bookId`
 - Request URL: `http://localhost:3000/users/34/books/8989`
 - `req.params`: `{ "userId": "34", "bookId": "8989" }`

```
app.get('/users/:userId/books/:bookId', function (req, res)
{
  res.send(req.params)
})
```

Specifying client data

- Now we have three ways of sending data from client to server
 - Route parameter
 - Route path: `/users/:userId/books/:bookId`
 - Url: `http://localhost:3000/users/34/books/8989`
 - `req.params.userId`
 - `req.params.bookId`
 - Query String
 - url: `http://localhost:3000/usersbooks?userId=34&bookId=8989`
 - `req.query.userId`
 - `req.query.bookId`
 - Request body
 - data `{userId:34, bookId:8989}` is sent as part of request body
 - if using body-parser middleware
 - `req.body.userId`
 - `Req.body.bookId`

Create REST API using ExpressJs

```
RevisionSchema.statics.getByTitle = function(title, callback){  
    return this.find({'title':title}).exec(callback)  
}
```

model

```
module.exports.getByTitle=function(req,res){  
    title = req.params.title  
    Revision.getByTitle(title,function(err,result){  
        if (err){  
            console.log("Cannot find revisions of title: " + title)  
        }else{  
            res.json(result)  
        }  
    })  
}
```

controller

```
router.get('/revisions/:title', controller.getByTitle)
```

route

Response

http://localhost:3000/revision/revisions/BBC

app.use('/revision', revroutes)

```
← → ↻ ⓘ localhost:3000/revision/revisions/BBC 🔍 ☆

[{"_id": "5909707382b4a32faf860a4b", "sha1": "be2cae2a1b48499d991524968adfc1cbf5d4937c", "title": "BBC", "timestamp": "2016-10-31T20:03:59Z", "parsedcomment": "<a href=\"/wiki/BBC#1939_to_2000\" title=\"BBC\"></a><span dir=\"auto\"><span class=\"autocomment\">1939 to 2000: </span> Spelling correction &quot;to the UK an all parts o the world on the National Day of Prayer.&quot; --&gt; &quot;to the UK and all parts of the world on the National Day of Prayer.&quot;</span>", "revid": 747161964, "anon": "yes", "user": "2.30.158.121", "parentid": 747080530, "size": 136568}, {"_id": "5909707382b4a32faf860a4c", "sha1": "a5b6208d6339937be2bafb77759b807258eaa490", "title": "BBC", "timestamp": "2016-10-31T09:24:29Z", "parsedcomment": "<a href=\"/wiki/BBC#Governance_and_corporate_structure\" title=\"BBC\"></a><span dir=\"auto\"><span class=\"autocomment\">Governance and corporate structure: </span>Removed &quot;he&quot; refering to the post of Director-General. The exclusion of female form is sexist and inappropriate.</span>", "revid": 747080530, "user": "James uk", "parentid": 747062197, "size": 136567}, {"_id": "5909707382b4a32faf860a4d", "sha1": "6b94a4ebeabe71a69c79b415690ea827ba1dd69e", "title": "BBC", "timestamp": "2016-10-31T06:17:08Z", "parsedcomment": "<a href=\"/wiki/BBC#Revenue\" title=\"BBC\"></a><span dir=\"auto\"><span class=\"autocomment\">Revenue</span></span>", "revid": 747062197, "user": "GaryGill", "parentid": 747062075, "minor": "", "size": 136573}, {"_id": "5909707382b4a32faf860a4e", "sha1": "9560f23b106e345c938621ec38f1bdf454fc9819", "title": "BBC", "timestamp": "2016-10-31T06:06:39Z", "parsedcomment": "<a href=\"/wiki/BBC#Cultural_significance\" title=\"BBC\"></a><span dir=\"auto\"><span class=\"autocomment\">Cultural significance</span></span>", "revid": 747061189, "user": "GaryGill", "parentid": 747060833, "size": 136348},
```

Outline

- Examples of published public web services
- Creating REST web services in Expressjs Application
- Consuming REST web services in Expressjs application

Consume REST API in ExpressJS

- Complex API calls may benefit from using a package that **wrap** up the API
- Simple GET type of queries can always be implemented using general modules designed for handling http requests
 - Core `node.js` modules: `http`, `https`
 - `request` module
- The **request** module (<https://github.com/request/request>)
 - To install
 - `npm install request --save`
 - To make a request: `request(options, callback)`

```
var request = require('request');
request('http://www.google.com', function (error, response, body) {
  console.log('error:', error); // Print the error if one occurred
  console.log('statusCode:', response && response.statusCode); // Print the response status code if a response was received
  console.log('body:', body); // Print the HTML for the Google homepage.
});
```

Sample code with request module

```
var request = require('request');
```

```
var wikiEndpoint = "https://en.wikipedia.org/w/api.php",
```

End point

```
parameters = ["action=query",  
              "format=json",  
              "prop=revisions",  
              "titles=australia",  
              "rvstart=2016-11-01T11:56:22Z",  
              "rvdir=newer",  
              "rvlimit=max",  
              "rvprop=timestamp|userid|user|ids"]
```

Action and all parameters

```
var url = wikiEndpoint + "?" + parameters.join("&")
```

Constructing an URL

```
console.log("url: " + url)
```

```
var options = {
```

```
  url: url,  
  Accept: 'application/json',  
  'Accept-Charset': 'utf-8'
```

Request header

```
}
```

Making request

```
request(options, function (err, res, data){
```

Send request

```
  if (err) {
```

Call back function

```
    console.log('Error:', err);
```

```
  } else if (res.statusCode !== 200) {
```

```
    console.log('Status:', res.statusCode);
```

```
  } else {
```

```
    json = JSON.parse(data);
```

Convert JSON format string into JavaScript object

```
    pages = json.query.pages
```

```
    revisions = pages[Object.keys(pages)[0]].revisions
```

```
    console.log("There are " + revisions.length + " revisions.");
```

```
    var users=[]
```

Object.keys(obj) returns a array of obj's property names. We only need the first one.

```
    for (revid in revisions){
```

```
      users.push(revisions[revid].user);
```

```
    }
```

```
    uniqueUsers = new Set(users);
```

```
    console.log("The revisions are made by " + uniqueUsers.size + " unique users");
```

```
  }
```

```
});
```

https version

```
var https = require('https')

var wikiEndpointHost = "en.wikipedia.org",
    path = "/w/api.php"
    parameters = ["action=query",
                  "format=json",
                  "prop=revisions",
                  "titles=australia",
                  "rvstart=2016-11-01T11:56:22Z",
                  "rvdir=newer",
                  "rvlimit=max",
                  "rvprop=timestamp|userid|user|ids"],
    headers = {
      Accept: 'application/json',
      'Accept-Charset': 'utf-8'
    }

var full_path = path + "?" + parameters.join("&")

var options = {
  host: wikiEndpointHost,
  path: full_path,
  headers: headers}
```

<https://nodejs.org/api/https.html>

https version (cont'd)

```
https.get(options, function(res){  
    var data = '';  
    res.on('data', function(chunk){  
        data += chunk  
    })  
    res.on('end', function(){  
        json = JSON.parse(data);  
        pages = json.query.pages  
        revisions = pages[Object.keys(pages)[0]].revisions  
        console.log("There are " + revisions.length + " revisions.");  
        var users=[]  
        for (revid in revisions){  
            users.push(revisions[revid].user);  
        }  
        uniqueUsers = new Set(users);  
        console.log("The revisions are made by " + uniqueUsers.size + " unique users");  
    })  
}).on('error', function(e){  
    console.log(e)  
})
```

If the response contains a large body, the **data** event may fire multiple times each with a chunk of the actual body. We need to concatenate all chunks. See lecture 6 slide on form data.

end means no more data, the rest of the processing is the same

The 'error' event fires on the request object, not the incomingMessage res

Admin

- There will be a quiz tonight starting from 7:30pm
- It is closed book, paper based
 - 5 minutes reading time
 - 1 hour writing time
- Please check Elearning for venues and seat allocation
- Please do not ask invigilators any content related question
- If you have doubt about certain question, write it down next to the question
- Write your answers on the space provided
 - If you use extra page
 - make sure you have your name and SID on the page
 - insert it in the quiz script