

Package 'DescriptiveRepresentationCalculator'

September 27, 2023

Title Descriptive Representation Calculator from 'The Composition of Descriptive Representation'

Version 2.0

Author 'John Gerring <jgerring@austin.utexas.edu> [aut], Connor Jerzak <connor.jerzak@gmail.com> [aut, cre], Erzen Oncel <erzen.oncel@ozyegin.edu.tr> [aut]'

Description This package contains two main functions. The first computes the expected degree of representation for a given group in a political body under a random sampling model. The second computes the residual standard deviation in using the expected value as a prediction for observed values under the model.

Depends R (>= 3.3.3)

License

Creative Commons Attribution-Noncommercial-No Derivative Works 4.0, for academic use only.

Encoding UTF-8

LazyData true

Maintainer 'Connor Jerzak' <connor.jerzak@gmail.com>

RoxygenNote 7.2.3

R topics documented:

ExpectedRepresentation	1
ObservedRepresentation	2
SDRepresentation	3

Index	5
--------------	----------

ExpectedRepresentation

Compute the expected degree of representation for any group in a political body

Description

Finds the degree of expected representation for any group in a political body under a random sampling model as described in Gerring, Jerzak and Oncel (2023+).

Usage

```
ExpectedRepresentation(PopShares, BodyN)
```

Arguments

PopShares	A numeric vector containing the group-level population proportions.
BodyN	A positive integer denoting the size of the political body in question.
a=-0.5, b=1	Parameters controlling the affine transformation for how the representation measure is summarized. That is, a and b control how the expected L1 deviation of the population shares from the body shares is re-weighted. The expected L1 deviation is the average value of the absolute deviation of the population from body shares under a random sampling model. This expected L1 deviation is multiplied by a; b is as an additive re-scaling term: $a \cdot E[L1] + b$. By default, $a = -0.5$ and $b = 1$ so that the expected Rose Index of Proportionality is returned.

Value

The expected degree of representation (a scalar).

Examples

```
ExpectedRep <- ExpectedRepresentation(PopShares = c(1/3, 2/3, 1/3),
                                     BodyN = 50)

print( ExpectedRep )
```

ObservedRepresentation

Compute the observed degree of representation for any group in a political body

Description

Finds the degree of observed representation for any group in a political body.

Usage

```
ObservedRepresentation(BodyMemberCharacteristics, PopShares)
```

Arguments

BodyMemberCharacteristics	A vector specifying the characteristics for members of a political body.
PopShares	A numeric vector specifying population shares of identities specified in BodyMemberCharacteristics. The names of the entries in PopShares should correspond to identities in BodyMemberCharacteristics (see Example).
BodyShares	(optional) A numeric vector with same structure as PopShares specifying group population shares of a given body. If specified, used by default instead of BodyMemberCharacteristics.

$a=-0.5$, $b=1$ Parameters controlling the affine transformation for how the representation measure is summarized. That is, a and b control how the L1 deviation of the population shares from the body shares is re-weighted. This expected L1 deviation is multiplied by a ; b is as an additive re-scaling term: $a*L1+b$. By default, $a=-0.5$ and $b=1$ so that the Rose Index of Proportionality is returned.

Value

The observed degree of representation (a scalar). By default, this quantity is the Rose Index of Proportionality.

Examples

```
ObsRep <- ObservedRepresentation(
  BodyMemberCharacteristics = c("A","A","C","A","C","A"),
  PopShares = c("A"=1/3,"B"=2/3, "C"=1/3))

print( ObsRep ) # 0.833
```

SDRepresentation	<i>Compute the amount of representation left unexplained by a random sampling model.</i>
------------------	--

Description

Finds the residual standard deviation when using the expected representation for any group in a political body to predict observed representation as described in Gerring, Jerzak and Oncel, 2023+.

Usage

```
SDRepresentation(PopShares, BodyN)
```

Arguments

PopShares	A numeric vector containing the group-level population proportions.
BodyN	A positive integer denoting the size of the political body in question.
$a=-0.5$, $b=1$	Parameters controlling the affine transformation for how the representation measure is summarized. That is, a and b control how the expected L1 deviation of the population shares from the body shares is re-weighted. The expected L1 deviation is the average value of the absolute deviation of the population from body shares under a random sampling model. This expected L1 deviation is multiplied by a ; b is as an additive re-scaling term: $a*E[L1]+b$. By default, $a=-0.5$ and $b=1$ so that the expected Rose Index of Proportionality is used in the calculation.

Value

A scalar summary of the amount of representation not explained by a random sampling model. More precisely, this function returns the the residual standard deviation when using the expected degree of representation to predict observed representation under a random sampling model.

Index

ExpectedRepresentation, [1](#)

ObservedRepresentation, [2](#)

SDRepresentation, [3](#)