

Package ‘asa’

January 11, 2026

Title AI Search Agent for Large-Scale Research Automation

Version 0.1.0

Author Connor Jerzak [aut, cre] (<<https://orcid.org/0000-0003-1914-8905>>)

Maintainer Connor Jerzak <connor.jerzak@gmail.com>

Description Provides an LLM-powered research agent for performing AI search tasks at large scales. Uses a ReAct (Reasoning + Acting) agent pattern with web search capabilities via DuckDuckGo and Wikipedia. Implements DeepAgent-style memory folding for context management. The agent is built on 'LangGraph' and supports multiple LLM backends including 'OpenAI', 'Groq', and 'xAI'.

URL <https://github.com/cjerzak/asa-software>

BugReports <https://github.com/cjerzak/asa-software/issues>

Depends R (>= 4.0.0)

License GPL-3

Encoding UTF-8

LazyData false

Imports reticulate (>= 1.28),
jsonlite,
rlang,
digest,
processx

Suggests testthat (>= 3.0.0),
knitr,
rmarkdown,
future,
future.apply

VignetteBuilder knitr

RoxygenNote 7.3.3

Config/testthat/edition 3

SystemRequirements Python (>= 3.11), Conda, Tor (optional, for anonymous searching)

Contents

as.data.frame.asa_audit_result	3
as.data.frame.asa_enumerate_result	3

as.data.frame.asa_result	4
asa_agent	4
asa_audit	5
asa_audit_result	7
asa_config	8
asa_enumerate	9
asa_enumerate_result	13
asa_response	13
asa_result	14
build_backend	15
build_prompt	16
check_backend	17
configure_search	17
configure_search_logging	19
configure_temporal	20
configure_tor_registry	21
extract_agent_results	22
extract_search_snippets	22
extract_search_tiers	23
extract_urls	24
extract_wikipedia_content	24
get_agent	25
get_tor_ip	25
initialize_agent	26
is_tor_running	28
print.asa_agent	29
print.asa_audit_result	29
print.asa_config	30
print.asa_enumerate_result	30
print.asa_response	31
print.asa_result	31
print.asa_search	32
print.asa_temporal	32
print.asa_tor	33
process_outputs	33
reset_agent	34
rotate_tor_circuit	34
run_task	35
run_task_batch	38
search_options	39
summary.asa_agent	41
summary.asa_audit_result	41
summary.asa_enumerate_result	42
summary.asa_response	42
summary.asa_result	43
temporal_options	43
tor_options	44
write_csv.asa_enumerate_result	45

`as.data.frame.asa_audit_result`*Convert asa_audit_result to Data Frame*

Description

Convert asa_audit_result to Data Frame

Usage

```
## S3 method for class 'asa_audit_result'  
as.data.frame(x, ...)
```

Arguments

x	An asa_audit_result object
...	Additional arguments (ignored)

Value

The audited data.frame with audit columns

`as.data.frame.asa_enumerate_result`*Convert asa_enumerate_result to Data Frame*

Description

Convert asa_enumerate_result to Data Frame

Usage

```
## S3 method for class 'asa_enumerate_result'  
as.data.frame(x, ...)
```

Arguments

x	An asa_enumerate_result object
...	Additional arguments (ignored)

Value

The data data.frame from the result

as.data.frame.asa_result

Convert asa_result to Data Frame

Description

Convert asa_result to Data Frame

Usage

```
## S3 method for class 'asa_result'
as.data.frame(x, ...)
```

Arguments

- x An asa_result object
- ... Additional arguments (ignored)

Value

A single-row data frame

asa_agent

Constructor for asa_agent Objects

Description

Creates an S3 object representing an initialized ASA search agent.

Usage

```
asa_agent(python_agent, backend, model, config, llm = NULL, tools = NULL)
```

Arguments

- python_agent The underlying Python agent object
- backend LLM backend name (e.g., "openai", "groq")
- model Model identifier
- config Agent configuration list
- llm Optional LLM object used by LangGraph
- tools Optional list of tools associated with the agent

Value

An object of class asa_agent

asa_audit

*Audit Enumeration Results for Completeness and Quality***Description**

Validates enumeration results for completeness, consistency, and data quality using either Claude Code (CLI) or a LangGraph-based audit pipeline.

Usage

```
asa_audit(
  result,
  query = NULL,
  known_universe = NULL,
  checks = c("completeness", "consistency", "gaps", "anomalies"),
  backend = c("claude_code", "langgraph"),
  claude_model = "claude-sonnet-4-20250514",
  llm_model = "gpt-4.1-mini",
  interactive = FALSE,
  confidence_threshold = 0.8,
  timeout = 120,
  verbose = TRUE,
  agent = NULL
)
```

Arguments

result	An <code>asa_enumerate_result</code> object or a <code>data.frame</code> to audit
query	The original enumeration query (inferred from result if NULL)
known_universe	Optional vector of expected items for completeness check
checks	Character vector of checks to perform. Options: "completeness", "consistency", "gaps", "anomalies". Default runs all checks.
backend	Backend to use for auditing: "claude_code" (CLI) or "langgraph"
claude_model	Model to use with Claude Code backend
llm_model	Model to use with LangGraph backend
interactive	If TRUE and using <code>claude_code</code> backend, spawn an interactive Claude Code session instead of programmatic invocation
confidence_threshold	Flag items with confidence below this threshold
timeout	Timeout in seconds for the audit operation
verbose	Print progress messages
agent	Existing <code>asa_agent</code> for LangGraph backend (optional)

Details

The audit function adds three columns to the data:

- `_audit_flag`: "ok", "warning", or "suspect"
- `_audit_notes`: Explanation of any issues
- `_confidence_adjusted`: Revised confidence after audit

Audit Checks

completeness: Checks for missing items by comparing against `known_universe` (if provided) or using domain knowledge.

consistency: Validates data types, patterns, and value ranges.

gaps: Identifies systematic patterns of missing data (geographic, temporal, categorical gaps).

anomalies: Detects duplicates, outliers, and suspicious patterns.

Value

An `asa_audit_result` object containing:

<code>data</code>	Original data with audit columns added (<code>_audit_flag</code> , <code>_audit_notes</code>)
<code>audit_summary</code>	High-level summary of findings
<code>issues</code>	List of identified issues with severity and descriptions
<code>recommendations</code>	Suggested remediation queries
<code>completeness_score</code>	0-1 score for data completeness
<code>consistency_score</code>	0-1 score for data consistency

Examples

```
## Not run:
# Audit enumeration results with Claude Code
senators <- asa_enumerate(
  query = "Find all current US senators",
  schema = c(name = "character", state = "character", party = "character")
)
audit <- asa_audit(senators, backend = "claude_code")
print(audit)

# Audit with known universe for precise completeness check
audit <- asa_audit(senators, known_universe = state.abb)

# Interactive mode for complex audits
asa_audit(senators, backend = "claude_code", interactive = TRUE)

# Use LangGraph backend
audit <- asa_audit(senators, backend = "langgraph", agent = agent)

## End(Not run)
```

asa_audit_result	<i>Constructor for asa_audit_result Objects</i>
------------------	---

Description

Creates an S3 object representing the result of a data quality audit.

Usage

```
asa_audit_result(  
  data,  
  audit_summary,  
  issues,  
  recommendations,  
  completeness_score,  
  consistency_score,  
  backend_used,  
  elapsed_time,  
  query = NULL,  
  checks = NULL  
)
```

Arguments

data	data.frame with original data plus audit columns (_audit_flag, _audit_notes)
audit_summary	Character string with high-level findings
issues	List of identified issues with severity and descriptions
recommendations	Character vector of suggested remediation queries
completeness_score	Numeric 0-1 score for data completeness
consistency_score	Numeric 0-1 score for data consistency
backend_used	Which backend performed the audit ("claude_code" or "langgraph")
elapsed_time	Execution time in seconds
query	The original query (if available)
checks	Character vector of checks that were performed

Value

An object of class `asa_audit_result`

asa_config

*Create ASA Configuration Object***Description**

Creates a configuration object that encapsulates all settings for ASA tasks. This provides a unified way to configure backend, model, search, temporal, and resource settings in a single object.

Usage

```
asa_config(
    backend = NULL,
    model = NULL,
    conda_env = NULL,
    proxy = NULL,
    workers = NULL,
    timeout = NULL,
    rate_limit = NULL,
    memory_folding = NULL,
    memory_threshold = NULL,
    memory_keep_recent = NULL,
    temporal = NULL,
    search = NULL,
    tor = NULL
)
```

Arguments

backend	LLM backend: "openai", "groq", "xai", "exo", "openrouter"
model	Model identifier (e.g., "gpt-4.1-mini")
conda_env	Conda environment name (default: "asa_env")
proxy	SOCKS5 proxy URL or NULL to disable
workers	Number of parallel workers for batch operations
timeout	Request timeout in seconds
rate_limit	Requests per second
memory_folding	Enable DeepAgent-style memory folding
memory_threshold	Messages before folding triggers
memory_keep_recent	Messages to preserve after folding
temporal	Temporal filtering options (use temporal_options())
search	Search configuration (use search_options())
tor	Tor registry options (use tor_options())

Details

The configuration object can be passed to run_task(), run_task_batch(), asa_enumerate(), and other functions to provide consistent settings across operations.

Value

An object of class `asa_config`

See Also

[temporal_options](#), [search_options](#)

Examples

```
## Not run:
# Create configuration
config <- asa_config(
  backend = "openai",
  model = "gpt-4.1-mini",
  workers = 4,
  temporal = temporal_options(time_filter = "y")
)

# Use with run_task
result <- run_task(prompt, config = config)

## End(Not run)
```

asa_enumerate

Multi-Agent Research for Open-Ended Queries

Description

Performs intelligent open-ended research tasks using multi-agent orchestration. Decomposes complex queries into sub-tasks, executes parallel searches, and aggregates results into structured output (data.frame, CSV, or JSON).

Usage

```
asa_enumerate(
  query,
  schema = NULL,
  output = c("data.frame", "csv", "json"),
  workers = NULL,
  max_rounds = NULL,
  budget = list(queries = 50L, tokens = 200000L, time_sec = 300L),
  stop_policy = list(target_items = NULL, plateau_rounds = 2L, novelty_min = 0.05,
    novelty_window = 20L),
  sources = list(web = TRUE, wikipedia = TRUE, wikidata = TRUE),
  temporal = NULL,
  pagination = TRUE,
  progress = TRUE,
  include_provenance = FALSE,
  checkpoint = TRUE,
  checkpoint_dir = tempdir(),
  resume_from = NULL,
```

```

    agent = NULL,
    backend = NULL,
    model = NULL,
    conda_env = NULL,
    verbose = TRUE
)

```

Arguments

query	Character string describing the research goal. Examples: "Find all current US senators with their state, party, and term end date"
schema	Named character vector defining the output schema. Names are column names, values are R types ("character", "numeric", "logical"). Use NULL or "auto" for LLM-proposed schema.
output	Output format: "data.frame" (default), "csv", or "json".
workers	Number of parallel search workers. Defaults to value from ASA_DEFAULT_WORKERS (typically 4).
max_rounds	Maximum research iterations. Defaults to value from ASA_DEFAULT_MAX_ROUNDS (typically 8).
budget	Named list with resource limits: <ul style="list-style-type: none"> queries: Maximum search queries (default: 50) tokens: Maximum LLM tokens (default: 200000) time_sec: Maximum execution time in seconds (default: 300)
stop_policy	Named list with stopping criteria: <ul style="list-style-type: none"> target_items: Stop when this many items found (NULL = unknown) plateau_rounds: Stop after N rounds with no new items (default: 2) novelty_min: Minimum new items ratio per round (default: 0.05) novelty_window: Window size for novelty calculation (default: 20)
sources	Named list controlling which sources to use: <ul style="list-style-type: none"> web: Use DuckDuckGo web search (default: TRUE) wikipedia: Use Wikipedia (default: TRUE) wikidata: Use Wikidata SPARQL for authoritative enumerations (default: TRUE)
temporal	Named list for temporal filtering: <ul style="list-style-type: none"> after: ISO 8601 date string (e.g., "2020-01-01") - results after this date before: ISO 8601 date string (e.g., "2024-01-01") - results before this date time_filter: DuckDuckGo time filter ("d", "w", "m", "y") for day/week/month/year strictness: "best_effort" (default) or "strict" (verifies dates via metadata) use_wayback: Use Wayback Machine for strict pre-date guarantees (default: FALSE)
pagination	Enable pagination for large result sets (default: TRUE).
progress	Show progress bar and status updates (default: TRUE).
include_provenance	Include source URLs and confidence per row (default: FALSE).
checkpoint	Enable auto-save after each round (default: TRUE).
checkpoint_dir	Directory for checkpoint files (default: tempdir()).

<code>resume_from</code>	Path to checkpoint file to resume from (default: NULL).
<code>agent</code>	An initialized <code>asa_agent</code> object. If NULL, uses the current agent or creates a new one with specified backend/model.
<code>backend</code>	LLM backend if creating new agent: "openai", "groq", "xai", "openrouter".
<code>model</code>	Model identifier if creating new agent.
<code>conda_env</code>	Conda environment name (default: "asa_env").
<code>verbose</code>	Print status messages (default: TRUE).

Details

The function uses a multi-agent architecture:

1. **Planner:** Decomposes query into facets and identifies authoritative sources
2. **Dispatcher:** Spawns parallel workers for each facet
3. **Workers:** Execute searches using DDG, Wikipedia, and Wikidata
4. **Extractor:** Normalizes results to match schema
5. **Deduper:** Removes duplicates using hash + fuzzy matching
6. **Stopper:** Evaluates stopping criteria (novelty, budget, saturation)

For known entity types (US senators, countries, Fortune 500), Wikidata provides authoritative enumerations with complete, verified data.

Value

An object of class `asa_enumerate_result` containing:

- `data`: data.frame with results matching the schema
- `status`: "complete", "partial", or "failed"
- `stop_reason`: Why the search stopped
- `metrics`: List with rounds, queries_used, novelty_curve, coverage
- `provenance`: If `include_provenance=TRUE`, source info per row
- `checkpoint_file`: Path to checkpoint if saved

Checkpointing

With `checkpoint=TRUE`, state is saved after each round. If interrupted, use `resume_from` to continue from the last checkpoint:

```
result <- asa_enumerate(query, resume_from = "/path/to/checkpoint.rds")
```

Schema

The schema defines expected output columns:

```
schema = c(name = "character", state = "character", party = "character")
```

With `schema = "auto"`, the planner agent proposes a schema based on the query.

See Also

[run_task](#), [initialize_agent](#)

Examples

```

## Not run:
# Find all US senators
senators <- asa_enumerate(
  query = "Find all current US senators with state, party, and term end date",
  schema = c(name = "character", state = "character",
             party = "character", term_end = "character"),
  stop_policy = list(target_items = 100),
  include_provenance = TRUE
)
head(senators$data)

# Find countries with auto schema
countries <- asa_enumerate(
  query = "Find all countries with their capitals and populations",
  schema = "auto",
  output = "csv"
)

# Resume from checkpoint
result <- asa_enumerate(
  query = "Find Fortune 500 CEOs",
  resume_from = "/tmp/asa_enumerate_abc123.rds"
)

# Temporal filtering: results from specific date range
companies_2020s <- asa_enumerate(
  query = "Find tech companies founded recently",
  temporal = list(
    after = "2020-01-01",
    before = "2024-01-01",
    strictness = "best_effort"
  )
)

# Temporal filtering: past year with DuckDuckGo time filter
recent_news <- asa_enumerate(
  query = "Find AI research breakthroughs",
  temporal = list(
    time_filter = "y" # past year
  )
)

# Strict temporal filtering with Wayback Machine
historical <- asa_enumerate(
  query = "Find Fortune 500 companies",
  temporal = list(
    before = "2015-01-01",
    strictness = "strict",
    use_wayback = TRUE
  )
)

## End(Not run)

```

asa_enumerate_result *Constructor for asa_enumerate_result Objects*

Description

Creates an S3 object representing the result of an enumeration task.

Usage

```
asa_enumerate_result(
  data,
  status,
  stop_reason,
  metrics,
  provenance = NULL,
  plan = NULL,
  checkpoint_file = NULL,
  query = NULL,
  schema = NULL
)
```

Arguments

data	data.frame containing the enumeration results
status	Result status: "complete", "partial", or "failed"
stop_reason	Why the enumeration stopped (e.g., "target_reached", "novelty_plateau")
metrics	List with execution metrics (rounds, queries_used, etc.)
provenance	Optional data.frame with source information per row
plan	The enumeration plan from the planner agent
checkpoint_file	Path to saved checkpoint file
query	The original enumeration query
schema	The schema used for extraction

Value

An object of class `asa_enumerate_result`

asa_response *Constructor for asa_response Objects*

Description

Creates an S3 object representing an agent response.

Usage

```
asa_response(  
  message,  
  status_code,  
  raw_response,  
  trace,  
  elapsed_time,  
  fold_count,  
  prompt  
)
```

Arguments

message	The final response text
status_code	Status code (200 = success, 100 = error)
raw_response	The full Python response object
trace	Full text trace of agent execution
elapsed_time	Execution time in minutes
fold_count	Number of memory folds performed
prompt	The original prompt

Value

An object of class `asa_response`

asa_result	<i>Constructor for asa_result Objects</i>
------------	---

Description

Creates an S3 object representing the result of a research task.

Usage

```
asa_result(  
  prompt,  
  message,  
  parsed,  
  raw_output,  
  elapsed_time,  
  status,  
  search_tier = "unknown",  
  parsing_status = NULL  
)
```

Arguments

prompt	The original prompt
message	The agent's response text
parsed	Parsed output (list or NULL)
raw_output	Full agent trace
elapsed_time	Execution time in minutes
status	Status ("success" or "error")
search_tier	Which search tier was used ("primp", "selenium", "ddgs", "requests", or "unknown"). Useful for assessing result quality.
parsing_status	List with JSON parsing validation info: valid (logical), reason ("ok", "parsing_failed", "not_object", "missing_fields", "null_values", "no_validation"), and missing (character vector of missing/invalid fields).

Value

An object of class `asa_result`

build_backend	<i>Build the Python Backend Environment</i>
---------------	---

Description

Creates a conda environment with all required Python dependencies for the asa search agent, including LangChain, LangGraph, and search tools.

Usage

```
build_backend(conda_env = "asa_env", conda = "auto", python_version = "3.13")
```

Arguments

conda_env	Name of the conda environment (default: "asa_env")
conda	Path to conda executable (default: "auto")
python_version	Python version to use (default: "3.13")

Details

This function creates a new conda environment and installs the following Python packages:

- langchain_groq, langchain_community, langchain_openai
- langgraph
- ddgs (DuckDuckGo search)
- selenium, primp (browser automation)
- undetected-chromedriver (stealth Chrome)
- beautifulsoup4, requests
- fake_headers, httpx
- stem (Tor control)
- pysocks, socksio (proxy support)

Value

Invisibly returns NULL; called for side effects.

Examples

```
## Not run:
# Create the default environment
build_backend()

# Create with a custom name
build_backend(conda_env = "my_asa_env")

## End(Not run)
```

 build_prompt

Build a Task Prompt from Template

Description

Creates a formatted prompt by substituting variables into a template.

Usage

```
build_prompt(template, ...)
```

Arguments

template	A character string with placeholders in the form {variable_name}
...	Named arguments to substitute into the template

Value

A formatted prompt string

Examples

```
## Not run:
prompt <- build_prompt(
  template = "Find information about {{name}} in {{country}} during {{year}}",
  name = "Marie Curie",
  country = "France",
  year = 1903
)

## End(Not run)
```

check_backend	<i>Check Python Environment Availability</i>
---------------	--

Description

Checks if the required Python environment and packages are available.

Usage

```
check_backend(conda_env = "asa_env")
```

Arguments

conda_env Name of the conda environment to check

Value

A list with components:

- available: Logical, TRUE if environment is ready
- conda_env: Name of the environment checked
- python_version: Python version if available
- missing_packages: Character vector of missing packages (if any)

Examples

```
## Not run:
status <- check_backend()
if (!status$available) {
  build_backend()
}

## End(Not run)
```

configure_search	<i>Configure Python Search Parameters</i>
------------------	---

Description

Sets global configuration values for the Python search module. These values control timeouts, retry behavior, and result limits.

Usage

```

configure_search(
  max_results = NULL,
  timeout = NULL,
  max_retries = NULL,
  retry_delay = NULL,
  backoff_multiplier = NULL,
  captcha_backoff_base = NULL,
  page_load_wait = NULL,
  inter_search_delay = NULL,
  conda_env = "asa_env"
)

```

Arguments

<code>max_results</code>	Maximum number of search results to return (default: 10)
<code>timeout</code>	HTTP request timeout in seconds (default: 15)
<code>max_retries</code>	Maximum retry attempts on failure (default: 3)
<code>retry_delay</code>	Initial delay between retries in seconds (default: 2)
<code>backoff_multiplier</code>	Multiplier for exponential backoff (default: 1.5)
<code>captcha_backoff_base</code>	Base multiplier for CAPTCHA backoff (default: 3)
<code>page_load_wait</code>	Wait time after page load in seconds (default: 2)
<code>inter_search_delay</code>	Delay between consecutive searches in seconds (default: 0.5)
<code>conda_env</code>	Name of the conda environment (default: "asa_env")

Value

Invisibly returns a list with the current configuration

Examples

```

## Not run:
# Increase timeout for slow connections
configure_search(timeout = 30, max_retries = 5)

# Get more results
configure_search(max_results = 20)

# Add delay between searches to avoid rate limiting
configure_search(inter_search_delay = 2.0)

## End(Not run)

```

`configure_search_logging`*Configure Python Search Logging Level*

Description

Sets the logging level for the Python search module. This controls how much diagnostic output is produced during web searches.

Usage

```
configure_search_logging(level = "WARNING", conda_env = "asa_env")
```

Arguments

<code>level</code>	Log level: "DEBUG", "INFO", "WARNING" (default), "ERROR", or "CRITICAL"
<code>conda_env</code>	Name of the conda environment (default: "asa_env")

Details

Log levels from most to least verbose:

- DEBUG: Detailed diagnostic information for debugging
- INFO: General operational information
- WARNING: Indicates something unexpected but not an error (default)
- ERROR: Serious problems that prevented an operation
- CRITICAL: Very serious errors

Value

Invisibly returns the current logging level

Examples

```
## Not run:  
# Enable verbose debugging output  
configure_search_logging("DEBUG")  
  
# Run a search (will show detailed logs)  
result <- run_task("What is the population of Tokyo?", agent = agent)  
  
# Disable verbose output  
configure_search_logging("WARNING")  
  
## End(Not run)
```

configure_temporal	<i>Configure Temporal Filtering for Search</i>
--------------------	--

Description

Sets or clears temporal filtering on the DuckDuckGo search tool. This affects all subsequent searches until changed or cleared.

Usage

```
configure_temporal(time_filter = NULL)
```

Arguments

time_filter	DuckDuckGo time filter: "d" (day), "w" (week), "m" (month), "y" (year), or NULL/NA/"none" to clear
-------------	--

Details

This function modifies the search tool's time parameter, which is passed to DuckDuckGo as the df parameter. The filter restricts results to content indexed within the specified time period.

Note: This only affects DuckDuckGo searches. For Wikidata queries with temporal filtering, use `asa_enumerate()` with its temporal parameter.

Value

Invisibly returns the previous time filter setting

Time Filter Values

- "d": Past 24 hours (day)
- "w": Past 7 days (week)
- "m": Past 30 days (month)
- "y": Past 365 days (year)
- NULL, NA, or "none": No time restriction (default)

See Also

[run_task](#), [asa_enumerate](#)

Examples

```
## Not run:
# Restrict to past year
configure_temporal("y")
result <- run_task("Find recent AI breakthroughs", agent = agent)

# Clear temporal filter
configure_temporal(NULL)

# Past week only
```

```

configure_temporal("w")

## End(Not run)

```

```
configure_tor_registry
```

Configure Tor Exit Registry

Description

Sets up the shared Tor exit health registry used by the Python search stack to avoid reusing tainted or overused exit nodes.

Usage

```

configure_tor_registry(
  registry_path = NULL,
  enable = ASA_TOR_REGISTRY_ENABLED,
  bad_ttl = ASA_TOR_BAD_TTL,
  good_ttl = ASA_TOR_GOOD_TTL,
  overuse_threshold = ASA_TOR_OVERUSE_THRESHOLD,
  overuse_decay = ASA_TOR_OVERUSE_DECAY,
  max_rotation_attempts = ASA_TOR_MAX_ROTATION_ATTEMPTS,
  ip_cache_ttl = ASA_TOR_IP_CACHE_TTL,
  conda_env = "asa_env"
)

```

Arguments

registry_path	Path to the SQLite registry file (default: user cache).
enable	Enable the registry (set FALSE to disable tracking).
bad_ttl	Seconds to keep a bad/tainted exit before reuse.
good_ttl	Seconds to treat an exit as good before refreshing.
overuse_threshold	Maximum recent uses before a good exit is treated as overloaded.
overuse_decay	Window (seconds) for counting recent uses before decay.
max_rotation_attempts	Maximum rotations to find a clean exit.
ip_cache_ttl	Seconds to cache exit IP lookups.
conda_env	Conda environment name for the Python module.

Value

Invisibly returns a list of the configured values (or NULL on error).

extract_agent_results *Extract Structured Data from Agent Traces*

Description

Parses raw agent output to extract search snippets, Wikipedia content, URLs, JSON data, and search tier information. This is the main function for post-processing agent traces.

Usage

```
extract_agent_results(raw_output)
```

Arguments

raw_output	Raw output string from agent invocation (the trace field from an asa_response object)
------------	---

Value

A list with components:

- search_snippets: Character vector of search result content
- search_urls: Character vector of URLs from search results
- wikipedia_snippets: Character vector of Wikipedia content
- json_data: Extracted JSON data as a list (if present)
- search_tiers: Character vector of unique search tiers used (e.g., "primp", "selenium", "ddgs", "requests")

Examples

```
## Not run:
response <- run_agent("Who is the president of France?", agent)
extracted <- extract_agent_results(response$trace)
print(extracted$search_snippets)
print(extracted$search_tiers) # Shows which search tier was used

## End(Not run)
```

extract_search_snippets

Extract Search Snippets by Source Number

Description

Extracts content from Search tool messages in the agent trace.

Usage

```
extract_search_snippets(text)
```

Arguments

text Raw agent trace text

Value

Character vector of search snippets, ordered by source number

Examples

```
## Not run:
snippets <- extract_search_snippets(response$trace)

## End(Not run)
```

extract_search_tiers *Extract Search Tier Information*

Description

Extracts which search tier was used from the agent trace. The search module uses a multi-tier fallback system:

- primp: Fast HTTP client with browser impersonation (Tier 0)
- selenium: Headless browser for JS-rendered content (Tier 1)
- ddgs: Standard DDGS Python library (Tier 2)
- requests: Raw POST to DuckDuckGo HTML endpoint (Tier 3)

Usage

```
extract_search_tiers(text)
```

Arguments

text Raw agent trace text

Value

Character vector of unique tier names encountered (e.g., "primp", "selenium", "ddgs", "requests")

Examples

```
## Not run:
tiers <- extract_search_tiers(response$trace)
print(tiers) # e.g., "primp"

## End(Not run)
```

extract_urls	<i>Extract URLs by Source Number</i>
--------------	--------------------------------------

Description

Extracts URLs from Search tool messages in the agent trace.

Usage

```
extract_urls(text)
```

Arguments

text	Raw agent trace text
------	----------------------

Value

Character vector of URLs, ordered by source number

Examples

```
## Not run:  
urls <- extract_urls(response$trace)  
  
## End(Not run)
```

extract_wikipedia_content	<i>Extract Wikipedia Content</i>
---------------------------	----------------------------------

Description

Extracts content from Wikipedia tool messages in the agent trace.

Usage

```
extract_wikipedia_content(text)
```

Arguments

text	Raw agent trace text
------	----------------------

Value

Character vector of Wikipedia snippets

Examples

```
## Not run:
wiki <- extract_wikipedia_content(response$trace)

## End(Not run)
```

get_agent*Get the Current Agent*

Description

Returns the currently initialized agent, or NULL if not initialized.

Usage

```
get_agent()
```

Value

An asa_agent object or NULL

Examples

```
## Not run:
agent <- get_agent()
if (is.null(agent)) {
  agent <- initialize_agent()
}

## End(Not run)
```

get_tor_ip*Get External IP via Tor*

Description

Retrieves the external IP address as seen through Tor proxy.

Usage

```
get_tor_ip(proxy = "socks5h://127.0.0.1:9050", timeout = 30L)
```

Arguments

proxy	Tor proxy URL (e.g., "socks5h://127.0.0.1:9050" for default, or "socks5h://127.0.0.1:9055" for instance on port 9055)
timeout	Timeout in seconds (default: 30). Useful for parallel workloads where some Tor exits may be slow.

Value

IP address string or NA on failure

Examples

```
## Not run:
# Default Tor instance
ip <- get_tor_ip()
message("Current Tor IP: ", ip)

# Check specific Tor instance (e.g., for parallel jobs)
ip <- get_tor_ip(proxy = "socks5h://127.0.0.1:9055")

## End(Not run)
```

initialize_agent	<i>Initialize the ASA Search Agent</i>
------------------	--

Description

Initializes the Python environment and creates the LangGraph agent with search tools (Wikipedia, DuckDuckGo). The agent can use multiple LLM backends and supports DeepAgent-style memory folding.

Usage

```
initialize_agent(
  backend = "openai",
  model = "gpt-4.1-mini",
  conda_env = "asa_env",
  proxy = "socks5h://127.0.0.1:9050",
  use_memory_folding = TRUE,
  memory_threshold = 4L,
  memory_keep_recent = 2L,
  rate_limit = 0.2,
  timeout = 120L,
  tor = tor_options(),
  verbose = TRUE
)
```

Arguments

backend	LLM backend to use. One of: "openai", "groq", "xai", "exo", "openrouter"
model	Model identifier (e.g., "gpt-4.1-mini", "llama-3.3-70b-versatile")
conda_env	Name of the conda environment with Python dependencies
proxy	SOCKS5 proxy URL for Tor (default: "socks5h://127.0.0.1:9050"). Set to NULL to disable proxy.
use_memory_folding	Enable DeepAgent-style memory compression (default: TRUE)

memory_threshold	Number of messages before folding triggers (default: 4)
memory_keep_recent	Number of recent messages to preserve after folding (default: 2)
rate_limit	Requests per second for rate limiting (default: 0.2)
timeout	Request timeout in seconds (default: 120)
tor	Tor registry options from tor_options . Disable shared tracking by setting <code>dirty_tor_exists = FALSE</code> .
verbose	Print status messages (default: TRUE)

Details

The agent is created with two tools:

- Wikipedia: For looking up encyclopedic information
- DuckDuckGo Search: For web searches with a 4-tier fallback system (PRIMP -> Selenium -> DDGS library -> raw requests)

Memory folding (enabled by default) compresses older messages into a summary to manage context length in long conversations, following the DeepAgent paper.

Value

An object of class `asa_agent` containing the initialized agent and configuration.

API Keys

The following environment variables should be set based on your backend:

- OpenAI: `OPENAI_API_KEY`
- Groq: `GROQ_API_KEY`
- xAI: `XAI_API_KEY`
- OpenRouter: `OPENROUTER_API_KEY`

OpenRouter Models

When using the "openrouter" backend, model names must be in provider/model-name format. Examples:

- "openai/gpt-4o"
- "anthropic/claude-3-sonnet"
- "google/gemma-2-9b-it:free"
- "meta-llama/llama-3-70b-instruct"

See <https://openrouter.ai/models> for available models.

See Also

[run_task](#), [run_task_batch](#)

Examples

```
## Not run:
# Initialize with OpenAI
agent <- initialize_agent(
  backend = "openai",
  model = "gpt-4.1-mini"
)

# Initialize with Groq and custom settings
agent <- initialize_agent(
  backend = "groq",
  model = "llama-3.3-70b-versatile",
  use_memory_folding = FALSE,
  proxy = NULL # No Tor proxy
)

# Initialize with OpenRouter (access to 100+ models)
agent <- initialize_agent(
  backend = "openrouter",
  model = "anthropic/claude-3-sonnet" # Note: provider/model format
)

## End(Not run)
```

is_tor_running	<i>Check if Tor is Running</i>
----------------	--------------------------------

Description

Checks if Tor is running and accessible on the default port.

Usage

```
is_tor_running(port = 9050L)
```

Arguments

port	Port number (default: 9050)
------	-----------------------------

Value

Logical indicating if Tor appears to be running

Examples

```
## Not run:
if (!is_tor_running()) {
  message("Start Tor with: brew services start tor")
}

## End(Not run)
```

print.asa_agent	<i>Print Method for asa_agent Objects</i>
-----------------	---

Description

Print Method for asa_agent Objects

Usage

```
## S3 method for class 'asa_agent'  
print(x, ...)
```

Arguments

x	An asa_agent object
...	Additional arguments (ignored)

Value

Invisibly returns the object

print.asa_audit_result	<i>Print Method for asa_audit_result Objects</i>
------------------------	--

Description

Print Method for asa_audit_result Objects

Usage

```
## S3 method for class 'asa_audit_result'  
print(x, n = 6, ...)
```

Arguments

x	An asa_audit_result object
n	Number of data rows to preview (default: 6)
...	Additional arguments (ignored)

Value

Invisibly returns the object

print.asa_config	<i>Print Method for asa_config Objects</i>
------------------	--

Description

Print Method for asa_config Objects

Usage

```
## S3 method for class 'asa_config'  
print(x, ...)
```

Arguments

x	An asa_config object
...	Additional arguments (ignored)

Value

Invisibly returns the object

print.asa_enumerate_result	<i>Print Method for asa_enumerate_result Objects</i>
----------------------------	--

Description

Print Method for asa_enumerate_result Objects

Usage

```
## S3 method for class 'asa_enumerate_result'  
print(x, n = 6, ...)
```

Arguments

x	An asa_enumerate_result object
n	Number of data rows to preview (default: 6)
...	Additional arguments (ignored)

Value

Invisibly returns the object

print.asa_response	<i>Print Method for asa_response Objects</i>
--------------------	--

Description

Print Method for asa_response Objects

Usage

```
## S3 method for class 'asa_response'  
print(x, ...)
```

Arguments

x	An asa_response object
...	Additional arguments (ignored)

Value

Invisibly returns the object

print.asa_result	<i>Print Method for asa_result Objects</i>
------------------	--

Description

Print Method for asa_result Objects

Usage

```
## S3 method for class 'asa_result'  
print(x, ...)
```

Arguments

x	An asa_result object
...	Additional arguments (ignored)

Value

Invisibly returns the object

print.asa_search	<i>Print Method for asa_search Objects</i>
------------------	--

Description

Print Method for asa_search Objects

Usage

```
## S3 method for class 'asa_search'  
print(x, ...)
```

Arguments

x	An asa_search object
...	Additional arguments (ignored)

print.asa_temporal	<i>Print Method for asa_temporal Objects</i>
--------------------	--

Description

Print Method for asa_temporal Objects

Usage

```
## S3 method for class 'asa_temporal'  
print(x, ...)
```

Arguments

x	An asa_temporal object
...	Additional arguments (ignored)

Value

Invisibly returns the object

print.asa_tor	<i>Print Method for asa_tor Objects</i>
---------------	---

Description

Print Method for asa_tor Objects

Usage

```
## S3 method for class 'asa_tor'  
print(x, ...)
```

Arguments

x	An asa_tor object
...	Additional arguments (ignored)

Value

Invisibly returns the object

process_outputs	<i>Process Multiple Agent Outputs</i>
-----------------	---------------------------------------

Description

Processes a data frame of raw agent outputs, extracting structured data.

Usage

```
process_outputs(df, parallel = FALSE, workers = 10L)
```

Arguments

df	Data frame with a 'raw_output' column containing agent traces
parallel	Use parallel processing
workers	Number of workers

Value

The input data frame with additional extracted columns: search_count, wiki_count, and any JSON fields found

reset_agent	<i>Reset the Agent</i>
-------------	------------------------

Description

Clears the initialized agent state, forcing reinitialization on next use. Also closes any open HTTP clients to prevent resource leaks.

Usage

```
reset_agent()
```

Value

Invisibly returns NULL

rotate_tor_circuit	<i>Rotate Tor Circuit (R-side, daemon restart)</i>
--------------------	--

Description

Requests a new Tor circuit by restarting the Tor service or sending SIGHUP.

Usage

```
rotate_tor_circuit(  
    method = c("signal", "brew", "systemctl"),  
    wait = 12L,  
    pid = NULL  
)
```

Arguments

method	Method to restart: "brew" (macOS), "systemctl" (Linux), or "signal"
wait	Seconds to wait for new circuit (default: 12)
pid	Optional PID of specific Tor process (only used with method="signal"). If NULL (default), finds the Tor process via pgrep.

Details

MEDIUM FIX: This function restarts the entire Tor daemon, which kills ALL circuits and affects parallel execution. For production use, prefer the Python-side control port rotation which sends SIGNAL NEWNYM to get a new circuit without restarting the daemon.

For parallel Tor setups with multiple instances, consider using Tor’s built-in circuit rotation via MaxCircuitDirtiness and NewCircuitPeriod config options instead of this function.

Value

Invisibly returns TRUE on success, FALSE on failure

Note

The "brew" and "systemctl" methods restart the entire Tor daemon and should only be used as a last resort for recovery. The "signal" method is preferred but still affects all circuits on the process.

Examples

```
## Not run:
# Preferred: Use Python-side control port rotation (via run_task/asa_enumerate)
# This R function is for manual recovery only

# Send SIGHUP to Tor process (least disruptive)
rotate_tor_circuit(method = "signal")

# macOS with Homebrew (restarts daemon - use sparingly)
rotate_tor_circuit(method = "brew")

# Linux with systemd (restarts daemon - use sparingly)
rotate_tor_circuit(method = "systemctl")

## End(Not run)
```

run_task	<i>Run a Structured Task with the Agent</i>
----------	---

Description

Executes a research task using the AI search agent with a structured prompt and returns parsed results. This is the primary function for running agent tasks.

Usage

```
run_task(
  prompt,
  output_format = "text",
  temporal = NULL,
  config = NULL,
  agent = NULL,
  expected_fields = NULL,
  thread_id = NULL,
  verbose = FALSE
)
```

Arguments

prompt	The task prompt or question for the agent to research
output_format	Expected output format. One of: <ul style="list-style-type: none">• "text": Returns response text (default)• "json": Parse response as JSON• "raw": Include full trace in result for debugging• Character vector: Extract specific fields from response

temporal	Named list or <code>asa_temporal</code> object for temporal filtering: <ul style="list-style-type: none"> • <code>time_filter</code>: DuckDuckGo time filter - "d" (day), "w" (week), "m" (month), "y" (year) • <code>after</code>: ISO 8601 date (e.g., "2020-01-01") - hint for results after this date (added to prompt context) • <code>before</code>: ISO 8601 date (e.g., "2024-01-01") - hint for results before this date (added to prompt context)
config	An <code>asa_config</code> object for unified configuration, or NULL to use defaults
agent	An <code>asa_agent</code> object from <code>initialize_agent</code> , or NULL to use the currently initialized agent
expected_fields	Optional character vector of field names expected in JSON output. When provided, validates that all fields are present and non-null. The result will include a <code>parsing_status</code> field with validation details.
thread_id	Optional stable identifier for memory folding sessions. When provided, the same thread ID is reused so folded summaries persist across invocations. Defaults to NULL (new thread each call).
verbose	Print progress messages (default: FALSE)

Details

This function provides the primary interface for running research tasks. For simple text responses, use `output_format = "text"`. For structured outputs, use `output_format = "json"` or specify field names to extract. For debugging and full trace access, use `output_format = "raw"`.

When temporal filtering is specified, the search tool's time filter is temporarily set for this task and restored afterward. Date hints (after/before) are appended to the prompt to guide the agent's search behavior.

Value

An `asa_result` object with:

- `prompt`: The original prompt
- `message`: The agent's response text
- `parsed`: Parsed output (list for JSON/field extraction, NULL for text/raw)
- `raw_output`: Full agent trace (always included, verbose for "raw" format)
- `elapsed_time`: Execution time in minutes
- `status`: "success" or "error"
- `search_tier`: Which search tier was used ("primp", "selenium", etc.)
- `parsing_status`: Validation result (if `expected_fields` provided)
- `trace`: Full execution trace (for "raw" `output_format`)
- `fold_count`: Number of memory folds (for "raw" `output_format`)

See Also

[initialize_agent](#), [run_task_batch](#), [asa_config](#), [temporal_options](#)

Examples

```
## Not run:
# Initialize agent first
agent <- initialize_agent(backend = "openai", model = "gpt-4.1-mini")

# Simple text query
result <- run_task(
  prompt = "What is the capital of France?",
  output_format = "text",
  agent = agent
)
print(result$message)

# JSON structured output
result <- run_task(
  prompt = "Find information about Albert Einstein and return JSON with
           fields: birth_year, death_year, nationality, field_of_study",
  output_format = "json",
  agent = agent
)
print(result$parsed)

# Raw output for debugging (includes full trace in asa_result)
result <- run_task(
  prompt = "Search for information",
  output_format = "raw",
  agent = agent
)
cat(result$trace) # View full agent trace

# With temporal filtering (past year only)
result <- run_task(
  prompt = "Find recent AI research breakthroughs",
  temporal = temporal_options(time_filter = "y"),
  agent = agent
)

# With date range hint
result <- run_task(
  prompt = "Find tech companies founded recently",
  temporal = list(
    time_filter = "y",
    after = "2020-01-01",
    before = "2024-01-01"
  ),
  agent = agent
)

# Using asa_config for unified configuration
config <- asa_config(
  backend = "openai",
  model = "gpt-4.1-mini",
  temporal = temporal_options(time_filter = "y")
)
result <- run_task(prompt, config = config)
```

```
## End(Not run)
```

run_task_batch	<i>Run Multiple Tasks in Batch</i>
----------------	------------------------------------

Description

Executes multiple research tasks, optionally in parallel. Includes a circuit breaker that monitors error rates and pauses execution if errors spike, preventing cascading failures.

Usage

```
run_task_batch(  
  prompts,  
  output_format = "text",  
  temporal = NULL,  
  agent = NULL,  
  parallel = FALSE,  
  workers = 4L,  
  progress = TRUE,  
  circuit_breaker = TRUE,  
  abort_on_trip = FALSE  
)
```

Arguments

prompts	Character vector of task prompts, or a data frame with a 'prompt' column
output_format	Expected output format (applies to all tasks)
temporal	Named list for temporal filtering (applies to all tasks). See run_task for details.
agent	An asa_agent object
parallel	Use parallel processing
workers	Number of parallel workers
progress	Show progress messages
circuit_breaker	Enable circuit breaker for error rate monitoring. When enabled, tracks recent error rates and pauses if threshold exceeded. Default TRUE.
abort_on_trip	If TRUE, abort the batch when circuit breaker trips. If FALSE (default), wait for cooldown and continue.

Value

A list of asa_result objects, or if prompts was a data frame, the data frame with result columns added. If circuit breaker aborts, includes attribute "circuit_breaker_aborted" = TRUE.

See Also

[run_task](#), [configure_temporal](#)

Examples

```
## Not run:
prompts <- c(
  "What is the population of Tokyo?",
  "What is the population of New York?",
  "What is the population of London?"
)
results <- run_task_batch(prompts, agent = agent)

# With temporal filtering for all tasks
results <- run_task_batch(
  prompts,
  temporal = list(time_filter = "y"),
  agent = agent
)

# Disable circuit breaker
results <- run_task_batch(prompts, agent = agent, circuit_breaker = FALSE)

# Abort on circuit breaker trip
results <- run_task_batch(prompts, agent = agent, abort_on_trip = TRUE)

## End(Not run)
```

search_options

*Create Search Options***Description**

Creates search configuration for controlling DuckDuckGo search behavior, including rate limiting, retry policies, and result limits. These options are used by the 4-tier search fallback system.

Usage

```
search_options(
  max_results = NULL,
  timeout = NULL,
  max_retries = NULL,
  retry_delay = NULL,
  backoff_multiplier = NULL,
  inter_search_delay = NULL
)
```

Arguments

max_results	Maximum number of search results to return per query. Higher values provide more context but increase latency. Default: 10.
timeout	Timeout in seconds for individual search requests. Applies to each tier attempt separately. Default: 15.
max_retries	Maximum number of retry attempts when a search tier fails. After exhausting retries, the system falls back to the next tier. Default: 3.

retry_delay	Initial delay in seconds before the first retry. Subsequent retries use exponential backoff. Default: 2.
backoff_multiplier	Multiplier for exponential backoff between retries. E.g., with retry_delay=2 and multiplier=1.5, delays are 2s, 3s, 4.5s. Default: 1.5.
inter_search_delay	Minimum delay in seconds between consecutive searches. Helps avoid rate limiting from search providers. Default: 0.5.

Details

The search system uses a 4-tier fallback architecture:

1. **PRIMP**: HTTP/2 with browser TLS fingerprint
2. **Selenium**: Headless browser for JS-rendered content
3. **DDGS**: Standard ddgs Python library
4. **Requests**: Raw POST to DuckDuckGo HTML endpoint

The retry/backoff settings apply within each tier. If all retries are exhausted, the system automatically falls back to the next tier.

Value

An object of class `asa_search`

See Also

[asa_config](#), [configure_search](#)

Examples

```
## Not run:
# Default settings
search <- search_options()

# More aggressive settings for faster searches
search <- search_options(
  max_results = 5,
  timeout = 10,
  max_retries = 2
)

# Conservative settings for rate-limited environments
search <- search_options(
  inter_search_delay = 2.0,
  max_retries = 5,
  backoff_multiplier = 2.0
)

# Use with asa_config
config <- asa_config(
  backend = "openai",
  search = search_options(max_results = 15)
)
```



```
## End(Not run)
```

summary.asa_agent	<i>Summary Method for asa_agent Objects</i>
-------------------	---

Description

Summary Method for asa_agent Objects

Usage

```
## S3 method for class 'asa_agent'  
summary(object, ...)
```

Arguments

object	An asa_agent object
...	Additional arguments (ignored)

Value

Invisibly returns a summary list

summary.asa_audit_result	<i>Summary Method for asa_audit_result Objects</i>
--------------------------	--

Description

Summary Method for asa_audit_result Objects

Usage

```
## S3 method for class 'asa_audit_result'  
summary(object, ...)
```

Arguments

object	An asa_audit_result object
...	Additional arguments (ignored)

Value

Invisibly returns a summary list

`summary.asa_enumerate_result`*Summary Method for asa_enumerate_result Objects*

Description

Summary Method for asa_enumerate_result Objects

Usage

```
## S3 method for class 'asa_enumerate_result'  
summary(object, ...)
```

Arguments

<code>object</code>	An asa_enumerate_result object
<code>...</code>	Additional arguments (ignored)

Value

Invisibly returns a summary list

`summary.asa_response` *Summary Method for asa_response Objects*

Description

Summary Method for asa_response Objects

Usage

```
## S3 method for class 'asa_response'  
summary(object, show_trace = FALSE, ...)
```

Arguments

<code>object</code>	An asa_response object
<code>show_trace</code>	Include full trace in output
<code>...</code>	Additional arguments (ignored)

Value

Invisibly returns a summary list

summary.asa_result	<i>Summary Method for asa_result Objects</i>
--------------------	--

Description

Summary Method for asa_result Objects

Usage

```
## S3 method for class 'asa_result'
summary(object, ...)
```

Arguments

object	An asa_result object
...	Additional arguments (ignored)

Value

Invisibly returns a summary list

temporal_options	<i>Create Temporal Filtering Options</i>
------------------	--

Description

Creates a temporal filtering configuration for constraining search results by date. Supports DuckDuckGo time filters, date ranges, and strict verification modes.

Usage

```
temporal_options(
  time_filter = NULL,
  after = NULL,
  before = NULL,
  strictness = "best_effort",
  use_wayback = FALSE
)
```

Arguments

time_filter	DuckDuckGo time filter: "d" (day), "w" (week), "m" (month), "y" (year), or NULL for no filter
after	ISO 8601 date string (e.g., "2020-01-01") - results after this date
before	ISO 8601 date string (e.g., "2024-01-01") - results before this date
strictness	Verification level: "best_effort" (default) or "strict"
use_wayback	Use Wayback Machine for strict pre-date guarantees

Details

Temporal filtering can operate at different levels:

- **time_filter**: DuckDuckGo native filter (fast, approximate)
- **after/before**: Date hints appended to prompts
- **strict**: Post-hoc verification of result dates
- **use_wayback**: Uses Internet Archive for guaranteed historical data

Value

An object of class `asa_temporal`

See Also

[asa_config](#), [run_task](#)

Examples

```
## Not run:
# Past year only
temporal <- temporal_options(time_filter = "y")

# Specific date range
temporal <- temporal_options(
  after = "2020-01-01",
  before = "2024-01-01"
)

# Strict historical verification
temporal <- temporal_options(
  before = "2015-01-01",
  strictness = "strict",
  use_wayback = TRUE
)

## End(Not run)
```

tor_options	<i>Tor Options</i>
-------------	--------------------

Description

Configure shared Tor exit tracking for healthier circuit rotation.

Usage

```
tor_options(
  registry_path = NULL,
  dirty_tor_exists = ASA_TOR_REGISTRY_ENABLED,
  bad_ttl = ASA_TOR_BAD_TTL,
  good_ttl = ASA_TOR_GOOD_TTL,
```

```

    overuse_threshold = ASA_TOR_OVERUSE_THRESHOLD,
    overuse_decay = ASA_TOR_OVERUSE_DECAY,
    max_rotation_attempts = ASA_TOR_MAX_ROTATION_ATTEMPTS,
    ip_cache_ttl = ASA_TOR_IP_CACHE_TTL
)

```

Arguments

registry_path	Path to the shared SQLite registry file (default: user cache).
dirty_tor_exists	Enable the registry (tracks good/bad/overused exits).
bad_ttl	Seconds to keep a bad/tainted exit before reuse (default: 3600).
good_ttl	Seconds to treat an exit as good before refreshing (default: 1800).
overuse_threshold	Max recent uses before a good exit is considered overloaded.
overuse_decay	Window (seconds) for overuse counting before decaying.
max_rotation_attempts	Max attempts to find a clean exit before giving up.
ip_cache_ttl	Seconds to cache exit IP lookups.

Value

An object of class `asa_tor`

write_csv.asa_enumerate_result	<i>Write asa_enumerate_result to CSV</i>
--------------------------------	--

Description

Write `asa_enumerate_result` to CSV

Usage

```
write_csv.asa_enumerate_result(x, file, include_provenance = FALSE, ...)
```

Arguments

x	An <code>asa_enumerate_result</code> object
file	Path to output CSV file
include_provenance	Include provenance as additional columns
...	Additional arguments passed to <code>write.csv</code>

Value

Invisibly returns the file path

Index

as.data.frame.asa_audit_result, 3
as.data.frame.asa_enumerate_result, 3
as.data.frame.asa_result, 4
asa_agent, 4
asa_audit, 5
asa_audit_result, 7
asa_config, 8, 36, 40, 44
asa_enumerate, 9, 20
asa_enumerate_result, 13
asa_response, 13
asa_result, 14

build_backend, 15
build_prompt, 16

check_backend, 17
configure_search, 17, 40
configure_search_logging, 19
configure_temporal, 20, 38
configure_tor_registry, 21

extract_agent_results, 22
extract_search_snippets, 22
extract_search_tiers, 23
extract_urls, 24
extract_wikipedia_content, 24

get_agent, 25
get_tor_ip, 25

initialize_agent, 11, 26, 36
is_tor_running, 28

print.asa_agent, 29
print.asa_audit_result, 29
print.asa_config, 30
print.asa_enumerate_result, 30
print.asa_response, 31
print.asa_result, 31
print.asa_search, 32
print.asa_temporal, 32
print.asa_tor, 33
process_outputs, 33

reset_agent, 34

rotate_tor_circuit, 34
run_task, 11, 20, 27, 35, 38, 44
run_task_batch, 27, 36, 38

search_options, 9, 39
summary.asa_agent, 41
summary.asa_audit_result, 41
summary.asa_enumerate_result, 42
summary.asa_response, 42
summary.asa_result, 43

temporal_options, 9, 36, 43
tor_options, 27, 44

write_csv.asa_enumerate_result, 45