

Package ‘fastrerandomize’

September 25, 2023

Title fastrerandomize: R Package for Ultra-fast Re-randomization Using a JAX Backend

Version 0.1

Authors 'Connor Jerzak <connor.jerzak@gmail.com> [aut, cre], Rebecca Goldstein <rgoldstein@berkeley.edu> [aut]'

Description An R Package for Ultra-fast Re-randomization Using a JAX Backend

Depends R (>= 3.3.3)

License

Creative Commons Attribution-Noncommercial-No Derivative Works 4.0, for academic use only.

Encoding UTF-8

LazyData false

Maintainer 'Connor Jerzak' <connor.jerzak@gmail.com>

Imports reticulate

RoxygenNote 7.2.3

R topics documented:

GenerateCausalData	1
InitializeJAX	2
InitializeJAXFxns	3
RandomizationTest	4

Index	6
--------------	----------

GenerateCausalData	<i>This function generates simulated causal data based on specified parameters.</i>
--------------------	---

Description

This function generates simulated causal data based on specified parameters.

Usage

GenerateCausalData(n_units)

Arguments

<code>n_units</code>	A numeric value specifying the total number of units in the sample.
<code>proportion_treated</code>	A numeric value between 0 and 1 indicating the proportion of units that receive treatment.
<code>k_covars</code>	A numeric value indicating the number of covariates to be generated.
<code>rho</code>	A numeric value representing the correlation coefficient.
<code>SD_inherent</code>	A numeric value indicating the standard deviation inherent to the data.
<code>treatment_effect_mean</code>	A numeric value representing the mean of the treatment effect.
<code>treatment_effect_SD</code>	A numeric value indicating the standard deviation of the treatment effect.
<code>covariates_SD</code>	A numeric value or vector specifying the standard deviation of the covariates.
<code>Y0_coefficients</code>	An optional numeric vector specifying the coefficients for the control outcome model. If not provided, the function assumes a NULL value.
<code>Y1_coefficients</code>	An optional numeric vector specifying the coefficients for the treated outcome model. If not provided, the function assumes a NULL value.

Value

A list consisting of

- `data_matrix` A data frame containing the simulated covariates and outcomes for both control (Y0) and treatment (Y1) groups.
- `Y0_coefficients` A numeric vector representing the coefficients used for the control outcome model.
- `Y1_coefficients` A numeric vector representing the coefficients used for the treated outcome model.

Examples

```
# For a tutorial, see
# github.com/cjerzak/fastrerandomization-software
```

InitializeJAX

Initialize JAX

Description

Initialize JAX

Usage

```
InitializeJax(conda_env, conda_env_required)
```

Arguments

- conda_env A character string representing the conda environment to activate. A version of JAX should live in that environment.
- conda_env_required A logical representing whether to force use the specified conda environment.

Value

This function initializes a JAX-containing conda environment as specified by conda_env. This function must be run before any others in fastrerandomize.

Examples

```
# For a tutorial, see
# github.com/cjerkzak/fastrerandomization-software
```

InitializeJAXFxns	<i>Initialize JAX functions</i>
-------------------	---------------------------------

Description

Initialize JAX functions

Usage

```
InitializeJAXFxns()
```

Arguments

... This function takes no arguments

Value

This function should be run just after fastrerandomize::InitializeJax. This sets up the internal JAX functions for rerandomization analysis.

Examples

```
# For tutorials, see
# github.com/cjerkzak/fastrerandomization-software
```

RandomizationTest	<i>Fast randomization test</i>
-------------------	--------------------------------

Description

Fast randomization test

Usage

RandomizationTest(X, ...)

Arguments

obsW	A numeric vector where 0's correspond to control units and 1's to treated units.
obsY	An optional numeric vector of observed outcomes. If not provided, the function assumes a NULL value.
X	A numeric matrix of covariates.
alpha	The significance level for the test. Default is 0.05.
candidate_randomizations	A numeric matrix of candidate randomizations.
candidate_randomizations_array	An optional JAX array of candidate randomizations. If not provided, the function coerces candidate_randomizations into a JAX array.
n0_array	An optional array specifying the number of control units.
n1_array	An optional array specifying the number of treated units.
prior_treatment_effect_mean	An optional numeric value for the prior mean of the treatment effect. Default is NULL.
prior_treatment_effect_SD	An optional numeric value for the prior standard deviation of the treatment effect. Default is NULL.
true_treatment_effect	An optional numeric value specifying the true treatment effect. Default is NULL.
simulate	A logical value indicating whether to run RandomizationTest in simulation mode. Default is FALSE.
coef_prior	An optional function generating coefficients on values of X for predicting $Y(0)$.
nSimulate_obsW	A numeric value specifying the number of simulated values for obsW. Default is 50L.
nSimulate_obsY	A numeric value specifying the number of simulated values for obsY. Default is 50L.
randomization_accept_prob	An numeric scalar or vector of probabilities for accepting each randomization.
findFI	A logical value indicating whether to find the fiducial interval. Default is FALSE.
c_initial	A numeric value representing the initial criterion for the randomization. Default is 2.

Value

A list consisting of

- `p_value` A numeric value or vector representing the p-value of the test (or the expected p-value under the prior structure specified in the function inputs).
- `FI` A numeric vector representing the fiducial interval if `findFI=T`.
- `tau_obs` A numeric value or vector representing the estimated treatment effect(s)

References

-

Examples

```
# For a tutorial, see  
# github.com/cjerzak/fastrerandomization-software
```

Index

`GenerateCausalData`, [1](#)

`InitializeJAX`, [2](#)

`InitializeJAXFxn`s, [3](#)

`RandomizationTest`, [4](#)