

# Package ‘fastrerandomize’

December 14, 2025

**Title** Hardware-Accelerated Rerandomization for Improved Balance

**Version** 0.3

**Description** Provides hardware-accelerated tools for performing rerandomization and randomization testing in experimental research. Using a 'JAX' backend, the package enables exact rerandomization inference even for large experiments with hundreds of billions of possible randomizations. Key functionalities include generating pools of acceptable rerandomizations based on covariate balance, conducting exact randomization tests, and performing pre-analysis evaluations to determine optimal rerandomization acceptance thresholds. The package supports various hardware acceleration frameworks including 'CPU', 'CUDA', and 'METAL', making it versatile across accelerated computing environments. This allows researchers to efficiently implement stringent rerandomization designs and conduct valid inference even with large sample sizes. The package is partly based on Jerzak and Goldstein (2023) <[doi:10.48550/arXiv.2310.00861](https://doi.org/10.48550/arXiv.2310.00861)>.

**URL** <https://github.com/cjerzak/fastrerandomize-software>

**BugReports** <https://github.com/cjerzak/fastrerandomize-software/issues>

**Depends** R (>= 3.5.0)

**License** GPL-3

**Encoding** UTF-8

**LazyData** false

**Imports** reticulate, assertthat, utils, stats, graphics

**Suggests** knitr, rmarkdown

**VignetteBuilder** knitr

**RoxygenNote** 7.3.3

**RemoteType** local

**RemotePkgRef** local::~~/Documents/fastrerandomize-software/fastrerandomize

**RemoteUrl** /Users/cjerzak/Documents/fastrerandomize-software/fastrerandomize

**NeedsCompilation** no

**Author** Fucheng Warren Zhu [aut] (ORCID:  
<<https://orcid.org/0009-0001-5692-7572>>),  
Aniket Sachin Kamat [aut] (ORCID:  
<<https://orcid.org/0009-0003-6411-1084>>),  
Connor Jerzak [aut, cre] (ORCID:  
<<https://orcid.org/0000-0003-1914-8905>>),

Rebecca Goldstein [aut] (ORCID:  
[<https://orcid.org/0000-0002-9944-8440>](https://orcid.org/0000-0002-9944-8440))

**Maintainer** Connor Jerzak <connor.jerzak@gmail.com>

## Contents

build_backend . . . . .	2
check_jax_availability . . . . .	3
compute_diff_at_tau_for_oneW_R . . . . .	4
diagnose_rerandomization . . . . .	4
diff_in_means_R . . . . .	6
fastrandomize_class . . . . .	7
fastrandomize_test . . . . .	8
fast_distance . . . . .	8
find_fiducial_interval_R . . . . .	10
generate_randomizations . . . . .	11
generate_randomizations_exact . . . . .	13
generate_randomizations_mc . . . . .	15
generate_randomizations_R . . . . .	17
hotellingT2_R . . . . .	18
plot.fastrandomize_randomizations . . . . .	19
plot.fastrandomize_test . . . . .	19
print.fastrandomize_randomizations . . . . .	20
print.fastrandomize_test . . . . .	20
print2 . . . . .	21
QJEData . . . . .	22
randomization_test . . . . .	23
randomization_test_R . . . . .	25
summary.fastrandomize_randomizations . . . . .	25
summary.fastrandomize_test . . . . .	26
YOPData . . . . .	26

<b>Index</b>	<b>27</b>
--------------	-----------

---

build_backend	<i>A function to build the environment for fastrandomize. Builds a conda environment in which 'JAX' and 'np' are installed. Users can also create a conda environment where 'JAX' and 'np' are installed themselves.</i>
---------------	--

---

## Description

A function to build the environment for fastrandomize. Builds a conda environment in which 'JAX' and 'np' are installed. Users can also create a conda environment where 'JAX' and 'np' are installed themselves.

## Usage

```
build_backend(conda_env = "fastrandomize_env", conda = "auto")
```

**Arguments**

conda_env	(default = "fastrerandomize_env") Name of the conda environment in which to place the backends.
conda	(default = auto) The path to a conda executable. Using "auto" allows reticulate to attempt to automatically find an appropriate conda binary.

**Value**

Invisibly returns NULL; this function is used for its side effects of creating and configuring a conda environment for fastrerandomize. This function requires an Internet connection. You can find out a list of conda Python paths via: `Sys.which("python")`

**Examples**

```
## Not run:
# Create a conda environment named "fastrerandomize_env"
# and install the required Python packages (jax, numpy, etc.)
build_backend(conda_env = "fastrerandomize_env", conda = "auto")

# If you want to specify a particular conda path:
# build_backend(conda_env = "fastrerandomize_env", conda = "/usr/local/bin/conda")

## End(Not run)
```

---

check\_jax\_availability

*Check if 'Python' and 'JAX' are available*

---

**Description**

This function checks if 'Python' and 'JAX' can be accessed via 'reticulate'. If not, it returns 'NULL' and prints a message suggesting to run 'build\_backend()'.

**Usage**

```
check_jax_availability(conda_env = "fastrerandomize_env", conda = "auto")
```

**Arguments**

conda_env	A character string specifying the name of the conda environment. Default is "fastrerandomize_env".
conda	The path to a conda executable, or "auto". Default is "auto".

**Value**

Returns 'TRUE' (invisibly) if both 'Python' and 'JAX' are available; otherwise returns 'NULL'.

**Examples**

```
## Not run:
  check_jax_availability()

## End(Not run)
```

---

```
compute_diff_at_tau_for_oneW_R
```

*Compute potential outcome difference in means for a single assignment under a hypothesized tau in base R*

---

**Description**

Compute potential outcome difference in means for a single assignment under a hypothesized tau in base R

**Usage**

```
compute_diff_at_tau_for_oneW_R(Wprime, obsY, obsW, tau)
```

**Arguments**

Wprime	A 0/1 assignment vector for which to compute the diff in means.
obsY	Observed outcome vector.
obsW	Observed assignment vector.
tau	The hypothesized true effect for the shift in outcomes under treatment.

**Value**

Scalar difference in means for the assignment Wprime.

---

```
diagnose_rerandomization
```

*Diagnostic map from observed (or targeted) balance to precision and stringency*

---

**Description**

Implements the calculations in Theorem 1 and Appendix D of the paper involving: (1) Realized RMSE from an observed Mahalanobis distance  $M$  (or SMDs); (2) Ex-ante RMSE when accepting assignments with  $M < a$  (equivalently, with acceptance probability  $q$  under complete randomization); (3) largest acceptance probability  $q$  that attains a user-specified precision goal, provided via an RMSE target or via a power target ( $\alpha$ ,  $1-\beta$ ,  $l_{\text{tau}}$ ).

**Usage**

```
diagnose_rerandomization(
  smd = NULL,
  M = NULL,
  d = NULL,
  n_T,
  n_C,
  sigma = NULL,
  R2 = NULL,
  rmse_goal = NULL,
  tau = NULL,
  alpha = 0.05,
  power = 0.8,
  two_sided = TRUE,
  q_min = 1e-09,
  q_tol = 1e-10
)
```

**Arguments**

smd	Optional numeric vector of standardized mean differences; if supplied, M is computed as $\text{sum}(\text{smd}^2)$ , and $d = \text{length}(\text{smd})$ .
M	Optional scalar Mahalanobis distance M; if provided without 'smd', you must also supply 'd' (the number of covariates used in M).
d	Optional integer number of covariates (needed if supplying only 'M').
n_T	Integer, number of treated units.
n_C	Integer, number of control units.
sigma	Optional outcome noise SD (sigma). If 'NULL', absolute RMSEs cannot be formed; dimensionless "per-sigma" factors are still returned.
R2	Optional model $R^2$ for $Y \sim X$ under the linear potential-outcomes model. Must lie in $[0,1)$ . If 'NULL', RMSEs that require $R^2$ are returned as NA, but the "per-sigma" formulas that do not need $R^2$ are still shown when possible.
rmse_goal	Optional numeric target for RMSE (same units as Y). If supplied (with sigma and R2), the largest q achieving this ex-ante goal is returned.
tau	Optional effect size $\text{ltail}$ (same units as Y) to back out an RMSE goal via a normal approximation to power.
alpha	Size of a two-sided test (default 0.05).
power	Desired power $1 - \beta$ (default 0.80). Used only if 'tau' is given.
two_sided	Logical; if FALSE, uses a one-sided z-threshold for power inversion.
q_min	Lower bound for numerical search over q (default $1e-9$ ).
q_tol	Absolute tolerance for q root-finding (default $1e-10$ ).

**Details**

Realized (conditional) RMSE: with standardized/whitened X and typical orientation,

$$\text{RMSE}_{\text{realized}} \approx \sqrt{\sigma^2 \left( \frac{1}{n_T} + \frac{1}{n_C} \right) + \frac{\sigma_{\text{Prog}}^2}{d} M} = \sigma \sqrt{\left( \frac{1}{n_T} + \frac{1}{n_C} \right) + \frac{R^2}{1 - R^2} \frac{M}{d}},$$

and the conservative upper bound replaces  $\sigma_{\text{Prog}}^2/d$  by  $\sigma_{\text{Prog}}^2$ .

Ex-ante (design-stage) RMSE under thresholding: with acceptance rule  $M \leq a$  (acceptance probability  $q$ ),

$$\mathbb{E}[\text{MSE} \mid M \leq a] = \left( \frac{1}{n_T} + \frac{1}{n_C} \right) (\sigma^2 + v_a(d) \sigma_{\text{Prog}}^2),$$

where  $v_a(d) = \Pr(\chi_{d+2}^2 \leq c) / \Pr(\chi_d^2 \leq c)$  and  $c = a / (\frac{1}{n_T} + \frac{1}{n_C})$ . Since  $q = \Pr(\chi_d^2 \leq c)$ , we can parameterize by  $q$ :  $v(q; d) = \Pr(\chi_{d+2}^2 \leq \chi_{d;q}^2) / q$ , with  $\chi_{d;q}^2$  the  $q$ -th quantile.

Power inversion (Appendix D): for two-sided size  $\alpha$  and power  $1 - \beta$ , a normal approximation suggests the RMSE goal  $|\tau| / (z_{1-\alpha/2} + z_{1-\beta})$ .

## Value

A list of class “fastrerandomize\_diagnostic” with elements:

- inputs: Echo of parsed inputs and derived quantities ( $M$ ,  $d$ ,  $S=1/n_T+1/n_C$ ).
- realized: rmse\_factor (dimensionless, per sigma), rmse, and conservative rmse\_upper\_factor, rmse\_upper.
- power\_check: If tau, alpha, power, sigma, R2 are given, includes z\_needed, z\_realized, and already\_sufficient.
- recommendation: If a target is supplied (via rmse\_goal or tau), returns q\_star, a\_star, v\_star, rmse\_exante, expected\_M\_accepted, and expected\_draws\_per\_accept =  $1/q_{\text{star}}$ .

## Examples

```
# Example 1: observed SMDs, realized precision only (dimensionless factors)
smd <- c(0.10, -0.05, 0.08, 0.02) # standardized mean differences
out1 <- diagnose_rerandomization(smd = smd, n_T = 100, n_C = 100)
print(out1)

# Example 2: same, but supply sigma and R^2 for absolute RMSE
out2 <- diagnose_rerandomization(smd = smd, n_T = 100, n_C = 100, sigma = 1.2, R2 = 0.4)

# Example 3: choose q to hit a power target (two-sided alpha=.05, 80% power, |tau|=0.2)
out3 <- diagnose_rerandomization(smd = smd, n_T = 100, n_C = 100, sigma = 1.2, R2 = 0.4,
                                tau = 0.2, alpha = 0.05, power = 0.80)

# Analyze rerandomization recommendation given contextual factors
out3$recommendation

# Example 4: choose q to hit an absolute RMSE goal directly
out4 <- diagnose_rerandomization(M = sum(smd^2), d = length(smd), n_T = 100, n_C = 100,
                                sigma = 1.2, R2 = 0.4, rmse_goal = 0.25)
```

---

diff\_in\_means\_R

*Simple difference in means in base R*

---

## Description

Simple difference in means in base R

**Usage**

```
diff_in_means_R(Y, W)
```

**Arguments**

Y	Numeric outcome vector.
W	0/1 treatment assignment vector.

**Value**

Scalar difference in means:  $\text{mean}(Y|W=1) - \text{mean}(Y|W=0)$ .

---

`fastrerandomize_class` *Constructor for fastrerandomize randomizations*

---

**Description**

Create an S3 object of class `fastrerandomize_randomizations` that stores the randomizations (and optionally balance statistics) generated by functions such as [generate\\_randomizations](#).

**Usage**

```
fastrerandomize_class(  
  randomizations,  
  balance = NULL,  
  fastrr_env = NULL,  
  call = NULL  
)
```

**Arguments**

randomizations	A matrix or array where each row (or slice) represents one randomization.
balance	A numeric vector or similar object holding balance statistics for each randomization, or NULL if not applicable.
fastrr_env	Associated <code>fastrr_env</code> environment.
call	The function call, if you wish to store it for reference (optional).

**Value**

An object of class `fastrerandomize_randomizations`.

---

fastrerandomize_test	<i>Constructor for fastrerandomize randomization test objects</i>
----------------------	---

---

### Description

Constructor for fastrerandomize randomization test objects

### Usage

```
fastrerandomize_test(p_value, FI, tau_obs, fastrr_env = NULL, call = NULL, ...)
```

### Arguments

p_value	A numeric value representing the p-value of the test.
FI	A numeric vector (length 2) representing the fiducial interval, or NULL if not requested.
tau_obs	A numeric value (or vector) representing the estimated treatment effect.
fastrr_env	Associated 'fastrr_env' environment.
call	An optional function call, stored for reference.
...	Other slots you may want to store (e.g. additional diagnostics).

### Value

An object of class fastrerandomize\_test.

---

fast_distance	<i>JAX-accelerated distance calculations</i>
---------------	--

---

### Description

Compute pairwise distances between the rows of one matrix A or two matrices A and B, using JAX-backed, JIT-compiled kernels. Supports common metrics: Euclidean, squared Euclidean, Manhattan, Chebyshev, Cosine, Minkowski (with optional feature weights), and Mahalanobis (with full or diagonal inverse covariance).

The function automatically batches computations to avoid excessive device memory use.

### Usage

```
fast_distance(
  A,
  B = NULL,
  metric = c("euclidean", "sqeuclidean", "manhattan", "chebyshev", "cosine", "minkowski",
    "mahalanobis"),
  p = 2,
  weights = NULL,
  cov_inv = NULL,
  approximate_inv = TRUE,
  squared = FALSE,
```



```

    row_batch_size = NULL,
    as_dist = FALSE,
    return_type = "R",
    verbose = FALSE,
    conda_env = "fastrerandomize_env",
    conda_env_required = TRUE
)

```

## Arguments

A	A numeric matrix with rows as observations and columns as features.
B	Optional numeric matrix with the same number of columns as A. If NULL, distances are computed within A (i.e., $n \times n$ ).
metric	Character; one of "euclidean", "sqeuclidean", "manhattan", "chebyshev", "cosine", "minkowski", "mahalanobis". Default is "euclidean".
p	Numeric order for Minkowski distance (must be $> 0$ ). Default is 2.
weights	Optional numeric vector of length <code>ncol(A)</code> with nonnegative feature weights. Used for "minkowski" and "manhattan" (the latter is equivalent to Minkowski with $p = 1$ ).
cov_inv	Optional inverse covariance matrix ( $p \times p$ ) for Mahalanobis (ignored if <code>approximate_inv = TRUE</code> ). If not supplied and <code>approximate_inv = FALSE</code> , it is estimated from <code>rbind(A, B)</code> and inverted in JAX.
approximate_inv	Logical; if TRUE and <code>metric = "mahalanobis"</code> , uses a diagonal inverse (reciprocal variances) for speed and robustness. Default TRUE.
squared	Logical; if TRUE, return squared distances when supported ("euclidean" and "mahalanobis"). Ignored for other metrics. Default FALSE.
row_batch_size	Optional integer; number of rows of A to process per batch. If NULL, a safe size is chosen automatically.
as_dist	Logical; if TRUE and B is NULL, return a base <code>dist</code> object (for symmetric metrics). Default FALSE.
return_type	Either "R" (convert to base R matrix/dist) or "jax" (return a JAX array). Default "R".
verbose	Logical; print batching progress. Default FALSE.
conda_env	Character; conda environment name used by reticulate. Default "fastrerandomize_env".
conda_env_required	Logical; whether the specified conda environment must be used. Default TRUE.

## Details

- **Mahalanobis**: with `approximate_inv = TRUE`, the diagonal of the pooled covariance is used (variance stabilizer); otherwise a full inverse covariance is used. - **Weighted distances**: supply `weights` (length  $p$ ) for "minkowski" and "manhattan" (the latter uses  $p = 1$ ). - Computations run in float32 and are JIT-compiled with JAX; where applicable, GPU/Metal/CPU device selection follows your existing backend.

## Value

An  $n \times m$  distance matrix in the format specified by `return_type`. If `as_dist = TRUE` and `B = NULL` (symmetric case), returns a `dist` object.

**See Also**[dist](#)**Examples**

```
## Not run:
# Simple Euclidean within-matrix distances (returns an n x n matrix)
X <- matrix(rnorm(50 * 8), 50, 8)
D <- fast_distance(X, metric = "euclidean")

# Cosine distance between two sets
A <- matrix(rnorm(100 * 16), 100, 16)
B <- matrix(rnorm(120 * 16), 120, 16)
Dcos <- fast_distance(A, B, metric = "cosine")

# Minkowski with p = 3 and feature weights
w <- runif(ncol(A))
Dm3 <- fast_distance(A, B, metric = "minkowski", p = 3, weights = w)

# Mahalanobis (diagonal approx, fast & robust)
Dmah_diag <- fast_distance(X, metric = "mahalanobis", approximate_inv = TRUE)

# Mahalanobis with full inverse (computed internally)
Dmah_full <- fast_distance(X, metric = "mahalanobis", approximate_inv = FALSE)

# Return a base R 'dist' object
D_dist <- fast_distance(X, metric = "euclidean", as_dist = TRUE)

## End(Not run)
```

---

find\_fiducial\_interval\_R

*Fiducial interval logic in base R, for randomization test*


---

**Description**

Fiducial interval logic in base R, for randomization test

**Usage**

```
find_fiducial_interval_R(
  obsW,
  obsY,
  allW,
  tau_obs,
  alpha = 0.05,
  c_initial = 2,
  n_search_attempts = 500
)
```

**Arguments**

obsW	Observed assignment (0/1).
obsY	Observed outcome.
allW	Matrix of candidate random assignments (rows = assignments).
tau_obs	Observed difference in means with obsW, obsY.
alpha	Significance level (default 0.05).
c_initial	A numeric step scale (default 2).
n_search_attempts	Number of bracket search attempts (default 500).

**Value**

2-element numeric vector [lower, upper] or [NA, NA] if none accepted.

---

generate\_randomizations

*Generate randomizations for a rerandomization-based experimental design*

---

**Description**

This function generates randomizations for experimental design using either exact enumeration or Monte Carlo sampling methods. It provides a unified interface to both approaches while handling memory and computational constraints appropriately.

**Usage**

```
generate_randomizations(
  n_units,
  n_treated,
  X = NULL,
  randomization_accept_prob,
  threshold_func = NULL,
  max_draws = 10^6,
  batch_size = 1000,
  randomization_type = "monte_carlo",
  approximate_inv = TRUE,
  file = NULL,
  return_type = "R",
  verbose = TRUE,
  conda_env = "fastrerandomize_env",
  conda_env_required = TRUE
)
```

**Arguments**

n_units	An integer specifying the total number of experimental units.
n_treated	An integer specifying the number of units to be assigned to treatment.
X	A numeric matrix of covariates used for balance checking. Cannot be NULL.
randomization_accept_prob	A numeric value between 0 and 1 specifying the probability threshold for accepting randomizations based on balance.
threshold_func	A 'JAX' function that computes a balance measure for each randomization. Only used for Monte Carlo sampling.
max_draws	An integer specifying the maximum number of randomizations to draw in Monte Carlo sampling.
batch_size	An integer specifying batch size for Monte Carlo processing.
randomization_type	A string specifying the type of randomization: either "exact" or "monte_carlo".
approximate_inv	A logical value indicating whether to use an approximate inverse (diagonal of the covariance matrix) instead of the full matrix inverse when computing balance metrics. This can speed up computations for high-dimensional covariates. Default is TRUE.
file	A string specifying where to save candidate randomizations (if saving, not returning).
return_type	A string specifying the format of the returned randomizations and balance measures. Allowed values are "R" for base R objects (e.g., matrix, numeric) or "jax" for 'JAX' arrays. Default is "R".
verbose	A logical value indicating whether to print progress information. Default is TRUE.
conda_env	A character string specifying the name of the conda environment to use via reticulate. Default is "fastrerandomize_env".
conda_env_required	A logical indicating whether the specified conda environment must be strictly used. If TRUE, an error is thrown if the environment is not found. Default is TRUE.

**Details**

The function supports two methods of generating randomizations:

1. Exact enumeration: Generates all possible randomizations (memory intensive but exact).
2. Monte Carlo sampling: Generates randomizations through sampling (more memory efficient).

For large problems (e.g., X with >20 rows), Monte Carlo sampling is recommended.

**Value**

Returns an S3 object with slots:

- assignments An array where each row represents one possible treatment assignment vector containing the accepted randomizations.
- balance\_measures A numeric vector containing the balance measure for each corresponding randomization.

- `fastrr_env` The `fastrerandomize` environment.
- `file_output` If file is specified, results are saved to the given file path instead of being returned.

### See Also

[generate\\_randomizations\\_exact](#) for the exact enumeration method. [generate\\_randomizations\\_mc](#) for the Monte Carlo sampling method.

### Examples

```
## Not run:
# Generate synthetic data
X <- matrix(rnorm(20*5), 20, 5)

# Generate randomizations using exact enumeration
RandomizationSet_Exact <- generate_randomizations(
  n_units = nrow(X),
  n_treated = round(nrow(X)/2),
  X = X,
  randomization_accept_prob=0.1,
  randomization_type="exact")

# Generate randomizations using Monte Carlo sampling
RandomizationSet_MC <- generate_randomizations(
  n_units = nrow(X),
  n_treated = round(nrow(X)/2),
  X = X,
  randomization_accept_prob = 0.1,
  randomization_type = "monte_carlo",
  max_draws = 100000,
  batch_size = 1000)

## End(Not run)
```

---

generate\_randomizations\_exact

*Generate Complete Randomizations with Optional Balance Constraints*

---

### Description

Generates all possible treatment assignments for a completely randomized experiment, optionally filtering them based on covariate balance criteria. The function can generate either all possible randomizations or a subset that meets specified balance thresholds using Hotelling's T-squared statistic.

### Usage

```
generate_randomizations_exact(
  n_units,
  n_treated,
  X = NULL,
```

```

randomization_accept_prob = 1,
approximate_inv = TRUE,
threshold_func = NULL,
verbose = TRUE,
conda_env = "fasterandomize_env",
conda_env_required = TRUE
)

```

## Arguments

n_units	An integer specifying the total number of experimental units
n_treated	An integer specifying the number of units to be assigned to treatment
X	A numeric matrix of covariates where rows represent units and columns represent different covariates. Default is NULL, in which case all possible randomizations are returned without balance filtering.
randomization_accept_prob	A numeric value between 0 and 1 specifying the quantile threshold for accepting randomizations based on balance statistics. Default is 1 (accept all randomizations).
approximate_inv	A logical value indicating whether to use an approximate inverse (diagonal of the covariance matrix) instead of the full matrix inverse when computing balance metrics. This can speed up computations for high-dimensional covariates. Default is TRUE.
threshold_func	A function that calculates balance statistics for candidate randomizations. Default is VectorizedFastHottel12T2 which computes Hotelling's T-squared statistic.
verbose	A logical value indicating whether to print progress information. Default is TRUE.
conda_env	A character string specifying the name of the conda environment to use via reticulate. Default is "fasterandomize_env".
conda_env_required	A logical indicating whether the specified conda environment must be strictly used. If TRUE, an error is thrown if the environment is not found. Default is TRUE.

## Details

The function works in two main steps: 1. Generates all possible combinations of treatment assignments given n\_units and n\_treated 2. If covariates (X) are provided, filters these combinations based on balance criteria using the specified threshold function

The balance filtering process uses Hotelling's T-squared statistic by default to measure multivariate balance between treatment and control groups. Randomizations are accepted if their balance measure is below the specified quantile threshold.

## Value

The function returns a *list* with two elements: candidate\_randomizations: an array of randomization vectors M\_candidate\_randomizations: an array of their balance measures.

**Note**

This function requires 'JAX' and 'NumPy' to be installed and accessible through the reticulate package.

**References**

Hotelling, H. (1931). The generalization of Student's ratio. The Annals of Mathematical Statistics, 2(3), 360-378.

**See Also**

[generate\\_randomizations](#) for full randomization generation function. [generate\\_randomizations\\_mc](#) for the Monte Carlo version.

**Examples**

```
## Not run:
# Generate synthetic data
X <- matrix(rnorm(60), nrow = 10) # 10 units, 6 covariates

# Generate balanced randomizations with covariates
BalancedRandomizations <- generate_randomizations_exact(
  n_units = 10,
  n_treated = 5,
  X = X,
  randomization_accept_prob = 0.25 # Keep top 25% most balanced
)

## End(Not run)
```

---

generate\_randomizations\_mc

*Draws a random sample of acceptable randomizations from all possible complete randomizations using Monte Carlo sampling*

---

**Description**

This function performs sampling with replacement to generate randomizations in a memory-efficient way. It processes randomizations in batches to avoid memory issues and filters them based on covariate balance. The function uses JAX for fast computation and memory management.

**Usage**

```
generate_randomizations_mc(
  n_units,
  n_treated,
  X,
  randomization_accept_prob = 1,
  threshold_func = NULL,
  max_draws = 1e+05,
  batch_size = 1000,
```

```

    approximate_inv = TRUE,
    verbose = TRUE,
    conda_env = "fastrerandomize_env",
    conda_env_required = TRUE
)

```

## Arguments

<code>n_units</code>	An integer specifying the total number of experimental units.
<code>n_treated</code>	An integer specifying the number of units to be assigned to treatment.
<code>X</code>	A numeric matrix of covariates used for balance checking. Cannot be NULL.
<code>randomization_accept_prob</code>	A numeric value between 0 and 1 specifying the probability threshold for accepting randomizations based on balance. Default is 1
<code>threshold_func</code>	A JAX function that computes a balance measure for each randomization. Must be vectorized using <code>jax.vmap</code> with <code>in_axes = list(NULL, 0L, NULL, NULL)</code> , and inputs <code>covariates</code> (matrix of <code>X</code> ), <code>treatment_assignment</code> (vector of 0s and 1s), <code>n0</code> (scalar), <code>n1</code> (scalar). Default is <code>VectorizedFastHotell12T2</code> which uses Hotelling's T-squared statistic.
<code>max_draws</code>	An integer specifying the maximum number of randomizations to draw.
<code>batch_size</code>	An integer specifying how many randomizations to process at once. Lower values use less memory but may be slower.
<code>approximate_inv</code>	A logical value indicating whether to use an approximate inverse (diagonal of the covariance matrix) instead of the full matrix inverse when computing balance metrics. This can speed up computations for high-dimensional covariates. Default is TRUE.
<code>verbose</code>	A logical value indicating whether to print detailed information about batch processing progress, and GPU memory usage. Default is FALSE.
<code>conda_env</code>	A character string specifying the name of the conda environment to use via <code>reticulate</code> . Default is "fastrerandomize_env".
<code>conda_env_required</code>	A logical indicating whether the specified conda environment must be strictly used. If TRUE, an error is thrown if the environment is not found. Default is TRUE.

## Details

The function works by:

1. Generating batches of random permutations.
2. Computing balance measures for each permutation using the provided threshold function.
3. Keeping only the top permutations that meet the acceptance probability threshold.
4. Managing memory by clearing unused objects and caches between batches.

The function uses smaller data types (int8, float16) where possible to reduce memory usage. It also includes assertions to verify array shapes and dimensions throughout.

## Value

The function returns a *list* with two elements: `candidate_randomizations`: an array of randomization vectors `M_candidate_randomizations`: an array of their balance measures.



**See Also**

[generate\\_randomizations](#) for full randomization generation function. [generate\\_randomizations\\_exact](#) for the exact version.

**Examples**

```
## Not run:
# Generate synthetic data
X <- matrix(rnorm(100*5), 100, 5) # 5 covariates

# Generate 1000 randomizations for 100 units with 50 treated
rand_less_strict <- generate_randomizations_mc(
  n_units = 100,
  n_treated = 50,
  X = X,
  randomization_accept_prob=0.01,
  max_draws = 100000,
  batch_size = 1000)

# Use a stricter balance criterion
rand_more_strict <- generate_randomizations_mc(
  n_units = 100,
  n_treated = 50,
  X = X,
  randomization_accept_prob=0.001,
  max_draws = 1000000,
  batch_size = 1000)

## End(Not run)
```

---

generate\_randomizations\_R

*Generate randomizations in base R, filtering by Hotelling's  $T^2$  acceptance*

---

**Description**

Base R function to either do exact enumeration or Monte Carlo random permutations, then keep the fraction whose  $T^2$  is below the acceptance cutoff.

**Usage**

```
generate_randomizations_R(
  n_units,
  n_treated,
  X,
  accept_prob,
  random_type,
  max_draws,
  batch_size
)
```

**Arguments**

n_units	Integer, total number of units.
n_treated	Integer, number of units to be assigned to treatment.
X	Covariate matrix (n_units x p).
accept_prob	Numeric in [0, 1]: keep the fraction of randomizations that have the lowest $T^2$ up to this quantile.
random_type	Either "exact" or "monte_carlo".
max_draws	If 'random_type="monte_carlo"', how many permutations to sample.
batch_size	If 'random_type="monte_carlo"', how many permutations to handle per chunk.

**Value**

A list with:

- randomizations: a matrix (rows = accepted assignments).
- balance: numeric vector of  $T^2$  values for each accepted assignment.

---

hotellingT2_R	<i>Compute Hotelling's T-squared statistic in base R</i>
---------------	--

---

**Description**

This function provides a base R implementation of Hotelling's T-squared balance measure, renamed with '\_R' for clarity that it is the R-based analog to the JAX version in `fastrerandomize`.

**Usage**

```
hotellingT2_R(X, W)
```

**Arguments**

X	A numeric matrix of covariates (observations in rows).
W	A 0/1 treatment assignment vector of the same length as <code>nrow(X)</code> .

**Value**

A numeric scalar: Hotelling's T-squared statistic for that assignment.

---

```
plot.fastrerandomize_randomizations
```

*Plot method for fastrerandomize\_test objects*

---

**Description**

Plots the observed treatment effect and, if available, the fiducial interval on a horizontal axis.

**Usage**

```
## S3 method for class 'fastrerandomize_randomizations'  
plot(x, ...)
```

**Arguments**

x	An object of class fastrerandomize_test.
...	Further graphical parameters passed to <a href="#">plot</a> .

**Value**

No return value. This function is called for the side effect of generating a histogram of the accepted balance measures of object with class fastrerandomize\_randomizations.

---

```
plot.fastrerandomize_test
```

*Plot method for fastrerandomize\_test objects*

---

**Description**

Plots a simple visualization of the observed effect and the fiducial interval (if present) on a horizontal axis.

**Usage**

```
## S3 method for class 'fastrerandomize_test'  
plot(x, ...)
```

**Arguments**

x	An object of class fastrerandomize_test.
...	Further graphical parameters passed to <a href="#">plot</a> .

**Value**

No output returned. Performs side effect of plotting fastrerandomize\_test class objects.

---

```
print.fastrerandomize_randomizations
```

*Print method for fastrerandomize\_randomizations objects*

---

### Description

Print method for fastrerandomize\_randomizations objects

### Usage

```
## S3 method for class 'fastrerandomize_randomizations'  
print(x, ...)
```

### Arguments

x	An object of class fastrerandomize_instance.
...	Further arguments passed to or from other methods.

### Value

Prints an object of class fastrerandomize\_randomizations.

---

```
print.fastrerandomize_test
```

*Print method for fastrerandomize\_test objects*

---

### Description

Print method for fastrerandomize\_test objects

### Usage

```
## S3 method for class 'fastrerandomize_test'  
print(x, ...)
```

### Arguments

x	An object of class fastrerandomize_test.
...	Further arguments passed to or from other methods.

### Value

No return value, prints object of class fastrerandomize\_test.

---

print2	<i>Print timestamped messages with optional quieting</i>
--------	--

---

### Description

This function prints messages prefixed with the current timestamp in a standardized format. Messages can be suppressed using the quiet parameter.

### Usage

```
print2(text, quiet = FALSE)
```

### Arguments

text	A character string containing the message to be printed.
quiet	A logical value indicating whether to suppress output. Default is FALSE.

### Details

The function prepends the current timestamp in "YYYY-MM-DD HH:MM:SS" format to the provided message.

### Value

No return value, called for side effect of printing with timestamp.

### See Also

`Sys.time` for the underlying timestamp functionality.

### Examples

```
# Print a basic message with timestamp
print2("Processing started")

# Suppress output
print2("This won't show", quiet = TRUE)

# Use in a loop
for(i in 1:3) {
  print2(sprintf("Processing item %d", i))
}
```

---

QJEData

*QJEData: Agricultural Treatment Experiment Data*


---

## Description

Data from a field experiment studying moral hazard in tenancy contracts in agriculture.

After subsetting, this dataset includes observations on 968 experimental units with the following variables of interest: household composition, treatment assignment, and agricultural outcomes.

## Usage

```
data(QJEData)
```

## Format

A data frame with 968 rows and 7 columns:

**children** Numeric (integer). Number of children in the household. Larger numbers may reflect increased household labor needs and different investment or effort incentives.

**married** Numeric/binary. Whether the household head is currently married (1) or not (0). Marital status may influence decision-making and risk preferences in farming.

**hh\_size** Numeric (integer). Household size. Differences in family labor availability or consumption needs can influence effort levels and thus relate to moral hazard in production decisions.

**hh\_sexrat** Numeric. The ratio of adult men to adult women in the household. Imbalances in the male–female ratio can affect labor division and investment decisions.

**treat1** Numeric/binary. Primary treatment indicator (e.g., whether a farmer is offered a specific tenancy contract or cost-sharing arrangement).

**R\_yield\_ELA\_sqm** Numeric. Crop yield per square meter (e.g., kilograms of output per square meter). This is a principal outcome measure for evaluating productivity and treatment impact on farm performance.

**ELA\_Fertil\_D** Numeric/binary. Indicator for whether fertilizer was used (1) or not (0). This measures input investment—a key mechanism in moral hazard models (farmers may alter input use under different contracts).

## Source

Burchardi, K.B., Ghatak, M., & Johanssen, A. (2019). Moral hazard: Experimental evidence from tenancy contracts. *The Quarterly Journal of Economics*, 134(1), 281-347.

---

randomization_test	<i>Fast randomization test</i>
--------------------	--------------------------------

---

## Description

Fast randomization test

## Usage

```
randomization_test(
  obsW = NULL,
  obsY = NULL,
  alpha = 0.05,
  candidate_randomizations = NULL,
  candidate_randomizations_array = NULL,
  n0_array = NULL,
  n1_array = NULL,
  findFI = FALSE,
  c_initial = 2,
  conda_env = "fastrerandomize_env",
  conda_env_required = TRUE
)
```

## Arguments

obsW	A numeric vector where 0's correspond to control units and 1's to treated units.
obsY	An optional numeric vector of observed outcomes. If not provided, the function assumes a NULL value.
alpha	The significance level for the test. Default is 0.05.
candidate_randomizations	A numeric matrix of candidate randomizations.
candidate_randomizations_array	An optional 'JAX' array of candidate randomizations. If not provided, the function coerces candidate_randomizations into a 'JAX' array.
n0_array	An optional array specifying the number of control units.
n1_array	An optional array specifying the number of treated units.
findFI	A logical value indicating whether to find the fiducial interval. Default is FALSE.
c_initial	A numeric value representing the initial criterion for the fiducial interval search. Default is 2.
conda_env	A character string specifying the name of the conda environment to use via reticulate. Default is "fastrerandomize_env".
conda_env_required	A logical indicating whether the specified conda environment must be strictly used. If TRUE, an error is thrown if the environment is not found. Default is TRUE.

## Value

Returns an S3 object with slots:

- `p_value` A numeric value or vector representing the p-value of the test (or the expected p-value under the prior structure specified in the function inputs).
- `FI` A numeric vector representing the fiducial interval if `findFI=TRUE`.
- `tau_obs` A numeric value or vector representing the estimated treatment effect(s).
- `fastrr_env` The `fastrerandomize` environment.

## References

- Zhang, Y. and Zhao, Q., 2023. What is a randomization test?. *Journal of the American Statistical Association*, 118(544), pp.2928-2942.

## See Also

[generate\\_randomizations](#) for randomization generation function.

## Examples

```
## Not run:
# A small synthetic demonstration with 6 units, 3 treated and 3 controls:

# Generate pre-treatment covariates
X <- matrix(rnorm(24*2), ncol = 2)

# Generate candidate randomizations
RandomizationSet_MC <- generate_randomizations(
  n_units = nrow(X),
  n_treated = round(nrow(X)/2),
  X = X,
  randomization_accept_prob = 0.1,
  randomization_type = "monte_carlo",
  max_draws = 100000,
  batch_size = 1000
)

# Generate outcome
W <- RandomizationSet_MC$randomizations[1,]
obsY <- rnorm(nrow(X), mean = 2 * W)

# Perform randomization test
results_base <- randomization_test(
  obsW = W,
  obsY = obsY,
  candidate_randomizations = RandomizationSet_MC$randomizations
)
print(results_base)

# Perform randomization test with fiducial interval
result_fi <- randomization_test(
  obsW = W,
  obsY = obsY,
  candidate_randomizations = RandomizationSet_MC$randomizations,
  findFI = TRUE
```



```
)
print(result_fi)

## End(Not run)
```

---

randomization_test_R	<i>Base R randomization test: difference in means + optional fiducial interval</i>
----------------------	--

---

### Description

Base R randomization test: difference in means + optional fiducial interval

### Usage

```
randomization_test_R(obsW, obsY, allW, findFI = FALSE, alpha = 0.05)
```

### Arguments

obsW	Observed assignment (0/1).
obsY	Observed outcome vector.
allW	Matrix of candidate random assignments (rows = assignments).
findFI	Logical, whether to compute fiducial interval as well.
alpha	Significance level (default 0.05).

### Value

A list with p\_value, tau\_obs, and (optionally) FI if 'findFI=TRUE'.

---

summary.fastrerandomize_randomizations	<i>Summary method for fastrerandomize_randomizations objects</i>
--	--

---

### Description

Summary method for fastrerandomize\_randomizations objects

### Usage

```
## S3 method for class 'fastrerandomize_randomizations'
summary(object, ...)
```

### Arguments

object	An object of class fastrerandomize_randomizations.
...	Further arguments passed to or from other methods.

### Value

A list with summary statistics, printed by default.

---

```
summary.fastrerandomize_test
```

*Summary method for fastrerandomize\_test objects*

---

### Description

Summary method for fastrerandomize\_test objects

### Usage

```
## S3 method for class 'fastrerandomize_test'
summary(object, ...)
```

### Arguments

<code>object</code>	An object of class <code>fastrerandomize_test</code> .
<code>...</code>	Further arguments passed to or from other methods.

### Value

Returns an (invisible) list with a summary of `fastrerandomize_test` class objects.

---

YOPData

*YOPData*

---

### Description

Data from a re-analysis of the Youth Opportunities Program anti-poverty RCT in Uganda, with satellite imagery neural representations linked to RCT units.

### Usage

```
data(YOPData)
```

### Format

A list containing two data frames:

**RCTData** Treatment, outcome, and geolocation information

**ImageEmbeddings** CLIP-RSICD neural embeddings of satellite imagery

### Source

- Blattman, C., Fiala, N. and Martinez, S. (2020). The Long-term Impacts of Grants on Poverty: Nine-year Evidence from Uganda's Youth Opportunities Program. *American Economic Review: Insights*, 2(3), 287-304.
- Jerzak, C.T., Johansson, F.D. and Daoud, A. (2023). Image-based Treatment Effect Heterogeneity. *Conference on Causal Learning and Reasoning*, 531-552. PMLR.

# Index

build\_backend, [2](#)

check\_jax\_availability, [3](#)  
compute\_diff\_at\_tau\_for\_oneW\_R, [4](#)

diagnose\_rerandomization, [4](#)  
diff\_in\_means\_R, [6](#)  
dist, [9](#), [10](#)

fast\_distance, [8](#)  
fastrerandomize\_class, [7](#)  
fastrerandomize\_test, [8](#)  
find\_fiducial\_interval\_R, [10](#)

generate\_randomizations, [7](#), [11](#), [15](#), [17](#), [24](#)  
generate\_randomizations\_exact, [13](#), [13](#),  
[17](#)  
generate\_randomizations\_mc, [13](#), [15](#), [15](#)  
generate\_randomizations\_R, [17](#)

hotellingT2\_R, [18](#)

plot, [19](#)  
plot.fastrerandomize\_randomizations,  
[19](#)  
plot.fastrerandomize\_test, [19](#)  
print.fastrerandomize\_randomizations,  
[20](#)  
print.fastrerandomize\_test, [20](#)  
print2, [21](#)

QJEData, [22](#)

randomization\_test, [23](#)  
randomization\_test\_R, [25](#)

summary.fastrerandomize\_randomizations,  
[25](#)  
summary.fastrerandomize\_test, [26](#)

YOPData, [26](#)