

Package ‘ndm’

March 15, 2026

Title Neural Disease Modeling Software

Version 0.0.1

Author Connor T. Jerzak [aut, cre]

Maintainer Connor T. Jerzak <connor.jerzak@austin.utexas.edu>

Description Provides an R-first interface for neural disease modeling with a reticulate-managed JAX backend. The package includes backend bootstrap helpers, built-in epidemiological model specifications, TFRecord-consuming data interfaces, a bundled self-contained analysis runtime, and package-native orchestration helpers for model execution.

Depends R (>= 4.1.0)

Imports data.table, ndmdatasets, rlang, reticulate, utils

Suggests fastmatch, progress, rapply, testthat (>= 3.0.0), yaml, zip,
zoo

License GPL-3

Encoding UTF-8

Config/testthat/edition 3

RoxygenNote 7.3.3

NeedsCompilation no

Contents

ndm-package	2
ndm_build_model	3
ndm_check_backend	4
ndm_create_config	6
ndm_create_real_run_config	7
ndm_create_tfrecord_parser	9
ndm_model_spec_presets	11
ndm_new_runtime_env	12
ndm_predict	13
ndm_prepare_runtime	14
ndm_print	15
ndm_tfrecord_fields_real	16
ndm_tf_batch_to_r	16

Index	19
--------------	-----------

Description

ndm is an R-first package for neural disease modeling with a reticulate-managed JAX backend. The package currently provides backend setup, epidemic model spec import/export, TFRecord readers, a bundled internal analysis runtime, and package-native runtime/model helpers.

Details

The current implementation preserves both historical model families, "DecoderOnly" and "NeuralODE", while defaulting to "DecoderOnly". The supported backbone is the transformer path only. Latent attention and Mamba are intentionally excluded.

The package treats the structured `ndm_model_spec` object as the canonical internal representation and supports `.tex` import/export for compatibility with the original epidemic specification workflow.

Key functions

- `ndm_create_config`
- `ndm_build_backend`
- `ndm_initialize_backend`
- `ndm_model_spec`
- `ndm_model_spec_from_tex`
- `ndm_model_spec_to_tex`
- `ndm_read_tfrecord_dataset`
- `ndm_load_tfrecord_bundle`
- `ndm_prepare_runtime`
- `ndm_prepare_data`
- `ndm_build_model`
- `ndm_train`
- `ndm_predict`
- `ndm_loss`
- `ndm_fit`

Author(s)

Connor T. Jerzak <connor.jerzak@austin.utexas.edu>

Description

These wrappers layer a small R API over local Phase 1 model build and training scripts.

Usage

```
ndm_build_model(
  runtime_env,
  model_type = c("DecoderOnly", "NeuralODE"),
  model_spec = NULL,
  backbone = "transformer",
  runtime_globals = list()
)

## S3 method for class 'ndm_model'
print(x, ...)

ndm_train(x, run_define = TRUE, run_loop = TRUE)

## S3 method for class 'ndm_trained_model'
print(x, ...)

ndm_fit(
  config = ndm_create_config(),
  model_spec = NULL,
  data_generator = c("sim", "real", "multidisease"),
  runtime_globals = list(),
  data_globals = list(),
  build_globals = list(),
  train_globals = list(),
  run_define = TRUE,
  run_loop = TRUE
)
```

Arguments

runtime_env	Runtime environment containing the sourced legacy helper code and data globals.
model_type	Model family to build. Either <code>"DecoderOnly"</code> or <code>"NeuralODE"</code> .
model_spec	Optional <code>'ndm_model_spec'</code> object used to override the model TeX specification supplied to the runtime model builder.
backbone	Backbone family. Phase 1 supports <code>"transformer"</code> only.
runtime_globals	Named list of additional globals assigned during the relevant runtime stage. <code>'ndm_build_model()'</code> uses them before building the model, while <code>'ndm_fit()'</code> uses them before sourcing the runtime.

<code>x</code>	Either an <code>'ndm_model'</code> , an <code>'ndm_trained_model'</code> , or a prepared runtime environment, depending on the function being called.
<code>...</code>	Unused; included for S3 method compatibility.
<code>run_define</code>	Logical scalar indicating whether the training definition script should be sourced.
<code>run_loop</code>	Logical scalar indicating whether the training loop script should be sourced.
<code>config</code>	An object of class <code>'ndm_config'</code> , usually created by <code>'ndm_create_config()'</code> .
<code>data_generator</code>	Which local data generator to source before calling <code>'ndm_build_model()'</code> inside <code>'ndm_fit()'</code> .
<code>data_globals</code>	Named list of globals assigned before sourcing the data generator in <code>'ndm_fit()'</code> .
<code>build_globals</code>	Named list of globals assigned before building the model in <code>'ndm_fit()'</code> .
<code>train_globals</code>	Named list of globals assigned immediately before training in <code>'ndm_fit()'</code> .

Value

`'ndm_build_model()'` returns an object of class `'ndm_model'`. `'ndm_train()'` and `'ndm_fit()'` return an object of class `'ndm_trained_model'`.

`'print.ndm_model()'` prints a brief summary of an `'ndm_model'` object and invisibly returns `'x'`.

`'print.ndm_trained_model()'` prints a brief summary of an `'ndm_trained_model'` object and invisibly returns `'x'`.

Examples

```
cfg <- ndm_create_config()
spec <- ndm_model_spec()
## Not run:
runtime_env <- ndm_prepare_runtime(cfg)
ndm_prepare_data(runtime_env, generator = "sim")
model <- ndm_build_model(runtime_env, model_spec = spec)
trained <- ndm_train(model)

## End(Not run)
```

ndm_check_backend

Provision and initialize the Python backend

Description

These helpers manage the reticulate-backed Python environment used by ndm. Use `'ndm_build_backend()'` to provision dependencies, `'ndm_check_backend()'` to verify availability, and `'ndm_initialize_backend()'` to import the active JAX stack into R.

Usage

```
ndm_check_backend(
  conda_env = "ndm_software_env",
  conda = "auto",
  modules = c("jax", "numpy", "optax", "equinox", "diffraction")
)
```

```

ndm_build_backend(
    conda_env = "ndm_software_env",
    conda = "auto",
    python_version = "3.13",
    include_tensorflow = TRUE,
    extra_packages = c("optax", "equinox", "diffrax")
)

ndm_initialize_backend(
    conda_env = "ndm_software_env",
    conda = "auto",
    conda_env_required = TRUE,
    float_type = c("32", "64"),
    import_tensorflow = TRUE
)

ndm_backend_modules()

```

Arguments

<code>conda_env</code>	Name of the conda environment that should contain the JAX runtime.
<code>conda</code>	Conda executable to use. <code>"auto"</code> delegates discovery to reticulate.
<code>modules</code>	Character vector of Python module names that must be importable for the backend to be considered healthy.
<code>python_version</code>	Python version requested when creating the conda environment.
<code>include_tensorflow</code>	Logical scalar indicating whether TensorFlow should be installed alongside JAX.
<code>extra_packages</code>	Additional Python packages to install with <code>'pip'</code> .
<code>conda_env_required</code>	Passed through to <code>'reticulate::use_condaenv()'</code> as the <code>'required'</code> flag.
<code>float_type</code>	Floating point precision used when configuring JAX. Either <code>"32"</code> or <code>"64"</code> .
<code>import_tensorflow</code>	Logical scalar indicating whether TensorFlow should be imported when it is available in the selected environment.

Value

`'ndm_check_backend()'` returns `'TRUE'` invisibly when the requested environment and modules are available. It returns `'NULL'` after printing a diagnostic message when the backend is not ready.

`'ndm_build_backend()'` invisibly returns the conda environment name after attempting to provision the requested packages.

`'ndm_initialize_backend()'` returns an object of class `'ndm_backend'`. The returned list contains imported Python modules, the configured float type, and a small compatibility shim used by the legacy runtime.

`'ndm_backend_modules()'` returns the currently initialized `'ndm_backend'` object.

Examples

```
ndm_check_backend()

## Not run:
ndm_build_backend()

## End(Not run)

## Not run:
backend <- ndm_initialize_backend()
backend$default_backend

## End(Not run)

## Not run:
ndm_initialize_backend()
ndm_backend_modules()

## End(Not run)
```

ndm_create_config	<i>Create runtime configuration objects</i>
-------------------	---

Description

Configuration objects collect the runtime options that are threaded through the higher-level orchestration helpers such as ‘ndm_prepare_runtime()’ and ‘ndm_fit()’.

Usage

```
ndm_create_config(
  model_type = c("DecoderOnly", "NeuralODE"),
  backbone = "transformer",
  float_type = c("32", "64"),
  force_to_gpu = TRUE,
  resave_tfrecords = FALSE,
  gpu_mem_frac = NULL,
  ...
)

## S3 method for class 'ndm_config'
print(x, ...)
```

Arguments

model_type	Model family metadata. Use “DecoderOnly” or “NeuralODE”.
backbone	Backbone family. Phase 1 supports “transformer” only.
float_type	Floating point precision used when initializing the backend. Use “32” or “64”.
force_to_gpu	Logical scalar indicating whether the runtime should try to place arrays on GPU when available.

resave_tfrerecords	Logical scalar preserved for compatibility with the legacy runtime.
gpu_mem_frac	Optional GPU memory fraction forwarded into the runtime bootstrap code.
...	Unused; included for S3 method compatibility.
x	An 'ndm_config' object.

Value

'ndm_create_config()' returns an object of class 'ndm_config'.

'print.ndm_config()' prints a brief summary of an 'ndm_config' object and invisibly returns 'x'.

Examples

```
cfg <- ndm_create_config()
print(cfg)
```

ndm_create_real_run_config

Package-native run configurations and workflow runners

Description

Package-native configuration constructors and workflow runners for the self-contained real, simulation, and multidisease execution paths.

Usage

```
ndm_create_real_run_config(
  project_root = getwd(),
  analysis_name = "RealApril15",
  grid = NULL,
  grid_file = file.path("Data", "RunGrids", "RealGrids", sprintf("RealGrid_%s.csv",
    analysis_name)),
  outer = 3L,
  model_type = NULL,
  respect_grid_model_type = FALSE,
  resave_tfrerecords = FALSE,
  tfrecord_dir = file.path("Data", "RunTFRecords", "RealTFRecords",
    analysis_name),
  raw_data_dir = file.path("Data", "MainData"),
  outcome_metric = "inc_death",
  data_subset = "high_income",
  dry_run = FALSE
)

ndm_create_sim_run_config(
  project_root = getwd(),
  analysis_name = "BigSimsLatest",
  grid = NULL,
```

```

grid_file = file.path("Data", "RunGrids", "SimGrids", sprintf("SimGrid_%s.csv",
  analysis_name)),
outer = 1L,
model_type = NULL,
respect_grid_model_type = FALSE,
resave_tfrerecords = TRUE,
tfrecord_dir = file.path("Data", "RunTFRecords", "SimTFRecords",
  analysis_name),
dry_run = FALSE
)

ndm_create_multidisease_run_config(
  project_root = getwd(),
  analysis_name = "RealLatest",
  grid = NULL,
  grid_file = file.path("Data", "RunGrids", "RealGrids", sprintf("RealGrid_%s.csv",
    analysis_name)),
  outer = 1L,
  model_type = NULL,
  respect_grid_model_type = FALSE,
  resave_tfrerecords = FALSE,
  tfrecord_dir = file.path("Data", "RunTFRecords", "RealTFRecords",
    analysis_name),
  outcome_metric = "CountValue",
  data_subset = "all",
  disease_names = c("Covid", "Flu"),
  data_format = "IHME",
  dry_run = FALSE
)

ndm_run_real(config = ndm_create_real_run_config())

ndm_run_sim(config = ndm_create_sim_run_config())

ndm_run_multidisease(config = ndm_create_multidisease_run_config())

```

Arguments

<code>project_root</code>	Working project directory used for grids, TFRecords, and outputs.
<code>analysis_name</code>	Analysis label threaded through output paths.
<code>grid</code>	Optional in-memory grid data frame. When supplied, <code>grid_file</code> must be NULL.
<code>grid_file</code>	Optional CSV path for the run grid.
<code>outer</code>	Integer vector of outer-iteration rows to execute.
<code>model_type</code>	Optional model family override.
<code>respect_grid_model_type</code>	Logical scalar indicating whether grid rows may override the requested model type.
<code>resave_tfrerecords</code>	Logical scalar controlling TFRecord regeneration.
<code>tfrecord_dir</code>	Optional TFRecord output directory.

raw_data_dir	Real-data input directory.
outcome_metric	Outcome metric name for real-data or multidisease runs.
data_subset	Optional real-data subset name.
disease_names	Character vector of multidisease names.
data_format	Multidisease data format.
dry_run	Logical scalar indicating whether the run should stop after resolving paths and grid rows.
config	A package-native run configuration created by the matching ndm_create*_run_config() helper.

Value

The ndm_create*_run_config() helpers return classed lists describing the requested workflow. The ndm_run_*() functions return the underlying workflow result, or a dry-run preview when config\$dry_run is TRUE.

Examples

```
## Not run:
cfg <- ndm_create_sim_run_config(
  project_root = getwd(),
  grid_file = "Data/RunGrids/SimGrids/SimGrid_BigSimsLatest.csv",
  outer = 1L,
  dry_run = TRUE
)

ndm_run_sim(cfg)

## End(Not run)
```

ndm_create_tfrecord_parser

Create and read TensorFlow TFRecord datasets

Description

These wrappers construct parsers for the ndm TFRecord schema and use them to build TensorFlow datasets or eagerly collect batches into R.

Usage

```
ndm_create_tfrecord_parser(field_names, dtype_map = NULL, tensorflow = NULL)

ndm_read_tfrecord_dataset(
  file,
  batch_size,
  field_names,
  dtype_map = NULL,
  max_examples = NULL,
  shuffle = FALSE,
```

```

    buffer_scaler = 10L,
    tensorflow = NULL
  )

  ndm_collect_tfrecord_batches(
    file,
    batch_size,
    field_names,
    dtype_map = NULL,
    max_batches = NULL,
    max_examples = NULL,
    shuffle = FALSE,
    buffer_scaler = 10L,
    tensorflow = NULL
  )

```

Arguments

field_names	Character vector of TFRecord field names that should be parsed from each example.
dtype_map	Optional named vector or list mapping 'field_names' to TensorFlow dtype names or TensorFlow dtype objects.
tensorflow	Optional TensorFlow module. When omitted, ndm uses the active backend's TensorFlow module when available and otherwise imports TensorFlow from the active reticulate environment at call time.
file	Path to the '.tfrecord' file to read.
batch_size	Batch size used when constructing the TensorFlow dataset.
max_examples	Optional maximum number of examples to consume from the file before batching.
shuffle	Logical scalar indicating whether the dataset should be shuffled.
buffer_scaler	Integer multiplier used to derive the TensorFlow shuffle buffer size from 'batch_size'.
max_batches	Optional maximum number of batches to collect when using 'ndm_collect_tfrecord_batches()'.

Value

'ndm_create_tfrecord_parser()' returns a parser function compatible with 'tf\$data\$Dataset\$map()'.
 'ndm_read_tfrecord_dataset()' returns a TensorFlow dataset object. 'ndm_collect_tfrecord_batches()' returns a list of parsed batches.

Examples

```

fields <- ndm_tfrecord_fields_real()
parser <- ndm_create_tfrecord_parser(fields, ndm_tfrecord_dtype_map("real"))
is.function(parser)

```

ndm_model_spec_presets

Inspect and create epidemic model specifications

Description

The package ships a small registry of built-in compartmental model specifications and also supports importing custom ‘.tex’ model definitions from disk. The structured ‘ndm_model_spec’ object is the canonical representation used by the runtime wrappers.

Usage

```
ndm_model_spec_presets()

ndm_model_spec(
  preset = NULL,
  compartments = c("seir", "seirs"),
  dynamic_beta = NULL,
  dynamic_global = FALSE,
  multi_outcome = FALSE,
  model_type = c("DecoderOnly", "NeuralODE"),
  time_varying_terms = NULL,
  endogenous_terms = NULL,
  tex_path = NULL
)

ndm_model_spec_from_tex(path, model_type = c("DecoderOnly", "NeuralODE"))

ndm_model_spec_to_tex(spec, path = NULL)

## S3 method for class 'ndm_model_spec'
print(x, ...)
```

Arguments

preset	Optional preset name from ‘ndm_model_spec_presets()’. When omitted, the remaining arguments are used to infer a built-in preset.
compartments	Compartment family used when inferring a built-in preset.
dynamic_beta	Logical scalar controlling whether the local transmission rate is time-varying for built-in presets.
dynamic_global	Logical scalar controlling whether the global rates are time-varying for built-in presets.
multi_outcome	Logical scalar indicating whether the observation model should include multiple outcomes.
model_type	Model family metadata attached to the returned specification. Either “DecoderOnly” or “NeuralODE”.
time_varying_terms	Optional character vector overriding the default time-varying term metadata stored on the returned spec.

endogenous_terms	Optional character vector overriding the default endogenous term metadata stored on the returned spec.
tex_path	Optional path to a custom '.tex' file. When supplied, 'ndm_model_spec()' delegates to 'ndm_model_spec_from_tex()'.
path	Path to a '.tex' model specification file on disk.
spec	An 'ndm_model_spec' object.
x	An 'ndm_model_spec' object.
...	Unused; included for S3 method compatibility.

Value

'ndm_model_spec_presets()' returns a data frame describing the built-in presets bundled with the package.

'ndm_model_spec()' returns an object of class 'ndm_model_spec'. Built-in presets include meta-data such as the packaged source path and the normalized TeX contents.

'ndm_model_spec_from_tex()' returns an 'ndm_model_spec' object whose 'source_path' points at the supplied file. When the basename matches a built-in preset, the preset metadata is reused.

'ndm_model_spec_to_tex()' returns the TeX text as a single character string when 'path' is 'NULL'. When 'path' is supplied, it writes the specification to disk and invisibly returns the normalized output path.

'print.ndm_model_spec()' prints a brief summary of an 'ndm_model_spec' object and invisibly returns 'x'.

Examples

```
ndm_model_spec_presets()

spec <- ndm_model_spec()
print(spec)

spec <- ndm_model_spec()
tex_path <- tempfile(fileext = ".tex")
ndm_model_spec_to_tex(spec, tex_path)
ndm_model_spec_from_tex(tex_path)

spec <- ndm_model_spec()
tex <- ndm_model_spec_to_tex(spec)
nchar(tex) > 0
```

ndm_new_runtime_env *Create and populate runtime environments*

Description

These helpers manage isolated environments used to source local model runtime code and seed it with R values.

Usage

```
ndm_new_runtime_env(parent = globalenv())

ndm_set_runtime_globals(env, values, overwrite = TRUE)
```

Arguments

parent	Parent environment for a new runtime environment. Defaults to ‘globalenv()’ so bundled runtime scripts can resolve attached-package functions the same way the legacy workflow did.
env	Runtime environment that should receive new bindings.
values	Named list of values to assign into ‘env’.
overwrite	Logical scalar indicating whether existing bindings in ‘env’ should be overwritten.

Value

‘ndm_new_runtime_env()’ returns an environment of class ‘ndm_runtime_env’. ‘ndm_set_runtime_globals()’ invisibly returns ‘env’.

Examples

```
env <- ndm_new_runtime_env()
ndm_set_runtime_globals(env, list(example_value = 1L))
env$example_value
```

ndm_predict

Generate predictions or evaluate the training loss

Description

These helpers call the runtime prediction and loss functions stored in a prepared runtime environment.

Usage

```
ndm_predict(x, batch = NULL, inference = TRUE, seed = 1L, update_state = TRUE)

ndm_loss(
  x,
  batch = NULL,
  y = NULL,
  y_mask = NULL,
  iteration = 1L,
  seed = 1L,
  update_state = TRUE
)
```

Arguments

x	Either an 'ndm_model', an 'ndm_trained_model', or a prepared runtime environment that already contains the required runtime objects.
batch	Optional batch object. Supply either a named TFRecord-style list or the four-element packaged list returned by 'ndm_batch_to_model_inputs()'. When 'NULL', the runtime must already contain 'batch_l_cal'.
inference	Logical scalar indicating whether 'ndm_predict()' should use the inference prediction path or the training prediction path.
seed	Integer seed used to derive the per-example JAX RNG keys.
update_state	Logical scalar indicating whether the runtime 'state' object should be updated with the returned state.
y	Optional observed outcome tensor passed to 'ndm_loss()'. When omitted, 'YTrue_out' is inferred from 'batch'.
y_mask	Optional outcome mask tensor passed to 'ndm_loss()'. When omitted, 'YTrue_out_mask' is inferred from 'batch'.
iteration	Training iteration number forwarded to the runtime loss function.

Value

'ndm_predict()' returns the prediction object produced by the runtime. 'ndm_loss()' returns the loss object produced by the runtime.

Examples

```
## Not run:
preds <- ndm_predict(model, batch = batch_l_cal)
loss <- ndm_loss(model, batch = batch_l_cal)

## End(Not run)
```

ndm_prepare_runtime *Prepare a local runtime for execution*

Description

These wrappers load caller-supplied runtime scripts into an isolated environment and then source the selected data generator.

Usage

```
ndm_prepare_runtime(
  config = ndm_create_config(),
  runtime_env = ndm_new_runtime_env(),
  runtime_globals = list()
)

ndm_prepare_data(
  runtime_env,
  generator = c("sim", "real", "multidisease"),
  runtime_globals = list()
)
```

Arguments

config	An object of class 'ndm_config', usually created by 'ndm_create_config()'.
runtime_env	Runtime environment that should receive the sourced objects.
runtime_globals	Named list of additional bindings to assign before the runtime code is sourced.
generator	Which data generator to source into 'runtime_env'.

Value

'ndm_prepare_runtime()' invisibly returns 'runtime_env' after loading the package-owned helper and backend code.

'ndm_prepare_data()' invisibly returns 'runtime_env' after sourcing the requested data generator.

Examples

```
env <- ndm_new_runtime_env()
cfg <- ndm_create_config()
## Not run:
ndm_prepare_runtime(cfg, env)

## End(Not run)

env <- ndm_new_runtime_env()
ndm_set_runtime_globals(env, list(example_value = 1L))
```

ndm_print

Print a timestamped diagnostic message

Description

'ndm_print()' is a small logging helper used throughout the package-facing orchestration code.

Usage

```
ndm_print(text, quiet = FALSE)
```

Arguments

text	Text to print.
quiet	Logical scalar indicating whether output should be suppressed.

Value

The input 'text', invisibly.

Examples

```
ndm_print("starting")
```

ndm_tfrecord_fields_real

Inspect TFRecord field contracts

Description

These helpers describe the field names and default TensorFlow dtypes expected by the packaged TFRecord readers.

Usage

```
ndm_tfrecord_fields_real()
```

```
ndm_tfrecord_fields_sim()
```

```
ndm_tfrecord_dtype_map(kind = c("real", "sim"))
```

Arguments

kind	TFRecord schema to inspect. Use "real" for observed-data records and "sim" for simulation records.
------	--

Value

'ndm_tfrecord_fields_real()' and 'ndm_tfrecord_fields_sim()' return character vectors of field names. 'ndm_tfrecord_dtype_map()' returns a named character vector mapping each field to its default TensorFlow dtype.

Examples

```
ndm_tfrecord_fields_real()
ndm_tfrecord_dtype_map("sim")
```

ndm_tf_batch_to_r

Convert and bundle TFRecord batches

Description

These helpers convert TensorFlow batches to native R or JAX objects, package them into the shape expected by the legacy runtime, and attach dataset handles to a runtime environment.

Usage

```
ndm_tf_batch_to_r(batch)
```

```
ndm_tf_batch_to_jax(batch, backend = NULL)
```

```
ndm_batch_to_model_inputs(batch)
```



```

ndm_load_tfrecord_bundle(
    train_file,
    inference_file = NULL,
    batch_size,
    kind = c("real", "sim"),
    dtype_map = NULL,
    tensorflow = NULL,
    max_train_examples = NULL,
    max_inference_examples = NULL,
    shuffle_train = TRUE,
    shuffle_inference = FALSE
)

ndm_attach_tfrecord_bundle(
    env,
    bundle,
    backend = NULL,
    calibration_source = c("inference", "train")
)

```

Arguments

batch	A parsed TFRecord batch or a nested list containing TensorFlow tensors.
backend	Optional 'ndm_backend' object. When omitted, 'ndm_tf_batch_to_jax()' and 'ndm_attach_tfrecord_bundle()' use the active backend from 'ndm_backend_modules()' when available.
train_file	Path to the training TFRecord file.
inference_file	Optional path to an inference TFRecord file.
batch_size	Batch size used when constructing the training and inference datasets.
kind	TFRecord schema to use when reading 'train_file' and 'inference_file'.
dtype_map	Optional named dtype mapping passed through to the TFRecord readers.
tensorflow	Optional TensorFlow module. When omitted, ndm uses the active backend's TensorFlow module when available and otherwise imports TensorFlow from the active reticulate environment at call time.
max_train_examples	Optional cap on the number of training examples to read.
max_inference_examples	Optional cap on the number of inference examples to read.
shuffle_train	Logical scalar indicating whether the training dataset should be shuffled.
shuffle_inference	Logical scalar indicating whether the inference dataset should be shuffled.
env	Runtime environment that should receive dataset handles and the preview calibration batch.
bundle	An object of class 'ndm_tfrecord_bundle' returned by 'ndm_load_tfrecord_bundle()'.
calibration_source	Which dataset should supply the preview batch used to seed runtime globals such as 'batch_l_cal'.

Value

`'ndm_tf_batch_to_r()'` recursively converts a TensorFlow batch to R arrays and lists. `'ndm_tf_batch_to_jax()'` recursively converts tensors into JAX arrays. `'ndm_batch_to_model_inputs()'` returns the packaged four-element list expected by the legacy model code. `'ndm_load_tfrecord_bundle()'` returns an `'ndm_tfrecord_bundle'` object. `'ndm_attach_tfrecord_bundle()'` invisibly returns `'env'`.

Examples

```
batch <- list(
  XPred = array(0, c(2, 3, 4)),
  XPred_mask = array(TRUE, c(2, 3, 4)),
  Context = array(0, c(2, 1, 4)),
  Context_mask = array(TRUE, c(2, 1, 4)),
  location_id_numeric = matrix(1L, nrow = 2),
  time_id_numeric = matrix(1L, nrow = 2)
)
packaged <- ndm_batch_to_model_inputs(batch)
length(packaged)
```

Index

ndm (ndm-package), 2
ndm-package, 2
ndm_attach_tfrecord_bundle
 (ndm_tf_batch_to_r), 16
ndm_backend_modules
 (ndm_check_backend), 4
ndm_batch_to_model_inputs
 (ndm_tf_batch_to_r), 16
ndm_build_backend, 2
ndm_build_backend (ndm_check_backend), 4
ndm_build_model, 2, 3
ndm_check_backend, 4
ndm_collect_tfrecord_batches
 (ndm_create_tfrecord_parser), 9
ndm_create_config, 2, 6
ndm_create_multidisease_run_config
 (ndm_create_real_run_config), 7
ndm_create_real_run_config, 7
ndm_create_sim_run_config
 (ndm_create_real_run_config), 7
ndm_create_tfrecord_parser, 9
ndm_fit, 2
ndm_fit (ndm_build_model), 3
ndm_initialize_backend, 2
ndm_initialize_backend
 (ndm_check_backend), 4
ndm_load_tfrecord_bundle, 2
ndm_load_tfrecord_bundle
 (ndm_tf_batch_to_r), 16
ndm_loss, 2
ndm_loss (ndm_predict), 13
ndm_model_spec, 2
ndm_model_spec
 (ndm_model_spec_presets), 11
ndm_model_spec_from_tex, 2
ndm_model_spec_from_tex
 (ndm_model_spec_presets), 11
ndm_model_spec_presets, 11
ndm_model_spec_to_tex, 2
ndm_model_spec_to_tex
 (ndm_model_spec_presets), 11
ndm_new_runtime_env, 12
ndm_predict, 2, 13
ndm_prepare_data, 2
ndm_prepare_data (ndm_prepare_runtime),
 14
ndm_prepare_runtime, 2, 14
ndm_print, 15
ndm_read_tfrecord_dataset, 2
ndm_read_tfrecord_dataset
 (ndm_create_tfrecord_parser), 9
ndm_run_multidisease
 (ndm_create_real_run_config), 7
ndm_run_real
 (ndm_create_real_run_config), 7
ndm_run_sim
 (ndm_create_real_run_config), 7
ndm_set_runtime_globals
 (ndm_new_runtime_env), 12
ndm_tf_batch_to_jax
 (ndm_tf_batch_to_r), 16
ndm_tf_batch_to_r, 16
ndm_tfrecord_dtype_map
 (ndm_tfrecord_fields_real), 16
ndm_tfrecord_fields_real, 16
ndm_tfrecord_fields_sim
 (ndm_tfrecord_fields_real), 16
ndm_train, 2
ndm_train (ndm_build_model), 3

print.ndm_config (ndm_create_config), 6
print.ndm_model (ndm_build_model), 3
print.ndm_model_spec
 (ndm_model_spec_presets), 11
print.ndm_trained_model
 (ndm_build_model), 3