

Package ‘ndm’

July 23, 2026

Title Neural Disease Modeling Software

Version 0.2.0

Author Connor T. Jerzak [aut, cre]

Maintainer Connor T. Jerzak <connor.jerzak@austin.utexas.edu>

Description Provides an R-first interface for neural disease modeling with a reticulate-managed JAX backend. The package includes backend bootstrap helpers, built-in epidemiological model specifications, TFRecord-consuming data interfaces, package-managed runtime helpers, and package-native orchestration helpers for model execution.

Depends R (>= 4.1.0)

Imports data.table,
digest,
ndmdatasets (>= 0.2.0),
rlang,
reticulate,
utils

Suggests fastmatch,
knitr,
rmarkdown,
rapply,
testthat (>= 3.0.0),
yaml,
zip,
zoo

VignetteBuilder knitr

License AGPL-3

Encoding UTF-8

Config/testthat/edition 3

Config/roxygen2/version 8.0.0

Contents

ndm-package	2
ndm_bootstrap_real_tfrecords	3
ndm_bootstrap_sim_tfrecords	4
ndm_build_model	5

ndm_check_backend	7
ndm_create_config	9
ndm_create_real_run_config	11
ndm_create_tfrecord_parser	14
ndm_extract_temporal_latents	16
ndm_model_spec_from_structure	17
ndm_model_spec_presets	18
ndm_new_runtime_env	21
ndm_predict	22
ndm_prepare_runtime	23
ndm_print	24
ndm_save_model	25
ndm_tfrecord_fields_real	26
ndm_tf_batch_to_r	27

Index	29
--------------	-----------

ndm-package	<i>Neural Disease Modeling Software</i>
-------------	---

Description

ndm is an R-first package for neural disease modeling with a reticulate-managed JAX backend. The package currently provides backend setup, epidemic model spec import/export, TFRecord readers, package-managed runtime helpers, package-native runtime/model helpers, package-native run APIs, and artifact helpers for saving and restoring trained models.

Details

The current implementation preserves both historical model families, "DecoderOnly" and "NeuralODE", while defaulting to "DecoderOnly". The supported backbone is the transformer path only. Latent attention and Mamba are intentionally excluded.

The package treats the structured `ndm_model_spec` object as the canonical internal representation and supports `.tex` import/export for compatibility with the original epidemic specification workflow.

For executable workflows rather than dry-run previews, install the helper packages listed under `Suggests`, initialize the backend with `ndm_initialize_backend`, and align that backend with `NDM_SOFTWARE_CONDA_ENV` or `NDM_CONDA_ENV` when using the package-native runner helpers. When both variables are unset, the runner layer currently falls back to `jax_cpu` on macOS and `ndm_software_env` elsewhere.

Key functions

- `ndm_create_config`
- `ndm_build_backend`
- `ndm_initialize_backend`
- `ndm_model_spec`
- `ndm_model_spec_from_tex`
- `ndm_model_spec_to_tex`
- `ndm_read_tfrecord_dataset`

- ndm_load_tfrecord_bundle
- ndm_prepare_runtime
- ndm_prepare_data
- ndm_build_model
- ndm_train
- ndm_predict
- ndm_loss
- ndm_fit
- ndm_create_real_run_config
- ndm_run_real
- ndm_run_sim
- ndm_run_multidisease
- ndm_save_model
- ndm_load_model
- ndm_resume_training

Author(s)

Connor T. Jerzak <connor.jerzak@austin.utexas.edu>

ndm_bootstrap_real_tfrecords

Bootstrap canonical real-data TFRecords by BaseID

Description

Materializes one canonical real-data train/inference artifact pair per ‘BaseID’, with the same cross-process lock and canonical-row selection used by [ndm_bootstrap_sim_tfrecords()].

Usage

```
ndm_bootstrap_real_tfrecords(
  project_root = getwd(),
  analysis_name = "RealApril15",
  grid = NULL,
  grid_file = file.path("Data", "RunGrids", "RealGrids", sprintf("RealGrid_%s.csv",
    analysis_name)),
  base_ids = NULL,
  tfrecord_dir = file.path("Data", "RunTFRecords", "RealTFRecords", analysis_name),
  raw_data_dir = file.path("Data", "MainData"),
  outcome_metric = "inc_death",
  data_subset = "high_income",
  producer = NULL,
  parallel_workers = 1L,
  overwrite = FALSE,
  dry_run = FALSE
)
```

Arguments

project_root	Working project directory used to resolve relative grid and TFRecord paths.
analysis_name	Analysis label used to derive default real-data paths.
grid	Optional in-memory real-data grid.
grid_file	Optional CSV path for the real-data grid.
base_ids	Optional integer vector of canonical 'BaseID' values to materialize. When 'NULL', bootstrap all 'BaseID's in raw grid order of first appearance.
tfrecord_dir	Output directory for canonical real-data TFRecords.
raw_data_dir	Directory containing the real-data source tables.
outcome_metric	Outcome metric passed to 'ndmdatasets'.
data_subset	Real-data subset passed to 'ndmdatasets'.
producer	Nonempty named producer metadata stored in every artifact manifest. Required for publication; dry runs may omit it.
parallel_workers	Positive integer number of forked BaseID workers on Linux. Inputs are prepared before forking. macOS and Windows use the deterministic serial path because TensorFlow/JAX runtimes are not fork-safe there.
overwrite	Logical scalar controlling whether existing canonical TFRecords should be re-generated.
dry_run	Logical scalar indicating whether to return the canonical write plan without writing TFRecords.

Value

A canonical per-'BaseID' write-plan data frame with a 'status' column.

ndm_bootstrap_sim_tfreCORDs

Bootstrap canonical simulation TFRecords by BaseID

Description

This helper materializes canonical simulation TFRecords without going through the legacy 'outer' scheduling path. It reads the simulation grid in raw CSV or data-frame order, builds one canonical write plan row per 'BaseID', and optionally writes those TFRecords with a per-'BaseID' cross-process lock.

Usage

```
ndm_bootstrap_sim_tfreCORDs(
  project_root = getwd(),
  analysis_name = "BigSimsLatest",
  grid = NULL,
  grid_file = file.path("Data", "RunGrids", "SimGrids", sprintf("SimGrid_%s.csv",
    analysis_name)),
  base_ids = NULL,
  tfrecord_dir = file.path("Data", "RunTFRecords", "SimTFRecords", analysis_name),
```

```

    producer = NULL,
    parallel_workers = 1L,
    overwrite = FALSE,
    dry_run = FALSE
  )

```

Arguments

<code>project_root</code>	Working project directory used to resolve relative grid and TFRecord paths.
<code>analysis_name</code>	Analysis label used to derive default grid and TFRecord paths.
<code>grid</code>	Optional in-memory simulation grid. When supplied, <code>'grid_file'</code> must be <code>'NULL'</code> .
<code>grid_file</code>	Optional CSV path for the simulation grid.
<code>base_ids</code>	Optional integer vector of canonical <code>'BaseID'</code> values to materialize. When <code>'NULL'</code> , bootstrap all <code>'BaseID'</code> s in raw grid order of first appearance.
<code>tfrecord_dir</code>	Output directory for canonical TFRecords.
<code>producer</code>	Nonempty named producer metadata stored in every artifact manifest. Required for publication; dry runs may omit it.
<code>parallel_workers</code>	Positive integer number of forked BaseID workers on Linux. Inputs are prepared before forking. macOS and Windows use the deterministic serial path because TensorFlow/JAX runtimes are not fork-safe there.
<code>overwrite</code>	Logical scalar controlling whether existing canonical TFRecords should be re-generated.
<code>dry_run</code>	Logical scalar indicating whether to return the canonical write plan without writing TFRecords.

Value

A data frame with one row per canonical `'BaseID'` and columns `'BaseID'`, `'selected_rows'`, `'canonical_row'`, `'artifact_n_samples_train'`, `'train_file'`, `'inference_file'`, and `'status'`.

<code>ndm_build_model</code>	<i>Build and train models with package-managed runtime stages</i>
------------------------------	---

Description

These wrappers layer a small R API over package-managed Phase 1 model build and training stages.

Usage

```

ndm_build_model(
  runtime_env,
  model_type = c("DecoderOnly", "NeuralODE"),
  model_spec = NULL,
  backbone = "transformer",
  runtime_globals = list()
)

## S3 method for class 'ndm_model'

```

```

print(x, ...)

ndm_train(x, run_define = TRUE, run_loop = TRUE)

## S3 method for class 'ndm_trained_model'
print(x, ...)

ndm_fit(
  config = ndm_create_config(),
  model_spec = NULL,
  data_generator = c("sim", "real", "multidisease"),
  runtime_globals = list(),
  data_globals = list(),
  build_globals = list(),
  train_globals = list(),
  run_define = TRUE,
  run_loop = TRUE
)

```

Arguments

<code>runtime_env</code>	Runtime environment containing loaded runtime helpers and data globals.
<code>model_type</code>	Model family to build. Either <code>"DecoderOnly"</code> or <code>"NeuralODE"</code> .
<code>model_spec</code>	Optional <code>'ndm_model_spec'</code> object used to override the model TeX specification supplied to the runtime model builder.
<code>backbone</code>	Backbone family. Phase 1 supports <code>"transformer"</code> only.
<code>runtime_globals</code>	Named list of additional globals assigned during the relevant runtime stage. <code>'ndm_build_model()'</code> uses them before building the model, while <code>'ndm_fit()'</code> uses them before sourcing the runtime.
<code>x</code>	Either an <code>'ndm_model'</code> , an <code>'ndm_trained_model'</code> , or a prepared runtime environment, depending on the function being called.
<code>...</code>	Unused; included for S3 method compatibility.
<code>run_define</code>	Logical scalar indicating whether the training definition script should be sourced.
<code>run_loop</code>	Logical scalar indicating whether the training loop script should be sourced.
<code>config</code>	An object of class <code>'ndm_config'</code> , usually created by <code>'ndm_create_config()'</code> .
<code>data_generator</code>	Which data workflow to prepare before calling <code>'ndm_build_model()'</code> inside <code>'ndm_fit()'</code> .
<code>data_globals</code>	Named list of globals assigned before data preparation in <code>'ndm_fit()'</code> .
<code>build_globals</code>	Named list of globals assigned before building the model in <code>'ndm_fit()'</code> .
<code>train_globals</code>	Named list of globals assigned immediately before training in <code>'ndm_fit()'</code> .

Details

These functions assume the backend has already been initialized with `'ndm_initialize_backend()'` and that `'runtime_env'` already contains the upstream runtime and data globals required by the selected workflow. `'ndm_train()'` requires `'rrapply'`; it also requires `'zip'` when checkpointing is enabled and `'zoo'` for multidisease training. Simulation preparation only requires `'zoo'` when `'SkipTFRecords = TRUE'` selects the in-memory compatibility path documented on `[ndm_prepare_runtime()]`.

Value

‘ndm_build_model()’ returns an object of class ‘ndm_model’. ‘ndm_train()’ and ‘ndm_fit()’ return an object of class ‘ndm_trained_model’.

‘print.ndm_model()’ prints a brief summary of an ‘ndm_model’ object and invisibly returns ‘x’.

‘print.ndm_trained_model()’ prints a brief summary of an ‘ndm_trained_model’ object and invisibly returns ‘x’.

Examples

```
cfg <- ndm_create_config()
spec <- ndm_model_spec()
## Not run:
runtime_env <- ndm_prepare_runtime(cfg)
ndm_prepare_data(runtime_env, generator = "sim")
model <- ndm_build_model(runtime_env, model_spec = spec)
trained <- ndm_train(model)

## End(Not run)
```

ndm_check_backend

Provision and initialize the Python backend

Description

These helpers manage the reticulate-backed Python environment used by ndm. Use ‘ndm_build_backend()’ to provision dependencies, ‘ndm_check_backend()’ to verify availability, and ‘ndm_initialize_backend()’ to import the active JAX stack into R.

Usage

```
ndm_check_backend(
  conda_env = "ndm_software_env",
  conda = "auto",
  modules = c("jax", "numpy", "optax", "equinox", "diffrax")
)

ndm_build_backend(
  conda_env = "ndm_software_env",
  conda = "auto",
  python_version = "3.13",
  include_tensorflow = TRUE,
  extra_packages = c("optax", "equinox", "diffrax")
)

ndm_initialize_backend(
  conda_env = "ndm_software_env",
  conda = "auto",
  conda_env_required = TRUE,
  float_type = c("32", "64"),
  import_tensorflow = TRUE
)
```

```
)

ndm_backend_modules()
```

Arguments

<code>conda_env</code>	Name of the conda environment that should contain the JAX runtime.
<code>conda</code>	Conda executable to use. <code>"auto"</code> delegates discovery to reticulate.
<code>modules</code>	Character vector of Python module names that must be importable for the backend to be considered healthy.
<code>python_version</code>	Python version requested when creating the conda environment.
<code>include_tensorflow</code>	Logical scalar indicating whether TensorFlow should be installed alongside JAX.
<code>extra_packages</code>	Additional Python packages to install with <code>'pip'</code> .
<code>conda_env_required</code>	Passed through to <code>'reticulate::use_condaenv()'</code> as the <code>'required'</code> flag.
<code>float_type</code>	Floating point precision used when configuring JAX. Either <code>"32"</code> or <code>"64"</code> .
<code>import_tensorflow</code>	Logical scalar indicating whether TensorFlow should be imported when it is available in the selected environment.

Details

When you want backend helpers and the package-native `'ndm_run_*()'` runners to target the same conda environment, set `'NDM_SOFTWARE_CONDA_ENV'` (or `'NDM_CONDA_ENV'`) once and pass that value into these helpers. The runner layer currently falls back to `'jax_cpu'` on macOS and `'ndm_software_env'` elsewhere when neither environment variable is set.

Value

`'ndm_check_backend()'` returns `'TRUE'` invisibly when the requested environment and modules are available. It returns `'NULL'` after printing a diagnostic message when the backend is not ready.

`'ndm_build_backend()'` invisibly returns the conda environment name after attempting to provision the requested packages.

`'ndm_initialize_backend()'` returns an object of class `'ndm_backend'`. The returned list contains imported Python modules, the configured float type, and a small compatibility shim used by the legacy runtime.

`'ndm_backend_modules()'` returns the currently initialized `'ndm_backend'` object.

Examples

```
ndm_check_backend()

## Not run:
ndm_build_backend()

## End(Not run)

## Not run:
backend <- ndm_initialize_backend()
backend$default_backend
```



```

## End(Not run)

## Not run:
ndm_initialize_backend()
ndm_backend_modules()

## End(Not run)

```

ndm_create_config	<i>Create runtime configuration objects</i>
-------------------	---

Description

Configuration objects collect the runtime options that are threaded through the higher-level orchestration helpers such as ‘ndm_prepare_runtime()’ and ‘ndm_fit()’.

Usage

```

ndm_create_config(
  model_type = c("DecoderOnly", "NeuralODE"),
  backbone = "transformer",
  float_type = c("32", "64"),
  force_to_gpu = TRUE,
  resave_tfrecords = FALSE,
  gpu_mem_frac = NULL,
  neuralode_local_latent_dim = NULL,
  neuralode_global_latent_dim = NULL,
  neuralode_init_state_logit_offset = NULL,
  neuralode_init_state_logit_scale_max = Inf,
  neuralode_optim_solver = c("tsit5", "dopri8"),
  neuralode_optim_dt0 = 0.001,
  neuralode_optim_controller = c("pid", "constant"),
  neuralode_optim_rtol = 1e-05,
  neuralode_optim_atol = 1e-07,
  neuralode_variational = TRUE,
  neuralode_kl_weight = 1,
  neuralode_mean_loss_weight = 0,
  ...
)

## S3 method for class 'ndm_config'
print(x, ...)

```

Arguments

model_type	Model family metadata. Use “DecoderOnly” or “NeuralODE”.
backbone	Backbone family. Phase 1 supports “transformer” only.
float_type	Floating point precision used when initializing the backend. Use “32” or “64”.

<code>force_to_gpu</code>	Logical scalar requiring a CUDA-capable JAX GPU when ‘TRUE’.
<code>resave_tfrerecords</code>	Logical scalar preserved for compatibility. Public training APIs require ‘FALSE’; prepare canonical inputs before training.
<code>gpu_mem_frac</code>	Optional finite GPU memory fraction in ‘(0, 1]’.
<code>neuralode_local_latent_dim</code>	Optional local NeuralODE latent width. When ‘NULL’, runtime code resolves this to ‘ModelDims’.
<code>neuralode_global_latent_dim</code>	Optional global NeuralODE latent width. When ‘NULL’, runtime code resolves this to ‘ModelDims’.
<code>neuralode_init_state_logit_offset</code>	Optional init-state logit offset vector for the NeuralODE state simplex initializer.
<code>neuralode_init_state_logit_scale_max</code>	Scalar cap applied to the NeuralODE init-state logit scale.
<code>neuralode_optim_solver</code>	NeuralODE optimization solver name. Use “tsit5” or “dopri8”.
<code>neuralode_optim_dt0</code>	Initial step size used by the NeuralODE optimization solve.
<code>neuralode_optim_controller</code>	NeuralODE optimization stepsize controller. Use “pid” or “constant”.
<code>neuralode_optim_rtol</code>	Relative tolerance used when ‘neuralode_optim_controller = “pid”’.
<code>neuralode_optim_atol</code>	Absolute tolerance used when ‘neuralode_optim_controller = “pid”’.
<code>neuralode_variational</code>	Logical scalar. When ‘FALSE’, NeuralODE training uses deterministic posterior means instead of stochastic variational samples.
<code>neuralode_kl_weight</code>	Non-negative scalar KL multiplier used only when ‘neuralode_variational = TRUE’.
<code>neuralode_mean_loss_weight</code>	Non-negative multiplier for an auxiliary masked mean-squared-error term applied to NeuralODE forecasts alongside the Student-t likelihood.
<code>...</code>	Unused; included for S3 method compatibility.
<code>x</code>	An ‘ndm_config’ object.

Value

‘ndm_create_config()’ returns an object of class ‘ndm_config’.

‘print.ndm_config()’ prints a brief summary of an ‘ndm_config’ object and invisibly returns ‘x’.

Examples

```
cfg <- ndm_create_config()
print(cfg)
```

ndm_create_real_run_config

Package-native run configurations and workflow runners

Description

Package-native configuration constructors and workflow runners for the self-contained real, simulation, and multidisease execution paths.

Usage

```
ndm_create_real_run_config(
  project_root = getwd(),
  analysis_name = "RealApril15",
  grid = NULL,
  grid_file = file.path("Data", "RunGrids", "RealGrids", sprintf("RealGrid_%s.csv",
    analysis_name)),
  outer = 3L,
  run_seed = NULL,
  force_to_gpu = TRUE,
  gpu_mem_frac = NULL,
  neuralode_kl_weight = 1,
  neuralode_mean_loss_weight = 0,
  n_checkpoints = 1L,
  max_sgd_steps = NULL,
  prior_sd_multiplier = 1,
  solver_profile = "default",
  model_type = NULL,
  respect_grid_model_type = TRUE,
  resave_tfrecords = FALSE,
  tfrecord_dir = file.path("Data", "RunTFRecords", "RealTFRecords",
    analysis_name),
  raw_data_dir = file.path("Data", "MainData"),
  outcome_metric = "inc_death",
  data_subset = "high_income",
  dry_run = FALSE
)
```

```
ndm_create_sim_run_config(
  project_root = getwd(),
  analysis_name = "BigSimsLatest",
  grid = NULL,
  grid_file = file.path("Data", "RunGrids", "SimGrids", sprintf("SimGrid_%s.csv",
    analysis_name)),
  outer = 1L,
  run_seed = NULL,
  force_to_gpu = TRUE,
  gpu_mem_frac = NULL,
  neuralode_kl_weight = 1,
  neuralode_mean_loss_weight = 0,
  n_checkpoints = 1L,
```

```

    max_sgd_steps = NULL,
    prior_sd_multiplier = 1,
    solver_profile = "default",
    model_type = NULL,
    respect_grid_model_type = TRUE,
    resave_tfrerecords = FALSE,
    tfrecord_dir = file.path("Data", "RunTFRecords", "SimTFRecords",
        analysis_name),
    dry_run = FALSE
)

ndm_create_multidisease_run_config(
  project_root = getwd(),
  analysis_name = "RealLatest",
  grid = NULL,
  grid_file = file.path("Data", "RunGrids", "RealGrids", sprintf("RealGrid_%s.csv",
    analysis_name)),
  outer = 1L,
  run_seed = NULL,
  force_to_gpu = TRUE,
  gpu_mem_frac = NULL,
  neuralode_kl_weight = 1,
  neuralode_mean_loss_weight = 0,
  n_checkpoints = 1L,
  max_sgd_steps = NULL,
  prior_sd_multiplier = 1,
  solver_profile = "default",
  model_type = NULL,
  respect_grid_model_type = TRUE,
  resave_tfrerecords = FALSE,
  tfrecord_dir = file.path("Data", "RunTFRecords", "RealTFRecords",
    analysis_name),
  outcome_metric = "CountValue",
  data_subset = "all",
  disease_names = c("Covid", "Flu"),
  data_format = "IHME",
  dry_run = FALSE
)

ndm_run_real(config = ndm_create_real_run_config())

ndm_run_sim(config = ndm_create_sim_run_config())

ndm_run_multidisease(config = ndm_create_multidisease_run_config())

```

Arguments

<code>project_root</code>	Working project directory used for grids, TFRecords, and outputs.
<code>analysis_name</code>	Analysis label threaded through output paths.
<code>grid</code>	Optional in-memory grid data frame. When supplied, <code>grid_file</code> must be <code>NULL</code> .
<code>grid_file</code>	Optional CSV path for the run grid.
<code>outer</code>	Integer vector of outer-iteration rows to execute.

run_seed	Optional non-negative integer used for model initialization, training Monte Carlo keys, and inference randomness. When NULL, the legacy outer-row-derived seed is retained.
force_to_gpu	Logical scalar requiring a CUDA-capable JAX GPU for fitting.
gpu_mem_frac	Optional finite GPU memory fraction in (0, 1].
neuralode_kl_weight	Finite non-negative NeuralODE KL multiplier. Zero disables KL evaluation while preserving variational sampling.
neuralode_mean_loss_weight	Finite non-negative multiplier for the NeuralODE auxiliary masked mean-squared-error term.
n_checkpoints	Positive integer number of checkpoint and analytics states to retain, including the terminal post-update state.
max_sgd_steps	Optional positive integer training-step cap for explicitly labeled pilot runs.
prior_sd_multiplier	Finite positive multiplier applied to ODE prior standard deviations.
solver_profile	ODE optimization profile: "default", "loose", "tight", or "alternative".
model_type	Optional model family override.
respect_grid_model_type	Logical scalar indicating whether grid rows may override the requested model type.
resave_tfrecords	Logical scalar retained for compatibility. Training workflows require FALSE. For real and simulation runs, build canonical artifacts separately with ndm_bootstrap_real_tfrecords() or ndm_bootstrap_sim_tfrecords(). Prepare multidisease inputs outside the training runner.
tfrecord_dir	Optional TFRecord output directory.
raw_data_dir	Real-data input directory.
outcome_metric	Outcome metric name for real-data or multidisease runs.
data_subset	Optional real-data or multidisease subset name.
disease_names	Character vector of multidisease names.
data_format	Multidisease data format.
dry_run	Logical scalar indicating whether the run should stop after resolving paths and grid rows.
config	A package-native run configuration created by the matching ndm_create*_run_config() helper.

Details

dry_run = TRUE resolves paths and selected rows without executing the underlying workflow. Dry runs can use lightweight in-memory grids such as the BaseID / ModelType preview shown in README.md.

Non-dry execution expects Analysis2-compatible grids. The tested simulation grids in this package are produced by ndmdatasets::ndm_sim_build_grid() and then augmented with fields such as paddingMethod, lookahead, n_time_steps, n_inference_batches, scaling_batches, and either model_spec_name or model_tex_loc. The tested real and multidisease grids include BaseID, ContextLength, evaluationTime, initialTransform, initialNormType, paddingMethod, OSSType,

dataInputs, ModelType, ModelDepth, ModelDims, nSamplesTrain, nObsInference, floatType, and either model_spec_name or model_tex_loc.

Non-dry runner workflows also require the full execution stack: the ndmdatasets package, the helper packages used by the runtime, and a backend environment aligned with NDM_SOFTWARE_CONDA_ENV, NDM_CONDA_ENV, or the platform-specific fallback used by the runner layer.

Value

The ndm_create*_run_config() helpers return classed lists describing the requested workflow. Each ndm_run_*() function returns a dry-run preview when config\$dry_run is TRUE and otherwise the underlying workflow result.

Examples

```
## Not run:
preview_grid <- data.frame(
  BaseID = c(1L, 2L),
  ModelType = c("DecoderOnly", "NeuralODE"),
  stringsAsFactors = FALSE
)

cfg <- ndm_create_sim_run_config(
  project_root = tempdir(),
  grid = preview_grid,
  outer = 1:2,
  dry_run = TRUE
)

ndm_run_sim(cfg)

## End(Not run)
```

ndm_create_tfrecord_parser

Create and read TensorFlow TFRecord datasets

Description

These wrappers construct parsers for the ndm TFRecord schema and use them to build TensorFlow datasets or eagerly collect batches into R.

Usage

```
ndm_create_tfrecord_parser(field_names, dtype_map = NULL, tensorflow = NULL)

ndm_read_tfrecord_dataset(
  file,
  batch_size,
  field_names,
  dtype_map = NULL,
  max_examples = NULL,
  shuffle = FALSE,
```

```

    buffer_scaler = 10L,
    tensorflow = NULL
  )

  ndm_collect_tfrecord_batches(
    file,
    batch_size,
    field_names,
    dtype_map = NULL,
    max_batches = NULL,
    max_examples = NULL,
    shuffle = FALSE,
    buffer_scaler = 10L,
    tensorflow = NULL
  )

```

Arguments

field_names	Character vector of TFRecord field names that should be parsed from each example.
dtype_map	Optional named vector or list mapping ‘field_names’ to TensorFlow dtype names or TensorFlow dtype objects.
tensorflow	Optional TensorFlow module. When omitted, ndm uses the active backend’s TensorFlow module when available and otherwise imports TensorFlow from the active reticulate environment at call time.
file	Path to the ‘.tfrecord’ file to read.
batch_size	Batch size used when constructing the TensorFlow dataset.
max_examples	Optional maximum number of examples to consume from the file before batching.
shuffle	Logical scalar indicating whether the dataset should be shuffled.
buffer_scaler	Integer multiplier used to derive the TensorFlow shuffle buffer size from ‘batch_size’.
max_batches	Optional maximum number of batches to collect when using ‘ndm_collect_tfrecord_batches()’.

Details

TFRecord parsing requires TensorFlow to be importable from the active reticulate environment. In practice this usually means provisioning the backend with ‘ndm_build_backend(include_tensorflow = TRUE)’ and then calling ‘ndm_initialize_backend(import_tensorflow = TRUE)’ for the same conda environment before reading datasets.

Value

‘ndm_create_tfrecord_parser()’ returns a parser function compatible with ‘tf\$data\$Dataset\$map()’. ‘ndm_read_tfrecord_dataset()’ returns a TensorFlow dataset object. ‘ndm_collect_tfrecord_batches()’ returns a list of parsed batches.

Examples

```

fields <- ndm_tfrecord_fields_real()
parser <- ndm_create_tfrecord_parser(fields, ndm_tfrecord_dtype_map("real"))
is.function(parser)

```

ndm_extract_temporal_latents

Extract temporal latent states for interpretability analyses

Description

‘ndm_extract_temporal_latents()’ runs the existing prediction path and returns aligned temporal representations for decoder-only and NeuralODE models. ‘ndm_latent_matrix()’ flattens one extracted representation to a two-dimensional matrix suitable for external analyses such as CCA.

Usage

```
ndm_extract_temporal_latents(
  x,
  batch = NULL,
  seed = 1L,
  inference = TRUE,
  update_state = FALSE,
  as_r = TRUE
)

ndm_latent_matrix(latents, source = "decoder_head_input", features = NULL)
```

Arguments

x	Either an ‘ndm_model’, an ‘ndm_trained_model’, or a prepared runtime environment that already contains the required runtime objects.
batch	Optional prediction batch passed through to [ndm_predict()].
seed	Integer seed used to derive the per-example JAX RNG keys.
inference	Logical scalar indicating whether the inference prediction path or training prediction path should be used.
update_state	Logical scalar indicating whether the runtime ‘state’ object should be updated with the returned state.
as_r	Logical scalar. When ‘TRUE’, JAX arrays are copied to R arrays.
latents	An object returned by ‘ndm_extract_temporal_latents()’.
source	Representation to flatten. Supported values include “decoder_head_input”, “ode_local_hidden”, “ode_global_hidden”, “ode_local_features”, “ode_global_features”, and “ode_states”.
features	Optional feature names or integer feature positions.

Value

‘ndm_extract_temporal_latents()’ returns an ‘ndm_temporal_latents’ list. ‘ndm_latent_matrix()’ returns a numeric matrix with rows ordered by batch within time.

Examples

```
## Not run:
latents <- ndm_extract_temporal_latents(trained, batch = batch_l_cal)
decoder_x <- ndm_latent_matrix(latents, "decoder_head_input")
ode_x <- ndm_latent_matrix(latents, "ode_local_hidden")

## End(Not run)
```

ndm_model_spec_from_structure

Inspect and create epidemic model specifications from structured declarations

Description

‘ndm_model_spec_from_structure()’ builds an ‘ndm_model_spec’ from a structured declaration. The declaration may either describe the full model directly or identify a supported built-in family plus optional ‘family_args’ that expand parameterized structures into explicit executable equations.

Usage

```
ndm_model_spec_from_structure(
  structure,
  model_type = c("DecoderOnly", "NeuralODE"),
  family_args = NULL
)
```

Arguments

structure	A structured model declaration.
model_type	Model family metadata attached to the returned specification. Either “DecoderOnly” or “NeuralODE”.
family_args	Optional named list used to expand parameterized family declarations. For structured TB families, ‘observation_target’ chooses “incidence” (default flow into ‘i_1’) or “cumulative” (‘i_1’). TB families use ‘dynamics_variant = “balanced_incidence”’ by default, preserving the original active-progression flow while adding normalized at-risk renewal (‘N = 1’), active-disease exit back to susceptibility, latent mortality, and incidence-flow observations. Set ‘dynamics_variant = “progression”’ for legacy one-way depletion dynamics. Set ‘dynamics_variant = “seir”’ for the SEIR-style form of ‘reports/TBModels/TBDiseaseTypes_v2.md’: the constant force of infection ‘lambda’ is replaced by mass-action incidence ‘beta * i_1 / N’, an explicit removed compartment ‘r_1’ is added with active-disease removal ‘gamma’, and demographic renewal ‘mu’ sustains endemic incidence. Both ‘balanced_incidence’ and ‘seir’ require incidence observations.

Details

For a maintainer-oriented guide to the required fields, parameter-spec shape, TeX contract, and extension workflow, see vignette(“ode-structures”, package = “ndm”).

Value

An object of class ‘ndm_model_spec’.

Examples

```
family_spec <- ndm_model_spec_from_structure(
  list(
    family = "tb_b",
    family_args = list(n = 4L)
  ),
  model_type = "NeuralODE"
)
family_spec$state_terms

toy_spec <- ndm_model_spec_from_structure(
  list(
    preset = "toy_slqi",
    description = "Toy four-state latent structure with a holding compartment.",
    states = c("s_l", "l_l", "q_l", "i_l"),
    parameters = list(
      lambda = list(
        transformation = "InvSoftPlus",
        prior_mean = 0.08,
        prior_sd = 0.25
      ),
      c = list(
        transformation = "InvSoftPlus",
        prior_mean = 0.05,
        prior_sd = 0.25
      ),
      h = list(
        transformation = "InvSoftPlus",
        prior_mean = 0.03,
        prior_sd = 0.25
      )
    ),
    equations = c(
      s_l = "- lambda * s_l",
      l_l = "lambda * s_l - (c + h) * l_l",
      q_l = "h * l_l",
      i_l = "c * l_l"
    ),
    observations = "i_l"
  ),
  model_type = "NeuralODE"
)
toy_spec$parameter_terms
```

Description

The package ships a small registry of built-in compartmental model specifications and also supports importing custom `.tex` model definitions from disk. The structured `ndm_model_spec` object is the canonical representation used by the runtime wrappers.

Usage

```
ndm_model_spec_presets()

ndm_model_spec(
  preset = NULL,
  compartments = c("seir", "seirs"),
  dynamic_beta = NULL,
  dynamic_global = FALSE,
  multi_outcome = FALSE,
  model_type = c("DecoderOnly", "NeuralODE"),
  time_varying_terms = NULL,
  endogenous_terms = NULL,
  tex_path = NULL,
  family_args = NULL
)

ndm_model_spec_from_tex(path, model_type = c("DecoderOnly", "NeuralODE"))

ndm_model_spec_to_tex(spec, path = NULL)

## S3 method for class 'ndm_model_spec'
print(x, ...)
```

Arguments

<code>preset</code>	Optional preset name from <code>ndm_model_spec_presets()</code> . When omitted, the remaining arguments are used to infer a built-in preset.
<code>compartments</code>	Compartment family used when inferring a built-in preset.
<code>dynamic_beta</code>	Logical scalar controlling whether the local transmission rate is time-varying for built-in presets.
<code>dynamic_global</code>	Logical scalar controlling whether the global rates are time-varying for built-in presets.
<code>multi_outcome</code>	Logical scalar indicating whether the observation model should include multiple outcomes.
<code>model_type</code>	Model family metadata attached to the returned specification. Either <code>"DecoderOnly"</code> or <code>"NeuralODE"</code> .
<code>time_varying_terms</code>	Optional character vector overriding the default time-varying term metadata stored on the returned spec.
<code>endogenous_terms</code>	Optional character vector overriding the default endogenous term metadata stored on the returned spec.
<code>tex_path</code>	Optional path to a custom <code>.tex</code> file. When supplied, <code>ndm_model_spec()</code> delegates to <code>ndm_model_spec_from_tex()</code> .

family_args	Optional named list used to expand parameterized model families such as chained latent-stage specifications. For structured TB presets, 'n' controls supported chain lengths and 'observation_target' chooses '"incidence"' (default flow into 'i_1') or '"cumulative"' ('i_1'). TB presets use 'dynamics_variant = "balanced_incidence"' by default to keep the original progression topology while adding demographic renewal, active-disease exit back to susceptibility, and incidence-flow observations. Set 'dynamics_variant = "progression"' for legacy one-way depletion dynamics. Set 'dynamics_variant = "seir"' for the SEIR-style form of 'reports/TBModels/TBDiseaseTypes_v2.md': mass-action incidence ' $\beta * S * I / N$ ' replaces the constant force of infection ' λ ', an explicit removed compartment ' r_1 ' is added with active-disease removal ' γ ' (I to R), and demographic renewal ' μ ' keeps incidence sustained (endemic) for fitting. Both 'balanced_incidence' and 'seir' require incidence observations.
path	Path to a '.tex' model specification file on disk.
spec	An 'ndm_model_spec' object.
x	An 'ndm_model_spec' object.
...	Unused; included for S3 method compatibility.

Details

For a maintainer-oriented walkthrough of preset selection, structured families, TeX round-tripping, and safe modification workflows, see `vignette("ode-structures", package = "ndm")`.

Value

'ndm_model_spec_presets()' returns a data frame describing the built-in presets bundled with the package.

'ndm_model_spec()' returns an object of class 'ndm_model_spec'. Built-in presets include meta-data such as the packaged source path and the normalized TeX contents.

'ndm_model_spec_from_tex()' returns an 'ndm_model_spec' object whose 'source_path' points at the supplied file. When the basename matches a built-in preset, the preset metadata is reused.

'ndm_model_spec_to_tex()' returns the TeX text as a single character string when 'path' is 'NULL'. When 'path' is supplied, it writes the specification to disk and invisibly returns the normalized output path.

'print.ndm_model_spec()' prints a brief summary of an 'ndm_model_spec' object and invisibly returns 'x'.

Examples

```
ndm_model_spec_presets()

spec <- ndm_model_spec()
print(spec)

tb_spec <- ndm_model_spec(
  preset = "tb_b",
  model_type = "NeuralODE",
  family_args = list(n = 4L)
)
tb_spec$family_args

spec <- ndm_model_spec()
```

```

tex_path <- tempfile(fileext = ".tex")
ndm_model_spec_to_tex(spec, tex_path)
ndm_model_spec_from_tex(tex_path)

tb_spec <- ndm_model_spec(
  preset = "tb_k",
  model_type = "NeuralODE"
)
tb_tex_path <- tempfile(fileext = ".tex")
ndm_model_spec_to_tex(tb_spec, tb_tex_path)
ndm_model_spec_from_tex(tb_tex_path, model_type = "NeuralODE")

spec <- ndm_model_spec()
tex <- ndm_model_spec_to_tex(spec)
nchar(tex) > 0

```

ndm_new_runtime_env *Create and populate runtime environments*

Description

These helpers manage isolated environments used to load package-managed runtime code and seed it with R values.

Usage

```

ndm_new_runtime_env(parent = globalenv())

ndm_set_runtime_globals(env, values, overwrite = TRUE)

```

Arguments

parent	Parent environment for a new runtime environment. Defaults to ‘globalenv()’ so package-managed runtime code can resolve attached-package functions consistently.
env	Runtime environment that should receive new bindings.
values	Named list of values to assign into ‘env’.
overwrite	Logical scalar indicating whether existing bindings in ‘env’ should be overwritten.

Value

‘ndm_new_runtime_env()’ returns an environment of class ‘ndm_runtime_env’. ‘ndm_set_runtime_globals()’ invisibly returns ‘env’.

Examples

```

env <- ndm_new_runtime_env()
ndm_set_runtime_globals(env, list(example_value = 1L))
env$example_value

```

ndm_predict

*Generate predictions or evaluate the training loss***Description**

These helpers call the runtime prediction and loss functions stored in a prepared runtime environment.

Usage

```
ndm_predict(x, batch = NULL, inference = TRUE, seed = 1L, update_state = TRUE)
```

```
ndm_loss(
  x,
  batch = NULL,
  y = NULL,
  y_mask = NULL,
  iteration = 1L,
  seed = 1L,
  update_state = TRUE
)
```

Arguments

x	Either an ‘ndm_model’, an ‘ndm_trained_model’, or a prepared runtime environment that already contains the required runtime objects.
batch	Optional batch object. Supply either a named TFRecord-style list or the four-element packaged list returned by ‘ndm_batch_to_model_inputs()’. When ‘NULL’, the runtime must already contain ‘batch_1_cal’.
inference	Logical scalar indicating whether ‘ndm_predict()’ should use the inference prediction path or the training prediction path.
seed	Integer seed used to derive the per-example JAX RNG keys.
update_state	Logical scalar indicating whether the runtime ‘state’ object should be updated with the returned state.
y	Optional observed outcome tensor passed to ‘ndm_loss()’. When omitted, ‘YTrue_out’ is inferred from ‘batch’.
y_mask	Optional outcome mask tensor passed to ‘ndm_loss()’. When omitted, ‘YTrue_out_mask’ is inferred from ‘batch’.
iteration	Training iteration number forwarded to the runtime loss function.

Value

‘ndm_predict()’ returns the prediction object produced by the runtime. ‘ndm_loss()’ returns the loss object produced by the runtime.

Examples

```
## Not run:
preds <- ndm_predict(model, batch = batch_l_cal)
loss <- ndm_loss(model, batch = batch_l_cal)

## End(Not run)
```

ndm_prepare_runtime	<i>Prepare a local runtime for execution</i>
---------------------	--

Description

These wrappers load package-owned runtime components into an isolated environment and prepare the selected data workflow.

Usage

```
ndm_prepare_runtime(
  config = ndm_create_config(),
  runtime_env = ndm_new_runtime_env(),
  runtime_globals = list()
)

ndm_prepare_data(
  runtime_env,
  generator = c("sim", "real", "multidisease"),
  runtime_globals = list()
)
```

Arguments

config	An object of class ‘ndm_config’, usually created by ‘ndm_create_config()’.
runtime_env	Runtime environment that should receive the sourced objects.
runtime_globals	Named list of additional bindings to assign before the relevant runtime or data-preparation stage.
generator	Which data workflow to prepare in ‘runtime_env’.

Details

Before building, training, predicting, or restoring artifacts from a runtime environment, initialize the backend for the target conda environment with ‘ndm_initialize_backend()’. ‘ndm_prepare_runtime()’ requires the ‘fastmatch’ package. Canonical real and simulation preparation requires a completed ‘train_<BaseID>.tfrecord’ / ‘inference_<BaseID>.tfrecord’ pair and their ndmdatasets manifests. Set ‘SkipTfRecords = TRUE’ only for explicit in-memory preparation; the simulation compatibility path then also requires ‘zoo’. The compatibility fields ‘resave_tfrecords’ and ‘ReSaveTfRecords’ must remain ‘FALSE’ in configs, runtime environments, and runtime globals.

Value

‘ndm_prepare_runtime()’ invisibly returns ‘runtime_env’ after loading the package-owned helper and backend code.

‘ndm_prepare_data()’ invisibly returns ‘runtime_env’ after preparing the requested data workflow.

Examples

```
env <- ndm_new_runtime_env()
cfg <- ndm_create_config()
## Not run:
ndm_prepare_runtime(cfg, env)

## End(Not run)

env <- ndm_new_runtime_env()
ndm_set_runtime_globals(env, list(example_value = 1L))
```

ndm_print

Print a timestamped diagnostic message

Description

‘ndm_print()’ is a small logging helper used throughout the package-facing orchestration code.

Usage

```
ndm_print(text, quiet = FALSE)
```

Arguments

text	Text to print.
quiet	Logical scalar indicating whether output should be suppressed.

Value

The input ‘text’, invisibly.

Examples

```
ndm_print("starting")
```

ndm_save_model

Save and restore model artifacts

Description

These helpers persist the public ‘ndm_model’ / ‘ndm_trained_model’ objects to a versioned artifact directory, restore them into a fresh runtime environment, and resume training from the restored optimizer state.

Usage

```
ndm_save_model(x, path, bundle = NULL, overwrite = FALSE)
```

```
ndm_load_model(
  path,
  bundle = NULL,
  calibration_source = c("inference", "train")
)
```

```
ndm_resume_training(
  path,
  bundle = NULL,
  calibration_source = c("train", "inference"),
  train_globals = list()
)
```

Arguments

x	An object of class ‘ndm_model’ or ‘ndm_trained_model’.
path	Artifact directory path.
bundle	Optional ‘ndm_tfrecord_bundle’ used to record TFRecord references for later resume workflows.
overwrite	Logical scalar indicating whether an existing artifact directory should be replaced.
calibration_source	Which dataset should supply the preview batch used to seed runtime globals such as ‘batch_l_cal’ when ‘bundle’ is attached.
train_globals	Optional named list of runtime globals applied immediately before ‘ndm_resume_training()’ continues the training loop.

Details

These helpers assume ‘ndm_initialize_backend()’ has already run for the active conda environment. ‘ndm_save_model()’ only works for runtime-backed ‘ndm_model’ / ‘ndm_trained_model’ objects whose environments still contain the built model state, including ‘ModelList’ and ‘state’. Exact resume also requires saved optimizer state. When ‘bundle = NULL’ in ‘ndm_resume_training()’, the artifact metadata must already contain a recorded TFRecord bundle reference. ‘ndm_load_model()’ and training-restore paths require the ‘rrapply’ package.

Value

‘ndm_save_model()’ returns the normalized artifact directory path, invisibly. ‘ndm_load_model()’ returns an ‘ndm_model’ or ‘ndm_trained_model’ matching the saved artifact. ‘ndm_resume_training()’ returns an ‘ndm_trained_model’.

Examples

```
## Not run:
# After ndm_initialize_backend() and ndm_train() / ndm_fit():
artifact_dir <- ndm_save_model(trained_model, tempfile("ndm-artifact-"))
restored <- ndm_load_model(artifact_dir, bundle = tf_bundle)
resumed <- ndm_resume_training(artifact_dir, bundle = tf_bundle)

## End(Not run)
```

ndm_tfrecord_fields_real

Inspect TFRecord field contracts

Description

These helpers describe the field names and default TensorFlow dtypes expected by the packaged TFRecord readers.

Usage

```
ndm_tfrecord_fields_real()

ndm_tfrecord_fields_sim()

ndm_tfrecord_dtype_map(kind = c("real", "sim"))
```

Arguments

kind	TFRecord schema to inspect. Use "real" for observed-data records and "sim" for simulation records.
------	--

Value

‘ndm_tfrecord_fields_real()’ and ‘ndm_tfrecord_fields_sim()’ return character vectors of field names. ‘ndm_tfrecord_dtype_map()’ returns a named character vector mapping each field to its default TensorFlow dtype.

Examples

```
ndm_tfrecord_fields_real()
ndm_tfrecord_dtype_map("sim")
```

ndm_tf_batch_to_r *Convert and bundle TFRecord batches*

Description

These helpers convert TensorFlow batches to native R or JAX objects, package them into the shape expected by the package-managed runtime, and attach dataset handles to a runtime environment.

Usage

```
ndm_tf_batch_to_r(batch)

ndm_tf_batch_to_jax(batch, backend = NULL)

ndm_batch_to_model_inputs(batch)

ndm_load_tfrecord_bundle(
  train_file,
  inference_file = NULL,
  batch_size,
  kind = c("real", "sim"),
  dtype_map = NULL,
  tensorflow = NULL,
  max_train_examples = NULL,
  max_inference_examples = NULL,
  shuffle_train = TRUE,
  shuffle_inference = FALSE
)

ndm_attach_tfrecord_bundle(
  env,
  bundle,
  backend = NULL,
  calibration_source = c("inference", "train")
)
```

Arguments

batch	A parsed TFRecord batch or a nested list containing TensorFlow tensors.
backend	Optional ‘ndm_backend’ object. When omitted, ‘ndm_tf_batch_to_jax()’ and ‘ndm_attach_tfrecord_bundle()’ use the active backend from ‘ndm_backend_modules()’ when available.
train_file	Path to the training TFRecord file.
inference_file	Optional path to an inference TFRecord file.
batch_size	Batch size used when constructing the training and inference datasets.
kind	TFRecord schema to use when reading ‘train_file’ and ‘inference_file’.
dtype_map	Optional named dtype mapping passed through to the TFRecord readers.
tensorflow	Optional TensorFlow module. When omitted, ndm uses the active backend’s TensorFlow module when available and otherwise imports TensorFlow from the active reticulate environment at call time.

<code>max_train_examples</code>	Optional cap on the number of training examples to read.
<code>max_inference_examples</code>	Optional cap on the number of inference examples to read.
<code>shuffle_train</code>	Logical scalar indicating whether the training dataset should be shuffled.
<code>shuffle_inference</code>	Logical scalar indicating whether the inference dataset should be shuffled.
<code>env</code>	Runtime environment that should receive dataset handles and the preview calibration batch.
<code>bundle</code>	An object of class 'ndm_tfrecord_bundle' returned by 'ndm_load_tfrecord_bundle()'.
<code>calibration_source</code>	Which dataset should supply the preview batch used to seed runtime globals such as 'batch_1_cal'.

Value

'ndm_tf_batch_to_r()' recursively converts a TensorFlow batch to R arrays and lists. 'ndm_tf_batch_to_jax()' recursively converts tensors into JAX arrays. 'ndm_batch_to_model_inputs()' returns the packaged four-element list expected by the package-managed model stages. 'ndm_load_tfrecord_bundle()' returns an 'ndm_tfrecord_bundle' object. 'ndm_attach_tfrecord_bundle()' invisibly returns 'env'.

Examples

```
batch <- list(
  XPred = array(0, c(2, 3, 4)),
  XPred_mask = array(TRUE, c(2, 3, 4)),
  Context = array(0, c(2, 1, 4)),
  Context_mask = array(TRUE, c(2, 1, 4)),
  location_id_numeric = matrix(1L, nrow = 2),
  time_id_numeric = matrix(1L, nrow = 2)
)
packaged <- ndm_batch_to_model_inputs(batch)
length(packaged)
```

Index

ndm (ndm-package), 2
ndm-package, 2
ndm_attach_tfrecord_bundle
 (ndm_tf_batch_to_r), 27
ndm_backend_modules
 (ndm_check_backend), 7
ndm_batch_to_model_inputs
 (ndm_tf_batch_to_r), 27
ndm_bootstrap_real_tfrecords, 3
ndm_bootstrap_sim_tfrecords, 4
ndm_build_backend, 2
ndm_build_backend (ndm_check_backend), 7
ndm_build_model, 3, 5
ndm_check_backend, 7
ndm_collect_tfrecord_batches
 (ndm_create_tfrecord_parser),
 14
ndm_create_config, 2, 9
ndm_create_multidisease_run_config
 (ndm_create_real_run_config),
 11
ndm_create_real_run_config, 3, 11
ndm_create_sim_run_config
 (ndm_create_real_run_config),
 11
ndm_create_tfrecord_parser, 14
ndm_extract_temporal_latents, 16
ndm_fit, 3
ndm_fit (ndm_build_model), 5
ndm_initialize_backend, 2
ndm_initialize_backend
 (ndm_check_backend), 7
ndm_latent_matrix
 (ndm_extract_temporal_latents),
 16
ndm_load_model, 3
ndm_load_model (ndm_save_model), 25
ndm_load_tfrecord_bundle, 3
ndm_load_tfrecord_bundle
 (ndm_tf_batch_to_r), 27
ndm_loss, 3
ndm_loss (ndm_predict), 22
ndm_model_spec, 2
ndm_model_spec
 (ndm_model_spec_presets), 18
ndm_model_spec_from_structure, 17
ndm_model_spec_from_tex, 2
ndm_model_spec_from_tex
 (ndm_model_spec_presets), 18
ndm_model_spec_presets, 18
ndm_model_spec_to_tex, 2
ndm_model_spec_to_tex
 (ndm_model_spec_presets), 18
ndm_new_runtime_env, 21
ndm_predict, 3, 22
ndm_prepare_data, 3
ndm_prepare_data (ndm_prepare_runtime),
 23
ndm_prepare_runtime, 3, 23
ndm_print, 24
ndm_read_tfrecord_dataset, 2
ndm_read_tfrecord_dataset
 (ndm_create_tfrecord_parser),
 14
ndm_resume_training, 3
ndm_resume_training (ndm_save_model), 25
ndm_run_multidisease, 3
ndm_run_multidisease
 (ndm_create_real_run_config),
 11
ndm_run_real, 3
ndm_run_real
 (ndm_create_real_run_config),
 11
ndm_run_sim, 3
ndm_run_sim
 (ndm_create_real_run_config),
 11
ndm_save_model, 3, 25
ndm_set_runtime_globals
 (ndm_new_runtime_env), 21
ndm_tf_batch_to_jax
 (ndm_tf_batch_to_r), 27
ndm_tf_batch_to_r, 27
ndm_tfrecord_dtype_map
 (ndm_tfrecord_fields_real), 26

```
ndm_tfrecord_fields_real, 26
ndm_tfrecord_fields_sim
    (ndm_tfrecord_fields_real), 26
ndm_train, 3
ndm_train(ndm_build_model), 5

print.ndm_config(ndm_create_config), 9
print.ndm_model(ndm_build_model), 5
print.ndm_model_spec
    (ndm_model_spec_presets), 18
print.ndm_trained_model
    (ndm_build_model), 5
```