

Package ‘optimalcausalities’

March 10, 2021

Title Optimal Stochastic Interventions in High-dimensional Data

Version 2.0

Authors

'Kosuke Imai <imai@harvard.edu> [aut], Rohit <rohitchaudhuri@g.harvard.edu> [aut, cre], Connor Jerzak <cjerzak@g.harvard.edu> [aut, cre]'

Description Description here.

Depends R (>= 3.3.3)

License

Creative Commons Attribution-Noncommercial-No Derivative Works 4.0, for academic use only.

Encoding UTF-8

LazyData true

Maintainer 'Connor Jerzak' <connor.jerzak@gmail.com>

Imports Rsolnp, keyATM

RoxygenNote 7.1.1

R topics documented:

computeQse_conjoint	1
computeQse_lda	2
computeQ_conjoint	3
computeQ_lda	4
optimizecausalities	5
optimizeQ_conjoint	5
optimizeQ_lda	6

Index	8
--------------	----------

computeQse_conjoint	<i>computeQse_conjoint</i>
---------------------	----------------------------

Description

Implements ...

Usage

```
computeQse_conjoint(theta, FactorMatrix, log_pr_w = NULL)
```

Arguments

dfm 'document-feature matrix'. A list ...

Value

A list consiting of

- Items.

References

- Kosuke, Rohit, Connor. Working Paper.

Examples

```
#set seed
set.seed(1)

#Geneate data
x <- rnorm(100)
```

computeQse_lda

computeQse_lda

Description

Implements ...

Usage

```
computeQse_lda(
  THETA__,
  INDICES_,
  DOC_INDICES_U,
  D_INDICES_U,
  PI_MAT_INPUT,
  MARGINAL_BOUNDS,
  DOC_LIST,
  MODAL_DOC_LEN,
  TERMS_MAT_INPUT,
  LOG_TREATCOMBS,
  YOBS,
  log = T,
  LOG_PR_W = NULL
)
```

Arguments

dfm 'document-feature matrix'. A list ...

Value

A list consiting of

- Items.

References

- Kosuke, Rohit, Connor. Working Paper.

Examples

```
#set seed
set.seed(1)

#Geneate data
x <- rnorm(100)
```

computeQ_conjoint	<i>computeQ_conjoint</i>
-------------------	--------------------------

Description

Implements ...

Usage

```
computeQ_conjoint(theta, FactorsMat, Yobs, log_pr_w = NULL)
```

Arguments

dfm 'document-feature matrix'. A list ...

Value

A list consiting of

- Items.

References

- Kosuke, Rohit, Connor. Working Paper.

Examples

```
#set seed
set.seed(1)

#Geneate data
x <- rnorm(100)
```

computeQ_lda

computeQ_lda

Description

Implements ...

Usage

```
computeQ_lda(
  theta = NULL,
  term_mat,
  Yobs,
  doc_words,
  dtm = NULL,
  pi_mat = NULL,
  alpha_mat = NULL,
  log_pr_w = NULL,
  computeSE = F,
  trim_q = 1,
  quiet = T,
  iters = 100,
  smoothWts = F,
  TreatFxn = NULL,
  maxWt = 1e+10,
  maxWt_hajek = NULL,
  term_mat_TRUE = NULL,
  doc_indices_u = NULL,
  d_indices_u = NULL,
  diagnostics = F
)
```

Arguments

dfm 'document-feature matrix'. A list ...

Value

A list consiting of

- Items.

References

- Kosuke, Rohit, Connor. Working Paper.

Examples

```
#set seed
set.seed(1)

#Geneate data
```

```
x <- rnorm(100)
```

optimizecausalities	<i>optimizecausalities</i>
---------------------	----------------------------

Description

Implements ...

Usage

```
optimizecausalities(Yobs, W, optimize = T, theta = NULL)
```

Arguments

dfm 'document-feature matrix'. A list ...

Value

A list consiting of

- Items.

References

- Kosuke Imai, Rohit, Connor

Examples

```
#set seed
set.seed(1)

#Geneate data
x <- rnorm(100)
```

optimizeQ_conjoint	<i>computeQ_conjoint</i>
--------------------	--------------------------

Description

Implements ...

Usage

```
optimizeQ_conjoint(FactorMatrix, SE_bound)
```

Arguments

dfm 'document-feature matrix'. A list ...

A list consisting of

- ## References

- ## Examples

<code>optimizeQ_lda</code>	<code>computeQ_lda</code>
----------------------------	---------------------------

Implements ...

```
optimize_Q_lda(  
  DATA_SPLIT1,  
  DATA_SPLIT2 = NULL,  
  DTM_MAT,  
  n_fold = 3,  
  YOBS,  
  PI_MAT,  
  DOC_LIST,  
  TERMS_MAT,  
  SE_UB = sd(YOBS)/10,  
  nboot = 10,  
  trim_q = 1,  
  maxWt = 1e+10,  
  maxWt_hajek = NULL,  
  computeSEs = T,  
  doMax = T,  
  alphaLevel = 0.05  
)
```

dfm	'document-feature matrix'. A list ...
-----	---------------------------------------

Value

A list consisting of

- Items.

References

- Kosuke Imai, Rohit, Connor

Examples

```
#set seed  
set.seed(1)
```

```
#Generate data  
x <- rnorm(100)
```

Index

`computeQ_conjoint`, [3](#)
`computeQ_lda`, [4](#)
`computeQse_conjoint`, [1](#)
`computeQse_lda`, [2](#)

`optimizecausalities`, [5](#)
`optimizeQ_conjoint`, [5](#)
`optimizeQ_lda`, [6](#)